

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (75-767) WASHINGTON, DC 20460	EPA REGISTRATION NO. 52367-1	DATE OF ISSUANCE SEP 25 1985
	TERM OF ISSUANCE	
NOTICE OF PESTICIDE: <input checked="" type="checkbox"/> REGISTRATION <input type="checkbox"/> REREGISTRATION (Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)	NAME OF PESTICIDE PRODUCT Corsair Vinyl Antifouling Paint A45 Black	
	NAME AND ADDRESS OF REGISTRANT (Include ZIP code)	
Precision Coating Systems, Inc. P.O. Box 36 Farmingdale, NJ 07727		
<p>NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.</p> <p>On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.</p> <p>A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.</p> <p>Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p>This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:</p> <ol style="list-style-type: none"> 1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data. 2. Comply with comment (a) in our letter of September , 1985. 3. Make the labeling changes listed below before you release the product for shipment: <ol style="list-style-type: none"> a. Add the phrase "EPA Registration No. 52367-1." b. Delete the word "Flammable" from the front panel; the words "Combustible" or "Flammable" may not appear under the general front panel signal word. The appropriate placement for this statement is under the heading "Physical/Chemical Hazard." If you believe that the flammability of the product warrants a front panel statement, you may propose an appropriate placement on the front panel. c. The statement "Flammable: Keep away from heat and open flame" should be removed (deleted) from the first paragraph of the Precautionary 		
<input checked="" type="checkbox"/> ATTACHMENT IS APPLICABLE		
SIGNATURE OF APPROVING OFFICIAL		DATE


statements (on the right panel) and should be used to replace the statement "Combustible: Do not store near heat or open flame" which appears as a "Physical or Chemical Hazard." - See comment (c) our letter of January 23, 1985.

- d. Make sure you have complied with the type size requirements for the front panel "Warning" and "Keep Out of Reach of Children" statements, - see enclosure on type size requirements.
- e. According to your Confidential Formula, "Copper expressed as metallic" should be 48.8%.
- f. The label should have a statement, "Contains petroleum distillates." It should be placed below the ingredient statement.
- g. At the bottom of the left panel, the Navy letter of September 4, 1984, indicates that the "MIL-P-16189, Formula 129/63" is now "MIL-P-15931 Rev E, Formula 129."

4. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

John H. Lee 
 Product Manager (31)
 Disinfectants Branch
 Registration Division (TS-767C)

Enclosures

RD/DIS:JOB-51768:Lee:CBI-B:Kendrick:898-1270:9/16/85:Del.9/25/1985:Kim

3/4
KEEP OUT OF REACH OF CHILDREN
WARNING! FLAMMABLE. SEE SIDE
PANEL FOR ADDITIONAL PRECAUTIONARY
STATEMENTS

P.C./Systems

CORSAIR
Vinyl Antifouling Paint
A45 Black

Active Ingredients 55.00
Cuprous Oxide ~~56.80%~~
Inert Ingredients 45.00 ~~43.20%~~
100.00%

EPA Reg. No. 52367
EPA Est. No. 52367-NJ-1
Copper Expressed as Metallic
50.3%

One U.S. Gallon

Manufactured and Sold by Precision Coating Systems Inc., Farmingdale, NJ 07727

ACCEPTED
with COMMENT
in EPA Letter

SEP 25 1981

Under the Federal
Fungicide, and Rodenticide
Act, as amended, for
registered under FIFRA

52367

IF SWALLOWED
available,
IF IN EYES
IF ON SKIN
IF INHALED
mouth. Get

This material
ment or dis
Dispose of

COMBUSTIBLE

It is a violation
product is
Enforcement
for Occup

Do not con
under acc
under the

CONTAINS
posal of ir

Mixing and Thinning Instructions: Mix well before use. Stir continuously while using. Only add thinner if necessary. Use only Precision's Thinner T106. On bare wood vessels, thin the first coat with about 10% Thinner T106 to provide maximum penetration.

Coverage: 470 square feet per gallon for one full coat.

Surface Preparation:

Wood: Surface must be dry, smooth and free of grease or oil. Remove all loose paint and foreign substances.

Fiberglass: New - Wipe down thoroughly with Precision's Fiberglass Cleaner T101. Change rags frequently to avoid contamination. Repair dents, scratches, etc. with a quality polyester filler/putty. Allow to properly cure and sand entire surface with 80-120 grit aluminum oxide sandpaper. Wipe off sanding dust with Thinner T101 or T104, allow to thoroughly dry and coat. Repaint - properly sand old vinyl antifouling paints to remove loosely adhering paint, wipe down and coat. All other types must be removed before recoating.

Aluminum: Do not use on aluminum.

Number of Coats: On new or bare wood, use 3 coats allowing at least 4 hours between applications. On old painted hulls in good condition and on fiberglass surfaces two coats are needed.

Launching: Allow at least 6 hours and up to one week day after final application before launching.

Clean Up: Use Precision Thinner T106.

Note: Corsair Vinyl Antifouling Paint Black A-45 complies with the U.S. Navy's specification antifouling paint MIL-P-16189, Formula 129/63.