

US ENVIRONMENTAL PROTECTION AGENCY  
OFFICE OF PESTICIDES PROGRAMS  
REGISTRATION DIVISION (75-767)  
WASHINGTON, DC 20460

EPA REGISTRATION NO.  
52367-2

DATE OF ISSUANCE  
**SEP 25 1985**

NOTICE OF PESTICIDE:  REGISTRATION  
 REREGISTRATION  
(Under the Federal Insecticide, Fungicide,  
and Rodenticide Act, as amended)

TERM OF ISSUANCE  
NAME OF PESTICIDE PRODUCT  
Corsair Antifouling Paint Super  
Red A49

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Precision Coating Systems, Inc.  
P.O. Box 36  
Farmingdale, NJ 07727

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Comply with comment (a) in our letter of September , 1985.
3. Make the labeling changes listed below before you release the product for shipment:
  - a. Add the phrase "EPA Registration No. 52367-2."
  - b. Delete the word "Flammable" from the front panel; the words "Combustible" or "Flammable" may not appear under the general front panel signal word. The appropriate placement for this statement is under the heading "Physical/Chemical Hazard." If you believe that the flammability of the product warrants a front panel statement, you may propose an appropriate placement on the front panel.
  - c. The statement "Flammable: Keep away from heat and open flame" should be removed (deleted) from the first paragraph of the Precautionary

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

DATE

statements (on the right panel) and should be used to replace the statement "Combustible: Do not store near heat or open flame" which appears as a "Physical or Chemical Hazard." - See comment (c) our letter of January 23, 1985.

- d. Make sure you have complied with the type size requirements for the front panel "Warning" and "Keep Out of Reach of Children" statements.
  - e. At the bottom of the left panel, the Navy letter of September 4, 1984, indicates that the "MIL-P-15931, Formula 121/63" is now "MIL-P-15931 Rev E, Formula 121."
3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

John H. Lee  
Product Manager (31)  
Disinfectants Branch  
Registration Division (TS-767C)

Enclosure

RD/DIS:JOB-51768:Lee:CBI-B:Kendrick:898-1270:9/16/85:Del.9/25/1985:Kim

KEEP OUT OF REACH OF CHILDREN  
WARNING! FLAMMABLE. SEE SIDE  
PANEL FOR ADDITIONAL PRECAUTIONARY  
STATEMENTS

# P.C./Systems

## CORSAIR Antifouling Paint Super Red A49

IF SWALLOWED: If available, drink large amount of water.  
IF IN EYES: Flush with water for 15 minutes.  
IF ON SKIN: Wash with soap and water.  
IF INHALED: Remove to fresh air. Get medical attention if symptoms persist.

This material is toxic. Do not ingest. Do not breathe vapors. Do not get on skin or clothes. Do not get in eyes. Do not get in mouth. Do not get on food or drink. Do not get on children's toys. Do not get on pets. Do not get on clothing. Do not get on shoes. Do not get on furniture. Do not get on walls or ceilings. Do not get on floors. Do not get on carpets. Do not get on drapes or curtains. Do not get on blinds or shades. Do not get on mirrors or glass. Do not get on electronics. Do not get on vehicles. Do not get on boats. Do not get on aircraft. Do not get on spacecraft. Do not get on satellites. Do not get on planets. Do not get on stars. Do not get on galaxies. Do not get on the universe.

COMBUSTIBLE: DANGER

It is a violation of federal law if this product is used in connection with the manufacture, use, or sale of a hazardous substance. For Occupational Safety and Health (OSHA) information, see 29 CFR 1910.106.

Do not contaminate water, food, or feed. Do not use in confined spaces. Do not use in areas where fire or explosion is a hazard. Do not use in areas where it may cause slipping, tripping, or falling. Do not use in areas where it may cause irritation or injury to the skin, eyes, or respiratory system. Do not use in areas where it may cause damage to property or the environment. Do not use in areas where it may cause damage to health or the environment.

CONTAINER DISPOSAL: Dispose of in a sanitary manner.

Ingredients 66.10  
33.90  
100.00%

EPA Reg. No. 52367  
EPA Est. No. 52367-NJ-1  
Copper Expressed as Metallic  
58.60%

One U.S. Gallon

by Precision Coating Systems Inc., Farmingdale, NJ 07727

Attachment, you may refer to the "Safety Data Sheet" for more information on heat and open flame" should refer to the Precautionary Statement of the Precautionary Statement.

DATE
USED UNTIL SUPPLY IS EXHAUSTED.

can rollers, by brush or by spray. Do not use over conventional soft  
bottom paints.

**Mixing and Thinning Instructions:** Mix well before use. Stir continuously while using. Only add thinner if necessary. Use only Precision's Thinner T104. On bare wood vessels, thin the first coat with about 10% Thinner T104 to provide maximum penetration.

**Coverage:** 470 square feet per gallon for one full coat.

**Surface Preparation:**

**Wood:** Surface must be dry, smooth and free of grease or oil. Remove all loose paint and foreign substances.

**Fiberglass: New -** Wipe down thoroughly with Precision's Fiberglass Cleaner T101. Change rags frequently to avoid contamination. Repair dents, scratches, etc. with a quality polyester filler/putty. Allow to properly cure and sand entire surface with 80-120 grit aluminum oxide sandpaper. Wipe off sanding dust with Thinner T101 or T104, allow to thoroughly dry and coat. **Repaint -** properly sand old vinyl antifouling paints to remove loosely adhering paint, wipe down and coat. All other types must be removed before recoating.

**Aluminum:** Do not use on aluminum.

**Number of Coats:** On new or bare wood, use 3 coats allowing at least 4 hours between applications. On painted hulls in good condition and on fiberglass surfaces two coats are needed.

**Launching:** Allow at least 6 hours and up to one week dry after final application before launching.

**Clean Up:** Use Precision Thinner T106.

**Note:** Corsair Super Vinyl Antifouling Paint Red A49 complies with the U.S. Navy specification MIL-P-15931, Formula 121/63.