

Saxon Signature/Best Quality

Latex Solid Color Stain & Preservative

BEST AVAILABLE COPY

This is the most durable stain I can possibly offer you. It's made in my factory with the latest advances in stain technology and materials to repel moisture and help preserve wood. One coat of this stain penetrates deep into the wood and won't chip, peel, blister or crack. And it's specially formulated by my chemists to withstand our severe Midwest weather for years.

For the best in durability and protection, that also enhances the natural beauty and texture of exterior wood, I highly recommend this stain. My personal endorsement is your guarantee of total satisfaction.

Alan Sisk President, Saxon Paint & Home Care Centers



One Gallon

Weight: 10.2 LBS.

EPA Reg. No. 52598-
EPA Est. No. 52598-11.-1

ACCEPTED
MAY 28 1985
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the product registered under EPA Reg. No. 52598-3

ACTIVE INGREDIENT:
3-Iodo-2-Propynyl Butyl Carbamate 0.5%
INERT INGREDIENTS: . . . 99.5%
100.0%

KEEP OUT OF REACH OF CHILDREN

CAUTION

See Side Panel for Additional Precautionary Statements.

Quick Facts About This Stain

Finish/Type
Opaque Flat exterior latex

Where to Use
On new or previously stained or painted wood, rough or smooth siding, fences, shingles, garages. Not recommended for horizontal surfaces, such as floors, decks, or outdoor furniture.

Coverage
One gallon covers approximately 200 square feet, depending on the porosity of the wood.

Drying Time
Dries in one hour to touch; 24 hours for recoating.

Clean-Up/Thinning
Clean-up with warm, soapy water. Thinning is not necessary. Use directly from can after thorough mixing.

NOTICE
Colors shown are approximate at best and will vary according to the type of wood and specific job. For more accurate tones, samples should be made on scraps or on the actual job itself in an inconspicuous spot before starting. Two coats will result in approximately twice as dark a tone.

SAXON'S
UNCONDITIONAL PAINT
GUARANTEE

If you are not satisfied with any
paint purchased at Saxon, just bring
in your remaining paint and sales
receipt and we will cheerfully re-
fund your money or replace your
purchase with comparably priced
paint

For any reason.

For any reason at all

Labor or cost of application not
included.



Manufactured in our own factory.

© 1981 Saxon Paint & Home Care Centers
Chicago, Illinois 60617

BEST AVAILABLE COPY

**PRECAUTIONARY STATEMENT
HAZARDS TO HUMAN AND DOMESTIC ANIMALS**

Harmful if swallowed or inhaled. Avoid breathing spray mist. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling and before smoking or eating. Remove contaminated clothing and wash before reuse.

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person. Call a physician immediately.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists.

IF INHALED: Remove victim to fresh air. Apply artificial respiration, preferably mouth to mouth, if indicated.

IF IN EYES: Flush with plenty of water. Get medical attention if irritation persists.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

SIGNATURE SOLID COLOR LATEX STAIN

Blocks Original Color and Grain, Allows Natural Texture to Show/Weatherproofs Vertical Siding and Shingles/Does not Chip, Peel, or Crack When Applied to Bare Wood or Over Sound Surfaces/Has Deep Penetration, Unlike Ordinary House Paint/Not Recommended for Floors, Decks, Outside Furniture, or below Grade Surfaces.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This product is for exterior use only and is recommended for shingles (not asbestos), shakes, clapboards, smooth or rough-cut wood siding, railings, structural support timbers, flat beds, cold frames and greenhouses. The product is not recommended for wood used for ground, food, feed or potable water contact. Cover desirable plants and shrubs to avoid possible injury. This product can be used where dairy and farm animals may come in contact with the treated wood.

SURFACE PREPARATION

Clean surface thoroughly, until free of soot, grease, loose sealing paint. Scrub away mildew if present (looks like dirt spots or streaks) with 1/2 water, 1/2 household bleach solution; allow solution to dry on the surface without rinsing off. Before applying stain, surface should always be completely dry. Patch cracks, holes and joints with matching colored caulk.

APPLYING STAIN

Stir thoroughly before using. Apply when temperature is over 50 . Avoid staining in hot sun; it is best to follow the shade around the house. Do not stain when rain is imminent. Before starting, mix together as many gallons as needed to do one side. Stain is best applied with 4 inch bristle stain brush, or flat pads. If rollers are used, simultaneous brushing out is required. Apply in direction of grain. For vertical siding, paint 3 or 4 boards at a time from top to bottom, keeping a wet edge. For better protection, vertical surfaces may receive 2 coats. On horizontal siding, apply a uniform coat to 3 or 4 boards all the way across to an edge to avoid lap marks.

STORAGE AND DISPOSAL

STORAGE:Do not expose this product to temperatures below 32 F.

DISPOSAL:

Household Users: Do not reuse original container. Securely wrap original container in several layers of newspaper and discard in trash.

Commercial Users:Pesticide/Product Disposal - Do not contaminate water, food or feed by storage or disposal. Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Container disposal -Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.