

PM 21  
52782-1  
P22-5

**ACCEPTED**  
OCT 09 1990

**FRONT LABEL**

**1 Coat Coverage!**  
**THOMPSON'S<sup>R</sup> WOOD PROTECTOR**

52782-1

**Superior 3-Way Protection for Exterior Wood**

**Consumer - Use Label**

**PRESERVES-**  
to prevent decay,  
mildew, wood rot  
and sapstain.

**WATERPROOFS-**  
to prevent warping,  
shrinking and  
cracking.

**PROTECTS-**  
against sun  
and weather  
damage.

**Clear Waterproofing Wood Preservative**

**1 GALLON**  
**3.785 Liters**

**5 GALLONS**  
**18.925 Liters**

**Profess - ional - Use Label**

**THOMPSON'S WOOD PROTECTOR**  
**Clear Waterproofing Wood Preservative**

**For Professional Use Only**

**PRESERVES · WATERPROOFS · PROTECTS**

**5 GALLONS**  
**18.925 Liters**

**55 GALLONS**  
**208.175 Liters**

FRONT LABEL (CONT.)


Active Ingredient:		
3-Iodo-2-Propynyl Butyl Carbamate	0.5%	
Inert Ingredients:	99.5%	
Total	100.0%	

CONTAINS PETROLEUM DISTILLATES.

KEEP OUT OF REACH OF CHILDREN.

CAUTION. Before using, carefully  
read PRECAUTIONARY STATEMENTS  
elsewhere on label.

EPA Reg. No. 52782-1; EPA Est. No. 52782-MS-01



BACK LABEL - LEFT SIDE

THOMPSON'S<sup>R</sup> WOOD PROTECTOR

Consumer-  
Use  
Labels

Water and Weather can cause serious damage to wood around your home.

Profess-  
ional -  
Use  
Labels

Water and Weather can cause serious damage to exterior wood. Excessive moisture conditions promote the growth of mold and mildew, and eventually cause wood to rot. Unprotected wood will crack, warp and split. Wood may become damaged and have to be replaced prematurely.

Consumer-  
Use  
Labels

Thompson's Wood Protector provides the extra protection your wood needs. Thompson's preserves, waterproofs and protects the wood around your home, helping to prevent costly damage.

Profess-  
ional-  
Use  
Labels

Thompson's Wood Protector provides the extra protection that wood needs. Thompson's preserves, waterproofs and protects exterior wood, helping to prevent costly damage.

**PRESERVES AND PROTECTS:**

- |                     |                 |                                |
|---------------------|-----------------|--------------------------------|
| · Wooden Decks      | · Window Frames | · Wooden Doors                 |
| · Outdoor Furniture | · House Siding  | · Other exterior wood surfaces |
| · Wooden Shingles   | · Fencing       |                                |

**WHAT IS THOMPSON'S WOOD PROTECTOR?**

Wood Protector is a clear, highly penetrating, non-drying oil-based waterproofing preservative especially formulated for wood substrates above ground level. Thompson's penetrating formula offers 3-way protection for wood: 1) as an excellent wood preservative that helps prevent the formation of mildew, sapstain and wood rot; 2) as a superior water repellent that helps prevent warping, shrinking and splitting caused by moisture; and 3) a protective agent that helps retard the damaging effects of sunlight. Wood Protector goes on with a simple one-coat application and cleans up with detergent and water.

**WOOD PROTECTOR'S BENEFITS**

Thompson's Wood Protector provides excellent long-lasting protection. It reduces splitting, grain-raising, shrinkage, swelling and deterioration from wet and dry weather cycles. It protects against decay and rot while retarding the growth of mold and mildew. Thompson's does not form a surface film but penetrates and replaces lost wood oils to reduce cracking, warping, splitting. It enhances the beauty of the wood grain and provides excellent water repellency. Thompson's exceeds the Federal Specification TT-W-572b for water repellency of wood. Wood Protector contains an ultraviolet light absorber to help retard the damaging effects of sunlight.

BACK LABEL - LEFT SIDE (CONT.)

HELPFUL HINTS:

- Only one coat is necessary in most applications. Do not saturate surfaces, puddle or build to wet film.
- Not recommended for use on previously painted or stained wood.
- Wood Protector can be used on pressure-treated lumber to waterproof and provide extra protection against sun and weather damage.
- Coverage for decking and other smooth wood surfaces is 300-400 square feet per gallon. For rougher cut wood used for siding and fencing, coverage is 200-300 square feet per gallon.
- Excessive oiliness, particularly in sitting areas, may be removed by scrubbing with detergent and water.
- Weathered wood will appear darker after application. A trial patch is recommended before you start.
- Overspray of Wood Protector onto metal or glass should be removed immediately by wiping clean or washing with detergent and water.
- Oil-based paint or stain may be applied over Wood Protector after at least 30 days. Latex-based coatings are not recommended for use over Thompson's Wood Protector.
- For best results, reapplication is recommended every 3 years.
- Do not overspray on vegetation.

Other Thompson's Products:

Consumer-  
Use  
Labels

For your other waterproofing needs, try Thompson's<sup>R</sup> Water Seal<sup>R</sup> Waterproofing Formula. The next time you need a stain, use Thompson's<sup>R</sup> Water Seal<sup>R</sup> Exterior Stain which waterproofs while enhancing the appearance of your wood with the color of your choice.

Profess-  
ional -  
Use  
Labels

For other waterproofing projects, try Thompson's<sup>R</sup> Water Seal<sup>R</sup>. It works on wood, brick, or concrete. For stain projects, use Thompson's<sup>R</sup> Water Seal<sup>R</sup> Exterior Stain. It provides superior waterproofing in rich beautiful color.

BACK LABEL - RIGHT SIDE

Waterproofing Preservative for Wood

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PREPARATION: Wood must be thoroughly dry since Thompson's Wood Protector will not fully penetrate wet or damp surfaces. Surface should be clean and porous enough to allow penetration. We recommend a trial patch before you start.

APPLICATION:

1. Apply when both air and surface temperatures are above 50° F.
2. Apply by brush, roller, dipping or spraying.
3. Only 1 light coat is necessary in most applications. Do not saturate surfaces, puddle or build wet film.

COVERAGE: Approximately 200-400 square feet per gallon depending on wood porosity and surface roughness. One coat is sufficient.

DRYING TIME: Allow 24 to 48 hours. Penetration will vary depending on the porosity of the surface and humidity. Wait a minimum of 30 days before painting over Thompson's Wood Protector with oil-base paint.

CLEANUP: Clean brushes and equipment with detergent and water. Overspray or accidental spillage can be wiped up or cleaned immediately with detergent and water.

Consumer-  
Use  
Labels

STORAGE AND DISPOSAL: Avoid storage near food or food products. Do not reuse empty container. Securely wrap original container in several layers of newspaper and discard in trash.

Profession-  
al -  
Use  
Labels

STORAGE AND DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by incineration if allowed by state and local authorities.

LIMITED ONE YEAR WARRANTY: Thompson & Formby, Inc. warrants the quality and performance of this product when used according to directions and will refund the purchase price or replace this product within one year from the date of purchase, if it is defective.

BACK LABEL - RIGHT SIDE (Cont.)

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals: CAUTION! CONTAINS PETROLEUM DISTILLATES. MAY BE HARMFUL IF SWALLOWED. Avoid contact with skin, eyes or clothing. Avoid breathing vapor or spray mist. Use in well ventilated area.

First Aid:

Ingestion: Do not induce vomiting. Call physician or Poison Control Center immediately.

Eye Contact: Immediately flush eyes with water, remove contact lenses and continue to flush eyes for fifteen minutes. If irritation persists, get medical attention.

Skin Contact: Wash skin thoroughly with soap and water. Wash contaminated clothing thoroughly with soap and water before reuse.

Inhalation: Remove to fresh air. If necessary, give artificial respiration or oxygen. Call a physician.

Environmental

Hazard: Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

Manufactured by  
Thompson & Formby Inc.  
Subsidiary of Sterling Drug Inc.  
Memphis, TN

HEALTH

2

Professional -  
Use Labels

FLAMMABILITY

1

REACTIVITY

0

PERSONAL PROTECTION

B

Hazardous Materials Information Systems (HMIS)