

FRONT LABEL

THOMPSON'S® WOOD PROTECTOR

Clear One Coat Coverage For Exterior Wood

Superior 3-Way Protection

PRESERVES-	WATERPROOFS-	SUNSCREENS-
to prevent decay,	to prevent water	helps protect
mildew, wood rot	damage on wood.	against fading
and sapstain.		and other weather
		damage.

Clear Waterproofing Wood Preservative

Active Ingredient:
3-Iodo-2-Propynyl Butyl Carbamate...0.5%
Inert Ingredients:.....99.5%
Total.....100.0%

CONTAINS PETROLEUM DISTILLATES.

KEEP OUT OF REACH OF CHILDREN.

CAUTION. Before using, carefully read Precautionary Statements elsewhere on label.

EPA Reg. No. 52782-1
EPA Est. No. 52782-MS-01

1 GALLON
3.785 Liters

5 GALLONS
18.925 Liters

BEST AVAILABLE COPY

ACCEPTED
FEB 27 1997
Under the Federal Insecticide, Fungicide, and
Rodenticide Act, as amended, for the
pesticide registered under
EPA Reg. No. 52782-1

REC'D EPA/OPP/DPD1
36 FEB -4 AM 1:34

274

BACK LABEL - RIGHT SIDE

-2-

THOMPSON'S® WOOD PROTECTOR

Water and Weather can cause serious damage to wood around your home. Excessive moisture conditions promote the growth of mold and mildew, and eventually cause wood to rot. Unprotected wood will crack, warp and split. Wood may become damaged and have to be replaced prematurely. Thompson's® Wood Protector provides the extra protection your wood needs. Thompson's® Wood Protector preserves, waterproofs and protects exterior wood, helping to prevent costly damage.

PRESERVES AND PROTECTS:

- | | | |
|---------------------------|-----------------|-----------------------|
| • Wooden Decks | • Window Frames | • Wooden Doors |
| • Outdoor Furniture | • House Siding | • Other exterior wood |
| • Wooden Shingles | • Fencing | surfaces |
| • Pressure-Treated Lumber | | |

WHAT IS THOMPSON'S® WOOD PROTECTOR?

Thompson's® Wood Protector is a clear, highly penetrating, non-drying oil-based waterproofing preservative especially formulated for wood above ground level. The penetrating formula offers 3-way protection for wood:

- 1) as a superior water repellent that helps prevent warping, shrinking and splitting caused by moisture;
- 2) as an excellent wood preservative that helps prevent the formation of mildew, sapstain and wood rot; and
- 3) with a dual acting UV sunscreensing agent that works to retard color change and damage caused by sunlight and enhances the longevity of the preservative ingredient. Thompson's® Wood Protector helps protect against sun damage but does not prevent the natural graying of the wood.

THOMPSON'S® WOOD PROTECTOR BENEFITS

Thompson's® Wood Protector provides excellent long-lasting protection. It reduces splitting, gain raising, shrinkage, swelling and deterioration from wet and dry weather cycles. It protects against decay and rot while retarding the growth of mold and mildew. Thompson's® Wood Protector does not form a surface film but penetrates and replaces lost wood oils to reduce cracking, warping and splitting. It enhances the beauty of the wood grain and provides excellent water repellency. Thompson's® Wood Protector contains an ultraviolet light absorber to help retard the damaging effects of sunlight.

BEST AVAILABLE COPY

374

HELPFUL HINTS:

- Only one coat is necessary in most applications. Do not saturate surfaces, puddle or build to wet film.
- Not recommended for use on previously painted or stained wood.
- Thompson's® Wood Protector can be used to waterproof pressure-treated lumber which helps reduce unsightly warping and splitting, while adding extra protection against sun and mildew damage.
- Excessive oiliness, particularly on horizontal surfaces, may be removed by scrubbing with detergent and water.

BACK LABEL - RIGHT SIDE CONTINUED -3-

- Weathered wood will appear darker after application. A trial patch is recommended before you start.
- Overspray of Thompson's® Wood Protector onto metal or glass should be removed immediately by wiping clean or washing with detergent and water.
- Oil-based paint or stain may be applied over Thompson's® Wood Protector after at least 30 days. Latex-based coatings are not recommended for use over Thompson's® Wood Protector.
- For best preservative and water repellency action, reapplication is recommended every 2 to 4 years.
- Do not overspray on vegetation.
- For maximum protection from color change and other damage caused by the sun, reapplication is recommended every year. Vertical and horizontal surfaces will experience color changes at different rates.

If you have any questions regarding Thompson's® Wood Protector or any of our other Thompson's® brand or Formby's® brand products, please call the Thompson & Formby Help line at 1-800-367-6297. We are open seven days a week. Hours are:

Monday - Friday	Noon - 8:00 p.m. (ET)
Saturday/Sunday/Holidays	10:00 a.m. - 6:00 p.m. (ET)

Maximum VOC 350g/L (2.9 Lbs/Gal)

BEST AVAILABLE COPY

Waterproofing Preservative for Wood

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PREPARATION: Wood must be thoroughly dry since Thompson's Wood Protector will not fully penetrate wet or damp surfaces. Surface should be clean and porous enough to allow penetration. For best results on wood that has been weathered or discolored from mold or mildew, clean with Thompson's Deck Wash according to the Package directions and cautions. Let area dry completely before applying Thompson's Wood Protector.

APPLICATION:

1. Apply when both air and surface temperatures are above 50°F. and will remain above 50°F. for at least 48 hours.
2. Shake well before using. Do not thin.
3. Apply by brush, roller, dipping or spraying.
4. Only 1 light coat is necessary in most applications. Do not saturate surfaces, puddle or build to wet film.

COVERAGE:

Actual coverage will vary depending on wood porosity and surface roughness.

APPROXIMATE

COVERAGE SQ. FT. /GAL.

Cedar, Oak, Redwood, Exotic woods
(i.e. Mahogany)

300-400

All other woods (i.e. Pine,
Pressure Treated Wood, Plywood)

200-300

One coat is sufficient.

DRYING TIME: Allow 24 to 48 hours. Penetration will vary depending on the porosity and water content of the surface. Wait a minimum of 30 days before painting over Thompson's® Wood Protector with oil-based paint.

CLEANUP: Clean brushes and equipment with detergent and water. Overspray or accidental spillage can be wiped up or cleaned immediately with detergent and water.

For sizes one gallon and less:

STORAGE AND DISPOSAL: Avoid storage near food or food products. Do