BOB MACDONALD Agent for INDUSCO LTD SCIENTIFIC & REGULATORY CONSULTANTS, INC PO Box 1014 COLUMBIA CITY, Indiana 46725

MAY 20 2013

ENVIROSYSTEMS® BIOSHIELD® 75 EPA Registration Number: 53053-7 Application Dated: February 22, 2013 Receipt Date: February 25, 2013

Dear Mr. MacDonald:

The following amendment, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), as amended, is acceptable.

Labeling amendment to delete certain application methods as prescribed in EPA letter dated January 25, 2013

General Comments

A stamped copy of the accepted labeling is enclosed. Submit 1 copy of your final printed label before distributing or selling the product bearing the revised labeling. Should you have any questions concerning this letter, please contact Emilia Oiguenblik at (703) 347 0199 or Velma Noble at (703) 308-6233.

Sincérely,

Product Manager (31)

Regulatory Management Branch I Antimicrobials Division (7510P)


Attachment: Stamped Label

			CONCURRENC	ΞS			
SYMBOL							
SURNAME	***************************************			***************************************	***************************************	*****************	
DATE				***********	***********		
EDA Com	1320-14 (1/00)	 	Printed on Day 1		·	OFFICE	AL FILE COP

Printed on Recycled Paper

EPA ...eg. No. 53053-7 02/22/2013 Page 1 of 11

ENVIROSYSTEMS® BIOSHIELD® 75 MICROBIOSTATIC AGENT*



KEEP OUT OF REACH OF CHILDREN

CAUTION

Active Ingredient: Octadecylaminodimethyltrihydroxysilyl propyl ammonium chloride0.7	5%
Other Ingredients:99.2	<u>5%</u>
Total Ingredients:	00%

EPA Reg. No. 53053-7

EPA Est. No. XXXX-XX-XXX

Net Contents: 32 fluid oz. {Only for sale to residential users}

1, 5, 30, 55, 275 gal.

Lot No.

* An microbiostatic agent is an agent that inhibits the growth of odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration, and algae. This product does not protect users or others against foodborne or disease causing bacteria or fungi.

Do not use in any application involving direct or indirect food or drinking water contact.

EPA r.g. No. 53053-7 02/22/2013 Page 2 of 11

FIRST AID

Have the product container or label with you when calling the poison control center or doctor, or going for treatment.

IF ON SKIN:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.
- Call poison control center or doctor for further treatment advice.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, and then continue rinsing.
- Call poison control center or doctor for treatment advice.

IF SWALLOWED:

- Call poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

4/12

EPA reg. No. 53053-7 02/22/2013 Page 3 of 11

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION. Causes moderate eye irritation. Avoid contact with skin, eyes and clothing. Harmful if inhaled or absorbed though the skin. Avoid breathing vapors or spray mist. Wear protective eyewear and protective clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum or using the toilet. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

<u>Commercial and Industrial uses</u>: This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

De-activation required during clean up if a spill occurs. De-activation of ENVIROSYSTEMS BIOSHIELD 75 can be achieved by the addition of anionic surfactant (such as soap, sulfonates, sulfates) in quantity equivalent to that of ENVIROSYSTEMS BIOSHIELD 75.

<u>Residential use</u>: This pesticide is toxic to fish. Do not contaminate water by cleaning of equipment or disposal of pesticide. Do not apply directly to water.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

Pesticide Storage: Store in original, tightly closed containers below 30°C (86°F) and above 0°C (32°F) in a secure area inaccessible to children and away from food or feed.

Pesticide Disposal:

{Residential use}

Wastes resulting from the use of this product may be disposed on site.

{Commercial/industrial use}

Wastes resulting from the use of this product may be disposed on site or at an approved waste disposal facility.

Container Disposal: Nonrefillable container. Do not reuse or refill this container, Triple rinse or pressure rinse container (or equivalent) promptly after emptying

{Insert applicable triple rinse instructions for container size below}

{5 gal or less}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

{More than 5 gal}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it

EPA (...g. No. 53053-7 02/22/2013 Page 4 of 11

back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

Then offer for recycling if available, or puncture and dispose in a sanitary landfill, or by other procedures approved by state and local authorities.

DIRECTIONS FOR USE Approved commercial and industrial applications

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Wear protective eyewear (goggles or face shield) and gloves when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry.

EnviroSystems BioShield 75 can be applied to organic or inorganic substrates by brushing, dipping, soaking, or spraying techniques.

The substrate can be dried at temperatures from ambient to a maximum of 160°C (320°F) to effect complete condensation of silanol groups and to remove water, solvents and/or traces of methanol from hydrolysis. Optimum application and drying conditions, such as time and temperature, should be determined for each application before use. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.

EnviroSystems BioShield 75 when used as a concrete additive is added directly during concrete preparation. Use 40 fluid ounces per cubic feet of concrete. Addition of EnviroSystems BioShield 75 reduces deterioration of sewer pipes and manholes by inhibiting microbiologically induced corrosion.

Approved commercial and industrial applications

The active ingredient in EnviroSystems BioShield 75 is effective against odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration, and algae as a static agent. EnviroSystems BioShield 75 can be used as a final bacteriostatic finish on the following items to impart bacteriostatic/fungistatic (mold and mildew) and algaestatic activity.

- Air filters for furnaces, air-conditioners, air purification devices, automobiles, recirculating air handling systems
- Air filters/materials
- Aquarium filter material
- Bed sheets, blankets, and bedspreads
- Buffer pads (abrasive and polishing)
- Carpets and draperies
- Concrete additive for sewer pipes, manholes and concrete sewer structures; not to be used in treatment of storm drains
- Concrete additive for repair and renewal of sewer pipes and manholes and concrete sewer structures (Not to be used in treatment of storm drains)
- Fiberfill for upholstery, sleeping bags, apparel, where the fiber is cotton, natural down, nylon, polyester, rayon, or wool
- Fiberglass ductboard
- Fire hose fabric
- Humidifier belts
- Mattress pads and ticking

EPA No. 53053-7 02/22/2013 Page 5 of 11

- Men's underwear and outerwear
- Non-woven disposable diapers
- Non-woven polyester
- Outerwear apparel (jackets, sweaters, sweatshirts, coats, raincoats, overcoats, jerseys, ponchos)
- Polyurethane and cellulose foam for household, industrial, and institutional mops
- Polyurethane and polyethylene foam, when covered
- Polyurethane foam for packaging and cushioning in non-food contact applications
- Polyurethane foam used as a growth medium for non-food crops and plants
- Pre-moistened towelettes and tissue wipes (these do not impart pesticidal properties)
- Roofing materials defined as shingles, roofing granules, wood shakes, felt, stone and synthetic overcoats
- Sand bags, tents, tarpaulins, sails and ropes
- Athletic and casual shoes
- Shoe insoles
- Shower curtains
- Socks comprised of nylon, nylon/orlon, cotton/nylon, linen/Lycra, acrylic/polypropylene/nylon/Lycra, wool/silk/nylon/Lycra and wool/acrylic/nylon/Lycra
- Throw rugs
- Toweling made of 100 percent cotton, 100 percent polyester, and blends of the two fibers
- Toilet tank and seat covers
- Umbrellas
- Upholstery made of acetates, acrylics, cotton, fiberglass, nylon, polyester, polyethylene, polyolefins, polypropylene, rayon, spandex, vinyl, and wool
- Vacuum cleaner bags and filters
- Vinyl paper-wallpaper for non-food contact surfaces
- Disposable wiping cloths that can be used for multiple purposes such as dusting or washing furniture, cars, walls, windows, floors, appliances, dishes, counter tops; the wiping cloths do not impart pesticide properties
- Women's hosiery
- Women's intimate apparel;

DIRECTIONS FOR USE

Approved commercial applications in homes, offices, automobiles and the following institutions: schools, hospitals, daycare centers, churches, correctional facilities.

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Wear protective eyewear (goggles or face shield) and gloves when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry. Clean surfaces prior to application.

The active ingredient in EnviroSystems BioShield 75 is effective against odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration, and algae as a static agent. EnviroSystems BioShield 75 can be used as a final bacteriostatic finish on the following items to impart bacteriostatic/fungistatic (mold and mildew) and algaestatic activity.

- Air filters for furnaces, air-conditioners, air purification devices, automobiles, recirculating air handling systems
- Air filters/materials
- Aquarium filter material

EPAg. No. 53053-7 02/22/2013 Page 6 of 11

- Bed sheets, blankets, and bedspreads
- Buffer pads (abrasive and polishing)
- Carpets and draperies
- Fiberfill for upholstery, sleeping bags, apparel, etc., where the fiber is cotton, natural down, nylon, polyester, rayon, or wool
- Fiberglass ductboard
- Fire hose fabric
- Humidifier belts
- Mattress pads and ticking
- Men's underwear and outerwear
- Non-woven polyester
- Outerwear apparel (jackets, sweaters, sweatshirts, coats, raincoats, overcoats, jerseys, ponchos)
- Polyurethane and cellulose foam for household, industrial, and institutional mops
- Polyurethane and polyethylene foam, when covered
- Polyurethane foam for packaging and cushioning in non-food contact applications
- Polyurethane foam used as a growth medium for non-food crops and plants
- Roofing materials defined as shingles, roofing granules, wood shakes, felt, stone and synthetic overcoats
- Sand bags, tents, tarpaulins, sails and ropes
- Athletic and casual shoes
- Shoe insoles
- Shower curtains
- Socks comprised of nylon, nylon/orlon, cotton/nylon, linen/Lycra, acrylic/polypropylene/nylon/Lycra, wool/silk/nylon/Lycra and wool/acrylic/nylon/Lycra
- Throw rugs
- Toweling made of 100 percent cotton, 100 percent polyester, and blends of the two fibers
- Toilet tank and seat covers
- Umbrellas
- Upholstery made of acetates, acrylics, cotton, fiberglass, nylon, polyester, polyethylene, polyolefins, polypropylene, rayon, spandex, vinyl, and wool
- Vacuum cleaner bags and filters
- Vinyl paper-wallpaper for non-food contact surfaces
- Disposable wiping cloths that can be used for multiple purposes such as dusting or washing furniture, cars, walls, windows, floors, appliances, dishes, counter tops; the wiping cloths do not impart pesticide properties
- Women's hosiery
- Women's intimate apparel

For Pump Spray Application: Using pump sprayer, spray entire area 4" – 6" from the surface making sure the surface is completely covered. Apply and then let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test for staining and color-fastness of fabrics and carpets by treating and drying a small, concealed area prior to application. One gallon of EnviroSystems BioShield 75 treats approximately 200 square feet. When treating coarser substrates, more EnviroSystems BioShield 75 may be required due to absorption. A fan may be used to assist in drying carpeting.

For Commercial Spray Application: For commercial application equipment (i.e. carpet/upholstery steamers, rotary jet extraction cleaners, pressure sprayers) apply and then let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test for staining and color-fastness of fabrics and carpets by treating and drying a small, concealed area prior to application. One gallon of EnviroSystems BioShield 75 treats approximately 200 square feet. When treating coarser substrates, more EnviroSystems BioShield 75 may be required due to absorption. Dry

EPA Reg. No. 53053-7 02/22/2013 Page 7 of 11

carpet areas and surfaces before re-entry and dry articles before use. A fan may be used to assist in drying carpeting.

For Dipping/Soaking Application: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Completely submerge item in solution for 3 minutes. Remove item and dry. Test for staining and color-fastness of fabrics by treating and drying a small, concealed area prior to application. Do not reuse solution after dipping/soaking.

The substrate can be dried at room temperatures or at temperatures to a maximum of 160°C (320°F), for example in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.

DIRECTIONS FOR USEFor residential applications

It is a violation of Federal Law to use this product in a manner inconsistent with its label.

Wear protective eyewear (goggles or face shield), gloves, and protective clothing when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry. Clean surfaces prior to application.

Approved residential uses

The active ingredient in EnviroSystems BioShield 75 is effective against odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae as a static agent.

	Pest controlled	Method of Application
Bedsheets, blankets, bedspreads,	Odor causing	DIP/SOAK : Use appropriate sized wash basin or
curtains, draperies (washable	bacteria, bacteria	tub for dipping/soaking the item you are treating.
only), underwear, socks, intimate	which cause	Use enough EnviroSystems BioShield 75 to
apparel, hosiery, throw rugs,	staining and	completely submerge item. Keep item in solution
toweling, toilet tank covers,	discoloration, and	for 3 minutes. Remove item and wring excess
shower curtains, shoe insoles,	fungi (mold and	liquid. Drying may be attained by dripping dry or
outerwear apparel (jackets,	∖ mildew)	wringing excess liquid from treated item. For
sweaters, sweatshirts, coats,		larger items (e.g., bedspreads, curtains, draperies),
raincoats, overcoats, jerseys,		place in washing machine on spin cycle to aid in
ponchos). EnviroSystems		the removal of excess liquid. Test staining and
BioShield 75 can be applied to		color-fastness of fabric and carpets by treating
fabrics made of acetates, acrylics,		and drying a small concealed area prior to
cotton, fiberglass, linen, Lycra,		application. Do not reuse solution after
nylon, orlon, polyester,		dipping/soaking. Dry treated articles before use.
polyethylene, polyolefins,		Substrates can be hang-dried at room temperature
polypropylene, rayon, silk,		or at temperatures to a maximum of 160°C
spandex, vinyl, and wool.		(320°F), (for example in a clothes dryer).
		Remove excess liquid before attempting to dry in
*		a clothes dryer. If necessary, reapply
,		EnviroSystems BioShield 75 every three months
		or when odor, staining and discoloration due to
		bacteria, mold stains, and mildew stains return.

EPA Reg. No. 53053-7 02/22/2013 Page 8 of 11

		rage o of 11
•		SPRAY: Clean surface prior to application.
		Using a trigger pump sprayer or pressure sprayer,
		spray the entire surface area 4" – 6" from the
	•	surface making sure the surface is completely
·		covered. Let stand until dry or let stand 3 minutes
·		and wipe dry with cloth or sponge. If spotting
		occurs, wipe with moist cloth or sponge. Test
		staining and color-fastness of fabric by treating
* •		and drying a small, concealed area prior to
		application. If necessary, reapply EnviroSystems
		BioShield 75 every three months or when odor,
		staining and discoloration due to bacteria, mold
		stains and mildew stains return.
1	Pest controlled	Method of Application
Air filters and air filter material	Odor causing	SPRAY: When treating filters, remove filter
for	bacteria, bacteria	from the unit. Using a trigger pump sprayer or
 Furnaces, air 	which cause	pressure sprayer, spray the entire surface area 4"
conditioners	staining and	-6" from the surface making sure the surface is
 Air purification systems 	discoloration, and	completely covered. Apply and then let stand
 Automobiles 	fungi (mold and	until dry. If necessary, reapply EnviroSystems
 Recirculating air 	mildew), and	BioShield 75 every three months or when odor,
handling systems	algae.	staining and discoloration due to bacteria, mold
Vacuum cleaner filters		stains, mildew stains and algae stains return.
		,
• Aquariums	Dood controlled	Mathad of Application
Competing	Pest controlled	Method of Application
Carpeting	Odor causing	SPRAY: Apply to clean carpet surface. Using a
	bacteria, bacteria	trigger pump sprayer or pressure sprayer, spray
	which cause	the entire surface area 4" – 6" from the surface
	staining and	making sure the surface is completely covered.
	discoloration, and	For rotary jet extraction cleaners and carpet
	fungi (mold and	steamers, add EnviroSystems BioShield 75
•	mildew)	directly to the cleaning tank, then operate the
		equipment in accordance with manufacturer's
·		instructions. Apply and then let stand until dry.
•		Test staining and color-fastness of carpets by
		treating and drying a small, concealed area prior
		to application. EnviroSystems BioShield 75
		treats approximately 200 square feet per gallon
		(50 square feet per quart). When treating coarser
		substrates (e.g. wool carpeting), more
		EnviroSystems BioShield 75 may be required due
		to absorption. Dry carpet areas and surfaces
		before re-entry. A fan may be used to assist in
•		drying carpeting. Remove children and pets from
		treated areas until completely dried. If necessary,
		reapply EnviroSystems BioShield 75 every three
		months or when odor, staining and discoloration
		due to bacteria, mold stains and mildew stains
	Dogt	return. Method of Application
	Pest controlled	Method of Application
Mattress pad and mattress ticking	Odor causing	SPRAY: Clean surfaces prior to application.
and upholstery composed of	bacteria, bacteria	Using a trigger pump sprayer, spray the entire
acetates, acrylics, cotton,	which cause	surface area $4"-6"$ from the surface making sure
fiberglass, nylon, polyester,	staining and	the surface is completely covered. Apply and
polyethylene, polyolefins,	discoloration, and	then let stand until dry or let stand 3 minutes and

EPA No. 53053-7 02/22/2013 Page 9 of 11

winyl, wool; fiberfill to be used in upholstery, sleeping bags, apparel, where the fiber is cotton, natural down, nylon, rayon or wool. Men applying to mattress pads and ticking do not soak. Remove children and pets from treated area until completely dried. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return. Pest controlled			Page 9 of 11
upholstery, sleeping bags, apparel, where the fiber is cotton, natural down, nylon, rayon or wool. Pest controlled Tents, tarpaulins, sails, ropes Odor causing bacteria, bacteria which cause staining and discoloration, fingi (mold and mildew) and algae. Pest controlled Tents, tarpaulins, sails, ropes Odor causing bacteria, bacteria which cause staining and discoloration, fingi (mold and mildew) and algae. Pest controlled Tents, tarpaulins, sails, ropes Odor causing bacteria, bacteria, which cause staining and discoloration, fingi (mold and mildew) and algae. Pest controlled Tents, tarpaulins, sails, ropes Odor causing bacteria, bacteria, which cause staining and dosloration, fingi (mold and mildew) and algae. Pest controlled Tents, tarpaulins, sails, ropes Odor causing bacteria, bacteria, which cause staining and dosloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°FF); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply: EnviroSystems BioShield 75, let stain grand adiscoloration, fingi (mold and mildew) and algae. Pest controlled Odor causing bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Pest controlled Odor causing the firm of t	polypropylene, rayon, spandex,	fungi (mold and	wipe dry with cloth or sponge. If spotting occurs,
a small, concealed area prior to application. When applying to mattress pads and ticking do not soak. Remove children and pets from treated area until completely dried. If necessary, reapply EnviroSystems BioShield 75 to every three months or when odor, staining and discoloration due to bacteria, mold stains and mildew stains return. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria overed. Let stand until dry or let stand 3 mimutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply. EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Roofing materials (such as shingles, roofing g		mildew)	
wool. When applying to mattress pads and ticking do not soak. Remove children and pets from treated area until completely dried. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. SPRAY: Clean surface prior to application. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4" - 6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fabric by treating and drying a small, concealed area prior to application. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°P); (for example in a clothes dryer.) Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 very three months or when odor, staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria which cause stains return. Pest controlled Odor causing and discoloration due to bacteria, mold stains, mildew stains and algae stains return.		,	
wool. Pest controlled Odor causing bacteria, hacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration of the stain gand discoloration of the stain gand discoloration of the stain gand color-fastness of fabric by treating and drying a small, concealed area prior to application. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria which cause stains return. Pest controlled of Application Provincysystems BioShield 75 to completely covered. After applying EnviroSystems BioShield 75 terest approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
rents, tarpaulins, sails, ropes Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. SPRAY: Clean surface prior to application. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4" - 6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer.). Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. Remove excess liquid be	· •		
Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4" – 6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and mildew) and algae. Beauting and algae and riving a small, concealed area prior to application. If necessary, reapply EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer.), Remove excess liquid before attempting to dry in a clothes dryer.) Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration due to bacteria, mold stains, mildew stains and mildew stand mildew stand mildew part of prior to application. Using a pressure sprayer, spray the entire surface area for 12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration fue to bacteria, bacteria which cause staining and discoloration fue to bacteria, bacteria which cause staining and discoloration fue to bacteria, bacteria which cause staining and discoloration fue to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. SPRAY: Method of Application. SPRAY: Herbod of Application.	wool.		
rents, tarpaulins, sails, ropes Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Dill'SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae. Dill'SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F), (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply—EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing the the surface is completely covered. After applying EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 treats approximately 200 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae.			
Tents, tarpaulins, sails, ropes Dest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking. Use enough EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems glioshield 75 every three months or when odor, staining and discoloration due to bacteria, bacteria which cause staining and discoloration. Using a pressure sprayer, spray the entire surface are a 4" - 6" from the surface making sure the surface as fabric by treating and discoloration due to bacteria, bacteria which cause staining and discoloration. Using a pressure sprayer, spray the entire surface are a 6" - 16" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply. EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae.			
Tents, tarpaulins, sails, ropes Dodor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer.) Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer.) Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae.			
Tents, tarpaulins, sails, ropes Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. SPRAY: Clean surface prior to application. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4" – 6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fabric by treating and drying a small, concealed area prior to application. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration for the surface area 6"-12" from the stand and mildew) and algae. Pest controlled odor causing bacteria, bacteria which cause staining and discoloration for the surface area 6"-12" from the stand and mildew stains and algae stains return. Pest controlled odor causing bacteria, bacteria which cause staining and discoloration of the surface area 6"-12" from the surface area 6"-12" fr			
bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Biggs, roofing granules, wood shakes, felt, stone, synthetic overcoats) Botactria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Botactria, bacteria, bacteria, which cause staining and discoloration which cause staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. Biggs, roofing granules, wood shakes, felt, stone, synthetic overcoats) Botactria, bacteria which cause staining and discoloration synthetic overcoats Botactria, bacteria which cause staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. Using a trigger pump sprayer or pressure sprayer, sprayer, spray the surface area 4" – 6" for form the surface area 6" - 12" from the surface is completely covered. Let stand until dry. EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply. EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, botacteria, bacteria, bacteria which cause stains return.			
which cause staining and discoloration, fungi (mold and mildew) and algae. spray the entire surface area 4" – 6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fabric by treating and drying a small, concealed area prior to application. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Method of Application Pest controlled Method of Application SPRAY: Make sure the roof is clean prior to bacteria, mold stains, mildew stains, and algae stains return. SPRAY: Make sure the roof is clean prior to applying EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae.	Tents, tarpaulins, sails, ropes		1 11
staining and discoloration, fungi (mold and mildew) and algae. In the properties of			
discoloration, fungi (mold and mildew) and algae. discoloration, fungi (mold and mildew) and algae. algae. discoloration, fungi (mold and mildew) and algae. algae. discoloration, fungi (mold and mildew) and algae. discoloration due to bacteria, bacteria which cause staining and discoloration fungi (mold and mildew) and algae. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) discoloration, fungi (mold and mildew) and algae. discoloration, fungi (mold and mildew) proviewed a staining and discoloration due to bacteria, bacteria which cause staining and discoloration fungi (mold and mildew) and algae. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) An ent stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. Test staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for tree minutes. Remove item and wring excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75, let stand until dry or let stand and sincoloration due to bacteria, bacteri			
fungi (mold and mildew) and algae. and wipe dry with cloth or sponge. Test stating and color-fastness of fabric by treating and drying a small, concealed area prior to application. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and dolor-fastness of fabric by treating and drying a small, concealed area prior to application. If necessary, reapply EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Odor causing bacteria, bacteria abcteria which cause staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor sausing bacteria, bacteria abcteria which cause staining and discoloration. Using a pressure sprayer, spray the entire surface area 6°-12° from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fastness of samal, concealed area prior to application. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Area applying EnviroSystems BioShield 75 let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
staining and color-fastness of fabric by treating and drying a small, concealed area prior to application. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Pest controlled. Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Pest controlled. Odor causing bacteria, bacteria which cause staining and discoloration of the surface area 6°-12° from the surface area 6°-12°			
and drying a small, concealed area prior to application. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. PRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6°-12° from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, terest approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
application. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Method of Application SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6°-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.		algae.	
BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6°-12° from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, and stains, mildew stains, and algae stains return. Pest controlled Pest controlled Method of Application SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6°-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
stains, mildew stains and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Pest controlled Pest controlled Pest controlled SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6°-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6°-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			stains, mildew stains and algae stains return.
tub for dipping/soaking the item you are treating. Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.	•		DID/COAIZ II
Use enough EnviroSystems BioShield 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Method of Application SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae.			
completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Odor causing bacteria, mold stains, mildew stains, and algae staining and discoloration. Using a pressure sprayer, spray the entire surface area 6°-12" from the surface making sure the surface area 6°-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75 treats approximately 200 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6°-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6°-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.	·		
dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Pest controlled Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Fest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Final provided After applying EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.	•		
(320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration. Using a pressure sprayer, spray the entire surface area 6°-12° from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Frank Emove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 treats approximately 200 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			· · · · · · · · · · · · · · · · · · ·
a clothes dryer. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. France staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
bacteria, mold stains, mildew stains, and algae stains return. Pest controlled Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.	·		
Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.		,	
Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) Pest controlled Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. Pest controlled Odor causing bacteria, bacteria application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			,
Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.	Į.	Pest controlled	
shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats) bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae. bacteria, bacteria application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.	Roofing materials (such as		
shakes, felt, stone, synthetic overcoats) which cause staining and discoloration, fungi (mold and mildew) and algae. which cause staining and discoloration, fungi (mold and mildew) and algae. which cause staining and discoloration are the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.	,		
overcoats) staining and discoloration, fungi (mold and mildew) and algae. staining and discoloration, fungi (mold and mildew) and algae. staining sure the surface is completely covered. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.		1	
discoloration, fungi (mold and mildew) and algae. After applying EnviroSystems BioShield 75, let stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.		staining and	
fungi (mold and mildew) and algae. stand until dry. EnviroSystems BioShield 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.	,		
mildew) and algae. treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
algae. per gallon (50 square feet per quart). If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.			
every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.		•	
discoloration due to bacteria, mold stains, mildew stains, and algae stains return.	,		
stains, and algae stains return.			
		Pest controlled	Method of Application

EPA reg. No. 53053-7 02/22/2013 Page 10 of 11

Buffer pads (polishing and abrasive), Polyurethane and cellulose foam for household mops, vacuum cleaner bags, umbrellas, casual shoes, athletic shoes	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	SPRAY: Clean surface prior to application. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4" – 6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains and mildew stains return.
1	Pest controlled	Method of Application
Tubs, glazed tiles, vanity tops, shower curtains, shower stalls (areas), sinks, washable walls, wall paper for non-food contact, floors, window sills, cabinets, garbage cans, appliances, refrigerators (exterior), fiberglass, formica, glazed tiles, glazed porcelain, synthetic marble, plastic, vinyl.	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	SPRAY: Using a trigger pump sprayer, spray the entire surface area 4"-6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. If necessary, reapply EnviroSystems BioShield 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return.

Imparts microbiostatic properties.

Use on carpet and upholstery to inhibit odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration.

Unscented.

Use on carpet and upholstery to inhibit the growth of odor causing bacteria.

Use on carpet and upholstery to inhibit the growth of bacteria which cause staining and discoloration. Use on carpet and upholstery to inhibit the growth of fungi (mold and mildew) which cause staining and discoloration.

Use on carpet and upholstery to inhibit the growth of odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration.

Provides an invisible microbiostatic coating to inhibit the growth of odor causing bacteria.

Provides an invisible microbiostatic coating to inhibit the growth of bacteria which cause staining and discoloration.

Provides an invisible microbiostatic coating to inhibit the growth of fungi (mold and mildew) which cause staining and discoloration.

Provides an invisible microbiostatic coating to inhibit the growth of algae.

Provides an invisible microbiostatic coating to inhibit the growth of odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration and algae. bacteria which cause staining and discoloration, fungi (mold and mildew) and algae.

Prevents deterioration caused by bacteria and fungi (mold and mildew) which cause staining and discoloration.

Inhibits deterioration caused by bacteria.

Resists development of microbial odors.

Resists development of stains and discoloration due to bacteria.

Resists development of stains due to fungi (mold and mildew) which cause staining and discoloration. Resists stains due to algae.

Resists development of microbial odors, stains and discoloration due to bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration and algae. Provides/creates an invisible barrier to inhibit the growth of odor causing bacteria.

Provides/creates an invisible barrier to inhibit the growth of bacteria which cause staining and discoloration.

EPA r. g. No. 53053-7 02/22/2013 Page 11 of 11

Provides/creates an invisible barrier to inhibit the growth of fungi (mold and mildew) which cause staining and discoloration.

Provides/creates an invisible barrier to inhibit the growth of algae.

Provides/creates an invisible barrier to inhibit the growth of odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration and algae. Inhibits the growth of odor causing bacteria between cleanings.

Inhibits the growth of bacteria which cause staining and discoloration between cleanings.

Inhibits the growth of fungi (mold and mildew) which cause staining and discoloration between cleanings. Inhibits the growth of algae between cleanings.

Inhibits the growth of odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration and algae between cleanings.

Mold, mildew, odor protector and inhibitor.

EnviroSystems BioShield 75 is an antimicrobial agent effective against odor causing bacteria.

EnviroSystems BioShield 75 is an antimicrobial agent effective against bacteria which cause staining and discoloration.

EnviroSystems BioShield 75 is an antimicrobial agent effective against fungi (mold and mildew) which cause staining and discoloration.

EnviroSystems BioShield 75 is an antimicrobial agent effective against algae.

EnviroSystems BioShield 75, an antimicrobial agent, controls the source of odors on surfaces in the home, in the bathroom, in the kitchen.

Bacteriostatic, fungistatic (mold and mildew), algaestatic.

EnviroSystems BioShield 75, an antimicrobial agent, inhibits smelly odors caused by mold and mildew that can grow even in the cleanest of homes.

EnviroSystems BioShield 75, an antimicrobial agent, inhibits the growth of odor causing bacteria. Effective on hard non-porous washable bathroom and kitchen surfaces and fixtures around the home. Effective on modern hard non-porous washable surfaces made of fiberglass, glazed porcelain, Formica®, stainless steel, synthetic marble.

FOR MORE INFORMATION CONCERNING THIS PRODUCT, PLEASE CONSULT THE MATERIAL SAFETY DATA SHEET (MSDS). THE MSDS CAN BE OBTAINED BY WRITING:

Indusco Ltd. 2319 Joe Brown Drive Greensboro, NC 27405 (336) 375-7555 www.induscoltd.com

IMPORTANT: WARRANTY AND DISCLAIMER INFORMATION

Indusco Ltd warrants that the product conforms to its chemical description and is reasonably fit for the purposes stated in this bulletin when used in accordance with directions under normal conditions of use; but this warranty of fitness for a particular purpose does not extend to the use of this product contrary to bulletin instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to the seller, and buyer assumes the risk of any such use.

INDUSCO LTD SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING THE WARRANTY OF MERCHANTABILITY.