

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

August 4, 2016

Cinda L. Bell Agent for IndusCo., Ltd. IndusCo, Ltd. 2319 Joe Brown Drive Greensboro, NC 27405

Subject: Label and CSF Amendment – Modify Basic CSF and Minor Label Changes

Product Name: BST Protectant RTU 75 EPA Registration Number: 53053-24 Application Date: April 14, 2016

Decision Number: 516305

Dear Ms. Bell:

The amended label and CSF referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, are acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Please note that the record for this product currently contains the following CSF:

Basic CSF dated 05/18/2016

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false

Page 2 of 2 EPA Reg. No. 53053-24 Decision No. 516305

or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, you may contact Joe Daniels at (703) 347-8669 or via email at daniels.joseph@epa.gov.

Sincerely,

Eric Miederhoff
Product Manager 31

Regulatory Management Branch I Antimicrobials Division (7510P) Office of Pesticide Programs

Date: August 4, 2016

Enclosure

ACCEPTED

08/04/2016

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 53053-24

EPA Reg. No. 53053-24 04/14/2016 Page 1 of 12

BST PROTECTANT RTU 75 MICROBIOSTATIC AGENT*

KEEP OUT OF REACH OF CHILDREN **CAUTION**

Active Ingredient: Octadecylaminodimethyltrihydroxysilyl propyl ammonium chloride	0.75%
Other Ingredients:	. <u>99.25%</u>
Total Ingredients:	100.00%

EPA Reg. No. 53053-24 EPA Est. No. XXXX-XX-XXX

Net Contents: 32 fluid oz.{Only for sale to residential users} 1, 5, 30, 55, 275 gal.

Lot No.

* An microbiostatic agent is an agent that inhibits the growth of odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration, and algae. This product does not protect users or others against foodborne or disease causing bacteria or fungi.

Do not use in any application involving direct or indirect food or drinking water contact.

FIRST AID

Have the product container or label with you when calling the poison control center or doctor, or going for treatment.

IF ON SKIN:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.
- Call poison control center or doctor for further treatment advice.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, and then continue rinsing.
- Call poison control center or doctor for treatment advice.

IF SWALLOWED:

- Call poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION. Causes moderate eye irritation. Avoid contact with skin, eyes and clothing. Harmful if inhaled or absorbed though the skin. Avoid breathing vapors or spray mist. Wear protective eyewear and protective clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum or using the toilet. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

<u>Commercial and Industrial uses</u>: This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

De-activation required during clean up if a spill occurs. De-activation of BST PROTECTANT RTU 75 can be achieved by the addition of anionic surfactant (such as soap, sulfonates, sulfates) in quantity equivalent to that of BST PROTECTANT RTU 75.

Residential use: This pesticide is toxic to fish. Do not contaminate water by cleaning of equipment or disposal of pesticide. Do not apply directly to water.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

Pesticide Storage: Store in original, tightly closed containers below 30°C (86°F) and above 0°C (32°F) in a secure area inaccessible to children and away from food or feed.

Pesticide Disposal:

{Residential use} Wastes resulting from the use of this product may be disposed on site.

{Commercial/industrial use} Wastes resulting from the use of this product may be disposed on site or at an approved waste disposal facility.

Container Handling:

{Residential use} Securely wrap original container in several layers of newspaper and discard in trash. {Commercial/industrial use} Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying.

{Insert applicable triple rinse instructions for container size below}

{5 gal or less}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

{More than 5 gal}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ½ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

Then offer for recycling if available, or puncture and dispose in a sanitary landfill, or by other procedures approved by state and local authorities.

DIRECTIONS FOR USE Approved commercial and industrial applications

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Wear protective eyewear (goggles or face shield) and gloves when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry.

BST PROTECTANT RTU 75 can be applied to organic or inorganic substrates by brushing, dipping, padding, soaking, spraying or by using foam finishing techniques.

The substrate can be dried at temperatures from ambient to a maximum of 160°C (320°F) to effect complete condensation of silanol groups and to remove water, solvents and/or traces of methanol from hydrolysis. Optimum application and drying conditions, such as time and temperature, should be determined for each application before use. If necessary, reapply BST PROTECTANT RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.

BST PROTECTANT RTU 75 when used as a concrete additive is added directly during concrete preparation. Use 40 fluid ounces per cubic feet of concrete. Addition of BST PROTECTANT RTU 75 reduces deterioration of sewer pipes and manholes by inhibiting microbiologically induced corrosion.

Approved commercial and industrial applications

The active ingredient in BST PROTECTANT RTU 75 is effective against odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration, and algae as a static agent. BST PROTECTANT RTU 75 can be used as a final bacteriostatic finish on the following items to impart bacteriostatic/fungistatic (mold and mildew) and algaestatic activity.

- Air filters for furnaces, air-conditioners, air purification devices, automobiles, recirculating air handling systems
- Air filters/materials
- Aquarium filter material
- Bed sheets, blankets, and bedspreads
- Buffer pads (abrasive and polishing)
- Carpets and draperies
- Concrete additive for sewer pipes, manholes and concrete sewer structures; not to be used in treatment of storm drains
- Concrete additive for repair and renewal of sewer pipes and manholes and concrete sewer structures (Not to be used in treatment of storm drains)
- Fiberfill for upholstery, sleeping bags, apparel, where the fiber is cotton, natural down, nylon, polyester, rayon, or wool

- Fiberglass ductboard
- Fire hose fabric
- Humidifier belts
- Mattress pads and ticking
- Men's underwear and outerwear
- Non-woven disposable diapers
- Non-woven polyester
- Outerwear apparel (jackets, sweaters, sweatshirts, coats, raincoats, overcoats, jerseys, ponchos)
- Polyurethane and cellulose foam for household, industrial, and institutional mops
- Polyurethane and polyethylene foam, when covered
- Polyurethane foam for packaging and cushioning in non-food contact applications
- Polyurethane foam used as a growth medium for non-food crops and plants
- Pre-moistened towelettes and tissue wipes (these do not impart pesticidal properties)
- Roofing materials defined as shingles, roofing granules, wood shakes, felt, stone and synthetic overcoats
- Sand bags, tents, tarpaulins, sails and ropes
- Athletic and casual shoes
- Shoe insoles
- Shower curtains
- Socks comprised of nylon, nylon/orlon, cotton/nylon, linen/Lycra, acrylic/polypropylene/nylon/Lycra, wool/silk/nylon/Lycra and wool/acrylic/nylon/Lycra
- Throw rugs
- Toweling made of 100 percent cotton, 100 percent polyester, and blends of the two fibers
- Toilet tank and seat covers
- Umbrellas
- Upholstery made of acetates, acrylics, cotton, fiberglass, nylon, polyester, polyethylene, polyolefins, polypropylene, rayon, spandex, vinyl, and wool
- Vacuum cleaner bags and filters
- Vinyl paper-wallpaper for non-food contact surfaces
- Disposable wiping cloths that can be used for multiple purposes such as dusting or washing furniture, cars, walls, windows, floors, appliances, dishes, counter tops; the wiping cloths do not impart pesticide properties
- Women's hosiery
- Women's intimate apparel

DIRECTIONS FOR USE

Approved commercial applications in homes, offices, automobiles and the following institutions: schools, hospitals, daycare centers, churches, correctional facilities.

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Wear protective eyewear (goggles or face shield) and gloves when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry. Clean surfaces prior to application.

The active ingredient in BST PROTECTANT RTU 75 is effective against odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration, and algae as a static agent. BST PROTECTANT RTU 75 can be used as a final bacteriostatic finish on the following items to impart bacteriostatic/fungistatic (mold and mildew) and algaestatic activity.

- Air filters for furnaces, air-conditioners, air purification devices, automobiles, recirculating air handling systems
- Air filters/materials
- Aquarium filter material
- Bed sheets, blankets, and bedspreads
- Buffer pads (abrasive and polishing)
- Carpets and draperies
- Fiberfill for upholstery, sleeping bags, apparel, etc., where the fiber is cotton, natural down, nylon, polyester, rayon, or wool
- Fiberglass ductboard
- Fire hose fabric
- Humidifier belts
- Mattress pads and ticking
- Men's underwear and outerwear
- Non-woven polyester
- Outerwear apparel (jackets, sweaters, sweatshirts, coats, raincoats, overcoats, jerseys, ponchos)
- Polyurethane and cellulose foam for household, industrial, and institutional mops
- Polyurethane and polyethylene foam, when covered
- Polyurethane foam for packaging and cushioning in non-food contact applications
- Polyurethane foam used as a growth medium for non-food crops and plants
- Roofing materials defined as shingles, roofing granules, wood shakes, felt, stone and synthetic overcoats
- Sand bags, tents, tarpaulins, sails and ropes
- Athletic and casual shoes
- Shoe insoles
- Shower curtains
- Socks comprised of nylon, nylon/orlon, cotton/nylon, linen/Lycra, acrylic/polypropylene/nylon/Lycra, wool/silk/nylon/Lycra and wool/acrylic/nylon/Lycra
- Throw rugs
- Toweling made of 100 percent cotton, 100 percent polyester, and blends of the two fibers
- Toilet tank and seat covers
- Umbrellas
- Upholstery made of acetates, acrylics, cotton, fiberglass, nylon, polyester, polyethylene, polyolefins, polypropylene, rayon, spandex, vinyl, and wool
- Vacuum cleaner bags and filters
- Vinyl paper-wallpaper for non-food contact surfaces
- Disposable wiping cloths that can be used for multiple purposes such as dusting or washing furniture, cars, walls, windows, floors, appliances, dishes, counter tops; the wiping cloths do not impart pesticide properties
- Women's hosiery
- Women's intimate apparel

For Pump Spray Application: Using pump sprayer, spray entire area 4" – 6" from the surface making sure the surface is completely covered. Apply and then let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test for staining and color-fastness of fabrics and carpets by treating and drying a small, concealed area prior to application. One gallon of BST PROTECTANT RTU 75 treats approximately 200 square feet. When treating coarser substrates, more BST PROTECTANT RTU 75 may be required due to absorption. A fan may be used to assist in drying carpeting.

For Commercial Spray Application: For commercial application equipment (i.e. carpet/upholstery steamers, rotary jet extraction cleaners, pressure sprayers) apply and then let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test for staining and color-fastness of fabrics and carpets by treating and drying a small, concealed area prior to application. One gallon of BST PROTECTANT RTU 75 treats approximately 200 square feet. When treating coarser substrates, more BST PROTECTANT RTU 75 may be required due to absorption. Dry carpet areas and surfaces before re-entry and dry articles before use. A fan may be used to assist in drying carpeting.

For Dipping/Soaking Application: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough BST PROTECTANT RTU 75 to completely submerge item. Completely submerge item in solution for 3 minutes. Remove item and dry. Test for staining and color-fastness of fabrics by treating and drying a small, concealed area prior to application. Do not reuse solution after dipping/soaking.

The substrate can be dried at room temperatures or at temperatures to a maximum of 160°C (320°F), for example in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply BST PROTECTANT RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.

DIRECTIONS FOR USEFor residential applications

It is a violation of Federal Law to use this product in a manner inconsistent with its label.

Wear protective eyewear (goggles or face shield), gloves, and protective clothing when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry. Clean surfaces prior to application.

Approved residential uses

The active ingredient in BST PROTECTANT RTU 75 is effective against odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae as a static agent.

	Pest controlled	Method of Application
Bedsheets, blankets, bedspreads,	Odor causing	DIP/SOAK : Use appropriate sized wash basin or
curtains, draperies (washable	bacteria, bacteria	tub for dipping/soaking the item you are treating.
only), underwear, socks, intimate	which cause	Use enough BST PROTECTANT RTU 75 to
apparel, hosiery, throw rugs,	staining and	completely submerge item. Keep item in solution
toweling, toilet tank covers,	discoloration, and	for 3 minutes. Remove item and wring excess
shower curtains, shoe insoles,	fungi (mold and	liquid. Drying may be attained by dripping dry or
outerwear apparel (jackets,	mildew)	wringing excess liquid from treated item. For
sweaters, sweatshirts, coats,		larger items (e.g., bedspreads, curtains, draperies),
raincoats, overcoats, jerseys,		place in washing machine on spin cycle to aid in
ponchos). BST PROTECTANT		the removal of excess liquid. Test staining and
RTU 75 can be applied to fabrics		color-fastness of fabric and carpets by treating
made of acetates, acrylics, cotton,		and drying a small concealed area prior to
fiberglass, linen, Lycra, nylon,		application. Do not reuse solution after
orlon, polyester, polyethylene,		dipping/soaking. Dry treated articles before use.
polyolefins, polypropylene,		Substrates can be hang-dried at room temperature
rayon, silk, spandex, vinyl, and		or at temperatures to a maximum of 160°C

	T	(22,007) (6 1 1 1 1 1 1 1 1
wool.		(320°F), (for example in a clothes dryer).
		Remove excess liquid before attempting to dry in
		a clothes dryer. If necessary, reapply BST
		PROTECTANT RTU 75 every three months or
		when odor, staining and discoloration due to
		bacteria, mold stains, and mildew stains return.
		SPRAY: Clean surface prior to application.
		Using a trigger pump sprayer or pressure sprayer,
		spray the entire surface area 4" – 6" from the
		surface making sure the surface is completely
		covered. Let stand until dry or let stand 3 minutes
		and wipe dry with cloth or sponge. If spotting
		occurs, wipe with moist cloth or sponge. Test
		staining and color-fastness of fabric by treating
		and drying a small, concealed area prior to
		application. If necessary, reapply BST
		PROTECTANT RTU 75 every three months or
		when odor, staining and discoloration due to
		bacteria, mold stains and mildew stains return.
	Pest controlled	Method of Application
Air filters and air filter material	Odor causing	SPRAY : When treating filters, remove filter
for	bacteria, bacteria	from the unit. Using a trigger pump sprayer or
 Furnaces, air 	which cause	pressure sprayer, spray the entire surface area 4"
conditioners	staining and	-6" from the surface making sure the surface is
 Air purification systems 	discoloration, and	completely covered. Apply and then let stand
 Automobiles 	fungi (mold and	until dry. If necessary, reapply BST
 Recirculating air 	mildew), and	PROTECTANT RTU 75 every three months or
handling systems	algae.	when odor, staining and discoloration due to
 Vacuum cleaner filters 		bacteria, mold stains, mildew stains and algae
 Aquariums 		stains return.
	Pest controlled	Method of Application
Carpeting	Odor causing	SPRAY : Apply to clean carpet surface. Using a
	bacteria, bacteria	trigger pump sprayer or pressure sprayer, spray
	which cause	the entire surface area 4 " -6 " from the surface
	staining and	making sure the surface is completely covered.
	discoloration, and	For rotary jet extraction cleaners and carpet
	fungi (mold and	steamers, add BST PROTECTANT RTU 75
	mildew)	directly to the cleaning tank, then operate the
		equipment in accordance with manufacturer's
	1	instructions. Apply and then let stand until dry.
		Test staining and color-fastness of carpets by
		Test staining and color-fastness of carpets by treating and drying a small, concealed area prior
		Test staining and color-fastness of carpets by treating and drying a small, concealed area prior to application. BST PROTECTANT RTU 75
		Test staining and color-fastness of carpets by treating and drying a small, concealed area prior to application. BST PROTECTANT RTU 75 treats approximately 200 square feet per gallon
		Test staining and color-fastness of carpets by treating and drying a small, concealed area prior to application. BST PROTECTANT RTU 75 treats approximately 200 square feet per gallon (50 square feet per quart). When treating coarser
		Test staining and color-fastness of carpets by treating and drying a small, concealed area prior to application. BST PROTECTANT RTU 75 treats approximately 200 square feet per gallon (50 square feet per quart). When treating coarser substrates (e.g. wool carpeting), more BST
		Test staining and color-fastness of carpets by treating and drying a small, concealed area prior to application. BST PROTECTANT RTU 75 treats approximately 200 square feet per gallon (50 square feet per quart). When treating coarser substrates (e.g. wool carpeting), more BST PROTECTANT RTU 75 may be required due to
		Test staining and color-fastness of carpets by treating and drying a small, concealed area prior to application. BST PROTECTANT RTU 75 treats approximately 200 square feet per gallon (50 square feet per quart). When treating coarser substrates (e.g. wool carpeting), more BST PROTECTANT RTU 75 may be required due to absorption. Dry carpet areas and surfaces before
		Test staining and color-fastness of carpets by treating and drying a small, concealed area prior to application. BST PROTECTANT RTU 75 treats approximately 200 square feet per gallon (50 square feet per quart). When treating coarser substrates (e.g. wool carpeting), more BST PROTECTANT RTU 75 may be required due to absorption. Dry carpet areas and surfaces before re-entry. A fan may be used to assist in drying
		Test staining and color-fastness of carpets by treating and drying a small, concealed area prior to application. BST PROTECTANT RTU 75 treats approximately 200 square feet per gallon (50 square feet per quart). When treating coarser substrates (e.g. wool carpeting), more BST PROTECTANT RTU 75 may be required due to absorption. Dry carpet areas and surfaces before re-entry. A fan may be used to assist in drying carpeting. Remove children and pets from treated
		Test staining and color-fastness of carpets by treating and drying a small, concealed area prior to application. BST PROTECTANT RTU 75 treats approximately 200 square feet per gallon (50 square feet per quart). When treating coarser substrates (e.g. wool carpeting), more BST PROTECTANT RTU 75 may be required due to absorption. Dry carpet areas and surfaces before re-entry. A fan may be used to assist in drying carpeting. Remove children and pets from treated areas until completely dried. If necessary,
		Test staining and color-fastness of carpets by treating and drying a small, concealed area prior to application. BST PROTECTANT RTU 75 treats approximately 200 square feet per gallon (50 square feet per quart). When treating coarser substrates (e.g. wool carpeting), more BST PROTECTANT RTU 75 may be required due to absorption. Dry carpet areas and surfaces before re-entry. A fan may be used to assist in drying carpeting. Remove children and pets from treated

		due to bacteria, mold stains and mildew stains return.
	Pest controlled	Method of Application
Mattress pad and mattress ticking and upholstery composed of acetates, acrylics, cotton, fiberglass, nylon, polyester, polyethylene, polyolefins, polypropylene, rayon, spandex, vinyl, wool; fiberfill to be used in upholstery, sleeping bags, apparel, where the fiber is cotton, natural down, nylon, rayon or wool.	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	SPRAY: Clean surfaces prior to application. Using a trigger pump sprayer, spray the entire surface area 4" – 6" from the surface making sure the surface is completely covered. Apply and then let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fabric by treating and drying a small, concealed area prior to application. When applying to mattress pads and ticking do not soak. Remove children and pets from treated area until completely dried. If necessary, reapply BST PROTECTANT RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains and mildew stains return.
	Pest controlled	Method of Application
Tents, tarpaulins, sails, ropes	Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae.	SPRAY: Clean surface prior to application. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4" – 6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fabric by treating and drying a small, concealed area prior to application. If necessary, reapply BST PROTECTANT RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains and algae stains return.
		DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough BST PROTECTANT RTU 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160°C (320°F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply BST PROTECTANT RTU 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.

	Pest controlled	Method of Application
Roofing materials (such as	Odor causing	SPRAY: Make sure the roof is clean prior to
shingles, roofing granules, wood	bacteria, bacteria	application. Using a pressure sprayer, spray the
shakes, felt, stone, synthetic	which cause	entire surface area 6"-12" from the surface
overcoats)	staining and	making sure the surface is completely covered.
	discoloration,	After applying BST PROTECTANT RTU 75, let
	fungi (mold and	stand until dry. BST PROTECTANT RTU 75
	mildew) and	treats approximately 200 square feet of roofing
	algae.	per gallon (50 square feet per quart). If
		necessary, reapply BST PROTECTANT RTU 75
		every three months or when odor, staining and
		discoloration due to bacteria, mold stains, mildew
		stains, and algae stains return.
	Pest controlled	Method of Application
Buffer pads (polishing and	Odor causing	SPRAY : Clean surface prior to application.
abrasive), Polyurethane and	bacteria, bacteria	Using a trigger pump sprayer or pressure sprayer,
cellulose foam for household	which cause	spray the entire surface area $4'' - 6''$ from the
mops, vacuum cleaner bags,	staining and	surface making sure the surface is completely
umbrellas, casual shoes, athletic	discoloration, and	covered. Let stand until dry or let stand 3 minutes
shoes	fungi (mold and	and wipe dry with cloth or sponge. If spotting
	mildew)	occurs, wipe with moist cloth or sponge. If
		necessary, reapply BST PROTECTANT RTU 75
		every three months or when odor, staining and
		discoloration due to bacteria, mold stains and
		mildew stains return.
	Pest controlled	Method of Application
Tubs, glazed tiles, vanity tops,	Odor causing	SPRAY : Using a trigger pump sprayer, spray the
shower curtains, shower stalls	bacteria, bacteria	entire surface area 4 " – 6 " from the surface
(areas), sinks, washable walls,	which cause	making sure the surface is completely covered.
wall paper for non-food contact,	staining and	Let stand until dry or let stand 3 minutes and wipe
floors, window sills, cabinets,	discoloration, and	dry with cloth or sponge. If spotting occurs, wipe
garbage cans, appliances,	fungi (mold and	with moist cloth or sponge. If necessary, reapply
refrigerators (exterior), fiberglass,	mildew)	BST PROTECTANT RTU 75 every three months
formica, glazed tiles, glazed		or when odor, staining and discoloration due to
porcelain, synthetic marble,		bacteria, mold stains, and mildew stains return.
plastic, vinyl.		

Imparts microbiostatic properties.

Use on carpet and upholstery to inhibit odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration.

Unscented.

Use on carpet and upholstery to inhibit the growth of odor causing bacteria.

Use on carpet and upholstery to inhibit the growth of bacteria which cause staining and discoloration. Use on carpet and upholstery to inhibit the growth of fungi (mold and mildew) which cause staining and discoloration.

Use on carpet and upholstery to inhibit the growth of odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration.

Provides an invisible microbiostatic coating to inhibit the growth of odor causing bacteria.

Provides an invisible microbiostatic coating to inhibit the growth of bacteria which cause staining and discoloration.

Provides an invisible microbiostatic coating to inhibit the growth of fungi (mold and mildew) which cause staining and discoloration.

Provides an invisible microbiostatic coating to inhibit the growth of algae.

Provides an invisible microbiostatic coating to inhibit the growth of odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration and algae. bacteria which cause staining and discoloration, fungi (mold and mildew) and algae.

Prevents deterioration caused by bacteria and fungi (mold and mildew) which cause staining and discoloration.

Inhibits deterioration caused by bacteria.

Resists development of microbial odors.

Resists development of stains and discoloration due to bacteria.

Resists development of stains due to fungi (mold and mildew) which cause staining and discoloration. Resists stains due to algae.

Resists development of microbial odors, stains and discoloration due to bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration and algae.

Provides/creates an invisible barrier to inhibit the growth of odor causing bacteria.

Provides/creates an invisible barrier to inhibit the growth of bacteria which cause staining and discoloration.

Provides/creates an invisible barrier to inhibit the growth of fungi (mold and mildew) which cause staining and discoloration.

Provides/creates an invisible barrier to inhibit the growth of algae.

Provides/creates an invisible barrier to inhibit the growth of odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration and algae. Inhibits the growth of odor causing bacteria between cleanings.

Inhibits the growth of bacteria which cause staining and discoloration between cleanings.

Inhibits the growth of fungi (mold and mildew) which cause staining and discoloration between cleanings. Inhibits the growth of algae between cleanings.

Inhibits the growth of odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration and algae between cleanings.

Mold, mildew, odor protector and inhibitor.

BST PROTECTANT RTU 75 is an antimicrobial agent effective against odor causing bacteria.

BST PROTECTANT RTU 75 is an antimicrobial agent effective against bacteria which cause staining and discoloration.

BST PROTECTANT RTU 75 is an antimicrobial agent effective against fungi (mold and mildew) which cause staining and discoloration.

BST PROTECTANT RTU 75 is an antimicrobial agent effective against algae.

BST PROTECTANT RTU 75, an antimicrobial agent, controls the source of odors on surfaces in the home, in the bathroom, in the kitchen.

Bacteriostatic, fungistatic (mold and mildew), algaestatic.

BST PROTECTANT RTU 75, an antimicrobial agent, inhibits smelly odors caused by mold and mildew that can grow even in the cleanest of homes.

BST PROTECTANT RTU 75, an antimicrobial agent, inhibits the growth of odor causing bacteria. Effective on hard non-porous washable bathroom and kitchen surfaces and fixtures around the home. Effective on modern hard non-porous washable surfaces made of fiberglass, glazed porcelain, Formica®, stainless steel, synthetic marble.

FOR MORE INFORMATION CONCERNING THIS PRODUCT, PLEASE CONSULT THE MATERIAL SAFETY DATA SHEET (MSDS). THE MSDS CAN BE OBTAINED BY WRITING:

IndusCo, Ltd. 2319 Joe Brown Drive Greensboro, NC 27405 (336) 375-7555 www.induscoltd.com

IMPORTANT: WARRANTY AND DISCLAIMER INFORMATION

IndusCo, Ltd warrants that the product conforms to its chemical description and is reasonably fit for the purposes stated in this bulletin when used in accordance with directions under normal conditions of use; but this warranty of fitness for a particular purpose does not extend to the use of this product contrary to bulletin instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to the seller, and buyer assumes the risk of any such use.

INDUSCO, LTD SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING THE WARRANTY OF MERCHANTABILITY.