## SANI-KING

## P-MAX VIII CARTRIDGE

For use only in the P-Max Automatic Delivery System Feeder

## DANGER!

KEEP OUT OF REACH OF CHILDREN SEE FIRST AID AND ADDITIONAL PRECAUTIONARY STATEMENTS ON BACK PANEL

## Net Wt. 8 lbs

T	cichle	oro-:	gient: s-Triazinetrione ients:	
Ava:	ilabl	e Chi	lorine:	. 898
EPA	REG.	NO:	53735-2	
EPA	EST.	NO:	64114-MN-001	

# ACCEPTED

**SEP 2 6 1991** 

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 53735-2

## PRODUCT DESCRIPTION:

This Chamber is part of an advanced system that uniformly feeds chlorine, efficiently kills bacteria and controls algae continously for weeks under normal conditions in a stabilized pool. The convenient disposable chamber lets you control the rate of chlorine delivery to meet changing conditions in your pool, by simply adjusting the control dial on the chlorine delivery system. You never have to touch the chlorinating tablets.

## DIRECTIONS FOR USE:

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

- 1. Adjust pH level to 7.2 7.6
- 2. Bring Free Available Chlorine (FAC) residual to 1-3 ppm using a chlorine shock. Follow Manufacturer's Label Directions.
- 3. Stabilize the pool with cyanuric acid stabilizer. Follow Manufacturer's Label Directions.
- 4. To install chamber: Take feeder cap off. Remove chamber cut offs A & B (fig. 1). Hold chamber so the open end faces insert into feeder (fig. 2). The end of the chamber must align with the L-key located inside the feeder at bottom (fig. 3). DO NOT FORCE. Replace feeder cap and the control dial to the appropriate setting. For a guideline, using a 13,500 gallon pool with a pump running 8 hours per day, begin with the control dial set on #2. For a 18,000 gallon pool, start at setting #3.5. To achieve the proper FAC, turn the control dial to the next higher setting to increase the FAC and turn it to the next lower setting to Operate the pool for 1 day. Check the FAC decrease the FAC. residual and increase/decrease one setting per day until you achieve 1-3 ppm.
- 5. Once you have determined the proper setting for your pool, you should not have to re-adjust the setting under normal conditions. Should conditions change (ie: weather, rain, pool use, bather load, etc), the control dial can be easily adjusted to increase or decrease the chlorine feed.
- 6. Superchlorinate if needed. Do not add shock treatment to the skimmer. Turn control dial to setting #0 before superchlorinating. Once desired FAC has been obtained, return the control dial to the normal operating setting.

#### STORAGE AND DISPOSAL

store cartridges in original container in a cool, dry, well-ventilated area away from heat or open flame. In case of decomposition, isolate container and flood area with large amounts of water to dissolve all material before discarding this cartridge. Do not contaminate food or feed with this product. This cartridge is designed for one time use. When empty, triple rinse in pool water, drain, wrap in newspaper and discard in trash.

PRECAUTIONARY STATEMENTS: HAZARDS TO HUMANS AND DOMESTIC ANIMALS: DANGER

Highly corrosive. Causes skin and eye damage. May be fatal if swallowed. Do not get in eyes, on skin or on clothing. Irritating to nose and throat. DO NOT handle chlorinating chemical without wearing rubber gloves and goggles.

#### FIRST AID (Practical Treatment)

IF CHEMICAL GETS ON SKIN: Brush off excess chemical and flush skin with cold water for at least 15 minutes. If irritation persists get medical attention.

IF INHALED: Remove person to fresh air. Get immediate medical attention.

IF IN EYES: Flush with cold water for at least 15 minutes. Get immediate medical attention.

IF SWALLOWED: Give bread soaked in milk followed by large amounts of water. If person is conscious and vomiting, place face down with head lower than hips. Get immediate medical attention.

#### CHEMICAL HAZARDS: DANGER:

Strong oxidizing agent. Do not refill empty cartridge. Contamination with any substance may start a chemical reaction with generation of heat, liberation of hazardous gases and possible fire and explosion. Avoid any contact with flame or burning material, such as a lighted cigarette.

#### **ENVIROMENTAL HAZARD:**

This product is toxic to fish. Do not contaminate lakes, ponds or streams.

KING TECHNOLOGY, INC., 9909 Smetana Drive, Minnetonka, MN 55343

Sani-King Perform-Max is a Registered Trademark of King Technology, Inc.

Patents pending

7. Periodically check the chamber and replace with a new one when empty. Do not attempt to open or refill this chamber. DO NOT REUSE.

## PRECAUTION:

The warranty will be void if this chamber is not used with the appropriate feeder. Fire or explosion may result if this chamber is used with an incorrect chemical feeder.

NOTE: Some settling may occur during shipment.