PRECAUTIONARY STATEMENTS Hazards To Humans And Domestic Animals

WARNING - Causes substantial, but temporary eye injury. Harmful if swallowed or absorbed through skin. Do not get in eyes or on clothing. Avoid contact with skin. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Wash thoroughly with soap and water after handling.

PERSONAL PROTECTIVE EQUIPMENT

Applicators and handlers performing in-service pole and tie treatment must wear long sleeve shirts and pants or wear coveralls over short sleeve shirts and short pants, impermeable gloves, work boots, and safety glasses.

All other applicators must wear long sleeve shirt and pants or coveralls over short sleeve shirts and pants, impermeable gloves, chemically resistant footwear and goggles or face shield.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic organisms. Do not apply directly to water, to areas where surface water is present, or to intertidal areas below the mean high water mark. Do not contaminate water by disposal of equipment wash waters.

PHYSICAL OR CHEMICAL HAZARDS

Use only with adequate ventilation. Close container after each use.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Store product in original container only. Do not store with fertilizers, food and feed. Keep container closed when not in use. If product has been spilled or is leaking, remove the source of the spill or leak. Recover free liquid. Spread absorbent, then pick up and place in containers. Then where applicable, wash area with detergent and water.

PESTICIDE DISPOSAL. Wastes resulting from tagof this product may be disposed of by applying them on site or at an approved waste disposal facility.

CONTAINER DISPOSAL:

Plastic Containers: Triple rinse (or equivalent Hen offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or illumed by state and local authorities, by burning. If burned, stay out of smoke.

BORAX COPPER HYDROXIDE WOOD PRESERVATIVE PASTE

EPA Reg. No. 54471-10 EPA Est. No. 54471-NB-001

KEEP OUT OF REACH OF CHILDREN

WARNING

FIRSTAID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a Poison Control Center or doctor for treatment advice.

IF SWALLOWED: Call a Poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.

IF ON SKIN OR CLOTHING: Take off-contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a Poison Control Center or doctor for further treatment advice.

Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage.

For information on this pesticide product (including health concerns, medical emergencies, or pesticide incidents), call the National Pesticide Information Center at 1-800-858-7378.

In case of emergency call 1-800-473-0179

Have the product container or label with you when calling a Poison Control Center or doctor or going in for treatment. See other precautionary statements on side panels

ACTIVE INGREDIENTS:

er the Federal Insecticide, Fungicide, enticide, Act as amended, for the

Copper Hydroxide*Sodium Tetraborate Decahydrate**		3.1%
		43.5%
Inert Ingredients		53.4%
	TOTAL	

* Metallic Copper Equivalent 2.0%

Boric Oxide (B₂O₃) Equivalent 16.4%

MANUFACTURED BY:

Copper Care Wood Preservatives, Inc. Humphrey, NE 68642 888-817-0131

Net Weight: 50 lbs.

DIRECTIONS FOR USE:

It is a violation of federal law to use this product in a manner inconsistent with its label.

This product is intended for the preservation of wood. Wood treated according to the following directions resists attack by decay and soft rot fungi, termites, carpenter ants, and wood boring beetles.

For utility poles, piling, posts, and other wooden structures standing in the ground, excavate the soil away from the structure to the depth of about 18 inches. Brush the surface to remove adhering soil and any damaged wood. Depending upon the degree of protection desired, apply from 1/16 to 1/2 inch of this product to the surface of the structure by spreading in a manner to achieve a consistent thickness from the bottom of the excavation to 3 inches above ground. Cover the treated surface with any contaminated packaging then with an impermeable wrap and back-fill around the structure. To treat internally decayed wood, inject this product into the affected area through drilled holes, then plug the drilled holes with tight-fitting wooden dowels. This product can be diluted with water if a less viscous solution is desired. To protect the ground line of poles, posts, and timbers before they are placed in the soil, apply this product in pouch packaging to the structure from 6 inches above to 12 inches below the anticipated ground level. Slit the pouch along the marked lines and press this slit side tightly against the wood, then staple to the pole, post or timber.

For cross-ties force 4.5 cubic inches of this product under the tie plate or apply 4.5 cubic inches to the tie plate area before the plate is put in place.

For untreated or insufficiently treated posts, poles, lumber, or timbers drill a hole or holes as near the sapwood portion of the wooden member as possible. These holes should be a maximum of 1 inch in diameter and of sufficient depth that the wooden member will be completely treated by diffusion. Posts are conveniently treated with the bark intact by drilling holes in both ends. The holes should be filled with this product to within 1/2 inch of the surface, then capped with impermeable plugs. Sufficient product should be used to achieve a retention of from 1 to 2 pounds per cubic foot.

For unseasoned wood which will be used under minimum leaching conditions, dissolve 1 to 2 pounds of this product in water then brush, dip, or spray with the diluted product. Deeper penetration and greater protection is achieved if an extended dip time is used and the boards are maintained in the unseasoned state for at least 2 weeks to allow for full diffusion.

For seasoned wood which will be used under minimum leaching conditions pressure treat using a full cell process to a retention ranging from 0.5 to 1 pound per cubic foot.

To protect wafer board from termites add this product to the wood wafers in conjunction with the wax emulsion addition. Use a level sufficient to produce a preservative treated board containing from 1.0% to 2:5% of this product by weight.

To protect solid wood from termites apply this product to the surface of unseasoned, sawn or debarked structures. Shroud them in plastic wrap until the wood has absorbed 0.5 to 1.5 pounds per cubic foot of the applied wood preservative.

Residential use of this product is disallowed; except by commercial applicators.