55363-2 Pm31 1 of 2

U.S. ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF PESTICIDES PROGRAMS
REGISTRATION DIVISION (WH-567)
WASHINGTON, D.C. 20460

NOTICE OF PESTICIDE: ☒ REGISTRATION ☐ REREGISTRATION

(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)

EPA REGISTRATION NO. 55363-2

DATE OF ISSUANCE AUG 18 1986

TERM OF ISSUANCE

NAME OF PESTICIDE PRODUCT

Classic Yacht Clear
Aerosol Antifoulant Coating

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

[illegible] Resins Corporation
[illegible] Drive
[illegible] 454
[illegible], PA 18936

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.

2. Note the labeling changes listed below before you release the product for shipment:

   a. At the phrase "EPA Registration No. 55363-2
   b. Delete the statement "Propellant [illegible]"
   c. Provide the appropriate EPA establishment [illegible].

3. Submit five (5) copies of your final printed labeling, before you release the product for shipment. Refer to the A-75 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

John E. Ivy
Product Manager (31)
Disinfectants Branch
Registration Division (TS-767C)

☐ ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

DATE

EPA Form 8570-6 (Rev. 5-76)

PREVIOUS EDITION MAY BE USED UNTIL SUPPLY IS EXHAUSTED.

KEEP OUT OF REACH OF CHILDREN

DANGER

Classic Yacht® Clear

AEROSOL ANTIFOULANT COATING

Advanced antifouling technology (patented). When applied properly, per instructions, long-term protection is provided.

May be used in fresh or salt water.

The unique Classic Yacht antifoulant coating combines unparalleled long-term resistance to barnacle growth with a high-gloss, extremely smooth, low-friction surface finish.

Hulls may be hauled, stored and re-launched without degrading the antifoulant properties.

ACTIVE INGREDIENTS:	Tributyltin Methacrylate (As a Part of a Polymer)	12.20%
INERT INGREDIENTS:		87.80%
		100.00%

PROPELLANT: DME

Total Tin Content 3.91% Contains Petroleum Distillates

STATEMENT OF PRACTICAL TREATMENT

DANGER — IF SWALLOWED — Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available drink large quantities of water. Avoid alcohol. Get medical attention. Note to Physicians: Probable mucosal damage may contraindicate the use of gastric lavage.

IF INHALED — Remove to fresh air. IF IN EYES — Flush eyes with plenty of water. Get medical attention. IF ON SKIN — Wash with plenty of soap and water. Get medical attention. See back panel for additional precautionary statements.

ITW Philadelphia Resins Corp.

P.O. Box 454 • Montgomeryville, PA 18936

Telephone (215) 855-8450 Telex 277595

DANGER PRECAUTIONARY STATEMENTS:

HAZARDS TO HUMANS & DOMESTIC ANIMALS: Corrosive. Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed or inhaled. Do not get on skin, in eyes or on clothing. Wear goggles, face shield or safety glasses. Wear protective clothing such as long sleeved cotton shirt, long pants, hat and gloves. Wash thoroughly with soapy water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapor or spray mist. Use with adequate ventilation. When used in confined areas, while spraying and/or sanding boat surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

ENVIRONMENTAL HAZARD: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or waste disposal. Do not allow chips or dust generated during paint removal to enter water. Deposit paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARD: Contents under pressure. Do not store near heat or open flame. Do not puncture or incinerate container. Exposure to temperatures above 130°F may cause bursting.

DIRECTIONS FOR USE

It is a violation of Federal law to
manner inconsistent with its labeli

When properly applied, this aerosol antifo
ing protection against barnacles and mar
a professionally sprayed appearance.

Classic Yacht Clear spray antifo
correctly applied Classic Yacht
outdrives, outboard motor lower

Classic Yacht Clear antifoulant is also rec
boot top and hull coatings in waterline
properly applied, Classic Yacht Clear wil
cumulation and scrubbing maintenance of

INSTRUCTIONS FOR USE:

1. Apply over Classic Yacht Pigmented ant
tions on Black and White Classic Yacht
2. When coating over boot top or hull c
thoroughly remove all old, wax residue o
detergent.
3. Bull surface lightly with 3M Scotch Br
good adhesion.
4. Apply Classic Yacht Clear over waterline
to coat thoroughly and evenly. Use care t
5. Allow one hour dry time then repeat app
coats is recommended. Note. Below 55
time for tack free surface before overco
6. Allow minimum six hours before launch
areas. Allow overnight dry when applic

STORAGE & DISPOSAL

- Do not contaminate water, food or feed
- Pesticide Disposal: Pesticide wastes a
excess pesticide, spray mixture or rin
Law. If these wastes cannot be dispose
instructions, contact your State Pestic
Agency or the Hazardous Waste Repr
Regional Office for guidance.
- Disposal. Do not reuse empty co
dispose of in a sanitary landfill
State and local procedures. Do

OSHA REGULATIONS (ICS CFR 1910.120
Exact Chemical Identity Being Withheld as
Solvents may present an inhalation and/or
not used in accordance with safety bris
Also, solvents herein may cause skin irri
forced contact, eye irritant.

Net Cont
EPA Reg
EPA Est

ACCEPTED with COMMENTS In EPA Letter Dated AUG 18 1986

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 55536-32