
SUPPLEMENTAL LABELING CSC COPPER SULFUR DUST

EPA Reg. No. 55429-5



FOR ALL CROP USES LISTED ON THE PRODUCT LABEL (for both ground and air applications)

Dusting sulfur can create situations where drift to non-target or sensitive areas can occur. To minimize the occurrence of drift incidents, the following conditions must be met:

DIRECTIONS FOR USE (GENERAL)

In addition to specific instructions under directions for use on the main sulfur label, the following conditions must also be followed for use in California:

- 1. The operator of the property and the applicator must establish a buffer zone of enough distance to prevent drift onto non-target areas such as hospitals, clinics, residential areas, schools, and any other area designated by the county agricultural commissioner.
- 2. The operator of the property and the applicator must evaluate the method and equipment for each site to ensure proper and safe use. Evaluations shall include, but not be limited to the appropriateness of ground or air application.
- 3. Sulfur shall not be applied when the wind velocity exceeds 10 miles per hour. Applicators should be aware that in some areas of California, "dead calm" conditions are often associated with an inversion situation. In these areas, applying sulfur when there is a minimum air movement of 2 miles per hour; will help ensure that an inversion situation does not exist.
- 4. All applicators, prior to use of dust formulations, should read and understand the Best Application Practices Manual.
- 5. Before using this product, read and follow all applicable directions, restrictions, and precautions on the EPA-registered label.