### ACCEPTED

ATS-314

MAR 1 4 1986

**ACTIVE INGREDIENT:** 

This product contains 0.87 lb. of active ingredient per gallon and weighs 8.68 lb. per gallon.

# KEEP OUT OF REACH OF CHILDREN DANGER

## PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye and skin demage. Hamful if swallowed. Do not get in eyes, on skin, or on dothing. Avoid contamination of food, Wash googles or face shield and rubber gloves when handling. Wash thoroughly after handling.

STATEMENT OF PRACTICAL TREATMENT: In case of akin contact, with plenty of acep and water. Remove contaminated clothing and week before rause. If product gets in the eyes, flush immediately with copious amounts of cleen, cool water for at least 15 minutes. Get medical attention immediately. If product is swallowed, drink promptly a large quantity of milk, agg whites, galetin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician. Never induce vomiting or give snything by mouth to an unconscious passor.

Hate to physicien: Probable mucosal damage may contraindicate gestric levege.

ENVIRONMENTAL HAZARDS: The people is toxic to fish, Do not discharge affluent containing this active ingradient into takes, streems, ponds, estuanes, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge affluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidence contact your State Water Board or Regional Office of the EPA.

· · · · · · · · · · · · · · · · · · ·	ŀ
Manufactured by:	
Alpine Technical Services	j
601 W. 6825 South	
Midvale, Utah 84047	1
EPA Reg. Nd EPA Est. No	<del>-</del>
Net Contents:	

#### DIRECTIONS FOR USE

Burner Carlot Ca

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
ATS-314 is used in industrial and/or commercia
recirculating cooling tower systems and industrial air-washing systems to control microbiological slime. Prior to the use orATS-314ir
industrial and/or commercial recirculating cooling tower systems, systems should be cleaned to remove algal growth, microbiological slime, and other deposits. Then make an initial slug addition of 12.0 to 17.9 ft. oz. of ATS-314
per 1000 gal, of water to provide 100 to 150 ppm of ATS-314 , based on total weight of water in the system. Repeat initial
until control is evident. Make subsequent slug addition of 6.0 to 17.9 ft. oz. or ATS-314 per 1000 gal. of water (50 to 150
ppm ATS-314 levery 2 to 5 days or as needed. The frequency
of addition depends upon the relative amount of bleedoff and the severity of the
microbiological problem. Slug additions should be made in the sump of recirculating cool
ing tower systems.
ATS-314 is used in industrial sir-washing systems
which maintain effective mist-eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial skip dose of 28.1 to 35.9 fl. oz. of ATS-314 per 1000 gal. of water is
recommended. Repeat initial dosage until control is avident. Subsequent slug additions of
21.0 to 35.9 fl. oz. of <u>ATS-314</u> per 1000
gallons of water should be employed every 1 to 5 days, or as needed. The frequency of ad
dition depends upon the relative amount of bleedoff and severity of the bacterial problem

### STORAGE AND DISPOSAL

Slug additions may be made to the sump or the water collection trays of the sinwash

Do not contaminate water, food, or feed by storage or deposal.

STORAGE: Do not expose to extrame temperatures. Do not stack more than four drums high. Leaking or demaged drums should be placed in overpack drums for disposal. Spalls should be absorbed in equivalent or send and disposed of in a sanstary landfall. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pseticide weeter are soutely hazardous. Improper disposal of excess pesticide, apray mixture, or sineate is a violation of Federal Law. If these weeter cannot be disposed of by use according to label instructions, contact your State Pseticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL:

system.

- El PLASTIC: Triple rines (or squivelent). Then offer for recycling or reconditioning, or puncture end dispose of in a servicery landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay our of amoke.
- METAL: Triple rines (or squivelent). Then offer for recycling or reconditioning, or puncture and dispose of in a senitary landfill, or by other procedures approved by state and local authorities.