

A stamped copy of the labeling is enclosed for your records.

The amended formula is acceptable.

Sincerely yours,

SL

Susan Lewis
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (H7505C)

Enclosure

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JAN 17 1991

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended for the pesticide
registered under EPA Reg. No.
57156-1

X-100

 GET THE FACTS
CUSTOMER
HOTLINE 1-800-346-7532
Let's Talk Wood Restoration!

NATURAL SEAL[®] WOOD PRESERVATIVE

PATENT PENDING

MEETS V.O.C. COMPLIANCE
WATERPROOFS and HOLDS NATURAL WOOD COLOR
IDEAL For SHAKE ROOFS and More.
PAINTABLE

MIXED IN
100% OIL SOLIDS
• LESS EVAPORATION
• DEEPER PENETRATION
• LONGER LIFE

HEAVY DUTY
CLEAR OIL FINISH
PREVENTS MOISTURE DAMAGE - ULTRA VIOLET PROTECTORS
Holds Natural Cedar & Wood Color - Even Weathered Grey

- KEEP OUT OF REACH OF CHILDREN -
WARNING! HARMFUL OR FATAL IF SWALLOWED
See Other CAUTIONS on Side Panel.

**3-YEAR
GUARANTEE**

1 GALLON - 3.785 LITERS





**THE FACTS
'OMER
46-7532
ration!**



PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful if swallowed or absorbed through skin. Avoid breathing vapors or mist. This product may cause skin sensitization.

STATEMENT OF PRACTICAL TREATMENT: In case of skin contact, wash promptly and thoroughly with soap and water. If product gets in eyes, flush immediately with copious amounts of clean, cool water for 15 to 20 minutes. Get medical attention immediately if product is swallowed, call physician or Poison Control Center. Drink a large quantity of milk, egg whites, or gelatin solution, or if these are not available drink large quantities of water. Avoid alcohol.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply directly to water. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame.

STORAGE OR DISPOSAL

STORAGE: Keep container closed when not in use. Store in cool place. Leaking or damaged containers should be placed in a plastic bag and discarded in trash. All pesticides should be kept out of reach of children and stored away from food.

DISPOSAL: Do not reuse empty can. Wrap can and place in trash.

*For copy of Independent Lab Study or Technical Assistance, write or call:
AMERICAN BUILDING RESTORATION CHEMICALS, INC.
9720 South 60th Street, Franklin, Wisconsin 53132
National 1-800-346-7532
In Wisconsin 414-761-2440
EPS Est. #56156-WI-001
EPA Registration No. 56156-1

DIRECTIONS FOR USE - It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Mix well before using. Surface & substrate must be thoroughly dry. This is very important since X-100 Natural Seal® Heavy Duty will not fully penetrate wet or damp surfaces. A test area should be processed before beginning overall project to determine dry time, wood porosity and total desired look.

APPLICATION:

1. For application, both surface and air temperature should be above 50°F
2. Apply by brush, roller, dipping, or flooding spray.
3. Do not allow to puddle. Wipe off excess before it dries.
4. On roofs saturate well with two passes (wet on wet coats.)
5. On horizontal and vertical surfaces, saturate well. Allow 48 hours for first coat to penetrate before applying second coat. **Warning:** Slippery while curing.
6. On decks, sitting areas, walkways, etc. allow sufficient time for X-100 Natural Seal® Heavy Duty to saturate the wood fiber before using. Remember oils saturate deeper and dry slower than paint thinner formulas but its worth the wait.
7. Allow 48 hours to dry to touch 5 days before painting over. 2 weeks for total penetration.
8. Rough sawn lumber will hold a wet look for 6 to 8 weeks before drying to natural look
9. Allow green and non kiln dried lumber to air dry for 8 weeks before applying.
10. Do not apply if rain is forecast within 24 hour period.
11. Do not apply latex paint over X-100 Natural Seal® Heavy Duty. Do not use as additive to latex paint. (Do not use on wood that will be in direct contact with soil)

LIMITED WARRANTY: If after proper surface preparation and proper application in accordance with label directions, this product is shown to be defective within three years of the date of purchase, American Building Restoration Chemicals, Inc., at its option, will either replace the product or refund its purchase price. Contact American Building Restoration Chemicals, Inc. to make claim under this warranty. You must have proof of purchase and original sales receipt.

Proper surface preparation is essential to the applicability of this warranty. Read and follow label directions.

American Building Restoration Chemicals, Inc. shall not be liable for cost of labor, direct or incidental or consequential damages. Cracking, peeling or blistering caused by inadequate ventilation of the breakdown of the underlying surface or previous paint film are also not covered by this warranty.

This warranty does not warrant against a gradual wood discoloration from staining, over a 3 year period of time, or a gradual diminishing of product effectiveness over a 3 year period of time.

Treating of discolored wood, will remain discolored. This product will not correct existing overage, cracking, splitting, cupping, curling or rot, but will aid in the prevention of it from originally causing and accelerating. No other written warranties, expressed or implied, are made.

This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

**- WARNING -
SLIPPERY DURING CURE TIME.
DO NOT WALK ON SURFACES UNTR. CURED.**



PROOF OF PURCHASE
Remove Carefully

**X-100
NATURAL
SEAL®
HEAVY DUTY**
One Gallon

X-100 NATURAL SEAL® HEAVY DUTY CLEAR OIL FINISH

If you prefer the natural rich look of real wood you will appreciate the long lasting beauty of X-100 Natural Seal® Heavy Duty.

X-100 Natural Seal® Heavy Duty is a blend of Paraffinic oil, fungicides, water repellents and ultra violet ray wood protectors that is ideal for Shake Roofs and more.

An integral part of X-100 Natural Seal® Heavy Duty is that a greater percentage of the formula consists of paraffinic oil. These oils are non U-V sensitive and are considered by themselves excellent wood sealers as compared to other wood preservative that contain as little as 10% solids and are mixed in fast evaporating solvents or water borne systems that have little effect on cracking and splitting of wood.

X-100 Natural Seal® Heavy Duty technology is in a class by itself. Independent tests have shown that X-100 Natural Seal® Heavy Duty will hold wood to its natural color for 3 to 5 years. To maintain natural wood look, reapply at 3 to 5 year intervals on vertical surfaces, or as needed on horizontal surfaces. Total life expectancy is 8 years before recoating is necessary.

X-100 Natural Seal® Heavy Duty protects wood against cracking, splitting, cupping, curling, mold and mildew. Termites avoid it. For use on cedar wood, wood surfaces, vertical wood and other wood surfaces susceptible to moisture damage including green and pressure treated lumber.

X-100 Natural Seal® Heavy Duty is also available in non-fade natural oxide toners. Note: The addition of toners increase the longevity of this product.

NOTE: For technical assistance on how to clean and strip exterior wood surfaces of varnish, paint and mildew, and restore grey and weathered wood back to new, call our Customer Hotline 1-800-346-7532 - In Wisconsin (414) 761-2440.

To obtain Training Video, inquire with store personnel.

AVERAGE Depending on density of surface 75 to 150
COVERAGE: Sq. Ft. per gallon.
DRY TIME: 48 hours for a single coat. Allow to dry at least 48 hours before applying second coat.
THINNER: None Required.
APPLICATION: Brush, roller or spray.
PRIMER: None.
CLEAN UP: Paint Thinner.

SUGGESTIONS:

- When spraying near vegetation, cover any plant life in case of over-spray.
- Before treating surface, make sure surface or material is thoroughly dry.
- If Natural Seal should get on surfaces such as glass, metal or paint, remove with Paint Thinner.

USE ONLY WITH ADEQUATE VENTILATION

ACTIVE INGREDIENTS:
Methylene bis (thiocyanate) 5%
2-(Thiocyanomethylthio) benzothiazole 5%
INERT INGREDIENTS: 90%
This product weighs 6.5 pounds per gallon

FOR USE ON...

- ROOFS
- HOMES
- LOG CABINS
- DECKS
- SIDING
- FENCES
- POSTS
- SHINGLES
- BARNs
- PORCHES
- WOOD STEPS
- WINDOW FRAMES
- SASHES
- LADDERS
- DOORS
- SM. DIMENSIONAL LUMBER
- POROUS WOOD SURFACES

WARNING: Not recommended for surfaces in direct contact with food.

— KEEP OUT OF REACH OF CHILDREN —
WARNING: HARMFUL OR FATAL IF SWALLOWED.