

PROOF OF PURCHASE
Remove Carefully

**X-100
NATURAL
SEAL®
DECK GRADE**
One Gallon

X-100 NATURAL SEAL® DECK GRADE CLEAR FINISH

If you prefer the natural rich look of real wood you will appreciate the long lasting beauty of X-100 Natural Seal® Deck Grade.

X-100 Natural Seal® Deck Grade is a blend of Paraffinic oil, fungicides, water repellents and ultra violet ray wood protectors that is ideal for Decks and more. It's a non film forming, fast drying wood preservative.

An integral part of X-100 Natural Seal® Deck Grade is that the formula consists of paraffinic oil. These oils are non U-V sensitive and are considered by themselves excellent wood sealers as compared to other wood preservative that contain as little as 10% solids and are mixed in fast evaporating solvents or water borne systems that have little effect on cracking and splitting of wood.

X-100 Natural Seal® Deck Grade technology is in a class by itself. Independent tests have shown that X-100 Natural Seal® Deck Grade will hold wood to its natural color for 2 to 4 years. To maintain natural wood look, reapply at 2 to 4 year intervals on vertical surfaces, or as needed on horizontal surfaces. Total life expectancy is 6 years before recoating is necessary.

X-100 Natural Seal® Deck Grade protects wood against cracking, splitting, cupping, curling, mold and mildew. Termites avoid it. For use on cedar wood, wood surfaces, vertical wood and other wood surfaces susceptible to moisture damage including green and pressure treated lumber.

X-100 Natural Seal® Deck Grade is also available in non fade natural oxide toners. Note: The addition of toners increase the longevity of this product.

NOTE: For technical assistance on how to clean and strip exterior wood surfaces of varnish, paint and mildew, and restore grey and weathered wood back to new, call our Customer Hotline 1-800-346-7532 - In Wisconsin (414) 761-2440.

To obtain Training Video, inquire with store personnel.

AVERAGE COVERAGE: Depending on density of surface 75 to 150 Sq. Ft. per gallon
DRY TIME: 24 hours for a single coat. Allow to dry at least 12 hours before applying second coat.
THINNER: None Required
APPLICATION: Brush, roller or spray
PRIMER: None
CLEAN UP: Paint Thinner

SUGGESTIONS:

- When spraying near vegetation, cover any plant life in case of over spray.
- Before treating surface, make sure surface or material is thoroughly dry.
- If Natural Seal should get on surfaces such as glass, metal or paint, remove with Paint Thinner.

USE ONLY WITH ADEQUATE VENTILATION

ACTIVE INGREDIENTS:

Methylol bis (thiocyanate) 0.5%
2-(Thiocyanomethylthio) benzothiazole 0.5%
INERT INGREDIENTS 99%

This product weighs 6.5 pounds per gallon.

FOR USE ON...

- HOMES ✓
- LOG CABINS ✓
- DECKS ✓
- SIDING ✓
- FENCES ✓
- POSTS ✓
- BARNs ✓
- PORCHES ✓
- WOOD STEPS ✓
- WINDOW FRAMES ✓
- SASHES ✓
- LADDERS ✓
- DOORS ✓
- SM. DIMENSIONAL LUMBER ✓
- POROUS WOOD SURFACES ✓

WARNING: Not recommended for surfaces in direct contact with food.

KEEP OUT OF REACH OF CHILDREN
WARNING: HARMFUL OR FATAL IF SWALLOWED.

GET THE FACTS
CUSTOMER
800-346-7532
and Restoration!



PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING. Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful if swallowed or absorbed through skin. Avoid breathing vapors or mist. This product may cause skin sensitization.

STATEMENT OF PRACTICAL TREATMENT: In case of skin contact, wash promptly and thoroughly with soap and water. If product gets in eyes, flush immediately with copious amounts of clean, cool water for 15 to 20 minutes. Get medical attention immediately. If product is swallowed, call physician or Poison Control Center. Drink a large quantity of milk, egg whites, or gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply directly to water. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame.

STORAGE OR DISPOSAL

STORAGE. Keep container closed when not in use. Store in cool place. Leaking or damaged containers should be placed in a plastic bag and discarded in trash. All pesticides should be kept out of reach of children and stored away from food.

DISPOSAL. Do not reuse empty can. Wrap can and place in trash.

*For copy of Independent Lab Study or Technical Assistance, write or call
AMERICAN BUILDING RESTORATION CHEMICALS, INC.
9720 South 60th Street, Franklin, Wisconsin 53132
National 1 800 346 7532
In Wisconsin 414 761 2440
EPS Est #56156 WI 001
EPA Registration No. 56156-1 DOT UN 1255

DIRECTIONS FOR USE - It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Mix well before using. Surface & substrate must be thoroughly dry. This is very important since X-100 Natural Seal® Deck Grade will not fully penetrate wet or damp surfaces. A test area should be processed before beginning overall project to determine dry time, wood porosity, and total desired look.

APPLICATION:

1. For application, both surface and air temperature should be above 50 F.
2. Apply by brush, roller, dipping, or flooding spray.
3. Do not allow to puddle. Wipe off excess before it dries.
4. On horizontal and vertical surfaces, saturate well. Allow 12 hours for first coat to penetrate before applying second coat. **Warning:** Slippery while curing.
5. On decks, sitting areas, walkways, etc. allow sufficient time for X-100 Natural Seal® Deck Grade to saturate the wood fiber before using.
6. Allow 24 hours to dry to touch, 2 days before painting over. 1 week for total penetration.
7. Rough sawn lumber will hold a wet coat for 1 to 2 weeks before drying to natural look.
8. Allow green and non-kiln dried lumber to air dry for 3 weeks before applying.
9. Do not apply if rain is forecast within 24 hour period.
10. Do not apply latex paint over X-100 Natural Seal® Deck Grade. Do not use as additive to latex paint. (Do not use on wood that will be in direct contact with soil).

LIMITED WARRANTY: If after proper surface preparation and proper application in accordance with label directions, this product is shown to be defective within two years of the date of purchase, American Building Restoration Chemicals, Inc., at its option, will either replace the product or refund its purchase price. Contact American Building Restoration Chemicals, Inc. to make claim under this warranty. You must have proof of purchase and original sales receipt.

Proper surface preparation is essential to the applicability of this warranty. Read and follow label directions.

American Building Restoration Chemicals, Inc. shall not be liable for cost of labor, direct or incidental or consequential damages, cracking, peeling or blistering caused by inadequate ventilation or the breakdown of the underlying surface or previous paint film are also not covered by this warranty.

This warranty does not warrant against a gradual wood discoloration from occurring over a 2 year period of time, or a gradual diminishing of products effectiveness over a 2 year period of time.

Treating of discolored wood, will remain discolored. This product will not correct existing warpage, cracking, splitting, cupping, curling or rot but will aid in the prevention of it from originally occurring and accelerating. No other written warranties, expressed or implied, are made.

This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

- WARNING -
SLIPPERY DURING CURE TIME.
DO NOT WALK ON SURFACES UNTIL CURED.

FEB 26 1991

CCEP

56156-1