

ACCEPTED

GLACIDE 530

AUG 18 1987

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 56216-5

ACTIVE INGREDIENT:

Potassium dimethyldithiocarbamate 50.0%

INERT INGREDIENTS 50.0%

This product contains 5.2 lb. of active ingredient per gallon and weighs 10.4 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN
DANGER

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye and skin damage. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid contamination of food. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling.

STATEMENT OF PRACTICAL TREATMENT: In case of skin contact, wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. If product gets in the eyes, flush immediately with copious amounts of clean, cool water for at least 15 minutes. Get medical attention immediately. If product is swallowed, promptly drink 1 or 2 glasses of water. Contact a physician or Poison Control Center immediately. DO NOT INDUCE VOMITING.

Note to physician: Probable mucosal damage may contraindicate gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Manufactured by:
Glacier Laboratories

P. O. Box 2154
Yorba Linda, CA 92686

EPA REG. NO. 56216-5

EPA EST. NO.

NET CONTENTS

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

GLACIDE 530 is used in industrial and/or commercial recirculating cooling tower systems and industrial air-washing systems to control microbiological slime. Prior to the use of GLACIDE 530 in industrial and/or commercial recirculating cooling tower systems, systems should be cleaned to remove algal growth, microbiological slime, and other deposits. Then make an initial slug addition of 2.0 to 3.0 fl. oz. of GLACIDE 530 per 1000 gal. of water to provide 20 to 30 ppm of GLACIDE 530 based on total weight of water in the system. Repeat initial dosage until control is evident. Make subsequent slug addition of 1.0 to 3.0 fl. oz. of GLACIDE 530 per 1000 gal. of water (10 to 30 ppm GLACIDE 530) every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of recirculating cooling tower systems.

GLACIDE 530 is used in industrial air-washing systems which maintain effective mist-eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 4.7 to 6.0 fl. oz. of GLACIDE 530 per 1000 gal. of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 3.5 to 6.0 fl. oz. of GLACIDE 530 per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or the water collection trays of the airwash system.

GLACIDE 530 is used to control sulfate-reducing bacteria in petroleum secondary-recovery waterflooding operations. In systems fouled with microbiological deposits, GLACIDE 530 should be added as a slug dose to provide a concentration of 8 to 16 ppm (0.83 to 1.66 fl. oz. of GLACIDE 530 per 1000 gal. of water treated). This should be followed by a continuous addition of GLACIDE 530 employing a chemical-metering pump to maintain a concentration of 8 ppm, based on total weight of water treated. Both slug additions and continuous addition of GLACIDE 530 should be made at the heater-treater dump, gathering lines, or receiving tanks. Addition should always be made upstream to the filter.

GLACIDE 530 is also used to inhibit the growth of fungi and bacteria in water-based drilling muds, completion fluids, packer fluids, and other water-based drilling fluids containing starch, gums, sugars, or other organic materials. For these purposes GLACIDE 530 is added at rates of 2.5 to 4.2 gal. per 100 barrels of fluid (0.06 to 0.1% by volume).

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than four drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or insecticide is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL:

PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.