PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING

After ignition, cartnoge produces the toxic gas, carbon monoxide. Fumes may be harmful if inhaled

ENVIRONMENTAL HAZARDS

This product is highly toxic to wildfile. Check all burrows for signs of nontarget species. If present, do not treat burrows.

CHEMICAL HAZARDS

Once ignited by the fuse, this cartridge will burn vigorously until completely spent and is capable of causing severe burns to exposed skin and clothes, and of igniting dry grass, leaves and other combustible materials

ENDANGERED SPECIES CONSIDERATIONS

NOTICE: It is a Federal offense to use any pesticide in a manner that results in the death of a member of an endangered species.

Do not use in those areas where the following Endangered Species may be known to have dens red wolf, gray wolf, and San Joacium kit fox.

GAS CARTRIDGE FOR COYOTES

For control of coyotes (Canis latrans) in dens only.

NOT FOR SALE TO PERSONS UNDER 16 YEARS OLD

ACTIVE INGREDIENTS:

Sodium Nitrate .							65.0%
Charcoal							35.0%
TOTAL		٠					100.0%

WARNING

STATEMENT OF PRACTICAL TREATMENT CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY!

If inhaled and person has poisoning symotoms (headache, nausea, dizziness, weakness), transfer victim to fresh air. Hill e victim lie down and keep warm. If respiration is adequate, recovery will be rapid. If breathing has stopped, use artificial respiration. If available, pure oxygen should be given.

SEE LEFT SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

UNITED STATES DEPARTMENT OF AGRICULTURE ANIMAL AND PLANT HEALTH INSPECTION SERVICE ANIMAL DAMAGE CONTROL Hyataville, MD 20782 EPA Est. No. 56228-ID-1 EPA Reg. No. 56228-21

Net Weight 240 grams

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Store in cool, dry place away from fire, heat and direct sunlight.

PESTICIDE DISPOSAL: To dispose of unused cartridges, soak in water, crush and bury at least 6" in loose soil.

CONTAINER DISPOSAL: Place in trash collection.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

USE RESTRICTIONS

APPLICATION DIRECTIONS

First select den for treatment. Make sure cartridge will pass easily into opening and obtain meterial to plug the entrance. Then, with a nail at teest 1/8" in diameter, puncture cap at end of cartridge at points marked. Insert fuse in one of center holes. Insure there is a minimum of 3 inches of exposed fuse. Hold cartridge away from face and body, then light.

NOTE: The minimum burn time for these fuses is 5 seconds.

Place cartridge, fuse-end first, as far into the entrance as possible. Close entrance to burrow immediately. (If burrow is steep, contents of cartridge may flow out of lighted end. If so, place cartridge as deep in burrow as possible with fuse-end up, light, and close burrow.

6/89

ACCEPTED
With CONDIDATES
in EPA Lott in Date 4:

SEP 12 1989

Under the Coderet Ingen-Puncted that Didunions of the Comtage of the Later

54228-21

immediately. (If burrow is **steep**, contents of cartridge may flow out of lighted end. If so, place cartridge as deep in burrow as possible with fuse-end up, light, then close burrow.)

Minimum Fuse Burn Time is 5 sec.

GAS CARTRIDGE FOR COYOTES REGISTRATION NO. 56228-21

CONTAINS SODIUM NITRATE (65.0%) AND CHARCOAL (35.0%)

Select den, make sure cartridge will enter freely and obtain material to plug entrance. With 1/8" nail, puncture cap at end of cartridge at points marked. Insert fuse in one of center holes. Insure there is a minimum of 3 inches of exposed fuse. Hold cartridge away from face and body, then light fuse. Place cartridge, fuse-end first, into burrow as far as possible. Plug burrow immediately. (If burrow is **steep**, contents of cartridge may flow out of lighted end. If so, place cartridge as deep in burrow as possible with fuse-end up, light, then close burrow.)

Minimum Fuse Burn Time is 5 sec.

GAS CARTRIDGE FOR COYOTES REGISTRATION NO. 5/228-21

CONTAINS SODIUM NITRATE (65 0%) AND CHARCOAL (35.0%)

Select den, make sure cartridge will enter freely and obtain material to plug entrance. With 1/8" nail, puncture cap at end of cartridge at points marked. Insert fuse in one of center holes. Insure there is a minimum of 3 inches of exposed fuse. Hold cartridge away from face and body, then light fuse. Place cartridge, fuse-end first, into burrow as far as possible. Plug burrow immediately (If burrow is **steep**, contents of cartridge may flow out of lighted end. If so, place cartridge as deep in burrow as possible with fuse-end up, light, then close burrow.)

Minimum Fuse Burn Time is 5 sec.