



BRITEGLOW

ANTIFOULING PAINT

INDIGO BLUE

Active Ingredient: Cuprous oxide 40%
 Inert Ingredients 60%
 This product contains 14.5 lb. of paint per gallon

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Warning: Causes eye irritation. Harmful if absorbed through the skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor, spray, mist, dust, or chips from sanding. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

Flammable! Keep away from heat or open flame.

TP CHEMICAL COMPANY, Inc.

Branchville, NJ 07826

EPA REGISTRATION NO. 56472-5
 EPA ESTABLISHMENT NO. 56472-NJ-001

One U.S. gallon

Made in U.S.A.

NOT REVIEWED

Accordance with 29 CFR 1910.1203
 Based on Draft MSDS, no. 8204

KEEP OUT OF THE REACH OF CHILDREN!


WARNING!

STATEMENT OF PRACTICAL TREATMENT

- If swallowed:** Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.
- If on skin:** Wash with plenty of soap and water. Get medical attention.
- If in eyes:** Flush with plenty of water. Get medical attention.
- If inhaled:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

See other cautions on side panels.



1200
EPA

GENERAL DESCRIPTION

BRITEGLOW ANTIFOULING PAINT is designed for use in salt water on steel, wood and fiberglass surfaces for the control of barnacles, tube worms, sea grasses and algae. It has excellent adhesion and toughness. The finish is glossy and water-repellent to reduce drag.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Stir paint thoroughly before and during use to prevent setting. If required, dilute with BRITEGLOW THINNER. For bare steel, apply anticorrosive coating. For bare wood or fiberglass, apply BRITEGLOW ANTIFOULING PAINT directly to surfaces. For previously painted surfaces, scrape and sand smooth before repainting. Apply one coat of paint normally. For absorbing surfaces, such as bare wood, apply two coats. Coverage is normally 400 sq. ft. per gallon, depending on surface roughness. Drying time is normally 2-4 hours, depending on temperature. Vessel may be launched after the paint is non-tacky to the touch. Do not apply in hot sun. Clean brushes and rollers with BRITEGLOW THINNER or acetone. Do not use on aluminum surfaces.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide, spray mixture, or rinse water that cannot be used according to label instructions must be disposed of according to applicable federal, state or local procedures.

CONTAINERS: Triple rinse (or equivalent) and dispose of in an approved landfill, or by other approved state and local procedures.