



MB 175

ACCEPTED  
COMMENTS  
DATE  
JAN 02 1987

ACTIVE INGREDIENTS:

Methylene bis(thiocyanate) ..... 10%  
2-(Thiocyanomethylthio)benzothiazole ..... 10%

INERT INGREDIENTS ..... 80%

KEEP OUT OF REACH OF CHILDREN  
DANGER

PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**DANGER:** Corrosive, causes irreversible eye damage and causes skin damage. Harmful or fatal if swallowed or absorbed through the skin. This product is a potential skin sensitizer. Workmen handling this product or treated material should wear impervious gloves, goggles or face shield, and protective clothing. All protective clothing, work shoes or boots, and equipment must be left at the work site at the end of the day. Eating, drinking, or smoking during use of this product is prohibited.

**FIRST AID:** In case of skin contact, wash promptly and thoroughly with soap and water and finally with glycerin. If product gets in the eyes, flush immediately with copious amounts of clean, cool water for 15 to 30 minutes. Get medical attention immediately. If product is swallowed, call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL AND CHEMICAL HAZARDS:** Do not use or store near heat or open flame.

Manufactured by:

CLIMATE CONTROL, INC.  
2534 W. CYPRESS STREET  
PHOENIX, AZ 85009

EPA REG. NO. \_\_\_\_\_ EPA Est. No. \_\_\_\_\_

NET CONTENTS \_\_\_\_\_

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in

**COOLING TOWERS:** \_\_\_\_\_ MB 175 \_\_\_\_\_  
wood against soft or surface rot and internal or dry rot. For wood surfaces containing 0.5 to 0.7% by weight \_\_\_\_\_ MB 175 \_\_\_\_\_ wood surfaces. The amount applied should provide 0.6 \_\_\_\_\_ MB 175 \_\_\_\_\_ per 1000 ft.<sup>2</sup> of wood surface. Soft or surface rot can \_\_\_\_\_ MB 175 \_\_\_\_\_ to the rec

cold well. The dosage should provide 1.25 lb. of \_\_\_\_\_ MB 175 \_\_\_\_\_ 1000 gal. of water, and the bleedoff should be stopped \_\_\_\_\_ MB 175 \_\_\_\_\_ ment should be repeated every four months.

**COOLING WATER:** \_\_\_\_\_ MB 175 \_\_\_\_\_  
and fungi in industrial recirculating cooling water systems should be cleaned thoroughly to remove old algal growth. System should then be drained, flushed, refilled with water. 3.7 fl. oz. of \_\_\_\_\_ MB 175 \_\_\_\_\_

quent additions of 0.2 to 1.2 fl. oz. per 1000 gal. should \_\_\_\_\_ MB 175 \_\_\_\_\_ amount of bleedoff and severity of microbiological fouling.

**DRILLING FLUIDS:** To inhibit bacterial and fungal degradation of wells, \_\_\_\_\_ MB 175 \_\_\_\_\_

centrations of 0.05 to 0.25% based on the total wet weight. \_\_\_\_\_ MB 175 \_\_\_\_\_

**PETROLEUM SECONDARY RECOVERY:** \_\_\_\_\_ MB 175 \_\_\_\_\_  
control sulfate-reducing bacteria, slime-forming bacteria, micellar floccs, water-disposal systems, and other oil-field \_\_\_\_\_ MB 175 \_\_\_\_\_

should be made continuously or intermittently by means of \_\_\_\_\_ MB 175 \_\_\_\_\_ knockouts, before or after injection pumps and injectors.

When system is noticeably fouled, add 3.9 to 13.0 fl. oz. \_\_\_\_\_ MB 175 \_\_\_\_\_ per 1000 gal. of water continuously until desired degree of \_\_\_\_\_ MB 175 \_\_\_\_\_

needed to maintain control. Intermittent or Slug Method \_\_\_\_\_ MB 175 \_\_\_\_\_ maintain control, add 3.9 to 13.0 fl. oz. \_\_\_\_\_ MB 175 \_\_\_\_\_

of water for 4 to 8 hr. per day and 1 to 4 times per week. \_\_\_\_\_ MB 175 \_\_\_\_\_

**CRUDE AND REFINED OILS:** \_\_\_\_\_ MB 175 \_\_\_\_\_  
vative for the control of bacteria and fungi that cause trouble \_\_\_\_\_ MB 175 \_\_\_\_\_ during storage. It should be added to the oil as it is being \_\_\_\_\_ MB 175 \_\_\_\_\_

the storage tank at the rate of 0.8 to 6.0 fl. oz. \_\_\_\_\_ MB 175 \_\_\_\_\_ 1000 gal. of oil. Addition should be made batchwise with \_\_\_\_\_ MB 175 \_\_\_\_\_

tion side of the transfer pump.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or \_\_\_\_\_ MB 175 \_\_\_\_\_

**STORAGE:** Do not expose to extreme temperatures. Do not \_\_\_\_\_ MB 175 \_\_\_\_\_ should be opened in well-ventilated areas. Leaking or \_\_\_\_\_ MB 175 \_\_\_\_\_ drums for disposal. Spills should be absorbed in sawdust \_\_\_\_\_ MB 175 \_\_\_\_\_

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely \_\_\_\_\_ MB 175 \_\_\_\_\_ pesticide, spray mixture, or rinsate is a violation of Federal \_\_\_\_\_ MB 175 \_\_\_\_\_ by use according to label instructions, contact your State \_\_\_\_\_ MB 175 \_\_\_\_\_ or the Hazardous Waste representative at your EPA Regional \_\_\_\_\_ MB 175 \_\_\_\_\_

**CONTAINER DISPOSAL:** Triple rinse (or equivalent). \_\_\_\_\_ MB 175 \_\_\_\_\_ puncture and dispose of in a sanitary landfill, by incineration \_\_\_\_\_ MB 175 \_\_\_\_\_ or by burning. If burned, stay out of smoke.