UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

FEB 26 1997

Mr. Eugene L. Mitch Contechem Inc. P.O. Box 3255 Portland, OR 97208

BRITEWOOD Q Sapstain Control Subject:

EPA Registration No. 57227-2 Notification Per PR-Notice 95-2

Dear Mr. Mitch:

.This will acknowledge receipt of your notification, of a minor change in DOT Proper shipping name, submitted under the provisions of FIFRA section 3 (c) 9. Based on a review of the submitted material, the following comments apply.

The application is acceptable and the notification has been made a part of the records for this file.

Sincerely,

Wanda Y. Mitchell Notification Coordinator Antimicrobial Program Branch Registration Division (7505)

| CONCURRENCES | | |
|-------------------------|--|--------------------|
| SYMBOL 75USC | | |
| SURNAME MITCHELL | | |
| DATE 2/26/97 | | |
| FDA Form 1990 14 (1990) | | OFFICIAL FILE COPY |

EPA Form 1320-1A (1/90)

Printed on Recycled Paper

*U.S. GPO: 1994-522-503/82085

BRITEWOOD Q

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

For the control of mold and fungus on green or freshly cut lumber, BRITEWOOD Q, Sapstain Control may be used in a dip or spray application. Before use, dilute at the rate of 25-100 gallons of water per gallon of this product. Seasonal variation in storage and shipping conditions, species and condition of wood should be considered in selection of end use concentration. For effective inhibition of mold and fungus, lumber and logs must be dipped or sprayed such that all surfaces are uniformly treated,

For best results, green wood should be treated immediately, at least within twenty four hours after cutting or sawing. Mold and fungus growth begins immediately after cutting so delayed treatment is much less effective and requires increased chemical concentration. Green, untreated lumber should not be used for stickers.

Freshly treated lumber should not be allowed to remain unprotected in heavy rains. Dip tanks and drip aprons must be roofed, paved and drained to prevent dilution and loss of the anti-stain solution.

DISCLAIMER

The manufacturer and distributor make no warranty, express or implied, concerning the use of this product other that as directed on the label. The use of this product being beyond the control of the manufacturer or distributor, no warranty, express or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. Upon acceptance of delivery of this product, the buyer assumes all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials.

SAPSTAIN CONTROL

For Fresh Cut Lumber

BRITEWOOD Q, Sapstain Control, inhibits the growth of mold and fungus that may cause discoloration and/or deterioration of freshly cut lumber during storage and shipment.

ACTIVE INGREDIENTS:
Didecyl Dimethyl Anumonium Chforide

50.0%

INERT INGREDIENTS:
50.0%

TOTAL:
100.00%

KEEP OUT OF REACH OF CHILDREN

DANGER

FOR INDUSTRIAL AND COMMERCIAL USE ONLY

(See side panel for additional precautionary and practical treatment statements.)

NET CONTENTS: 55 GALLONS

CONTECHEM INC. P.O. BOX 3255 PORTLAND, OR 97208 (503) 283-3021

EPA Reg. No. 57227-2 EPA Est. No. 57227-OR-003

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals

DANGER CORROSIVE: Causes severe eye and skin damage. Do not get in eyes or on skin. Wash contaminated clothing before reuse. Wear gloggles or face shield and rubber gloves when handling concentrate. May be harmful or fatal if swallowed. Avoid contamination of food.

In case of contact, impediately flush oyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Call a physician immediately.

HENVIRORMENTAL HAZARDS

Do not discharge effluent containing this product into lakes streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

PROHIBITIONS: This product must be kept under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its use. Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Do not reuse empty container.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your state Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse or equivalent, then offer for recycling/reconditioning or puncture and dispose of in a sanitary landfill, or by incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

DOT Proper Shipping Name Corrosive liquids, n.o.s.(Quaternary ammonium chloride), 8, UN 1760, PG II Emergency Phone

CHEMTREC 1-800-424-9300