

INSULATED

PEST CONTROL INSULATION

MADE FROM
100% NATURAL
FIBER

Contains No Asbestos, Glass Fibers or Formaldehyde

KILLS

COCKROACHES, ANTS,
DRYWOOD TERMITES,
SUBTERRANEAN TERMITES,
SILVERFISH, EARWIGS,
CRICKETS, SOWBUGS,
MILLIPEDES, CENTIPEDES,
AND BOOKLICE

LONG LASTING PROTECTION THAT IS
EFFECTIVE UNDER NORMAL USAGE AND
CONDITIONS FOR INSTALLED INSULATION

- Odorless and Non-Corrosive
- Reduces Air Infiltration
- Excellent Thermal Insulator
- Patented Fire Retardant
- Superior Sound Barrier
- Easy to Install

FOR USE IN NEW CONSTRUCTION AND
RETROFIT APPLICATION IN ATTICS,
SIDEWALLS AND CRAWL SPACE:

- HOUSES
- APARTMENTS
- OFFICES
- RESTAURANTS
- SCHOOLS
- HOSPITALS
- FOOD PROCESSING PLANTS
- HOTELS

ACTIVE INGREDIENTS

Orthoboric Acid 14.72%

INERT INGREDIENTS

85.28%

TOTAL

100.00%

EPA REG NO 58139

EPA EST NO

KEEP OUT OF THE REACH OF CHILDREN
CAUTION

(See other precautions on back panel.)

MINIMUM NET WT 30LB (13.61 KG)

ACCOUNT NO

INSULIDE

PEST CONTROL INSULATION

INSULIDE PEST CONTROL INSULATION is a ready to use insect control insulation. This product is toxic to listed insects and is intended to prevent their infestations in those building voids (wall, attic, under floor) where the product is applied. It works after insect contact with the product.

KILLS

Cockroaches, Ants, Drywood Termites, Subterranean Termites, Silverfish, Earwigs, Crickets, Sowbugs, Millipedes, Centipedes and Booklice

VALUES VARY, FIND OUT WHY IN THE SELLER'S SHEET ON R-VALUES

THE MARKED R-VALUE. IT IS ESSENTIAL THAT INSULATION BE INSTALLED PROPERLY IF YOU YOURSELF. GET INSTRUCTIONS AND FOLLOW CAREFULLY. INSTRUCTIONS DO NOT COME WITH THIS PACKAGE

DIRECTIONS FOR USE

In accordance with Federal Law to apply this product in a manner consistent with its labeling

NEW CONSTRUCTION AND RETROFIT APPLICATIONS: WALLS, SIDEWALLS AND CRAWL SPACES APPLY INSULATION INTO STRUCTURAL VOIDS. COCKROACHES, SILVERFISH, EARWIGS, CRICKETS, SOWBUGS, TERMITES, CENTIPEDES AND BOOKLICE. This insulation is intended to prevent new drywood and subterranean termite infestations in walls and attics where the product is applied. Control of insects is limited to contact with insulation.

WOOD AND SUBTERRANEAN TERMITES: This insulation is intended to prevent new drywood and subterranean termite infestations in walls and attics where the product is applied. Protection from drywood and subterranean termites is limited to wood in direct contact with insulation.

CAUTION TO HELP AVOID FIRE: Keep insulation at least three inches away from the sides of recessed light fixtures. Do not place insulation over such fixtures so as to trap heat.

Also keep insulation away from exhaust flues of furnaces, water heaters, space heaters, or other heat producing devices.

To be sure the insulation is kept away from light fixtures and flues, use a barrier to permanently maintain clearance around these items. Check with local building or fire officials for guidance on installation and barrier requirements.

REQUEST TO RETAILER: Remove the label and give it to the consumer at completion of job.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. May cause eye irritation. Avoid eye contact. Wash thoroughly after handling.

DURING INSTALLATION: WEAR A PROTECTIVE RESPIRATOR TO PREVENT INHALATION.

STATEMENT OF PRACTICAL TREATMENT: If swallowed, contact a physician. If in eyes, flush eyes with plenty of water. Get medical attention if irritation persists.

STORAGE AND DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Completely empty bag into application equipment. Then dispose of empty bag in a sanitary fashion or by incineration, or if allowed by State and local authorities, by burning. If burned, stay out of smoke.

Manufactured By:

COVERAGE CHART

Pest Control Insulation should be blown of these thicknesses and maximum coverages if divided the terms of installed insulation resistance values shown on per ASTM C-739 Blown-In Compliance with Federal (USA) Specification.

R-Value	Minimum Thickness (Settled) Inches	Minimum Weight per 100 sq. ft.	Maximum Coverage Per Bag (Sq. Ft.)			Minimum Bags Per Thousand Sq. Ft.		
			flat	2'-6" on 16" Centers	2'-4" on 24" Centers	flat	2'-6" on 16" Centers	2'-4" on 24" Centers
R-11	3.0	53	368	824	812	177	181	164
R-13	3.5	61	482	545	517	203	184	190
R-19	5.1	89	337	370	362	297	269	294
R-24	6.5	114	263	289	273	280	250	281
R-30	8.1	142	211	228	217	474	434	481
R-32	8.7	151	189	211	204	583	563	570
R-38	10.3	180	167	175	171	589	569	588
R-40	10.8	189	159	167	162	629	589	616
R-44	11.9	208	144	151	147	684	664	681
R-48	13.0	227	132	138	135	758	728	745

Nationwide Consumer Testing Institute, Inc.



Madison, New Jersey 07702

Release No. Listed for Compliance with FM-1-518D

When representative samples of this product were tested in accordance with the requirements of Federal Specification FM-1-518D and the American CPSC Standard, the following were determined:

Critical Radiant Flux	Greater than or equal to 0.12 w/cm ²
Smoldering Combustion	Less than or equal to 15.0%
Settled Density	1.0 - 1.2 g/cc
Thermal Resistance	3.0 R
Moisture Absorption	Less than 15.0%
Odor Emission	No apparent difference
Corrosiveness	Negative
Search Criteria	Negative
Fungus Resistance	Resistant

Under License From:

INSULIDE PATENT AND TRADEMARK OF JCB ENTERPRISES

JCB ENTERPRISES
8619 EAST SAN JACINTO DRIVE
SCOTTSDALE, ARIZONA 85258

BEST AVAILABLE COPY