

# RIPENER I CONCENTRATE

For use with ARCO Ethylene Generators to produce ethylene gas to accelerate ripening of:

Bananas	Avocados	Papayas	Melons
Tomatoes	Citrus	Pears	Tobacco

ACTIVE INGREDIENT 92.46% ETHANOL

INERT INGREDIENTS 7.54%

TOTAL 100.00%

CONTAINS METHANOL

KEEP OUT OF REACH OF CHILDREN.

**DANGER - POISON**



**DANGER:** Not to be taken internally. Fatal if swallowed. Methanol may cause blindness. Avoid breathing spray mist or vapors. Avoid contact with skin.

#### STATEMENT OF PRACTICAL TREATMENT

**IF SWALLOWED:** Induce vomiting by touching the back of the throat with finger or blunt object. Get medical attention immediately.

**IF IN EYES:** Flush with water for at least 15 minutes. Get medical attention immediately. See other panel for additional Precautionary Statements.

**IF ON SKIN:** Irrigate immediately with water.

**IF INHALED:** Remove from exposure. Get medical attention immediately.

**PHYSICAL OR CHEMICAL HAZARDS.**  
**FLAMMABLE:** Keep away from heat and flame.

EPA REG NO. 58502-1 EST. NO. 58502-NC-001

## AMERICAN RIPENER

Net Contents 32 Fluid Ounces (1 U.S. Quart)

#### DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

#### STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment. Store in dry, locked storage at temperatures below 125°F. **DO NOT REUSE EMPTY CONTAINER**

#### CONTAINER DISPOSAL

Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill or incinerator or, if allowed by State or Local Authorities, by burning. If burned, stay out of smoke.

#### RIPENING ROOMS

**PRODUCE.** Use in the first 24 hours of ripening period. Example: one quart properly used in 4,000 to 8,000 cubic feet ripening room produces ethylene concentrations varying from 20 to 1,200 P.P.M. over a period of 16 hours. One pint properly used in 1,000 to 4,000 cubic feet ripening room produces ethylene concentrations varying from 20 to 600 P.P.M. over a period of 8 hours. By using the ARCO Ethylene Generator and selecting the appropriate method, the output of ethylene can be constant and dependable. See ARCO Ethylene Generator instructions.  
**TOBACCO (FLUE-CURED):** Use 2 quarts immediately after filling 1,500 to 2,500 cubic foot curing barn over a period of 12 hours. Use additional 2 quarts as required.

#### USE PRECAUTIONS

Use of this product in enclosures less than 1,000 cubic feet is prohibited. The treated room should be reasonably airtight, all vents and doors closed, cracks or holes in walls and doors should be repaired or covered over.

#### WARRANTY

Seller's liability to: breach of warranty, express or implied, in connection with the sale of this product shall be limited to replacement at seller's expense of the product, and in no case shall be liable for incidental or consequential damages

PRODUCED AND DISTRIBUTED BY:  
American Ripener Company, Inc.  
803 Pressley Road, Suite 106  
Charlotte NC 28217 (800) 338-2836

**DO NOT REUSE CONTAINER**

PM 22

58502-1

*Final Printed Label*

171