

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (75-767) WASHINGTON, DC 20460	EPA REGISTRATION NUMBER 6078-2	DATE OF ISSUANCE NOV 14 1988
	TERM OF ISSUANCE	
	NAME OF PESTICIDE PRODUCT LL-11	

NOTICE OF PESTICIDE: REGISTRATION
 REREГИSTRATION
(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)

NAME AND ADDRESS OF REGISTRANT (include ZIP code)

A.S., INC.
 1000 N. 10th St.
 KENOSHA, WI 53140

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an endorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

John N. K...

ATTACHMENT IF APPLICABLE

SIGNATURE OF APPROVING OFFICIAL	DATE
---------------------------------	------

AS-115

INDUSTRIAL MICROBICIDE

ACTIVE INGREDIENTS

Methylene bis(1-thiocyanate) 2.5%

2-Thiocyanomethylthiolbenzothiazole 2.5%

INERT INGREDIENTS

95.0%

This product weighs 7.99 pounds per gallon

**KEEP OUT OF REACH OF CHILDREN
DANGER**

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive, causes irreversible eye damage and causes skin damage. Harmful or fatal if swallowed or absorbed through the skin. This product is a potential skin sensitizer. Workmen handling this product or treated material should wear impervious gloves, goggles or face shield, and protective clothing. All protective clothing, work shoes or boots, and equipment must be left at the work site at the end of the day. Eating, drinking, or smoking during use of this product is prohibited.

FIRST AID: In case of skin contact, wash promptly and thoroughly with soap and water and finally with glycerin. If product gets in the eyes, flush immediately with copious amounts of clean, cool water for 15 to 30 minutes. Get medical attention immediately. If product is swallowed, call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply directly to water or wetlands. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS: Do not expose to extreme temperatures

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal

STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COOLING TOWERS: AS-115

Apply AS-115 to wood against soft or surface rot and internal or dry rot. It contains 2.0 to 2.8% AS-115

Apply AS-115 to wood surfaces. The amount applied should provide 2.4 to 3.2 lb of AS-115 per 1000 ft² of wood surface. Soft or surface rot can also be controlled by AS-115.

Apply AS-115 to the recirculating well. The dosage should provide 5.0 lb of AS-115 per 1000 gal of water and the bleedoff should be stopped for 4 to 6 hr after application and repeated every four months.

COOLING WATER: AS-115

Apply AS-115 to industrial recirculating cooling water systems. The system should be cleaned thoroughly to remove old algal growth.

Apply AS-115 to the recirculating well. The dosage should provide 5.0 lb of AS-115 per 1000 gal of water and the bleedoff should be stopped for 4 to 6 hr after application and repeated every four months.

DRILLING FLUIDS: To inhibit bacterial and fungal drilling of wells, AS-115

Apply AS-115 to drilling fluids. The dosage should provide 0.2 to 1.0% based on the total wet weight of drilling fluids.

PETROLEUM SECONDARY RECOVERY: AS-115

Apply AS-115 to control sulfate reducing bacteria, slime forming bacteria, and other oil field problems. The dosage should provide 2.4 to 24.0 lb of AS-115 per 1000 gal of oil.

Apply AS-115 to control sulfate reducing bacteria, slime forming bacteria, and other oil field problems. The dosage should provide 2.4 to 24.0 lb of AS-115 per 1000 gal of oil.

Apply AS-115 to control sulfate reducing bacteria, slime forming bacteria, and other oil field problems. The dosage should provide 2.4 to 24.0 lb of AS-115 per 1000 gal of oil.

Apply AS-115 to control sulfate reducing bacteria, slime forming bacteria, and other oil field problems. The dosage should provide 2.4 to 24.0 lb of AS-115 per 1000 gal of oil.

Apply AS-115 to control sulfate reducing bacteria, slime forming bacteria, and other oil field problems. The dosage should provide 2.4 to 24.0 lb of AS-115 per 1000 gal of oil.

Apply AS-115 to control sulfate reducing bacteria, slime forming bacteria, and other oil field problems. The dosage should provide 2.4 to 24.0 lb of AS-115 per 1000 gal of oil.

Apply AS-115 to control sulfate reducing bacteria, slime forming bacteria, and other oil field problems. The dosage should provide 2.4 to 24.0 lb of AS-115 per 1000 gal of oil.

Apply AS-115 to control sulfate reducing bacteria, slime forming bacteria, and other oil field problems. The dosage should provide 2.4 to 24.0 lb of AS-115 per 1000 gal of oil.

Apply AS-115 to control sulfate reducing bacteria, slime forming bacteria, and other oil field problems. The dosage should provide 2.4 to 24.0 lb of AS-115 per 1000 gal of oil.

Manufactured by

AS-115, INC.

118 SEVILLE

HERNANDO, LA 70424

EPA REG. NO. _____

EPA _____

NET CONTENTS _____