PM32 59209-1

To: Nr. P.C. Ashae.

RESTRICTED USE PESTICIDE

DUE TO ACUTE INHALATION TOXICITY OF HIGHLY TOXIC PHOSPHINE GAS For retail sale to and use only by certified applicators for those uses covered by the applicator's certification or persons trained in accordance with the applicator's manual working under the direct supervision and in the physical presence of the certified applicator. Physical presence means on site or on premises. Read and follow the label and the applicator's manual which contains complete instructions for safe use of this pesticide.

APPLICATOR'S MANUAL

QUIK-FUME

Tablets, Pellets and Bags

Aluminum Phosphide Fumigant A fumigant for use against listed insects which infest listed raw agricultural commodities, specified processed foods and animal feeds Active ingredient: Aluminum Phosphide Inert Ingredients PRECAUTION AL USUARIO: Si usted no lee ingles no use este producto

hasta que la eliqueta se le haya sido explicado ampliamente.

KEEP OUT OF REACH OF CHILDREN DANGER/PELIGRO-POISON

PRACTICAL TREATMENT STATEMENT

SYMPTOMS of overexposure to phosphine are headache, dizziness, nauses, difficult breathing, vemiling and diarrhea. In all cases of overexposure, get immediate medical attention. Take the victim to a doctor or emergency treatment facility.

If the gas from aluminum phosphide is INHALED: Move exposed person to fresh air. Keep person warm and make sure person can breathe freely. If breathing has stopped, give artificial respiration by mouth-to-mouth or other means of resuscitation. Do not give anything by mouth to an unconscious person.

If atuminum phosphide powder, granules, tablets or pellets are SWALLOWED: Drink or administer one or two glasses of water and induce vomiting by touching back of throat with linger, or if available, syrup of ipecac. Do not give anything by mouth if victim is unconscious or not alert.

If powder, granules, tablets or pellots of aluminum phosphide get on SKIN; Brush material off clothes and shoes in a well vanillated area. Allow clothes to serate in a ventilated area prior to laundering. Wash contami-ated bare standhoroughly with soap and water.

If in EYES; Clish with plenty of water. Got medical attention immediately.

Manufactured for INVENTA CORPORATION

990 Highland Drive, Suite 110-T, Solana Beach, California 92075 USA Phone : (619) 702 5665 Fax : (619) 792-8578 EPA Registration Nos. 5920947 59205-2 and 59209-3 MANUAL. READ AND UNDERSTAND THE ENTIRE LABELING AND MANUAL. ALL PARTS OF THE LABELING AND MANUAL ARE EQUALLY IMPORTANT. FOR SAFE AND EFFECTIVE USE OF THIS PRODUCT CONTACT INVENTA CORPORATION 990 Highland Drive, Suite 110-T

THIS PRODUCT IS ACCOMPANIED BY AN APPROVED LABEL AND APPLICATOR'S

Solana Beach, California 92075 USA IF YOU HAVE ANY QUESTIONS REGARDING THIS LABELING OR MANUAL OR DO NOT UNDERSTAND ANY PARY OF THIS LABELING OR MANUAL, REFER TO THE APPLICATOR'S MANUAL FOR DETAILED PRECAUTIONS, RECOMMENDATIONS, AND DIRECTIONS FOR USE.

STATEMENT OF WARRANTY

Manufacturer warrants that the product conforms to its chemical description and when used according to label directions under normal conditions of use, it is reasonably fit for the purposes stated. Seller makes no other warranty, either expressed or implied, and buyer assumes all risk should the product be used contrary to label instructions.

TABLE OF CONTENTS

1. INTRODUCTION AND SAFETY RECOMMENDATIONS SUMMARY

- 2. PRECAUTIONARY STATEMENTS
 - A. Hazards to Humans and Domestic Animals
 - B. Practical Treatment Statement
 - C. Note to Physician
 - D. Physical and Chemical Hazards

3. DIRECTIONS FOR USE

- A. General
- B. Efficacy
- C. Exposure Conditions
- D. Commodities Which May Be Fumigated with Quik-Fume
- E. Recommended Dosages
- F. Application Procedures

. AERATION OF FUMIGATED COMMODITIES

- A. Foods and Feeds
- B. Tobacco
- 5. PLACARDING OF FUMIGATED AREAS
- 5. PROTECTIVE CLOTHING
- APPLICATOR AND WORKER EXPOSURE
- 8. STORAGE INSTRUCTIONS
- DISPOSAL INSTRUCTIONS

9.

ACCEPTED

Under the Federal Insect of te. Fungicide, and Bode stirt? Act, as amon ted, for the pesticide

rogistated under EPA Reg No. 59209.

- A. General Disposal Statements
 - B.* Directions For Disposal Of Residual Dust From Quik-Fume
 - C. Directions For Deactivation Of Residual Dust From Quik-Fume

10. SPILL AND LEAK PROCEDURES

SECTION 1

INTRODUCTION

1.12.

ACCEPTED

JAN 15 1007

Under the Federal Insecticide, Fungicide and Redemicide Act,

as amonded, by the pesticide

EPA Rog. No. 59209 -

registered under

Ould Fume fumigants are used to protect stored commodities from damage by insects and for control of burrowing pests. Fumigation of stored products with Oulk-Fume in the manner prescribed in the labeling does not contaminate the stored commodity. Oulk-Fume and other aluminum phosphide fumigants are acted upon by atmospheric moisture to produce phosphine (PH, hydrogen phosphide) gas. Quik-Fume Tablets, Petiets and Bags contain aluminum phosphide (AIP) as their active ingredient and will liberate phosphine via the following chemical reaction:

AIP + 3H O ---> AI(OH) + PH

Phosphine gas is highly loxic to insects, burrowing peats, humans and other forms of animal life. In addition to its toxic properties, this gas will corrode certain metals and may ignite spontaneously in air at concentrations above its lower flammable limit of 1.8%. (V/V). These hazards will be described in greater detail later in this manual. Quik Furne Tablets & Pellets also contains ammonium carbamate which liberates ammonia and carbon dioxide as follows:

NH COONH ---> 2NH + CO

These gases are essentially nonflammable and act as inerting agents to reduce fire hazards, The ammonia gas also serves as a warming agent.

Quik-Fune is prepared in three forms, tablets, pellets and bags. The rounded tablets weigh approximately 3 grams and release 1 gram of phosphine gas. They are about 16.5 mm in diameter and are bulk packaged in reseatable aluminum flasks containing 100 or 500 tablets each. The pellets weigh approximately 0.6 gram and release 0.2 gram of phosphine gas. They are about 9.5 mm indiameter and are packaged in reseatable tlasks containing about 1660 pellets. The bags contain 34 grams each and release 11 grams of phosphine gas. They are packaged in metal containers of six, ten or one hundred bags to the container. Other package sizes may be available. The bags are packaged in an inert environment.

Upon exposure to air, Quik-Fume Tablets, Pellets and Bags begin to react with atmospheric moisture to produce small quantities of phosphine gas. This reaction starts slowly, gradually accelerates and lhen tapers off again as the aluminum phosphide is spont. Quik-Fume Tablets and Pellets react somewhat faster than do the bags. The rates of decomposition of the tablets, pellets and bags vary, depending upon the moisture and temperature conditions. For example, when moisture and temperature of the fumigated commodity are high, decomposition of Quik-Fume may be complete in less than 3 days. However, at lower ambient temperatures and low relative humidity levels, decomposition of Quik-Fume may require 5 days or more. After decomposition, Quik-Fume leaves a gray-white powder composed almost entirely of aluminum hydroxide and other approved inert ingredients. If properly exposed, the spent Quik-Fume will normally contain only a small amount of unreacted aluminum phosphide and may be disposed of without hazard. Partially spent residue from incompletely exposed Quik-Fume will require special care. Precaultors and instructions for further deactivation and disposal will be given later in the applicator's manual.

Quik-Fume Pallets, Tablets and Bags are supplied in gastight containers and their shelf life is unlimited as long as the packaging remains intact. Once opened for fumigation, the flasks of tablets and pellets may be tightly resealed and stored for future use. The Quik-Fume Bag's container cannot be resealed for future use. Storage and handling instructions will be given in detail later in the applicator's manual.

SAFETY RECOMMENDATION SUMMARY

1. Carefully read the labeling and follow instructions.

- 2. Never fumigate alone from inside the storage structure.
- Person supervising must be a cartilled fumigator, and the personnel assisting must be trained in the use of aluminum phosphide. Never allow uninstructed personnel to handle aluminum phosphide.
- Approved respiratory protection must be available for the furnigation of structures from within.

 Wear dry gloves of collon or other materials if contact with Quik-Fume Tablets, Pellets or the powder from Bags is likely. Aerate used gloves and other contaminated clothing in a well ventilated area prior to laundering. Wash hands thoroughly after using Quik-Fume.

36. Open lumigant container in open air only. Never open in a flammable atmosphere.

- 7. Do not allow Quik-Fume to contact water or pile up.
- Dispose of empty containers and spent residual dust in a manner consistent with the label instructions.
- 9. Post warning placards on fumigated areas.

- Prior to lumigation, notify appropriate company employees. Provide to local officials (fire department, rescue squad, police, etc.) on an annual basis, relevant safety information for use in the event of an emergency.
- 11. Phosphine lumigants are not to be used for vacum lumigations.
- 12. Exposure to phosphine must not exceed the eight hour TWA of 0.3 ppm during application or a ceiling concentration of 0.3 ppm after application is completed.
- Furnigated areas must be aerated to 0.3 ppm phosphine or less prior to reentry by unprotected workers."
- 14. Finished loods and feeds that have been furnigated with Quik-Fume must be aerated for 48 hours prior to offering to the end use consumer.
- 15. Transfer of a treated commodity to another site without complete aeration is permissible provided that the new storage site is placarded if the phosphine concentration is above 0.3 ppm.
- 16. Keep containers of Quik-Furne tightly closed except while removing product for application.
- Protect-materials containing metals such as copper, silver, gold and their alloys and salts from corrogive exposure to phosphine.
- 18. Tablets, pellets and bags must not come in contact with any processed food, except that tablets and pellets may be added directly to processed brewers rice, mait and corn grits used in the manufacture of beer.

ACCEPTED

JAN 15 1997 Under the Pederal Insecticide, Pungle that and Bodomicide Act, as an ended, for the posticide

EPA Roy. No. 5720 9

- 19. Do not use aluminum phosphide containers for any purpose other than recycling or reconditioning. *
- OSHA recommends pre-exposure screening of employees to detect impaired pulmonary function. They recommend that any employee developing this condition be referred for medical examination.

SECTION 2

PRECAUTIONARY STATEMENTS

A. HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

DANGER: Aluminum phosphide powder, granules, tablets or pellets may be fatal if swallowed. Do not get in eyes, on skin or on clothing. Do not eat, drink or smoke while handling aluminum phosphide furnigants. If a sealed container is opened or if the material comes into contact with moisture, water or acids, extremely toxic phosphine gas will be released. If a garlic odor is detected, refer to APPLICATOR AND WORKER EXPOSURE section of the applicator's manual for appropriate monitoring procedures. Pure phosphine gas is odorless; the odor is due to a contaminant. Since an odor may not be detected under certain circumstances, the absence of a garlic odor does not mean that phosphine gas is absent. Observe proper application, aeration, reentry and disposal procedures specified etsewhere in the labeling and in this manual to prevent overexposure.

B. PRACTICAL TREATMENT STATEMENT

SYMPTOMS of overexposure to phosphine are headache, dizziness, nausea, difficult breathing, vomitting and diarmea. In all cases of overexposure, get immediate medical attention. Take the victim to a doctor or emergency treatment facility.

If the gas from aluminum phosphide is INHALED: Move exposed person to fresh air. Keep person warm and make sure person can breathe freely. If breathing has stopped, give artificial respiration by mouth to mouth or other means of resuscitation. Do not give anything by mouth to an unconscious person.

If aluminum phosphide powder, granules, tablets or pellets are SWALLOWED: Drink or administer one or two glasses of water and induce vomiting by touching back of throat with finger, or if available, syrup of ipecac. Do not give anything by mouth it victim is unconscious or not alert.

If powder, granules, tablets or pellets of aluminum phosphide get on SKIN: Brush material off clothes and shoes in a well ventilated area. Allow clothes to aerate in a ventilated area prior to faundering. Wash contaminated bare skin thoroughly with soap and water.

If in EYES: Flush with plenty of water. Get medical attention immediately.

C. NOTE TO PHYSICIAN (We recommend that this section be given to the attending physician):

Aluminum phosphide granules, powder, tablets or pellets react with moisture in the air, acids, and many other liquids to release phosphine gas. Mild exposure by inhalallon causes malaise, ringing of ears, faligue, nausea and pressure in the chest which is relieved by removal to fresh air.

Moderate poisoning causes weakness, vomiting, epigastric pain, chest pain, diarrhea and dyspnea.

. . 60 -

Severe poisoning may occur in a few hours to several days, resulting in pulmonary edema and may lead to dizzines, cyanosis, unconsciousness and death.

In sufficient quantity, phosphine affects the liver, kidneys, lungs, nervous system and circulatory system. Inhalation can cause lung edema and hyperemia. Small perivascular brain hemorrhages, and brain edema. Ingestion can cause lung and brain symptoms, but damage to the viscera is more common. Phosphine poisoning may result in (1) pulmonary edema; (2) liver elevated servin GOT, LDH and alkaline phosphalase; reduced prothrombin; hemorrhage and [aundice; and (3) kidney hematuria and anuria. Pathology is characteristic of hypoxia. Frequent exposure over a period of days or woeks may cause poisoning. Treatment is symptomatic. For further information, contact the national polson control center.

D. PHYSICAL AND CHEMICAL HAZARDS

Aluminum phosphide in tablets, pellets, bags and partially spent dust will release phosphine gas if exposed to moisture from the air or if it comes into contact with water, acids and many other liquids. Pilling of tablets, pellets or dust from their fragmentation may cause a temperature increase and confine the release of gas so that ignition could occur.

Hydrogen phosphide air mixtures at concentrations above the lower flammable limit may ignite spontaneously. Ignition of high concentrations of hydrogen phosphide can produce a very energetic reaction. Explosions can occur under these conditions and may cause severe personal lnjury. Never allow the buildor of hydrogen phosphide lo. exceed explosive from the solution of an explosive atmosphere.

Always open containers of aluminum phosphide products outdoors or indoors in the presence of mechanical ventilation that vents immediately outside, as under certain conditions, they may liash upon opening. When opening, point the container away from the face and body and slowly loosen the cap. Although the chances for flash are very remote, never open the container in a flammable atmosphere. These precautions will also reduce the applicator's exposure to phosphine gas.

Pure phosphine gas is practically insoluble in water and oils and is stable at normal fumigation temperatures. However, it may react with cartain metals and cause corrosion, especially at higher temperatures and relative humidities. Metals such as copper, brass and other copper alloys, and practicus metals such as gold and silver are susceptible to corrosion by phosphine. Thus, small electric motors; smoke detectors, brass sprinkler heads, batteries and battery chargers, fork lifts, temperature monitoring systems, electrical switch gear, communication devices, computers, calculators and other electrical equipment should be protected or removed before fumigation.

Phosphine gas will also react with certain metallic salts and therefore, sensitive items such as pholographic film, some programs pigments, etc. should not be exposed

÷	v		Η			٠	
~		*	٠		-	•	
÷	÷	•	¥.			٠	
	ų –	*	٠	*	٠	٠	

ACCEPTED JAN 15 1997 Under the Federal Insectede, Funcente, and Bodanti-Ke Act, as a south to the pesticide regression of the control of the PDA Reg. No.59/209 - /

SECTION 3

DIRECTIONS FOR USE

. GENERAL

المرجع المرجع المرجع

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

- 1. Quik-Fume Tablets, Pellets and Bags are RESTRICTED USE PESTICIDES due to the acute inhalation toxicity of phosphine gas. These products are for retail sale to and use only by certified applicators for uses covered by the applicator's certification or persons trained in accordance with the manual, working under the direct supervision and in the physical presence of the applicator. Physical presence means on site or on the premises. Read and follow the label and the manual which contains complete instructions for the safe use of this pesticide.
- Quik-Fume is a highly hazardous material and should be used only by Individuals trained in its proper usa. Before using, read and follow the precautions and directions contained in the Quik-Fume label and in the applicator's menual.
 - Persons working with Quik-Fume should be knowledgeable of the hazards of this chemical and trained in the use of required respiratory equipment and detector device, emergency procedures and use of the fumigant.
- Additional copies of the applicator's manual are available from:

INVENTA CORPORATION 990 Highland Drive, Suite 110-T Solana Beach, California 92075 USA

- 3. At least two persons trained in the use of aluminum phosphide must be present during fumigation of a structure if entry into the structure is required for application of the fumigant. Two trained persons must also be present during reentry into fumigated or partially aerated structures. Only one trained person is required to be present when Quik-Fume is applied from outside the area to be treated.
- 4. Ship holds, barges, containers on ships, railroad cars and containers shipped piggyback by railway may be fumigated in transit. However, trucks, vans, trailers and similar transport vehicles cannot be moved over public roads and highways until they are aerated and the warning placards removed.
- Do not fumigate commodilles with Quik-Fume when commodily temperature or the temperature to which aluminum phosphide is exposed is below 40°F (5°C). A dd
- 8. The site to be fumigated must first be inspected to determine if it can be made sufficiently gastight. Then a plan should be developed to provide for safe and efficient application of the fumigant to include emergency procedures etc., where required, and to decide how monitoring should be conducted to prevent excessive exposures.
- 7. Weardry gloves of cotton or other material while handling Quik-Furne Tablets or Pellets. Wash hands thoroughly after use. removed work in Parago
- Phosphine gas may flash at concentrations above its flammable limit. Therefore, always
 open Quik-Fume containers in open air and never in a flammable atmosphere. This

precaution will not only prevent harm in the unlikely event of a ftash but will reduce the applicator's exposure to phosphine gas.

: 27

9. Piling of tablets, cellets or bags or addition of water to Quik-Fume may speed up the reaction, cause a temperature increase and/or confine the gas so that ignition could occur.

10. As much as is possible, protect unused Quik-Fume from excessive exposure to atmospheric moisture during application and tightly reseal the aluminum flask prior to returning tablets or pellets to storage, Quik-Fume Bag containers, once opened, cannot be resealed for future use.

11. Phosphine gas may react with certain metals and their salts to produce corrosion, Copper, copper alloys and precious metals such as silver and gold are susceptible to corrosion and items containing these elements should be removed or protected prior to fumigation with Quik-Fume.

12. Do not allow Quik-Fume or its residual dust to come in contact with processed loods or commodily packages intended for retailers except that Quik-Fume Tablets, Pellels or Bags may be added directly to processed brewers rice, mall and corn grits used in the manufacture of beer.

13. Respiratory protection approved for the concentration to which the fumigator will be exposed must be available if Quik-Fume is to be applied from within the structure to be lumigated. Respiratory protection need not be available for uses such as outdoor application or addition of tablets or pellets to automatic dispensing devices etc., if exposure above the TLV's will not be encountered. A NIOSH/MSHA approved, full-face gas mask, phosphine canister combination may be used at levels up to 15 nom. Above this level or in situations where the phosphine concentration is unknown a NIOSH/ MSHA approved, self-contained breathing apparatus (SCBA) or its equivalent must be used.

14. Notify appropriate company employees prior to fumigation. Provide to local officials (fire department, rescue squad, police, etc.) on annual basis relevant safety information for use in the event of an emergency.

B. EFFICACY

Quik-Pume has been found effective against the following insects and their preadult stages (edgs, larvae and pupae):

٠	almond moth	•	European grain moth	٩	Medilerranean flour moth
٠	angoumois grain moth	٠	flat grain beette	•	pink boliworm
٠	bean weevil	•	fruit flies	٠	raisin moth
٠	bees	•	granary weevil	٠	red flour beetle
•	cadella	٠	grealer wax moth	•	rice weevil
+	cereal los beelle	•	hairy fungus beelle	٠	rusty grain beetle
٠	cigarejte beelje 🟅 💦	•	Hessian fly	•	saw-toothed grain beetle
٠	conjused flour beeller 🐂	٠	indian meal moth	•	spider beelle
٠	dermastid beetle	•	khapra beelle	•	tobacco moth
1	dried fruit beetle	•	lesser grain borer	•	yellow meal worm
.*	ູ້ d!ontjiuni banb		กาล์เรู้ๆ พยชงฟ		
		<u>.</u> `			A
-		Ű.	6		

ACCEPTED

JAN 15.1997

Under the federal Insecticitie, Fungitale and Rodon; cide Act, as user led, for the pusticide

te mar el cuder EPA Rug. N:59.209-1 Although it is possible to achieve total control of the listed insect pests, this is frequently not realized in actual practice. Factors contributing to less than 100% control are leaks, poor gas distribution, unfavourable exposure conditions, etc. In addition, some insects are less susceptible to phosphine than others, if maximum control is to be attained, extreme care must be taken in sealing, the higher dosages must be used, exposure periods must be lengthened, proper application procedures followed and temperature and humidity must be favourable.

C. EXPOSURE CONDITIONS

The following conditions may be used as a guide in determining the minimum length of th exposure period at the indicated temperatures: Highware Exposure Deriods for Ouily Europ

withintern Exposite Forious for dark-i dire				
Temperature to which Fumigant or	Pellets	Tablets	Bags	
insects are Exposed			•	
			.	
below 40°F (5°C) .	Do not fumigate	Do not lumigate -	Do not fumigate	
40°-53°F (5-12°C)	8 days (192 hours)	10 days (240 hours)	14 days (336 hours)	
54•-59°F (12-15°Ć)	4 days (96 hours)	5 days (120 hours)	9 days (216 hours)	1.1 2 12
60°-68°F (16-20°C)	3 days (72 hours)	4 days (96 hours)	6 days (144 hours)	ADD 48hr
above 66°F (20°C)	2 days (48 hours)	3 days (72 hours)	4 days (96 hours)	
above 77°F (25°C)		_	3 days (72 hours)	add 77°F

DA

The length of the fumigation must be great enough to provide for adequate control of the insect posts which infest the commodity being treated. Additionally, the furnigation period should be long enough to allow for more or tess complete reaction of Quik-Fume with moisture so that little or no unreacted aluminum phosphide remains. This will minimize phosphine exposure during further storage and/or processing of the treated bulk commodity as well as reduce hazards in the disposal of partially spent aluminum phosphide products remaining after space furnigations. The proper length of the furnigation period will vary with exposure conditions, since in general, insects are more difficult to control at lower temperatures and the rate of phosphine gas production by Quik-Fume is less at lower temperatures and humidities.

It should be noted that there is tittle to be gained by extending the exposure period if the structure to be lumigated has not been carefully sealed or if the distribution of gas is poor and insects are not subjected to lethal concentrations of phosphine. Caroful sealing is required to ensure that adequate gas levels are retained and proper application procedures must be followed to provide satisfactory distribution of phosphine gas. Some structures can only be treated when completely larped; while others cannot be properly sealed by any means and should not be fumigated. Exposure times must be lengthened to allow for penetration of gas throughout the commodily when furnigant is not uniformly added to the mass, for example by surface application or shallow probing. This is particularly important in the fumigation of a bulk commodily contained in large storages. Exposure times need not be lengthened if phosphine is being re-circulated in bulk storage.

Remember, exposure periods in the table are minimum periods and may not be adequate to control all stored product pests under all conditions nor will they always provide for total reaction of Quik-Fume, particularly if temperature and commodity moisture levels or humidity are low during the fumigation, A temperature of 70°F and 11.5% grain moisture (60% relative humidity) provides excellent conditions for fumigation. At lower humidities the listed exposure period must be increased.

D. COMMODITIES WHICH MAY BE FUMIGATED WITH QUIK-FUME

Quik-Fume may be used for the tumigation of the listed raw agricultural commodities, animal feed and feed ingredients, processed foods, tobacco and certain other nonfood items.

1. Raw Agricultural Commodities, Animal Feed and Feed Ingredients

The listed commodilies may be furnigated with Quik-Furne, Quik-Furne Tablets, Pellets and Bags may be added directly to animal feed, feed ingredients and raw agricultural commodities. For space lumigations Quik-Fume. Tablets & Pellets may also be applied in moisture permeable envelopes or on Irays or similar devices. Chon,

1 almonde	* hadan	•	• • • • •
annonus	- Daney	Conce beans	peanuls
🔮 animal feed and	* wheat	• corn	Decans
**Cileed ingredients	 filberts 	 collonseed 	 pistachio nuls
* millet	Ilower seed	* dates	* popcorn
 soybeans 	* grass seed	sallower seed	rapeseed h do "
 sunilower seeds 	* sorghum	' sesame seed	(including canola)
 Initicale 	 Brazil nuts 	seed & pod vegetables	rice
 vegetable seeds 	° cashews	* walnuts	* rye i
		toals .	 cocoa beans

2. **Processed Foods**

The fisted processed foods may be furnigated with Quik-Furne. Under no conditions shall any processed lood come in contact with Quik-Fume Tablets, Pellets, Bags or residual dust except that Quik-Fume may be added directly to processed brewer's rice, mall and dorn grits for use in the manufacture of beer.

- Processed candy and sugar
- Cereal flours and bakery mixes
- Cereal foods (including cookies, crackers, macaroni, noodles, pasta, pretzels, snack foods and spaghetti)
- Processed cereals (including milled fractions and packaged cereals)
- Cheese and cheese by products
- Chocolate and chocolate products (assorted chocolate, chocolate liquor, cocoa, cocoa powder, dark chocolate coating and milk chocolate)
- Processed collee
- Corn grits
- Curad, dried and processed meat products and dried fish
- Dates and fios
- Dried eggs and egg yolk solids
- Dried milk, dried milk powder, nondairy creamers, and nonfat dried milk
- Dried or dehydrated fruits (apples, dates, ligs, peaches, pears, prunes, raisins and sultanas)
- Processed herbs, spices, seasonings and condiments
- Malt -. ...
- Processed nuts, Calmonda, apricot kernels, Brazil nuts, cashews, filberts, peanuts pecan, pistachio-nuts and walnuts)
- Processed oats (including oatmeal)
- Rice (brewers rice, grits, enriched and polished rice and wild rice)
- Soybean flour and milled fractions
- Processed tea

Dekted Dried + dehydrated

Yeast (including primary yeas)

3. Nonfood Commodities, including Tobacco

The listed nonlood items may be fumigated with Quik-Fume. Tobacco and certain other of the nonlood commodities should not be contacted by tablets, pellets or residual dust.

- Processed or unprocessed collon, wool and other natural fibers or cloth
- Clothing
- Straw and hav
- Feathers
- Human hair, rubberized hair, vulcanized hair, and mohair
- Leather products, animal hides and furs
- Tobacco

ACCEPTED

JAN 15 1997

Under the Federal Insecticide. Fungi 11a. un: Rodenticide Act. us a sended, for the posticide

rend under EPA Reg. No. 59209-1

- Wood, cul trees, wood chips, and wood and bamboo products
- Paper and paper products
- Dried plants and flowers
- 810 seeds and vegetable seed)

E. RECOMMENDED DOSAGES

Phosphine is a mobile gas and will penetrate to all parts of the storage structure. Therefore, dosage must be based upon the total volume of the space being treated and not on the amount of commodity it contains. The same amount of Quik-Fume is required to treat a 30,000 bushel silo whether it is empty or full of grain, unless the surface of the commodity is sealed off by a tarpautin. The following dosage ranges are recommended for bulk and space lumidations:

Dosage Guidelines For Fumigation With Quik-Fume

Product	per 1000 cu. ft.*	per 1000 bu.*	
Bags	2 - 13 (ᠠ≌ৣ≍/ ᠠ	2 - 16 (bl/ 6)	
Pellets	100 - 725	120 - 900	
Tablets	20 - 145	25 - 180	
		20 100	

*Dosage range for dates, nuts and dried fruits is 20 - 40 tablets, 100 - 200 pellats, 2 - 4 baos/ 1000 cu. ft; 25 - 50 tablets, 125 - 250 pellets, 2.5-5 bags/1000 bu,

These dosages are not to be exceeded. It is important to be aware that a shortened exposure period cannot be fully compensated for with an increased dosage of phosphine. The wide range of dosages listed above is required to handle the variety of fumigation situations encountered in practice. Somewhat higher dosages are usually recommended under cooler, drier conditions or where exposure periods are relatively short. However, the major factor in selection of dosage is the ability of the structure to hold phosphine gas during the fumigation. A good illustration of this point is a comparison of the low dosages required to treat modern, well-sealed warehouses with the higher dosage used for poorly constructed buildings that cannot be sealed adequately. In certain other lumigations, proper distribution of lethal concentrations of gas becomes a very important factor in dose selection. An example where this may occur is in the treatment of grain stored in flat storage. Poor gas distribution frequently results when the furnigant cannot be uniformly added to the grain, and it must be treated by surface application.

Although it is permissible to choose from the full range of dosages listed above, the following • dosages are recommended for the various types of fumigations:

Recommended Quik-Fume Dosages for Various Types of Fumigations

Type of Fumigation	Bags	Pellets	Tablets
i. 🖟 Space			
Mills, warehouses etc	2-6/1000 cu fl.	100-300/1000 cu.fl.	20-60/1000 cu.ft,
Bagged commodities	(2)3-6/1000 cu.H.	150-300/1000 cu.fl.	30-60/1000 cu.fl.
Processed fruits & nu	ts 2-471000 cu.lt.	100-200/1000 cu.fl.	20-40/1000 cu.ll.
Stored Tobacco	2-4/1000 cu ff.	100-200/1000 cu.ft.	20-40/1000 cu.lt
		•	'i
2. Bulk Stored Commod	illes		
Venical storage	3-6/1000 cu.ll.	150-300/1000 cu.n.	30-60/1000 cu.ii.
	4-7/1000 bu.	200-375/1000 bu.	40-75/1000 bu
Tanks	4-7/1000 cu.fl.	150-350/1000 cu.ft,	30-70/1000 cu.fl.
	58/1000 bu:*	200-450/1000 bu.	40-90/1000 bu
Flat storages	5-13/1000 cu.ft.	250-725/1000 cu.ft.	50-145/1000 cu.fl.
÷	6-16/1000 bu.	300-900/1000 bu,	60-180/1000 bu.
Farm bins	6-13/1000 cu.ft.	350-725/1000 cu.ft.	70-145/1000 cu.fl;
•	8-16/1000 bu.	450-900/1000 bu.	90-180/1000 bu.
Bunker & tarped	3-6/1000 cu.ft.	150-400/1000 cu.ft.	30-80/1000 cu.ft.
ground storages	4-8/1000 bu	200-500/1000 bu.	40-100/1000 bu
Bailcars	3-6/1000 cu.ll.	150-325/1000 cu.ft.	30-65/1000 cu.ft.
	4-7/1000 bu.	200-400/1000 bu.	40-80/1000 bu.
Barnes	3-7/1000 cu.fl.	150-400/1000 cu.ft.	30-80/1000 cu.fl.
	4.9/1000 bu	200-500/1000 bu	40-100/1000 bu
Ship holds	3.6/1000 cu.lt	150-990/1000 cu ft	30_66/1000 cu fi
orep ribids	4.7/1000 bu	200 275/1000 bu	40 75/1000 bu
	41771000 00.	200-070/1000 00.	40-7071000 DU.

Higher dosages are recommended in structures that are loose construction and in the lumigation of bulk stored commodities in which diffusion will be slowed and result in poor distribution of obsorbine cas.

- F. APPLICATION PROCEDURES
- . General Statement

Regardless of the type of storage to be treated, there are several important factors common to all application procedures. A number of these points have been covered in other sections of the applicator's manual but are listed again in the following for completeness.

a. A plan should be devised for application, aeration and disposal of the furnigant to keep at a minimum any exposure to phosphine. See the requirements in the APPLICATOR AND WORKER EXPOSURE section of the applicator's manual.

b. Quik-Furbo Tablets, Pellets or Bags should be applied to provide effective gas - concentrations throughout the storage. When Quik-Furnels not applied uniformly tot a full continuous storage application in a flat storage or ship hold for - axample, exposure times should be lengthened to allow for penetration of gas throughout the storage.

The storage structure should be sealed to maintain a suitable gas concentration over the יוואכ period rcquirred for control of insect pests. Ideally, exposure periods should be long enough to provide for adequate control of insect pests and also more or less completely react the furnigant. Pilling of tablets, peliets or bags, whether applied to a bulk commodity or for space furnigation, may prevent complete breakdown of the product by limiting its access to moist air. This can result in decreased efficacy as a result of poor gas release and may leave an active residual for disposal which contains considerable amounts of unreacted aluminum phosphide. Piling of product may also result in increased hazard of the particularly it contacted by water.

Contact with water should be carefully avoided when applying Ouik-Fume for treatment of bulk commodities or space.

Aluminum phosphide lumigants should not be applied to confined spaces where the concentration of phosphine may build up to exceed its lower flammable limit.

 h. Observe the precautionary and safety statements mentioned in the applicator's manual.

NOTE: The following instructions are intended to provide general guidelines for typical fumigations. These instructions are not intended to cover every type of situation nor are they meant to be restrictive. Other procedures may be used if they are safe, effective and consistent with the properties of aluminum phosphide products.

2. Fumigations of Farm Bins

d.

romoved to

LUNCH LUTAN

Leakage is the single most important cause of failure in the treatment of farm storages. Since these storages are often small, they usually have a higher leakage area in proportion to their capacity. Most wooden storage structures are so porous that they cannot be successfully fumigated unless they are completely tarped. Do not fumigate storages which will be entered by humans or animals prior to aeration. Do not fumigate areas which house sensitive equipment containing copper or other metals likely to be corroded by phosphine gas. [See Physical and Chemical Hazards section in this manual.]



ACCEPTED

Under the Federal Lisectory in Fungeride, and Research the set as assended, for the passance

registered under EPA Reg. No. 592.00 All vents and aeration ducts must be tightly sealed using 4 mil polyethylene sheeling or its equivalent. The plastic must be sealed directly to the metal with tape or other achesive. It is not sufficient to "cinch up" the plastic as with a belt. The surface of the grain may be covered with plastic sheeling after Quik-Fume has been applied. Tarping of the grain surface will greatly reduce teakage. Other sealing techniques are recommended, i.e. closure of all large cracks with caulking, loam insulation or other sealant. Sealing these cracks will greatly reduce the required dosage. Two mil or thicker plastic can be used for tarping the grain surface; however, the plastic used on the outside of the bin should be at least 4 mils. When an entire structure is tarped, the plastic must be at least 6 mils thick to prevent excessive tearing during the funigation.

Probing tablets or pellets into the grain mass is a recommended method of application. Probe insertions should be scattered evenly over the surface. A rigid pipe, about 510 7 feet long and 17 inch diameter can be used. In this event, use about 20-50 tablets or 100-250 pellets per probe. The fumigant is gradually released into the probe as it is withdrawn from the grain. Releasing all the fumigant into the probe at once may retard the production of hydrogen phosphide and might cause an ignilion of gas trapped in the clump of tablets or pellots. The uniform spreading of a large portion of the fumigant in toor level aeration ducts in combination with tarping the grain surface is a preferred method of treatment. Be sure the inside of the aeration duct is dry before adding the fumigant. This method should not be used if it is likely or suspected that the grain immediately surrounding the aeration duct is caked' or otherwise in such a condition as to hinder phosphine penetration has a face facility of Quite an aeration duct an aeration face is a face of the grain mass. Addition of Quike Furme to water in an aeration duct can cause a fire. Seal the seration face as described above.

Post fumination warning signs on entrances to the bin and near the ladder.

If monitoring equipment is not available, an approved canister respirator must be worn for Sindoor application. If an approved respirator is not available, application must be done from outside of the site to be jumipated. Also refer to all other precautions given in this manual.

26

Following seration of the bin, the surface of the grain may be sprayed with an approved protectant to discourage reinfestation.

Fumigation of Flat Storages з.

ù.

а, Establish a plan for application of fumigant to the structure. Treatment of these types of storages may require considerable effort; therefore, sufficient manpower should be available to complete the work rapidly enough to prevent excessive exposure to phosphine gas. Vent flasks outside the storage, conduct fungations during the cooler periods of the day, and employ other work practices to minimize exposures. It is advisable to wear respiratory protection during application of lumigant to flat storages, Refer to the sections on APPLICATOR AND WORKER EXPOSURE AND RESPIRATORY PROTECTION in the applicator's manual.

Seal any vents, cracks and other sources of leaks. Ь.

Apply tablets or pellets by surface application, shallow probing, deep probing or C. uniform addition as the bin is filled. Bags are usually surface applied unless. equiped for shallow probing.

Storages requiring more than 24 hours to fill should not be treated by addition of fumigant to the commodity stream as large quantities of phosphine may escape before the bin is completely sealed. Probes should be inserted vertically at b off intervals along the length and width of the flat storage. Tablets or pellets may be dropped into the probe at intervals as it is withdrawn.

Surface application may be used if the bin can be made sufficiently gastight to contain the furnigant long enough for it to penetrate the commodity. In this Instance, it is advisable to place about 25 per cent or more of the dosage in the floor level aeration ducts. Check the ducts prior to addition of Quik-Fume to make sure that they contain no water. For bins that are difficult to adequately seal, it Arid may be desirable to uniformly spread a larger percentage of the dosage in the aeration ducts. Refer to instructions given in the farm bin section above.

- Tarping the surface of the commodity is often advisable, particularly if the d. overhead section of the storage cannot be well sealed.
- Lock all entrances to the storage and post fumigation warning placards.
- Fumigation of Vertical Storage (Concrete Upright Bins And Other Silos In Which 4. Commodilies Can Be Rapidly Transferred)

ç

- "Close all ppenings and seal all cracks to make the structure as airtight as а. pocsible. Enor to the funigation, seal the vents near the bin top which connects
- -lo udjacent bins.

-12

Tablets or pellets may be applied continuously by hand or by an automatic dispenser on the headhouse/gallery belt or the fill opening as the commodity is loaded into the bin. ... we remove last gente can

Seal the bin deck openings after the furnigation has been completed.

Bins requiring more than 24 hours to fill should not be fumigated by continuous d. addition into the commodity stream. These bins must be fumigated by probing. surface application, re-circulation or a combination of these methods. Exposure periods should be lengthened to allow for diffusion of cas to all parts of the bins if Quik-Fume has not been applied uniformly throughout the commodity mass. Shallow probing and surface application should only be used as a fast resort and Ad only in bins that can be sealed virtually gas tight. Long exposure periods are

required to assure complete penetration of the gas.

Place warning placards on the discharge gate and on all entrances.

Recirculation of Phosphine in Bulk Storage

194 at

4

It is permissible and sometimes desirable to recirculate phosphine gas in certain bulk storages. This method may be used in ship's holds, various types of flat storage and vertical storane bins.

Recirculation usually involves the application of furnigant to the surface of the commodity. The phosphine gas is then continuously or intermittently drawn out of the over space and blown into the bottom of the storage using specially designed tow volume fans and duct work. This, method facilitates the quick and uniform penetration of phosphine throughout the commodity. In some instances a reduced dosage may be used.

6. Fumigation of Mills, Food Processing Plants and Warehouses

- Using the label, calculate the length of the fumigation and dosage of tablets, а. pellets or bags to be applied based upon volume of the building, air and/or commodity temperature and the general tightness of the structure.
- b, Carefully seal and placard the space to be fumigated.
 - Place trays or sheets of paper or foil on the floor throughout the structure to hold Quik-Fume Pellets or Tablets, Bags can be placed directly on the floor.
- Spread Quik-Fume on the sheets at a density no greater than 30 tablets or ď 150 pellets per so.it. This corresponds to appx, 7,th's flask of tablels or slightly more than one flask of pellets per 3'X4' area.
- Nentes Check to see that Quik-Fume has not piled up and that it is spread evenly to minimize contact between the individual tablets, pellets, and bags.
- Hed. Doors leading to the fumigated space should be closed, soaled, locked, and placarded with warning signs.
 - The fumigation period usually tasts from 3 to 7 days, depending upon the g٠. temperature and humidity. Upon completion of the exposure period, windows, doors, vents, etc. should be opened and the fumigated structure allowed to aerate for at least two hours before entering. Remote monitoring Add is recommended prior to entering. When required, gas concentration readings may be taken using low level detector tubes or similar devices to ensure safety of personnel who reenter the treated area. Refer to the APPLICATOR AND WORKER EXPOSURE section in the applicator's manual.

13

Rewide

ACCEPTED

Under the Federal Insection in. Fungicide, and Rodemiol: 3.c. as amended, for the pesticide

recisioned under PA Rog. No. 54209-

Collect the spant baos and Oulk-Furnedust, and dispose of them, with or h. without further deactivation. Follow the recommendations given under **DISPOSAL INSTRUCTIONS in this manual,**

- Remove fumigation warning placards from the aerated structure. 1.
- 7. Fumigation of Rall Cars, Containers, Trucks, Vans and Other Transport Vehicles . poord
- General Information ۰.

Hev

Rail cars, containers, trucks, vans and other transport vehicles loaded with bulk raw $_{
m eff}v^{*}$ agricultural commodities or other commodities approved for direct addition are treated in essentially the same way as any other flat storage facility. The dose may be scattered over the surface after loading has been completed or may be probed below the surface. Bags are usually applied in vehicles on the boards or discs described below.

Carefully seal any vents, cracks, or other leaks. Remember, rail cars and containers shipped piggyback by rail may be fumigated in transit, but it is not legal to move trucks, trailers, vansietc; over public roads or highways until they are aerated. See PLACARDING OF FUMIGATED AREAS in the applicator's manual.

The shipper must provide advance notification to the consignee that treated commodilies will be shipped. Proper handling of the rail cars at their destination is the responsibility of the consignee. The consignee must be familiar with the physical, chemical and toxicological properties of hydrogen phosphilde (phosphine), worker exposure limits and symptoms and first aid treatment for hydrogen phosphide polsoning and must be knowledgeable in making gas concentration measurements. Unless prior arrangements have been made to return the rail cars containing the spent fumigant back to the shipper, consignees must also know proper procedures for deactivation and disposal of spent furnigant. Unaerated rail cars being returned in this manner must bear fumigation warning placards and be carefully sealed. It is the consignee's responsibility to aerate the car unless prior arrangements have been made to return the unaerated car directly to the shipper. Consignees must also ensure that industrial hygiene exposure limits are not exceeded and that the storage for the treated commodity is placarded if the airspace in and/or around the commodity contains more than 0.3 ppm hydrogen phosphide.

Quik-Fume Bags are suited to fumigation of packaged commodities or bulk processed foods. MU They shall not be placed in or attached directly to commodity packages containing processed lood. If placement of bags on the floor of a boxcar is not convenient, or if the vehicle is being furnigated in transit, they may be attached to a wall or other support. They may also be applied by laping the bags on cardboard with spacing between bags. Tape across the bag ends only. Specially designed discs or boards are also available for this purpose.

If these boards or discs are used, taping the bags is not necessary.

Instructions that follow suggest specific procedures for treatment of rail cars and containers when diract addition to the commodity is not used.

- Procedures (br Hopber Rall cars Round Hatch ۰ь. بنادين
-

Close and secure all hatch covers except those being utilized for the lumigation. 1.

Seal all other openings. Pay particular attention to vents. 2.

ACCEPTED Under the Federal Insectioide, Funn as an Rodenticide Act. as a.s. 194, for the possibide mol Lased under EPF. R.g. No. 5420 9-

з. Clean the flance lip of hatch (or hatches) being utilized. If the commodity extends into the throat of the hatch, force it away to the extent possible.

Open cans, and insert bags into the pockets, or tape the bags on the disc. 4. Bags must not be folded.

New

- 5. Place the loaded disc into position, bag side up.
- Secure the disc into place with tape. 6

Cover the hatch opening with "poly" sheeting before closing the cover. 71

- Lower the cover into place and secure. Insert a "DANGER" placard into a 8. clear plastic bag, and glue or otherwise affix it to the hatch cover.
- Insert "DANGER" placards into clear plastic bags, and secure with glue, or 9. otherwise affix near the ladder on each side of the car. Pre-plued, press on envelopes are available for this purpose.
- Procedures for Hopper Rail Cars Slot Hatch c.
 - Fold the edges of a board to form a tray. The board is designed to "hang" in 1. the halch opening
 - 2. Open containers, and insert bags into pockets of the board. Bags must not be folded.
 - 3. Place the loaded board into position, bag side up.
 - 4 Secure into place with tape.
 - Cover the entire hatch opening with "poly" sheeting.
 - Lower the hatch covers. 6.
 - Insert a "DANGER" placard into a clear plastic bag, and glue or otherwise 7. affix it securely to the hatch cover.
 - Insert "DANGER" placards into a clear plastic baos and secure with glue, or 8. otherwise affix them near the ladder on each side of the car, Pro-glued, press on envelopes are available for this purpose.
- Procedures for Box Cars d.
 - Close and secure one of the doors. Seal all openings and joints, if needed, caulk joints, and drape entire doorway with "poly" film, securing the edges to the inner wall, floor and celling with tape or suitable adhesive.
 - 2. Inspect the roof, floor and walls for holes and/or cracks. Seal all openings with either tape or caulking compound.
 - If needed, drape remaining doorway with polyethylene film before door is closed. Secure edges to door jams and floor. Close door and secure. If doorway is draped with 'poly', it may not be necessary to seal the door from the outside. If doorway is not draped, seal all cracks, openings and leaky joints with masking tape and/or caulking compound from the outside.

- Open cans, and insert bags into pockets of disc or board, or use tape to secure the bags.
- Place the loaded disc or board onto the load, bag side up. Secure it into place with tape,
- 6. Or nail it to the wall.
- Post "DANGER" placards by inserting into clear plastic bags and gluing or otherwise affixing them to each door. Pre-glued envelopes are available for this purpose.
- e. Procedures for Containers

Procedures for containers are essentially the same as box cars; except their doors tend to be more gas light and they often have only a rear door which must be seated after application is completed. If a refrigeration unit present, it must be seated from inside protecting it from phosphine damage.

Procedures for Receivers of Fumigated Rail Cars

1. General

Persons responsible for receiving rail cars which have been fumigated in transit must be familiar with the pertinent regulations, hazards, safety considerations, aeration and disposal procedures, etc. which apply to practices and situations enumerated in performing this function.

The appropriate sections of this applicator's manual should be reviewed as part of the training program for persons involved in receiving fumigated rail cars. These persons should be knowledgeable in the following areas;

- a. health hazards and symptoms of overexposure
- b. practical treatment for overexposed persons
- cc physical and chemical hazards
- d. worker exposure limits
- e. techniques and requirements for monitoring
- odor of phosphine
- g. respiratory protection and protective clothing
- aeration and disposal
- i. plagaroing 🖉 🎽
- 2. Worker Esposure, Crew Size, Respiratory Protection

When receiving rail cars in ouldoor locations, certain safety procedures are not required, i.e. monitoring outdoors for worker exposure, a minimum crew size of 2 and the avallability of respiratory equipment. However, in no case may the post application worker be exposed to over 0.3 ppm as a colling concentration. Some facilities where rail

ACCEPTED

Under the Paderal Instation. Fungt via, and Rodentiale for as and that for the posticide

124 January and 44 1228 Reg. No. 5

J 16

a cars are received may be closed on more than one side, and the distinction between an "indoor and outdoor operation is not clear cut. Worker exposure monitoring should be performed initially in these situations where exposure may be excessive.

.3. Responsibilities of Consignees

Unless prior arrangements have been made to return unaerated rail cars containing the spent furnigant back to the shipper, the consignee receiving the tunigated rail car must:

- aerate the rail cars and verify that it contains 0.3 ppm PH, or tess;
- b. remove the fumigation warning placards from the rail car, and
- c. Remove and dispose of the fumigant, unless pellets or tablets have been added directly to the commodity.

The consignee must also:

- ensure that the post-application worker exposure limit is not exceeded.
- e. transfer the fumigated commodity from the rail car, with or without prior aeration; and
- placard the new storage if it contains more than 0.3 ppm PH, in or above the commodity mass.
- 8. Tarpaulin and Bunker Fumigations.

Use of plastic sheeting or tarpaulins to cover commodities is one of the easiest means for providing relatively gastight enclosures which are very well suited for fumigation. Polyethylene tarps are penetrated only very slowly by phosphine gas, and tight coverings are readily formed from the sheets. These enclosures may vary widely from a tarpaulin placed over a small stack of bagged commodify containing a few cubic foet to a plastic covered bunker storage capable of holding 600,000 bushels of grain or more.

An enclosure suitable for fumigation may be formed by covering bulk or packaged commodity with polyethylene sheeting. The sheets may be taped logether to provide a sufficient width of material to ensure that adequate sealing is obtained. If the flooring upon which the commodity rests is of wood or other porous material, it should be repositioned onto a tarpaulin prior to covering for fumigation. The plastic covering sold or sand on water snakes or by shoveling solf or sand onto the ends of the plastic covering or by other suitable procedures. The "poly" covering should be reinforced by tape or other means around any sharp corners or edges in the stack to reduce the risk of tearing. Thinner polyethylene sheeting, about 2 mills, is suitable for most indoor tarp fumigations and for sealing windows, doors and other openings in structures. However, 4 mill, or thicker "poly" to be encountered.

Tablets, pellets or bags may be applied to the tarped stack or bunker storage of bulk commodily through slits in the polyethylene covering, Probing or other means of dosing may be used. Avoid application of large amounts of Quik-Fuma at any one point. The Ourk-Fume should be added below the surface of the bulk commodily if condensation or other source of moisture is likely to form beneath the "poly". The slits in the covoring should be carefully taped to prevent loss of gas once the dose has been applied. Quik-FumeBags are recommended for the treatment of bagged commodilies and processed loods, although tablets and pellets on trays or sheets of paper may be used. Care should

be taken to ensure that the polyethylene sheeting is not allowed to cover the Quik-Fume, confining the gas, 'thus preventing confact with moist air.

Distribution of phosphine gas is generally not a problem in the treatment of bagged commodities and packaged processed loods. However, tumigation of larger bunker storages containing bulk commodity will require proper application procedures to obtain adequate results.

See appropriate precautions if the fumigation is conducted indoors as opposed to outdoors. Indoor fumigation precautions are handled as any other situation where the application is made from outside the area being tumigated. Workers may occupy

adjacent indoor areas, but they must be protected from overexposure to hydrogen, phosphide by adequate sealing, phosphine monitoring, ventilation or as a last resort, respiratory equipment.

Do not walk on stacks during the fumigation.

Place "Danger" placards at conspicuous locations on the tarped stack or bunker only.

If concentrations in excess of 0.3 ppm are observed in adjacent indoor areas, the areas must be evacuated of unprotected workers and posted with "Danger" signs until this adjacent area is aerated to 0.3 ppm or below.

- 9. Fumigation of Ships
- a. General Information
 - IMPORTANT -- shipboard, in transit ship holds fumigation is also governed by U.S. Coast Guard Regulation 46 CFR 147A. Refer to this regulation prior to fumigation.
- 2. The Fumigation Handbook of the U.S. Department of Agriculture, Federal Grain Inspection Service (FGIS) contains additional procedures which must be followed If intosted bulk grain is to be fumigated to avoid the designation "infested" by the FGIS, or to obtain a USDA phytosanitary inspection certification. This Fumigation Handbook may also be followed voluntarily.
- b. Pre-voyage Fumigation Procedures
 - Prior to fumigating a vessel for in transit cargo fumigation, the master of the vessel or his representative and the fumigator must determine whether the vessel is suitably dosigned and configured to allow for sale occupancy by the ship's crew throughout the duration of the fumigation. If it is determined that the design and configuration of the vessel does not allow sale occupancy by the ship's crew throughout the duration of the fumigation, then the vessel will not be fumigated unless all crew members are removed from the vessel will not be fumigated unless all crew members will not be allowed to reaccup the vessel and the fumigator "that" the vessel is sale for occupancy.
 - 21 "The person responsible for the furnigation must notify the master of the vessel of his representative of the requirements relating to personal protection equipment and detection equipment. Personal protection equipment ments a NIOSHV MSHA approved respirator or gas mask litted with an approved canister for phosphine. The canister is approved for use up to 15 ppm. An SCBA or its

ъ 8

equivalent must be used above 15 ppm or at unknown concentrations. A person qualified in the use of this equipment must accompany the vessel with the cargo under fumigation. Emergency procedures, cargo ventilation, periodic monitoring / and inspections and first aid measures must be discussed with and understood by the master of the vessel or his representative.

- 3. Seal all openings to the cargo hold or lank, and lock or otherwise secure all openings, manways, etc. which might be used to enter the hold. The over space pressure relief system of each tank aboard tankers must be sealed by closing the appropriate valves and sealing the openings into the overspace with gastight materials.
- Placard all entrances to the treated spaces with fumigation warning signs.
- 5. If the fumigation is not completed and the vessel aerated before the manned vessel leaves port, the person in charge of the vessel shall ensure that at least two units of personal protection equipment and one gas or vapor detection device, and a person qualified in their operation be on board the vessel during the voyage.
- 6. During the fumigation or until the manned vessel leaves port or the cargo is aerated, the person in charge of the fumigation shall ensure that a qualified person using gas or vapor detection equipment tests spaces adjacent to areas containing fumigated cargo and all regularly occupied spaces for fumigant leakage. If leakage of the fumigant is detected, the person in charge of the fumigation shall take action to correct the leakage or shall inform the master of the vessel or his representative of the leakage so that corrective action can be taken.
- Review with the master or his representative, the precautions and procedures for the voyage.
- c. Application Procedures for Bulk Dry Cargo Vessels and Tankers
 - Apply tablets, pellets or bags by scattering uniformly over the commodity surface. Product may be shallow or deep probed into the commodity mass. Recirculation systems may be used to aid the penetration of phosphine throughout the commodity.
 - Immediately after the application of the fumigant, close and secure all hatch covers, lank tops, butterworth valves, manways, etc.

d. In Transit Fumigation of Containers Aboard Ships

In transit fumigation of containers on ships is also governed by the U.S. Department of Transportation Regulation 49 CFR 176.76.

Application procedures for fumigation of raw commodilies or processed foods in containers and other transport vehicles are described in the DIRECTIONS FOR USE section of the applicator's manual.

Precautions and Procedures During Voyage

ACCEPTED

Under the Federal Insectioide, Fungic, se une Rodemicide Act, as agrended, for the pesticide

EPA Rey No. 59209-

 Using appropriate gas detection equipment, monitor spaces adjacent to areas containing lumigated cargo and all regularly occupied areas for

fumigant leakage. If leakage is detected, the area should be evacuated of all personnel, ventilated and action taken to correct the leakage before allowing the area to be occupied.

- 2. Do not enter furnigated areas except under emergency conditions. If necessary to enter the furnigated area, appropriate personal protection equipment must be used. Never enter furnigated areas alone. At least one other person, wearing personal protection equipment, should be available to assist in case of an emergency.
- 1. Precautions and Procedures During Discharge

 If necessary to enter holds prior to discharge, test spaces directly above grain surface for fumigant concentration, using appropriate gas detection and personal safety equipment. Do not allow entry to fumigated areas without personal safety equipment, unless fumigation concentrations are at safe levels, as indicated by a suitable detector.

2. It is the responsibility of the consignee to see that the spent fumigant, is disposed of properly and that industrial hygiene exposure limits are not exceeded during unloading of the ship or during subsequent transfer and storage of the treated commodity. Safety, aeration and disposal require , ments in the United States are given herein as a guide. Consult regulations in the receiving country for local requirements.

- g. Personal Protective Equipment and Monitoring
 - Fully loaded holds on dry bulk carriers are considered an outdoor fumigation, and therefore monitoring and respiratory protection are not required during application.
 - NIOSH/MSHA approved respiratory protection must be available at the site in case it is needed during application to tanker holds and in partially filled holds if the hold must be entered for fumigant application. This respiratory protection must consist of a full face gas mask - phosphine canister combination or self-contained breathing apparatus (SCBA) or its equivalent. If an SCBA or its equivalent is not available at the application site, it must be available locally, for example, at a fire station or rescue squad.
 - If hydrogen phosphide is detected leaking into crew's quarters, housing or work areas, a minimum of two qualified persons on ship should wear the gas mask and canister described above while aerating the area and locating and sealing the leak.
 - Refer to the following sections 4 through 11 for additional required and recommended practices.

9. Fumigation of Barges

Barge fumipations are also regulated by U.S. Coast Guard regulation 46 CFR 147A as modified by U.S. Coast Guard Special Permit 2-75. This permit must be obtained prior to the fumigation, and is available from: U.S. Coast Guard, Hazardous Branch, MTH-1, Washington, DC 20553-0001

Leaks are a common cause of failures in the treatment of commodities aboard barges. Carefully inspect all hatch covers prior to application of Quik-Fume and seal, if necessary. Notify consignee if the barge is to be furningled in transit.

20

The consignee has the same responsibilities concerning aeration, monitoring, knowledge and disposal as does the rail car receiver,

10. Fumigations in Small Sealable Enclosures.

Excellent results may be attained in the treatment of small enclosures since it is often possible to control the fumigation and also to make the enclosure virtually gastight. Take care not to overdose, during these tumigations. A single pellel will treat a space of 1.4 to 10 cubic feet. From 6.9 to 50 cubic feet may be fumigated with a single Culk-Fume Tablet. A single bag will treat 77 to 500 cubic feet.

11. Treatment of Beehives, Supers And Other Beekeeping Equipment.

Quik-Fume Tablets, Pellets, and Bags may be used for the control of the greater wax moth in stored beehives, supers and other beekseping equipment and for the destruction of bees, Africanized bees, and diseased bees including those infested with tracheal mitos and foulbrood. The recommended dosage for this use is 30-45 tablets, 150-225 pellets or 3 or 4 bags per 1000 cu.ft. Furnigations may be performed in chambers at atmospheric pressure, under tarpaulins, etc. by using bags or placing tablets or pellets on trays or in moisture permeable envelopes. Do not add more than 2 tablets or 10 pellets to trays or in moisture permeable envelopes. Do not add more than 2 tablets or 10 pellets to each envelope. Honey from treated hives or supers may only be used for bee tood.

12. Burrowing Pest Control

a. List of Burrowing Pests.

Quik-Fume Tablets and Pellets may be used out of doors only for the control of the following burrowing rodents and moles: woodchucks and yellow-belly marmots (rockchucks), prairie dogs (except Ulah prairie dogs). Norway and roof rats, mice, ground squirrets, moles, voles, goohers and chiomunks.

. b. Directions for Use

Add from 1 to 4 tablets or 5 to 20 pellets to each burrow opening. Then seal tightly by shoveling soil over the entrance. Place the tablets or pellets far enough down the burrow that the soil used to plug the burrow doesn't cover the tablets or pellets, slowing down their action. Where possible, subsurface tunnels or runways should be treated every 5 to 10 feet with a dose of 2 to 4 tablets or 10 to 20 pellets. Use lower rates in smaller burrows, in tight soils, under most soil conditions and higher rates in larger burrows, in porous soils when soil moisture is low, in extremely dry or porous soil, it is sometimes not possible to obtain satisfactory results. This is particularly true in instances where the burrow systems are extensive such as moles or gophers. It is always better not to fumigate during extended periods of dry weather. Addition of several cups of water to the burrow prior to dosing with Quik-Fume may improve efficacy in some porous soils. Treat reopened burrows and fresh runways a second time 1 to 3 days after the initial treatment. Quik-Fume may be used out of doors only for control of burrows which may open under or into occupied buildings. For use on all agricultural and noncropland areas.

c. Environmental Hazards

Ť.

ort pad magon a Co. Si Dan man to Sint. Jos shi protectore This product is very highly toxic to wildlife. Non-target organisms exposed to phosphine gas in burrows will be killed. Do not apply directly to water or wellands (swamps, bogs,

Endangered Species Restrictions d.

The use of any poslicide in a manner that may kill or otherwise harm an endangered or threatened species or adversely modify their habital is a violation of federal law. The use of this product is controlled to prevent death or harm to endangered or threatened species that occur in the following counties or elsewhere in their range.

STATE (REGIONAL U.S. FISH AND WILDLIFE OFFICE) * SPECIES COUNTY ! -

ARIZONA (Albuquerque, NM)

* Black footed Ferrel - Statewide

CALIFORNIA (Ponland, OR)

San Joaquin Kit Fox-Fresno, Kern, Kings, Merced, Monterey, San Benilo, San Luis Obispo, Santa Barbara, Tulare, Ventura

Blunt-nosed Leopard Lizard-Fresno, Kern, Kings, Madera, Merced, Tulare COLORADO (Denver, CO)

Black-footed Ferret - Statewide FLORIDA (Atlanta, GA)

Eastern Indigo Snake - Statewide

GEORGIA (Allania, GA)

* Eastern Indigo Snake - Statewide

KANSAS (Deriver, CO) Black-fooled Ferrel - Statewide

MONTANA (Denver, CO)

Black-footed Ferret - Statewide NEBRASKA (Denver, CO)

Black-footed Ferrel - Statewide

NEW MEXICO (Albuquerque, NM) * Black-looled Ferrel - Statewide

NORTH DAKOTA (Denver, CO)

* Black-fooled Ferrel - Statewide OKLAHOMA (Albuquerque, NM)

Black-looted Ferrel - Statewide SOUTH DAKOTA (Denver, CO)

Black-looled Ferrel - Statewide TEXAS (Albuquerque, NM) Black-footed Ferrel - Stalewide

•UTAH (Denver, CO)

* Desert Tortoise-Washington * Black-footed Ferrel - Statewide

WYOMING (Denver, CO)

* Black-footed Ferret - Statewide

Use of this product in the above areas is prohibited without first contacting and obtaining permission from the endangered species specialist in the regional offices of the U.S. Fish and Wildlife Selvice (FWS) network to you.

Special Local Restrictions

North Carolina - Ouix-Fume Tablets and Peilets may only be used for control of 1. rats and mice in the state of North Carolina. Use against other pests is not permitted.

22

1. ACCEPTED Under the Pederal Discussion Pun na 's and Roy on i & Act as environment and for the plast the reg: tern ! under EPA Rug No. 59300

Oklehoma - A special permit for black-tailed prairie dog control by poisoning is. 2. required in Oklahoma. Contact the Oklahoma State Department of Wildlife Conservation to obtain this permit.

- Wisconsin A state permit is required for use of pesticides to control small Э. mammals, except rais and mice. Contact your local Department of Natural Resources for information.
- Indiana Use of Oulk-Fume Tablets and Pellets for mole control is not legal in 4. the state of Indiana.
- Missouri A state permit is required for use of pesticides in Missouri to control 5 small mammals, except rats and mice. Contact the Missouri Department of Conservation for Information.
- 6. Kansas - A special permit for black-tailed prairie dog control by poisoning is required in Kansas. Contact the Kansas Dept. of Wildlife and Parks for information.
- 7. California - Use of Quik-Fume Tablets and Pellets for chipmunk control is not legal in the State of California.

SECTION 4

AERATION OF FUMIGATED COMMODITIES

Α. Foods and Feeds

Tolerances for phosphine residues have been established at 0.1 ppm for animal feeds and 0.01 ppm for linished foods. To assure compliance with these tolerances, it is necessary to aerale these commodities for 48 hours prior to offering to the end use consumer.

в. Tobacco

Tobacco must be serated for at least three-days (72 hours) when fumigated in hogsheads and for at least two days (48 hours) when lumigated in other containers. Tobacco fumigated in containers with plastic liners will probably require longer aeration periods to reach 0.3 ppm.

C. Aiternatives

As an alternative to these aeration periods, each container of a treated commodity may be analyzed for residues using accepted analytical methods. If residues are less than tolorance levels, the commodily may be shipped to the consumer regardless of the above holding periods,

SECTION 5

PLACARDING OF FUMIGATED AREAS

The applicator must placard or post all entrances to the furnigated area with signs bearing.

23

The signal word DANGER/PELIGRO and the SKULL AND CROSSBONES symbol in red.

2. The statement, "Area and/or commodity under fumigation, DO NOT ENTER/ NO ENTRE."

We (* 1997)

- 3. The statement. "This sign may only be removed after the commodity is completely aerated (contains 0.3 ppm or less phosphine gas). If incompletely aerated commodity is transferred to a new site, the new site must also be placarded, and workers must not be exposed to more than 0.3 ppm phosphine.
- The date and time fumigation begins and is completed.
- 5. Name of furnigant used.
- 6. Name, address and lelephone number of the applicator.

All entrances to a lumigated area must be placarded. Where possible, placards should be placed in advance of the lumigation in order to keep unauthorized persons away. For the rail road hopper cars, placarding must be placed on both sides of the car near the ladders and on or next to the top hatches into which the furnigant is introduced.

Do not remove a placard until the treated commodity is completely aerated. To determine whether aeration is complete, each furnigated site or vehicle must be monitored and shown to contain 0.3 ppm or less phosphine gas in the air space around and when feasible, in the mass of the commodity. If 0.3 ppm or less phosphine is detected, the placard may be removed. However, if more than 0.3 ppm is detected, the placard must be transferred with the commodity to the new site. Workers who transfer or handle incompletely aerated commodity must be informed and appropriate measures must be taken (i.e. ventilation or respiratory protection) to prevent explaures from exceeding 0.3 ppm phosphine. It is recommended that the person removing the placard be knowledgeable in the physical, chemical and toxicological properties of phosphine; how to take gas readings; the exposure limits for phosphine; and symptoms of and first aid treatment for poisoning.

SECTION 6

PROTECTIVE CLOTHING

Wear dry gloves made of cotton or other material if contact with tablets, pellets, or their dust is likely. Wash hands after use. It is not necessary to wear gloves when handling bags.

SECTION 7

RESPIRATORY PROTECTION

A. WHEN RESPIRATORY PROTECTION MUST BE WORN

NIOSH/MSHA approved respiratory protection must be worn during exposure to concentrations in excess of permitted limits or when concentrations are unknown.

B. PERMISSIBLE GAS CONCENTRATION RANGES FOR RESPIRATORY PROTECTION DEVICES

A NIOSKYLICHA approved, Jult face gas mask - phosphine canister combination may be used at levels up to 15 ppm or to escape from levels up to 1500 ppm. Above this level or in situations where the phosphyriz constraint is unknown, a NIOSH/MSHA approved, self-contained breathing apparatus (SCBA) or its equivalent must be used. The NIOSH/MSHA Pocket Guide, 8-85, DHEW/NIOSH 78-210, lists these and other types of approved respirators and the concentration limits at which they may be used. C. REQUIREMENTS FOR AVAILABILITY OF RESPIRATORY PROTECTION Respiratory protection must be available at the site of application in case it is needed when applying Quik-Fume from within the structure being fumigated. An approved full face gas mask - phosphine canister combination or self-contained breathing apparatus (SCBA) or its equivalent must be available at the site of application. If an SCBA or its equivalent is not available at the application site, it must be available locally, for example, at a fire station or rescue squad.

Respiratory protection need not be available for application from outside the area to be furnigated such as addition of tablets or pellets to automatic dispensing devices, etc., if exposures above the permitted exposure limit will not be encountered.

Respiratory protection need not be available for outdoor applications.

If monitoring equipment is not available on a farm and application cannot be done from outside the structure, an approved canister respirator must be worn during application from within the enclosed indoor area.

SECTION 8

GAS DETECTION EQUIPMENT

There are several reliable devices marketed. One type is the hand pump when used in conjunction with the appropriate detector tube. They are portable, simple devices and do not require intensive training or elaborate supporting equipment to operate. Furthermore, they are inexpensively adaptable to remote monitoring procedures and will measure concentrations of hydrogen phosphilde in air in trace amounts on up. Use instructions are enclosed with each purchase.

Consult your local supplier of such equipment or contact your Quik-Fume distributor for more information.

Hew

KIR W

SECTION 9 APPLICATOR AND WORKER EXPOSURE

A. HYDROGEN PHOSPHIDE EXPOSURE LIMITS

Exposure to hydrogen phosphide must not exceed the 8 hour TWA of 0.3 ppm for applicators and workers during application. Application is defined as the time period covering the opening of the first container, applying the appropriate dosage of fumigant and closing up the site to be fumigated. All persons in the treated site and in adjacent indoor areas are covered by this exposure standard.

After application is completed worker or applicator exposure must not exceed 0.3 ppm maximum concentration. Such exposures may occur because of leakage into enclosed areas from fumigation sites, during reentry or during transfer of unaerated commodity.

B. APPLICATION OF FUMIGANT

1.0

Depending upon temperature and humidity, Quik-Fume releases hydrogen phosphide (phosphine) gas slowly upon exposure to molsture from the air. This release is

sometimes slow-onough to permit applicators to deposit fumigant in the desired areas and then vacate the premises without significant exposure to the gas. If the fumigator's exposure exceeds the 8 hour TWA of 0.3 ppm, approved respiratory protection must be worn. Gas concentration measurements for safely purposes must be made using low level detector tubes or other suitable low level detection equipment. See the "Industrial Hygiene Monitoring" section below.

336

It is often practical to wear respiratory protection from start to linish. This is particularly true when performing large space lumigations or when furnigating bulk stored commodities in flat storage buildings.

C. LEAKAGE FROM FUMIGATED SITES

Hydrogen phosphide is highly mobile and given enough time may penetrate seemingly gas||ght materials such as concrete and cinder block. Therefore, adjacent enclosed areas likely to be occupied should be examined to ensure that significant leakage has not occurred. Sealing of the lumigated site and/or air flow in the occupied areas should be used to reduce excession.

D. AERATION AND REENTRY

If the area is to be entered after lumigation, it must be serated until the level of hydrogen phosphide gas is 0.3 ppm or below. The area or site must be monitored to ensure that liberation of gas from the treated commodity does not result in the development of unacceptable levels of hydrogen phosphide. Do not allow reentry into treated areas by any person before this time unless protected by an approved respirator.

E. HANDLING UNAERATED COMMODITIES

Transfer and processing of a treated commodity prior to complete aeration is permissible; however, workers must not be exposed to hydrogen phosphide in excess of the permitted exposure limit.

F. INDUSTRIAL HYGIENE MONITORING

It is recommended that hydrogen phosphilde exposure be documented in an operation log or manual for each site and operation where exposure may occur. The purpose of this monitoring is to prevent excessive exposure and to determine when and where respiratory protection is required. This monitoring is mandatory although once exposures have been adequately characterized, subsequent monitoring is not routinely required. However, spot checks should be made occasionally, especially if conditions significantly change or an unexpected gatile odor is detected. Gas concentration measurements should be taken in the worker's breathing zone. Monitoring is not required outdoors.

G. ENGINEERING CONTROLS AND WORK PRACTICES

If initial monitoring shows that workers are exposed to concentrations in excess of the permitted exposure limits then engineering controls (such as forced air ventilation) and/or appropriate work practices should be used, where possible, in an attempt to reduce exposure to below-permittee limits.

SECTION 10

STORAGE AND DISPOSAL

STORAGE

Containers should be stored in a dry, well ventilated area, away from heat and underlock and key. Post as a pesticide storage area. Do not contaminate water, food or reed by storing pesticides in the same areas used to store these commodilies. Do not store in buildings where humans or domestic animals reside. Keep out of reach of children.

Quik-Fume Tablets and Pellets are supplied in resealable, aluminum flasks. Do not expose the product inside flasks to almospheric moisture any longer than is necessary. Seal tightly before returning opened flasks to storage.

Tablet and pellet flasks should not be stored at sub-zero temperatures because this will increase the possibility of an ignition (flash) when opened.

The shelf life of Ouk-Fume is virtually unlimited if the containers are lightly sealed.

B. DISPOSAL OF UNBEACTED OR PARTIALLY REACTED QUIK-FUME

(From spills,leaking containers or other sources) Unreacted or partially reacted aluminum phosphide is acutely hazardous. Improper disposal of these products is a violation of federal law. If these products cannot be disposed of by ordinary use or according to the instructions that follow, contact your state pesticide or environmental control agency or the hazardous waste representative at the nearest EPA regional office for guidance. Do not contaminate water by disposal.



FOR SPECIFIC INSTRUCTIONS CONCERNING SPILLS AND LEAKS, REFER TO SECTION 11.

C. DISPOSAL OF QUIK-FUME FOLLOWING A SPACE FUMIGATION

1. General

If properly exposed, the residual dust remaining after a fumigation will be a grayish while, spent, nonhazardous waste and will contain only a small amount of unreacted aluminum phosphide, However, residual dust from incompletely exposed aluminum phosphide (See "Exposure Guide" on page 7 of this manual.) will require special care. Confinement of <u>partially</u> spent aluminum phosphide as in a closed container or collection and storage of large quantities of the dust may result in a line hazard. Small amounts of hydrogon phosphide may be given off from the partially reacted aluminum phosphide, and confinement of the gas may result in a flash.

2. Deactivation and Disposal of Quik-Fume Tablets and Pellets.

a. General

ACCEPTED

Under the Federal Inspirited, Fungier in, and Rodwritch is fact, as achieved, for the posticide

regrissed under EPA Reg. No. 59309Unless it can be determined with certainty that the tablets or pellots are spent, they must be held for several days beyond the required exposure time prior to disposal, or the wet method of deactivation must be used. If the dust retains any of its greenish color, the wet method is recommended. Extension of the

lumigation period is the simplest method for further deactivation of "green" or partially spent product prior to ultimate disposal.

1 A 1 1 1 1

b. Dry Method

In open areas, small amounts (up to 5 flasks) of residual dust may be disposed of on sile by burial or by spreading over the fand surface away from inhabited buildings. Up to 3 flasks of this residual dust (4 to 7 lbs.) may be collected in a one gallon bucket for holding or disposal. Larger amounts of residual dust may be collected in a poreous cloth bag (burlap cotton, etc.) for holding and/or transportation to a suitable disposal site. Do not put more than one half case (7 flasks of tablets or 10 flasks of pellets) of residual dust in each bag. Always transport these bags in an open vehicle. CAUTION: Do not use this method for dust that still retains some of its original greenish color. Never confine, dispose of or store residual dust in closed containers such as dumpsters, drums or plastic bags.

Spent residual dust from pellets or tablets may be collected and disposed of at a sanitary landfill, approved pesticide incinerator or other approved sites or by other procedures approved by federal, state and local authorities.

Do not dispose of dust in a toilet.

c, Wet Method.

Fill an appropriate sized metal container 2/3 full with water. For each gallon of water add 1/4 oup of low sudsing detergent or sundatant. Use no less than 10 gallons of water/detergent solution for each case of spent material. Slowly pour the dust into the container as the water is siltred. Wear appropriate respiratory protection, DO NOT COVER THE CONTAINER AT ANY TIME. IF THE CONTAINER IS COVERED, THE PHOSPHINE BEING GENERATED WILL BE CONFINED AND MAY DECOMPOSE EXPLOSIVELY. This must be done outdoors or in front of an adequate fan that exhausts immediately outside.

Dispose of the water/dust mixture (sturry) (with or without preliminary pouring out of excess water) in a sanitary landfill or other suitable burlal site approved by local authorities. Where permissible, the sturry may be poured out on the ground. The water from the sturry may be evaporated prior to disposal. After being held for 36 hours, it may be poured into a sanitary saver if approved by local authorities.

d. Disposal of Empty Flasks

Method One: Triple rinse flasks and stoppers with water: Then offer for recycling or reconditioning, or puncture and dispose of them in a sanitary landfill or other approved site or by other procedures approved by state and local authorities. The water from the rinsate may be evaporated prior to disposal. Dispose of rinsate or rinsate residue in a sanitary landfill or by other approved procedures. Small quantities can be poured out on the ground.

After being held for 38 hours the rinsate may be poured into a sanitary sewer if approved by local authorities.

"<u>Meltricd Two:</u>"Remove lids and place empty liasks in a secure location outdoors or in structure being lumigated until residue in flasks is reacted. Puncture and dispose of litem in a sanitary landlik or other approved site or by other procedures approved by state and local authorities.

28

NOTE: It is permissible to tighten lids back in place on the triple rinsed or reacted empty flasks, place them in the original carton and ship them back to the distributor. They are not hazardous waste. Contact your distributor for information and approval.

D. DEACTIVATION AND DISPOSAL OF QUIK-FUME BAGS

1. General

Unless it can be determined with certainly that the bags are spent, they must be deaclivated as described below prior to disposal.

All the methods below may be used for deactivating used or unused Quik-Fume Bags, regardless of the extent to which the aluminum phosphide has been consumed in the production of hydrogen phosphide.

2. Dry Deactivation

Gollect bags, and place them into a secure, ventilated holding container. Store the bags until they are spent. It is recommended that unused or partially spent bags be spread out on the ground in a secure open area away from occupied buildings to be deactived by atmospheric moisture. Care should be taken so that they are not carried away by the wind. Prior to final disposal, bags may be spread out in a single layer on the ground or concrete and covered with several inches of sand until they are spent. Bags that have not been exposed for the minimum times specified in the exposure guide on page 7 should not be covered with sand. Dry deactivation is the recommended procedure for unused or partially spent bags. If in doubt concerning whether the bags are spent, contact your Cluik-Forme distributor.

Ignition can occur if large numbers of incompletely reacted bags are contacted by liquid water. This can occur in open or perforated storage containers. Therefore, such storage should be out of doors in a relatively isolated area, protected from rain.

3. Wet Deactivation - Method One

Fill an appropriate sized container with water a few inches from the top. Submerge intact bags for 36 hours. A metal grid works well to keep bags submerged. Do not cover container. Wear appropriate respiratory protection. This must be done outdoors or in front of an adequate fan that exhausts outside. The water may be disposed of in a storm sewer, sanitary sewer or by pouring it out on the ground.

Wet Deactivation – Method Two

Fill an appropriate sized metal container 2/3 full with water. For each gallon of water, add 1/4 cup of low sudsing detergent or surfactant. Use no less than 1 gallon of water/detergent solution for 60 bags. Open each bag and dump the contents into the container as the water is stirred. Wear appropriate respiratory protection. DO NOT COVER THE CONTAINER AT ANY TIME. IF THE CONTAINER IS COVERED, THE PHOSPHINE BEING GENERATED WILL BE CONFINED AND MAY DECOMPOSE EXPLOSIVELY. This must be done outdoors or in front of an adequate fan that exhausts immediately outside.

5. Disposal Procedures

In open areas, small amounts (up to 7.0 kg) of the spent bags may be disposed of on site by bural of the bags or by opening the bags and spreading the dust over the land surface away from inhabited buildings.

29

ACCEPTED Under the Federat Inspirite. Punce the federat Inspirite. Punce the first of product of the second state of the product of the second state of the product of EPA Ring No. 59209-1 Spent bags may also be collected and disposed of at a sanitary landfill, approved pesticide incinerator or other approved sites or by other procedures approved by federal, state and local authorities.

Do not dispose of dust in a toilet.

Dispose of the water/dust mixture (slurry) (with or without preliminary pouring out of excess water) in a sanitary landhil or other suitable burial site approved by local authorities. The water from the slurry may be evaporated prior to disposal. Where permissible, the slurry may be poured out on the ground. After being held for 36 hours it may be poured into a sanitary sewer it approved by local authorities.

Never confine partially spent bags or slurry in closed containers such as closed drums or plastic bags.

6. Disposal of Empty Quik-Fume Bag Containers

Dispose of containers in a sanitary landfill or by other approved state or local procedures. They need not be rinsed.

SECTION 11

SPILL AND LEAK PROCEDURES

A. GENERAL

A split, other than incidental to application or normal handling or punctured containers can produce high levels of gas, and therefore, attending personnel must wear an SCBA or its equivalent when the concentration of hydrogen phosphide gas is unknown. If the concentration is known, other NIOSH/MSHA approved respiratory protection can be worn. Wear day gloves made of cotton or other material when contact with the powdered formulation, pellets or tablets, is likely.

B. DAMAGE TO FIBERBOARD CASE

Check metal containers. If they are damaged, handle as described below. If they are undam-aged return them to cardboard cartons or other suitable packaging which complies with DOT regulations.

C. LEAKING PRODUCT CONTAINER PROCEDURES

If containers have been punctured or damaged causing a leak, the product may be immediately used, the containers may be temporarily repaired with atuminum tape, the furnigant may be transferred from the damaged containers to sound metal containers which should be seated and properly labeled as atuminum phosphide, or it may be deactivated and disposed. See pages 27-30 of this manual for deactivation and disposal procedures. Transport the damaged containers to an area suitable for pesticide storage for inspection. Further functions and focommendations may be obtained, if required, from your distributor.

Handle hmpty, damaged containers as described in container disposal sections.

- D. SPILL PROCEDURES
- 1. General

Do not flust-spillag, down drain with walar. DO NOT use water at anytime to clean up a spill. Water in contact with uprescted atuminum phosphide will rapidly accelerate the production of hydrogen phosphide gas and could cause spontaneous ignition of the gas. If the spill is only a few minutes old and is not contaminated by other materials, collect the spillage and place it back into the original or other sound metal container and tightly seal. Seal punctures with foil tape. If possible, use immediately, CAUTION: AN IGNITION MAY OCCUR WHEN THESE CONTAINERS ARE REOPENED.

2. Quik-Fume Bags

Since the formulation is placed in small, tough bags, a spill will be either bags or a small quantity of powder spilled from a punctured bag. Consequently, spills are not likely to constitute a frequent problem.

If the spill is more than a few minutes old or has been contaminated with water, gather it up, and place it into an open top can and deactivate it immediately.

If on-site deactivation is not feasible, these open containers should be transported in open vehicles to a suitable area away from occupied buildings. Well or dry deactivation may then be carried out.

3. QUIK-FUME TABLETS AND PELLETS

If the spilled material is contaminated or has begun to visibly decompose, gather it up and, place it into open top, perforated gallon cans and process it immediately.

Do not add more than about one flask (2 to 3 lbs.) of spilled material to the bucket. If on-site deactivation is not feasible, these open containers should be quickly transported in open vehicles to a suitable area away from occupied buildings. Protect from rainfall but do not seal or cover cans. Wet or dry deactivation may then be carried out as described in the section immediately below.

E. DEACTIVATION AND DISPOSAL OF UNREACTED TABLETS, PELLETS AND BAGS

1. Wet Method

ACCEPTED

Under the Pederal Insecticide, Fungicide, and Referricide Act, as a worded, for the posticide

EPA Rag. No. 59-209

Transport meterial by hand or in open vehicles to open air away from occupied structures. Fill a drum 2/3 full with water.

Add 1/4 cup of low sudsing detergent or surfactant in each gallon of water. Each flask of lablets or pellets or the contents of 45 bags should be mixed with no less than 1 gallon of water/ detergent solution. Slowly pour the material into the water as it is stirred. After 5 flasks or the contents of 200 bags have been added to a 55 gallon drum of water, wait until bubbling is very slow before proceeding to add 5 more flasks or 200 bags. Repeat this procedure until the limit is reached. Concentration readings should be taken to ensure that inhalation exposure does not exceed the prescribed limits. Stir occasionally thereafter for at least 36 hours. Wear appropriate respiratory protection. DO NOT COVER THE CONTAINER IF THE CONTAINER IS COVERED, THE HYDROGEN PHOSPHIDE BEING GENERATED WILL BE CONFINED AND WILL DECOMPOSE EXPLOSIVELY. The well method of deactivation is the method of choice for quantities in excess of 5 flasks (10 to 15 pounds). It is safe to dispose of this sturry.

Dispose off the resulting deactivated slurry, with or without preliminary pouring out of excess water, at a landfill or other suitable burial site approved by local authorities. The water from the slurry may be evaporated prior to disposal. Where permissible, this slurry may be poured into a sanitary sever or out onto the ground.

: :.; NOTE: Never place pellets, tablets, their dust or the dust/water sturry in a confined container such as a closed drum or plastic bags. Any hydrogen phosphide generated will be confined and may decompose explosively. Sea instructions in disposal section above. 2. Dry Method ÷. -• • • -1 • į . ω 2 ÷ : Uniter the Pederal Lescurdue, Punja 14 and Relaminite Act as convided for the resultide EPArag. No. 5 9 24 9-1 $\mathbf{\Sigma}$ \bigcirc \bigcirc EPTED 1. N. M. 1. . 1. V. 33