

60061-10

10-27-2000

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

OCT 27 2000

Kop-Coat, Inc.
436 Seventh Avenue
Pittsburgh, PA 15219-1818

Attn: Alan S. Ross, Vice President


Subject: Z*Spar "The Protector" TF B-91 Blue
EPA Registration No. 60061-10
Amendment Dated October 5, 2000

This will acknowledge receipt of your notification to include the additional brand names "Pettit Marine Paint Premium Line Super Premium Performance Antifouling Finish 1290 blue" and "Pettit Marine Paint Premium Line super Premium Performance Antifouling Finish 1890 Black", submitted under the provisions of FIFRA Section 3(c)9. Based on a review of the submitted material, the following comments apply.

The notification is in compliance with PR Notice 98-10 and is acceptable. This information has been made a part of your file.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely



Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobial Division (7510C)

CONCURRENCES

SYMBOL								
SURNAME								
DATE								



United States
Environmental Protection Agency
Washington, DC 20460

Registration
Amendment
☒ Other

OPP Identifier Number

243479

Application for Pesticide - Section I

1. Company/Product Number 60061-10	2. EPA Product Manager Marshall Swindell	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Z*Spar "The Protector" TF R-91 Blue	PM# 33	
5. Name and Address of Applicant (Include ZIP Code) Kop-Coat Inc. 436 Seventh Avenue Pittsburgh, PA 15219-1818 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Pettit Marine Paint Premium Line Super Premium Performance Antifouling Finish 1290 Blue

Pettit Marine Paint Premium Line Super Premium Performance Antifouling Finish 1890 Black

Section - III

1. Material This Product Will Be Packaged In:			
Child-Resistant Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	2. Type of Container <input checked="" type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____
* Certification must be submitted		If "Yes" Unit Packaging wgt. No. per container	If "Yes" Package wgt. No. per container
3. Location of Net Contents Information <input checked="" type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container	5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled		<input type="checkbox"/> Other _____	

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name Kim Treloar	Title Product Registration Specialist	Telephone No. (Include Area Code) (412) 826-3323
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature 	3. Title Vice President	
4. Typed Name Alan S. Ross	5. Date October 5, 2000	

07/20/00

PREMIUM LINE

SUPER PREMIUM

ANTIFOULING FINISH

- Economical Antifouling Protection
- Hard Smooth Finish
- Apply Over Most Other Antifouling
- Excellent For Fiberglass, Wood & Steel Boats

NON-COMMERCIAL USE

KEEP OUT OF REACH OF CHILDREN.

WARNING!

HARMFUL OR FATAL IF SWALLOWED.

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

NET CONTENTS
1 GALLON (128 FL. OZ.)
3.785 LITERS

$$\frac{w}{v}$$

SUPER PREMIUM PERFORMANCE BRAND ANTIFOULING FINISH

Super Premium Performance Brand Antifouling Paint: A highly effective hard antifouling bottom paint of premium quality. Contains a high concentration of cuprous oxide. Protects against attachment of barnacles, hydroids, bryozoa, algae and other marine or fresh water growths. Protects wood boats against borers. For use in both salt and fresh water. Do not apply to any surfaces other than boat bottoms.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with it's labeling.

GENERAL

Be sure surface is clean and dry before painting. When sanding is necessary on surfaces, remove sanding dust by clean air blast, clean soft brushes, or wiping with clean rags, then follow by tack rag wipe to insure complete removal of sanding dust. NOTE: Face mask should be used when sanding.

Stir paint well before and during use. Apply generously with brush or roller at package consistency. If thinning is necessary due to evaporation of solvent from the can, use Pettit 120 Brushing Thinner. Do not spray as inhalation of spray mist is hazardous. Do not apply at temperatures below 40°F, or if rain is expected before the coating is dry.

COVERAGE: Approximately 400 sq. ft. per gallon (allows for a 20% loss).

NUMBER OF COATS: 2 or 3 depending on the surface.

DRYING TIME AT 70°F AND 50% HUMIDITY:

Between coats: 6 hours minimum.

Prior to Launching: 6 hours minimum to overnight, preferably; 60 days maximum.

THINNER: Pettit 120 Brushing Thinner

CLEANER: Pettit 120 Brushing Thinner

OLD BOTTOM PAINTS: After hauling the boat, allow the hull to dry thoroughly of absorbed water before repainting. Over old dry paint apply two coats of this product for best results after scrubbing, cleaning, and removing any loose paint. **WHEN SANDING OLD BOTTOM PAINT, ALWAYS WET SAND** and take precautions against getting the material in your eyes, nostrils, open cuts, etc. Where excess bottom substrate is visible, prime per instructions for the substrate.

WOOD BOTTOMS: Sand wood surfaces with 80-100 grit wet or dry sandpaper. Apply three coats of this product to bare wood. Thin first coat with Pettit 120 Brushing Thinner to allow greater penetration. The next two coats should be applied at package consistency. Any metal parts must be properly primed before applying the bottom paint.

FIBERGLASS BOTTOMS: Wash with soap, ammonia, and water. Let dry, then thoroughly clean hull with Pettit 95 Fiberglass Dewaxer. Then sand with 80-grit sandpaper to dull and roughen the surface. Wipe off sanding dust with clean cloth or tack rag. Apply two coats of this product. For prevention and repair of bottom blisters, use three coats of Pettit 4700/4701 High Build Epoxy Primer "wet-on-wet" with this product. See the 4700/4701 technical data sheet for application details.

STEEL BOTTOMS: Sandblast to near-white metal surface and apply three coats of 4700/4701 High Build Epoxy Primer to a minimum 12 dry mils film thickness, following the 4700/4701 High Build Epoxy Primer label instructions. Then follow with two coats of this product.

ALUMINUM BOTTOMS: This product is NOT recommended for aluminum.

STORAGE AND DISPOSAL

STORAGE: Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

PESTICIDE DISPOSAL: Do not contaminate water, Pesticide wastes are toxic. Improper disposal of excess is a violation of Federal Law. If these wastes cannot be disposed of in accordance with label instructions, contact your State Pesticide or Environmental Hazardous Waste representative at the nearest EPA Regional Office.
CONTAINER DISPOSAL: Triple rinse (or equivalent) conditioning, or puncture and dispose of in sanitary approved by state and local authorities.
VOC: 374 grams per liter (as supplied).

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS WARNING

CONTAINS AROMATIC AND ALIPHATIC HYDROCARBON ACETATES. See Material Safety Data Sheet for details. Do not get on skin, in eyes, or on clothing. Wear goggles, clothing such as long-sleeved cotton shirt, long pants, and gloves. Wash thoroughly with soap and water after handling. Wash thoroughly with soap and water after clothing and wash before reuse. Do not breathe sand or dust not take internally.

FIRST AID

In case of skin contact, wash thoroughly with soap and water immediately with plenty of water for 15 minutes and remove contaminated clothing. **In case of breathing of vapor,** move to fresh air. If not breathing, give artificial respiration. If swallowed, drink plenty of water, preferably mouth-to-mouth. If these are not available, drink milk or water. **CALL A PHYSICIAN IMMEDIATELY.** NOTE: This product may contraindicate the use of gastric lavage.

KEEP OUT OF REACH OF CHILDREN

Use with adequate ventilation during application and areas, use only with adequate forced air ventilation to remove vapors which could cause death from explosion or used in confined areas or while sanding boat surfaces approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health, CFR 11. Prevent flames, sparks, welding and smoking.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to cleaning of equipment or disposal of wastes. Do not during the paint removal to enter water. Dispose of in accordance with local regulations.

PHYSICAL OR CHEMICAL HAZARDS

Flammable. Keep away from heat and open flames. Avoid contact with acids, alkalis, foams, water fog or CO₂. Cool closed containers. Photochemically Reactive.

Medical Emergencies 1-800-424-9293



ACTIVE INGREDIENT:

Cuprous Oxide 65.8%

INERT INGREDIENTS 34.2%

TOTAL 100.0%

This product contains petroleum distillates.

EPA EST. NO. 30061-NJ-2

EPA REGISTRATION NO. 30061-112

ADP-COAT, INC.
PETTIT PAINT BRAND
ROCKAWAY, NJ 07866

An RPM Company



**PREMIUM
LINE**

DISCLAIMER: The information on this label is provided for informational purposes only. It is not intended to constitute an offer of insurance or any other financial product. The information is not intended to be used as a basis for any investment decision. The information is not intended to be used as a basis for any investment decision. The information is not intended to be used as a basis for any investment decision.

SUPER PREMIUM
PERFORMANCE

**ANTIFOULING FINISH
1890 BLACK**

- Economical Antifouling Protection
- Hard Smooth Finish
- Apply Over Most Other Antifoulings
- Excellent For Fiberglass, Wood & Steel Boats

NON-COMMERCIAL USE


KEEP OUT OF REACH OF CHILDREN.

WARNING!

HARMFUL OR FATAL IF SWALLOWED.

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

**NET CONTENTS
1 GALLON (128 FL. OZ.)
3.785 LITERS**



5/16

SUPER PREMIUM PERFORMANCE BRAND ANTIFOULING FINISH

Super Premium Performance Brand Antifouling Paint: A highly effective hard antifouling bottom paint of premium quality. Contains a high concentration of cuprous oxide. Protects against attachment of barnacles, hydroids, bryozoa, algae and other marine or fresh water growths. Protects wood boats against borers. For use in both salt and fresh water. Do not apply to any surfaces other than boat bottoms.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with it's labeling.

GENERAL

Be sure surface is clean and dry before painting. When sanding is necessary on surfaces, remove sanding dust by clean air blast, clean soft brushes, or wiping with clean rags, then follow by tack rag wipe to insure complete removal of sanding dust. NOTE: Face mask... should be used when sanding.

Stir paint well before and during use. Apply generously with brush or roller at package consistency. If thinning is necessary due to evaporation of solvent from the can, use Pettit 120 Brushing Thinner. Do not spray as inhalation of spray mist is hazardous. Do not apply at temperatures below 40°F, or if rain is expected before the coating is dry.

COVERAGE: Approximately 400 sq. ft. per gallon (allows for a 20% loss).

NUMBER OF COATS: 2 or 3 depending on the surface.

DRYING TIME AT 70°F AND 50% HUMIDITY:

Between coats: 6 hours minimum.

Prior to Launching: 6 hours minimum to overnight, preferably; 60 days maximum.

THINNER: Pettit 120 Brushing Thinner

CLEANER: Pettit 120 Brushing Thinner

OLD BOTTOM PAINTS: After hauling the boat, allow the hull to dry thoroughly of absorbed water before repainting. Over old dry paint apply two coats of this product for best results after scrubbing, cleaning, and removing any loose paint. **WHEN SANDING OLD BOTTOM PAINT, ALWAYS WET SAND** and take precautions against getting the material in your eyes, nostrils, open cuts, etc. Where excess bottom substrate is visible, prime per instructions for the substrate.

WOOD BOTTOMS: Sand wood surfaces with 80-100 grit wet or dry sandpaper. Apply three coats of this product to bare wood. Thin first coat with Pettit 120 Brushing Thinner to allow greater penetration. The next two coats should be applied at package consistency. Any metal parts must be properly primed before applying the bottom paint.

FIBERGLASS BOTTOMS: Wash with soap, ammonia, and water. Let dry, then thoroughly clean hull with Pettit 95 Fiberglass Dewaxer. Then sand with 80-grit sandpaper to dull and roughen the surface. Wipe off sanding dust with clean cloth or tack rag. Apply two coats of this product. For prevention and repair of bottom blisters, use three coats of Pettit 4700/4701 High Build Epoxy Primer "wet-on-wet" with this product. See the 4700/4701 technical data sheet for application details.

STEEL BOTTOMS: Sandblast to near-white metal surface and apply three coats of 4700/4701 High Build Epoxy Primer to a minimum 12 dry mils film thickness, following the 4700/4701 High Build Epoxy Primer label instructions. Then follow with two coats of this product.

ALUMINUM BOTTOMS: This product is NOT recommended for aluminum.

STORAGE AND DISPOSAL

STORAGE: Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

PESTICIDE DISPOSAL: Do not contaminate Pesticide wastes are toxic. Improper disposal is a violation of Federal Law. If these wastes label instructions, contact your State Pesticide Hazardous Waste representative at the nearest

CONTAINER DISPOSAL: Triple rinse (or equivalent) and reuse for same purpose, or reconditioning, or puncture and dispose of in approved by state and local authorities.

VOC: 374 grams per liter (as supplied).

PRECAUTIONARY HAZARDS TO HUMANS AND THE ENVIRONMENT

CONTAINS AROMATIC AND ALIPHATIC HYDROCARBON ACETATES. See Material Safety Data Sheet for more information. Do not get on skin, in eyes, or on clothing. Wash clothing such as long-sleeved cotton shirt, long pants, etc. thoroughly with soap and water before reuse. Do not breathe vapors. Do not take internally.

FIRST AID: In case of skin contact, wash thoroughly with immediately with plenty of water for 15 minutes. If breathing of vapor, move to fresh air. If inhaled, preferably mouth-to-mouth. If swallowed, give white, gelatin solution or if these are not available, give alcohol. CALL A PHYSICIAN IMMEDIATELY. Eye damage may contraindicate the use of gastric lavage.

KEEP OUT OF REACH OF CHILDREN: Use with adequate ventilation during application in areas, use only with adequate forced air ventilation of vapors which could cause death from exposure used in confined areas or while sanding boat approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health (NIOSH) CFR 11. Prevent flames, sparks, welding and

ENVIRONMENTAL: This material is toxic to fish. Do not apply directly to cleaning of equipment or disposal of wastes. Do not allow paint to enter water. Dispose of in accordance with local, state, and federal regulations.

PHYSICAL OR CHEMICAL: Flammable. Keep away from heat and open flames, chemicals, foam, water fog or CO2. Cool with water. Photochemically Reactive.

Medical Emergency:



ACTIVE INGREDIENT:

Cuprous Oxide 66.8%

INERT INGREDIENTS 34.2%

TOTAL 100.0%

This product contains petroleum distillates

EPA EST. NO. 60061-NJ-2
EPA REGISTRATION NO. 30061-110

KOP-COAT, INC.
PETTIT PAINT BRAND
ROCKAWAY, NJ 07866

An RPM Company