

60061-10

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

4-30-2001

1/6

APR 30 2001

Kop-Coat, Inc.
3020 William Pitt Way
Pittsburgh, PA 15238

Attention: Kim Treloar
Product Registration Specialist

Subject: Z Spar the Protector TF Hard Type Antifouling Paint
EPA Registration No. 60061-10
Notification Dated March 30, 2001

This will acknowledge receipt of your notification to make a minor change in marketing claim per PR Notice 98-10 for the following alternate brand names, submitted under the provisions of FIFRA Section 3(c)9. Based on a review of the submitted material, the following comments apply.

- (1) Pettit Marine Paint Premium Line Super Premium Performance
Antifouling Finish 1290 Blue
- (2) Pettit Marine Paint Premium Line Super Premium Performance
Antifouling Finish 1890 Black

The Notification to add the claim "Economical Antifouling Protection" to the label, is in compliance with PR Notice 98-10 and is acceptable. This information has been made a part of your file.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely



Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobial Division (7510C)

CONCURRENCES

SYMBOL								
SURNAME								
DATE								



Please read instructions on reverse before completing form.

Form Approved, OMB No. 2070-0060, Approval expires 2-28-95



United States
Environmental Protection Agency
Washington, DC 20460

☐ Registration
☐ Amendment
☒ Other

OPP Identifier Number

Application for Pesticide - Section I

1. Company/Product Number Kop-Coat Inc./60061-10	2. EPA Product Manager Marshall Swindell	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Z Spar The Protector TF Hard type Antifouling Paint	PM# 33	
5. Name and Address of Applicant (Include ZIP Code) Kop-Coat, Inc 436 Seventh Avenue Pittsburgh, PA 15219-1818 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input checked="" type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Notification of minor change in marketing claim on label for Pettit Marine Paint Premium Line Super Premium Performance Antifouling Finish 1290 Blue and Pettit marine Paint Premium Line Super Premium Performance Antifouling Finish 1890 Black


The additional claim added to label reads "Economical Antifouling Protection"

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		<input checked="" type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____	
* Certification must be submitted		If "Yes" Unit Packaging wgt.	No. per container	If "Yes" Package wgt	No. per container
3. Location of Net Contents Information <input checked="" type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/>	
6. Manner in Which Label is Affixed to Product <input checked="" type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled		<input type="checkbox"/> Other _____			

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name Kim Treloar	Title Product Registration Specialist	Telephone No. (Include Area Code) (412) 826-3323
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped: _____)
2. Signature 	3. Title Vice President	
4. Typed Name Alan S. Ross	5. Date 3/30/01	



PREMIUM LINE

NET CONTENTS
1 GAL. (128 FL. OZ.)
3.785 LITERS

SUPER PREMIUM
PERFORMANCE
ANTIFOULING FINISH
1290 BLUE

- **Economical Antifouling Protection**
- **Hard Smooth Finish**
- **Apply Over Most Other Antifoulings**
- **Excellent For Fiberglass, Wood & Steel Boats**

NON-COMMERCIAL USE
KEEP OUT OF REACH OF CHILDREN.

WARNING

HARMFUL OR FATAL IF SWALLOWED.
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

RAND ANTIFOULING FINISH

Paint: A highly effective hard antifouling concentration of cuprous oxide. Protects against barnacles, algae and other marine or fresh water organisms. For use in both salt and fresh water.

USE

Apply in a manner inconsistent with its labeling.

When sanding is necessary on surfaces, use brushes, or wiping with clean rags, then remove all sanding dust. NOTE: Face mask

Apply with brush or roller at package consistency. If solvent from the can, use Pettit 120 Brushing Thinner. Do not apply if the coating is dry. (allows for a 20% loss).

Shelf life: 60 days maximum.

Remove the hull to dry thoroughly of absorbed solvent. Apply three coats of this product for best results. WHEN SANDING OLD BOTTOM, be careful not to get the material in your eyes. If irritation is visible, prime per instructions.

Apply with 80-grit wet or dry sandpaper. Apply three coats of Pettit 120 Brushing Thinner to allow proper consistency. Any grit on the bottom paint.

Apply with 80-grit sandpaper to dull and remove old paint. Apply two coats in blisters, use three coats of Pettit with this product. See the 4700/4701

Instructions and apply three coats of 4700/4701 in thickness, following the 4700/4701 instructions with two coats of this product. Recommended for aluminum.

OSAL

Prevent leakage. Keep container closed when not in use in accordance with local applicable

Procedures for storage or disposal. Do not use as pesticide, spray mixture or rinse. Do not be disposed of by use according to Environmental Control Agency, or the Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in sanitary landfill, or by other procedures approved by state and local authorities.

VOC: 374 grams per liter (as supplied).

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS WARNING

CONTAINS AROMATIC AND ALIPHATIC HYDROCARBONS, N-BUTYL ALCOHOL, AND ACETATES. See Material Safety Data Sheet for this product.

Do not get on skin, in eyes, or on clothing. Wear goggles or face shield and protective clothing such as long-sleeved cotton shirt, long pants, hat and rubber gloves when handling. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse. Do not breathe sanding dust, vapor or spray mist. Do not take internally.

FIRST AID

In case of skin contact, wash thoroughly with soap and water; for eyes, flush immediately with plenty of water for 15 minutes and call a physician. If affected by breathing of vapor, move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If swallowed, drink promptly a large quantity of milk, egg white, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. CALL A PHYSICIAN IMMEDIATELY. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

KEEP OUT OF REACH OF CHILDREN

Use with adequate ventilation during application and drying. In tanks and other confined areas, use only with adequate forced air ventilation to prevent dangerous concentrations of vapors which could cause death from explosion or from breathing. When product is used in confined areas or while sanding boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration (U.S. Bureau of Mines) and the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11. Prevent flames, sparks, welding and smoking.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during the paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS


Flammable. Keep away from heat and open flame. IN CASE OF FIRE: Use dry chemicals, foam, water fog or CO₂. Cool closed container with water. Non-Photochemically Reactive.

Medical Emergencies 1-800-548-0489

Made in USA P3068 1290 Gal 10/00

4/16

50-469-D 07/20/00



PREMIUM LINE

DISCLAIMER: The performance of any
coatings is dependent upon the quality of the
substrate and the application of the coating.
Pettit Paints, Inc. makes no warranty, express
or implied, as to the performance of its
coatings. The user assumes all liability for
any damage or injury resulting from the use
of this product. Pettit Paints, Inc. is not
responsible for any damage or injury
resulting from the use of this product.
Pettit Paints, Inc. is not responsible for
any damage or injury resulting from the use
of this product. Pettit Paints, Inc. is not
responsible for any damage or injury
resulting from the use of this product.
By purchase or use
of this product, buyer agrees that the sole
and exclusive remedy, if any, is limited to
the refund of the purchase price or replacement
of the product at Pettit Paints, Inc.'s option.

NET CONTENTS
1 GAL. (128 FL. OZ.)
3.785 LITERS

SUPER PREMIUM

PERFORMANCE

ANTIFOULING FINISH 1290 BLUE

- Economical Antifouling Protection
- Hard Smooth Finish
- Apply Over Most Other Antifouling
- Excellent For Fiberglass, Wood & Steel Boats

NON-COMMERCIAL USE
KEEP OUT OF REACH OF CHILDREN.

WARNING
HARMFUL OR FATAL IF SWALLOWED.
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

2/16

SUPER PREMIUM PERFORMANCE BRAND ANTIFOULING FINISH

Super Premium Performance Brand Antifouling Paint: A highly effective hard antifouling bottom paint of premium quality. Contains a high concentration of cuprous oxide. Protects against the attachment of barnacles, hydroids, bryozoa, algae and other marine or fresh water growths. Protects wood boats against borers. For use in both salt and fresh water. Do not apply to any surfaces other than boat bottoms.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

GENERAL

Be sure surface is clean and dry before painting. When sanding is necessary on surfaces, remove sanding dust by clean air blast, clean soft brushes, or wiping with clean rags, then follow by tack rag wipe to insure complete removal of sanding dust. NOTE: Face mask should be used when sanding.

Stir paint well before and during use. Apply generously with brush or roller at package consistency. If thinning is necessary due to evaporation of solvent from the can, use Pettit 120 Brushing Thinner. Do not spray as inhalation of spray mist is hazardous. Do not apply at temperatures below 40°F, or if rain is expected before the coating is dry.

COVERAGE: Approximately 400 sq. ft. per gallon (allows for a 20% loss).

NUMBER OF COATS: 2 or 3 depending on the surface.

DRYING TIME AT 70°F AND 50% HUMIDITY:

Between coats: 6 hours minimum.

Prior to Launching: 6 hours minimum to overnight, preferably; 60 days maximum.

THINNER: Pettit 120 Brushing Thinner

CLEANER: Pettit 120 Brushing Thinner

OLD BOTTOM PAINTS: After hauling the boat, allow the hull to dry thoroughly of absorbed water before repainting. Over old dry paint apply two coats of this product for best results after scrubbing, cleaning, and removing any loose paint. **WHEN SANDING OLD BOTTOM PAINT, ALWAYS WET SAND** and take precautions against getting the material in your eyes, nostrils, open cuts, etc. Where excess bottom substrate is visible, prime per instructions for the substrate.

WOOD BOTTOMS: Sand wood surfaces with 80-100 grit wet or dry sandpaper. Apply three coats of this product to bare wood. Thin first coat with Pettit 120 Brushing Thinner to allow greater penetration. The next two coats should be applied at package consistency. Any metal parts must be properly primed before applying the bottom paint.

FIBERGLASS BOTTOMS: Wash with soap, ammonia, and water. Let dry, then thoroughly clean hull with Pettit 95 Fiberglass Dewaxer. Then sand with 80-grit sandpaper to dull and roughen the surface. Wipe off sanding dust with clean cloth or tack rag. Apply two coats of this product. For prevention and repair of bottom blisters, use three coats of Pettit 4700/4701 High Build Epoxy Primer "wet-on-wet" with this product. See the 4700/4701 technical data sheet for application details.

STEEL BOTTOMS: Sandblast to near-white metal surface and apply three coats of 4700/4701 High Build Epoxy Primer to a minimum 12 dry mils film thickness, following the 4700/4701 High Build Epoxy Primer label instructions. Then follow with two coats of this product.

ALUMINUM BOTTOMS: This product is NOT recommended for aluminum.

STORAGE AND DISPOSAL

STORAGE: Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent), or puncture and dispose of in sanitary state and local authorities.

VOC: 374 grams per liter (as supplied).

PRECAUTIONARY HAZARDS TO HUMANS AND WATERS

**CONTAINS AROMATIC AND ALIPHATIC
HOL, AND ACETATES. See Material Safety Data Sheet.**
Do not get on skin, in eyes, or on clothing. Wear protective clothing such as long-sleeved shirt, pants, rubber gloves when handling. Wash thoroughly after handling. Remove contaminated clothing and shoes. Do not breathe sanding dust, vapor or fumes.

FIRST AID:
In case of skin contact, wash thoroughly with plenty of water. If affected by breathing of vapor, move to fresh air. If necessary, administer artificial respiration, preferably mouth-to-mouth. If breathing apparatus not available, drink large quantities of water. If swallowed, drink large quantities of water. **NOTE TO PHYSICIAN:** Immediately inform physician of the use of gastric lavage.

KEEP OUT OF REACH OF CHILDREN.
Use with adequate ventilation. Do not use in tanks and other confined areas, use only in well-ventilated areas to prevent dangerous concentrations from explosion or from breathing. When sanding boat surfaces, wear a respirator (see the Mining Enforcement and Safety Administration (MESA) and the National Institute for Occupational Safety and Health (NIOSH) provisions of 30 CFR 11. Prevent fire and explosion.

ENVIRONMENTAL PRECAUTIONS:
This material is toxic to fish. Do not apply to water by cleaning of equipment, chips and dust generated during the process of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS:
Flammable. Keep away from heat and open flames. May react with strong oxidizing chemicals, foam, water fog or CO₂. Corrosive. Photochemically Reactive.

Medical Emergency:



ACTIVE INGREDIENT:

Cuprous Oxide	65.8%
INERT INGREDIENTS	34.2%
	100.0%

This product contains petroleum distillates.

EPA EST. NO. 60061-MJ-2

EPA REGISTRATION NO. 60061-10

KOP-PAINT, INC.
PETTIT PAINT BRAND
ROCKAWAY, NJ 07866

An **RPM** Company