

# KOP-COAT

## COPPERTREAT 120

Ready To Use  
Copper Naphthenate Preservative

- Protects against termites and decay
- For above and below ground and water contact applications
- Protection for end-cuts, docks, posts, piers, fences, and landscape timbers
- Long-lasting water repellency and mildew resistance

Consumer label only: From the Wolman® Wood Care People

KEEP OUT OF REACH OF CHILDREN

### WARNING

MAY BE FATAL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN.  
CAUSES EYE AND SKIN IRRITATION. COMBUSTIBLE  
See side panel for additional precautionary statements.

EPA Reg. No. 60061-19  
EPA Est. No. 60061-MO-1

|                     |        |
|---------------------|--------|
| ACTIVE INGREDIENT:  |        |
| Copper naphthenate* | 21.6%  |
| Other Ingredients:  | 78.4%  |
| TOTAL               | 100.0% |

Read warranty before buying or using. If such terms are not acceptable return at once unopened.

\*Contains a minimum of 68 gm/gal (77°F) of copper naphthenate as copper or 0.15 pounds or 2.14% metal copper as copper naphthenate.

This product contains petroleum distillates (mineral spirits).

Kop-Coat, Inc.  
Protection Products Division  
5137 Southwest Avenue  
St. Louis, MO 63110-3497  
314-772-2200

V.O.C. MAX 4 Lbs/Gal (480 g/l) 60061-19

KOP-COAT MAKES NO FURTHER WARRANTIES EXPRESSED OR IMPLIED INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OF MERCHANTABILITY WHICH EXTENDS BEYOND THE DURATION OF THIS WRITTEN WARRANTY

SIGN & Date Lee Ann Briggs (AP) 10/2/00  
Alan S. Ross (AP) 10/4/00 PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**WARNING:** May be fatal if swallowed. Do not breathe vapor. Do not get in eyes, on skin or on clothing. Wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Wash Thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Remove contaminated clothing and wash clothing before reuse.

Contains mineral spirits. Vapor harmful. May affect the brain or nervous system causing dizziness, headache, or nausea. May be absorbed through skin. Avoid contact with eyes, skin, or clothing. Wash thoroughly with soap and water after handling. Use of goggles and protective clothing (rubber gloves) when dipping or brushing is recommended. Do not breathe vapors or mist during brush, roll, and spray or dip applications. Wear a MSHA/NIOSH approved respirator when spraying for continued or prolonged use of this product or for frequent use of this product. Use only with adequate ventilation. Do not take internally.

Application of this product may produce a strong, lingering unpleasant odor.

| FIRST AID  |   |
|--|---|
| If Swallowed:  | • Call a Poison Control Center or doctor immediately for treatment advice. DO NOT induce vomiting. Do not give anything by mouth to an unconscious person.  |
| If Inhaled:  | • Remove person to fresh air. If not breathing call 911 or an ambulance, then give artificial respiration preferably mouth-to-mouth if possible. Call a Poison Control Center or doctor for further treatment advice.       |
| If In Eyes:  | • Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a Poison Control Center or doctor for treatment advice. |
| If on Skin:  | • Wash with plenty of soap and water. Wash clothing before reuse.   |
| In case of medical questions, emergencies, or accidents involving this product, Call 1-800-548-0489. |   |

#### ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters. This product is hazardous to domestic animals. Treated sawdust and other wood wastes should be disposed of properly and should not come in contact with ornamental shrubs, trees, grass and other desirable vegetation. Vapors may cause injury if adequate ventilation is not ensured. Do not use this product indoors, or in any other confined areas where the vapors may concentrate or migrate indoors and cause injury to plant or animal life.

#### PHYSICAL AND CHEMICAL HAZARDS

**COMBUSTIBLE.** Do not use, pour, spill, or store near heat or open flame.

**IN CASE OF FIRE:** Use dry chemicals, foam, water, fog, or CO<sub>2</sub>. Cool closed containers with water.

**LIMITED WARRANTY:** This product will perform as claimed if directions are followed. Directions are as complete as possible but cannot encompass all conditions, applications, techniques, and/or surfaces which are beyond our control if you have a question check with your dealer, or call (industrial - 412-227-2426) (consumer - Wolman Wood Care Products 1-800-556-7737). Warranty is limited to replacement or refunded value of product actually used if such product proves defective within on (1) year of purchase. NOTIFY KOP-COAT, INC., 436 SEVENTH AVENUE, PITTSBURGH, PA 15219 WITHIN SIXTY (60) DAYS OF LEARNING OF DEFECT.

PPD CT120 0600  
An RPM Company

#### DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

#### **FOR EXTERIOR USE ONLY.**

Apply this product regularly to nonpressure treated wood to provide protection against termites, molds, mildew, bacteria, and decay and algae growth. Special water repellents also provide protection against moisture movement. This product can be used to treat wood for above or below ground exposure as well as for contact with fresh water. The bluish green color is imparted by the copper naphthenate and it will effectively darken redwood and cedar. Therefore, a test application to your wood is recommended to determine suitability.

**SURFACE PREPARATION:** All surfaces should be dry and free of mold, mildew, dust, oil, soot, dirt, and other contaminants before applying this product.

#### **INDUSTRIAL USE**

**APPLICATIONS:** Use brush, dip, or roller. Spray application is not recommended. Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry and well seasoned and immersed in the product for a period of 12 to 24 hours for adequate protection for in-ground application. For lumber or other smaller wooden members, dip treatment should be 3 to 30 minutes per inch of thickness for in-ground application. For burlap, duck, rope, nets, textiles brush on solution allowing several minutes for absorption. If wood is dipped it would then be layered for best drying results. Allow 24 hours drying time between two coats. Treated surfaces are not recommended to finish with stain, paint, or varnish, nor is this product intended for use over these finishes. Do not apply this product at temperatures below 50 degrees F, or above 90 degrees F. Do not thin or mix with other wood preservatives. Do not use any item treated with this product until the solvents have completely volatilized and they are thoroughly dry.

**COVERAGE:** Rate will vary between 150 and 300 square feet per gallon depending on method of application, surface texture, and species of wood.

**CLEAN-UP** Clean tools with mineral spirits.

#### **CONSUMER USE**

**APPLICATIONS** Use brush, dip, or roller. Spray application is not recommended. For treatment of posts and large timbers, dipping should be for a period of 12 to 24 hours for adequate protection for in-ground applications. For lumber or other smaller wooden members, dip treatment should be 3 to 30 minutes per inch of thickness for in-ground application. If wood is dipped it should then be layered for best drying results. Allow 24 hours drying time between two coats. Treated surfaces are not recommended to be finished with stain, paint or varnish, nor is this product intended for use over these finishes. Do not apply this product at temperatures below 50 degrees F or above 90 degrees F. Do not thin or mix with other wood preservatives. Do not use any item treated with this product until the solvents have completely volatilized and they are thoroughly dry. **NOTE: NOT DESIGNED FOR APPLICATIONS ON DECKS, OUTDOOR FURNITURE OR AREAS OF FOOT TRAFFIC.**

**COVERAGE:** Rate will vary between 150 and 300 square feet per gallon depending on method of application, surface texture, and species of wood.

**CLEAN-UP** Clean tools with mineral spirits.

#### **STORAGE AND DISPOSAL**

**STORAGE:** Store this product in its originally labeled container in a locked storage area located in a cool place. This product will not freeze but may become cloudy at colder temperatures. Keep container and freshly treated articles away from high temperature areas, sparks, fire, or open flame. If static generating conditions exist, provide necessary grounding and bonding. Keep this product separate from other pesticides during storage to prevent cross contamination of other pesticides, fertilizers, food, and feed. Keep container tightly closed when not in use.

**PESTICIDE DISPOSAL:** Do not contaminate water, food or feed by storage or disposal. Pesticide wastes are toxic. Improper disposal of excess pesticide spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA office for guidance.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent), then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.