

97-22 60061-27 124
MAR 18 1992

Mr. Alan S. Ross, Ph.D.
Kop-Coat, Inc.
3020 William Pitt Way
Pittsburgh, PA 15238

Dear Dr. Ross:

Subject: NP-1 Sapstain Control Chemical
EPA Registration No. 60061-27
Alternate Brand Name & Additional Use
Your Letter Dated 1/24/92

The labeling referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable provided the following revisions are incorporated.

As previously stated in our letter of 1/31/92, the skull and crossbones and the word "Poison" are not required for this product. The statement "May be fatal if swallowed, absorbed through skin, or inhaled", in the Precautionary Statements section of the label, should be revised to read, "May be harmful if swallowed or inhaled. Harmful if absorbed through skin."

The statement "Do not apply directly to any body of water.", under Environmental Hazards, should be revised to read, "Do not apply directly to water, to areas where surface water is present or to intertidal areas below the mean high water mark."

Finally, you must submit five (5) copies of your finished, printed labeling, incorporating these changes, prior to releasing the product for shipment.

Sincerely Yours,

Cynthia Giles-Parker
Product Manager (22)
Fungicide-Herbicide Branch
Registration Division (H7505C)

CONCURRENCES							
SYMBOL	Enclosure						
SURNAME							
DATE							

Woodtreat® PT

Wood Preservative Concentrate

U.S. Patent No. 4,950,525 and Foreign Patents

PRESERVES wood. Controls decay, stain and mold fungi, and soft rot. Effective for beams, shingles, millwork and architectural building products.

KEEP OUT OF REACH OF CHILDREN.

DANGER

POISON

See side panel for additional precautionary statements.

READ WARRANTY ON SIDE PANEL BEFORE
BUYING OR USING. IF SUCH TERMS ARE
NOT ACCEPTABLE, RETURN ALL ONCE
UNOPENED.

EPA Reg. No. 60061-27
EPA Est. 60061-MO-1

ACTIVE INGREDIENTS

Dicoyl dimethyl	
Ammonium Chloride ..	64.50%
3-Iodo-2-Propynyl	
Butyl Carbamate	7.50%
INERT INGREDIENTS ...	27.50%
TOTAL	100.00%

STATEMENTS OF PRACTICAL TREATMENT

IF IN EYES: Flush with plenty of water. Call a physician.

IF ON SKIN: Wash with soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate use of gastric lavage.

Kop-Coat, Inc.
Protection Products Division
5137 Southwest Avenue, St. Louis, Missouri 63110
314/772-2200

NET CONTENTS

U.S. GALLONS

BEST AVAILABLE COPY

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This preservative is recognized as effective for aboveground use and is not recommended for wood in direct contact with the ground. It may be combined with compatible additives such as water repellents, fire retardants, colorants, defoamers and insecticides. Contact Kop-Coat for a list of approved WOODTREAT PT additives.

MIXING INSTRUCTIONS

Mix one gallon of this Concentrate with from 15 to 150 gallons of an appropriate solvent. Solvent choice and dilution rate will depend upon desired end use and method of application. Recommended solvents include water, mineral spirits and other organic carriers such as fuel oil.

Pour about 1/3 of solvent in the mixing tank. Add the correct amount of this Concentrate and rinse container into tank. Add the required balance of solvent along with additives, if any, and mix thoroughly. Additional agitation is usually not needed during use. On standing raised for 24 hours or longer, remix thoroughly before reuse.

APPLICATION TECHNIQUES

PRESSURE TREATMENT - For best results this product should be applied to effect maximum penetration into the wood. Recommended pressure treatment cycles include full cell, modified full cell, Vac-Vac and similar techniques. The WOODTREAT PT Concentrate should be diluted with an amount of carrier solvent needed to achieve a retention of from 0.1 to 0.4 pounds per cubic foot of active ingredients in the wood. Contact Kop-Coat for methods of analyzing retention and penetration of WOODTREAT PT.

SURFACE TREATMENT - WOODTREAT PT can be applied by surface treatment methods such as dip, flood coat or spray. Dilute with an appropriate carrier solvent to obtain a solution concentration of active ingredients in the range of 0.5 to 4.0%. A minimum immersion period of 30 seconds is recommended when treating millwork components. All wood should be dry and the machining or cutting completed before the application of this product.

STORAGE AND DISPOSAL

STORAGE: Store in a closed, properly labelled container in a cool place. If static generating conditions exist, provide necessary grounding and bonding. Keep containers closed when not in use.

DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticides, spray mixture, or residue is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

ACCEPTED
with COMMENTS
In EPA Letter # 100-10-001

MAR 18 1992

BEST AVAILABLE COPY

40001-27

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC
ANIMALS

DANGER

**CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE.
CAUSES BURNS. MAY BE FATAL IF SWALLOWED,
ABSORBED THROUGH SKIN, OR INHALED.**

Do not get in eyes, on skin, or on clothing. Wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Do not breathe mist or vapors. Wear goggles, face shield, or safety glasses. Wear protective clothing and rubber gloves. Wash thoroughly with soap and water after handling and before eating, drinking or smoking. Remove contaminated clothing and wash before reuse.

FIRST AID: For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash clothes before reuse. Get medical attention. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention.

ENVIRONMENTAL HAZARDS:

This product is toxic to fish and wildlife. Do not apply directly to any body of water. Do not contaminate water when disposing of equipment wash-waters.

This product is toxic to domestic animals. Treated sawdust and other wood wastes should be disposed of properly and should not come in contact with domestic animals or be used as mulch where it will come in contact with useful living plants. Care should be taken to prevent drip or spray from contacting ornamental shrubs, trees, grass and other desirable vegetation.

Vapors may cause injury if adequate ventilation is not insured. Do not use this product indoors, or any other confined areas, where the vapors may concentrate or migrate indoors and cause injury to plant or animal life.

PHYSICAL OR CHEMICAL HAZARDS. COMBUSTIBLE. DO NOT use, pour, spill or store near heat or open flame.

IN CASE OF FIRE: Use dry chemicals, foam, water fog or CO₂. Cool closed containers with water.

WARRANTY: We warrant this material to comply with our published specifications and to be of good merchantable quality and such as will regularly pass in the trade for goods within the description, and further warrant such goods to be fit for the normal purposes which goods are used. We assume no responsibility that the goods concerned in this contract are fit for any particular purpose for which they are being bought outside of the general purposes of goods of the description.

For Product Emergencies: 1-800-548-0489

BEST AVAILABLE COPY