

Hadre the Federal Interchinde, in federal and Brit at the fact contacted for the position thread under they. No. 100001-27

FOR INDUSTRIAL USE ONLY DIRECTIONS FOR USE

It is a violation of Federai law to use this product in a manner inconsistent with its labeling.

DILUTE BEFORE USING

Wear synthetic rubber gloves or plastic coated gloves in handling solutions and freshly treated lumber.

For the best results lumber should be treated immediately after it is sawn. A delay in treatment of 24 hours or more permits stain, mold and decay growth to start which requires a heavier treatment to achieve control of surface growth Delayed application and log borne infection result in Internal stain often under a bright surface. Lumber and logs should be totally immersed, or sprayed so as to ensure all surfaces are treated.

Freshly dipped or sprayed lumber should be protected from rain washing. Dip tanks and drip aprons must be roofed, paved and drained to prevent dilution and loss of the anti-stain solution. Anti-stain treatment concentrations must be geared to achieve protection of the thickest or most valuable item being treated. The concentration of the ready-to-use anti-stain solution must be adjusted to accommodate seasonal changes in the exposure and species being treated. Dip tanks and spray equipment must be properly maintained.

MIXING INSTRUCTIONS——For high pressure spray applications: Thoroughly mix one gallon of MP-1 Concentrate per 25 to 50 gallons of water. For dip applications: Thoroughly mix one gallon of MP-1 Concentrate per 40 to 300 gallons of water. In all cases, dilution levels will depend upon application methods, lumber species and conditions of lumber storage. Hills should conduct tests to determine treatment requirements for their individual needs. Contact Kop-Coat for further information. When using proportioning pumps for mixing, this product should be maintained at temperatures above 50 degrees F to prevent inaccurate mixing due to viscosity changes. Minor proportioning rate changes can be affected by changing the setting on the pump dial.

NOTE: With normal dip or spray application long term control of decay cannot be achieved. This product is intended to provide decay, mold and blue stain control during storage. Such control would not likely extend to the use site.

STORAGE AND DISPOSAL

STORAGE: Store in a closed, properly labeled container in a cool place If static generating conditions exist, provide necessary grounding and bonding. Keep containers closed when not in use.

DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or finsate is a inolation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA. Regional Office for guida.

CONTAINE A DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or incineration, or, if allowed by state and local authorities, by burning. If burned stay out of smoke

BEST AVAILABLE COPY



NP-1[®] Sapstain Control Chemical

U.S. Patent No. 4,950,685 and Foreign Patents

Aids in the control of blue stain, mold and decay of freshly cut lumber when properly used. Effective on softwoods including Douglas fir, White fir, Spruce, Hemlock, the Pines including both the Southern and Western Yellow Pines, Eastern and Western White Pines and many of the hardwoods.

KEEP OUT OF REACH OF CHILDREN

DANGER

See side panel for additional precautionary statements.

READ WARRANTY ON SIDE PANEL BEFORE BUYING OR USING. IF SUCH TERMS ARE NOT ACCEPTABLE, RETURN AT ONCE UNOPENED.

EPA Reg. No. 60061-27 EPA Est.60061 MQ-1

STATEMENTS OF PRACTICAL TREATMENT

IF IN EYES: Flush immediately with plenty of water. Get medical attention.

IF ON SKIN: Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Get medical attention.

IF IMMALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

IF SWALLGEED. Prink promptly a large quantity of wilk, egg whites, selatin solution, or, solid finese are not available, drink large quantities of water. Avoid alcohol. Get modical attention.

, SOTE TO PHYSICIAN. Probable mucosal damage may contraindicate use of gastric lavage.

Kop-Coat, Inc.
Protection Products Division

15137 Southwest Avenue, St. Louis, MO 63110 11 314/772-2200

: .NET CONTENTS

U.S. GALLONS

PRECAUTIONARY STATEMENT
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE. CAUSES BURNS. MAY BE FATAL IF SWALLOWED OR INHALED. HARMFUL IF ABSORBED THROUGH SKIN.

Do not get in eyes, on skin, or on clothing. Wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Do not breathe mist or vapors. Wear goggles, tace shield, or safety glasses. Wear protective clothing and rubber gloves. Wash thoroughly with soap and water after handling and before eating, drinking or smoking. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS:

This product is toxic to fish and wildlife. Do not apply directly to water, to areas where surface water is present, or to intertigal areas below the mean high water mark. Do not contaminate water by disposal of equipment washwaters.

This product is toxic to domestic animals. Treated sawdust and other wood wastes should be disposed of properly and should not come in contact with domestic animals or be used as mulch where it will come in contact with useful fiving plants. Care should be taken to prevent drip or spray from contacting ornamental shrubs, trees grass and other desirable vegetation.

Vapors may cause injury if adequate ventilation is not insured. Do not use this product indoors or in any other confined areas where the vapors may concentrate or migrate indoors and cause injury to plant or animal life.

PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE, DO NOT use, pour, spill or store near heat or open flame

IN CASE OF FIRE: Use dry chemicals, feam, water fog or CO2 Cool closed containers with water

WARRANTY: We warrant this material to comply with our published specifications and to be of good merchantable quality and such as will regularly pass in the trade for goods within the description, and further warrant such goods to be fit for the normal purposes which goods are used. We assume no responsibility that the goods concerned in this contract are fit for any particular purpose for which they are being bought outside of the general purposes of goods of the description.

For Product Emergencies: 1-800-\$48-0489.

PPD 1246 R06 0692