PRECAUTIONARY STATEMENT

HAZARDS TO HUMANS AND DOMESTIC ANIMALS DANGER

CORROSIVE, CAUSES IRREVERSIBLE EYE DAMAGE.
A CAUSES BURNS. MAY BE FATAL IF SWALLOWED OR
INHALED. HARMFUL IF ABSORBED THROUGH SKIN.

Do not get in eyes, on skin, or on clothing. Wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Do not breathe mist or vapors. Wear goggles, face shield, or safety glasses. Wear protective clothing and rubber gloves. Wash thoroughly with soap and water after handling and before eating, drinking or smoking. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS:

This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

This product is toxic to domestic animals. Treated sawdust and other wood wastes should be disposed of properly and should not come in contact with domestic animals or be used as mulch where it will come in contact with useful living plants. Care should be taken to prevent drip or spray from contacting ornamental shrubs, trees, grass and other desirable vegetation.

Vapors may cause injury if adequate ventilation is not insured. Do not use this product indoors or in any other confined areas where the vapors may concentrate or migrate indoors and cause injury to plant or animal life.

PHYSICAL OR CHEMICAL HAZARDS; COMBUSTIBLE. DO NOT use, pour, spill or store near heat or open flame.

IN CASE OF FIRE: Use dry chemicals, foam, water fog or ${\rm CO}_2$. Cool closed containers with water.

WARRANTY: We warrant this material to comply with our published specifications and to be of good merchantable quality and such as will regularly pass in the trade for goods within the description, and further warrant such goods to be fit for the normal purposes which goods are used. We assume no responsibility that the goods concerned in this contract are fit for any particular purpose for which they are being bought outside of the general purposes of goods of the description.

For Product Emergencies: 1-800-548-0489.

FOR INDUSTRIAL USE ONLY

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

DILUTE BEFORE USING

Wear synthetic rubber gloves or plastic coated gloves in handling solutions and freshly treated lumber.

For the best results lumber should be treated immediately after it is sawn. A delay in treatment of 24 hours or more permits stain, mold and decay growth to start which requires a heavier treatment to achieve control of surface growth. Delayed application and log borne infection result in internal stain often under a bright surface. Lumber and logs should be totally immersed or sprayed so as to ensure all surfaces are treated.

Freshly dipped or sprayed lumber should be protected from rain washing. Dip tanks and drip aprons must be roofed, paved and drained to prevent dilution and loss of the anti-stain solution. Anti-stain treatment concentrations must be geared to achieve protection of the thickest or most valuable item being treated. The concentration of the ready-to-use anti-stain solution must be adjusted to accommodate seasonal changes in the exposure and species being treated. Dip tanks and spray equipment must be properly maintained,

MIXING INSTRUCTIONS — For high pressure spray applications: Thoroughly mix one gallon of NP-1 Concentrate per 15 to 50 gallons of water. For dip applications: Thoroughly mix one gallon of NP-1 Concentrate per 40 to 300 gallons of water. In all cases, dilution levels will depend upon application methods, lumber species and conditions of lumber storage. Mills should conduct tests to determine treatment requirements for their individual needs. Contact Kop-Coat for further, information. When using proportioning pumps for mixing, this product should be maintained at temperatures above 50 degrees. F to prevent inaccurate mixing due to viscosity changes. Milnor proportioning rate changes can be affected by changing the setting on the pump dial.

NOTE: With normal dip or spray application long term control of decay cannot be achieved. This product is intended to provide decay, mold and blue stain control during storage. Such control would not likely extend to the use site.

STORAGE AND DISPOSAL

STORAGE: Store in a closed, properly labeled container in a cool place. If static generating conditions exist, provide necessary grounding and bonding. Keep containers closed when not in use.

DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

MAY 30 1997 NP-1® Sapstain St. der The Federal Insecticide, fund Gran Ontrol Chemical St. der The Federal Insecticide, fund Gran Ontrol Chemical St. des Constant of the Chemical

U.S. Patent No. 4,950,685 and Foreign Patents

Aids in the control of blue stain, mold and decay of freshly cut lumber when properly used. Effective on softwoods including Douglas fir, White fir, Spruce, Hemlock, the Pines including both the Southern and Western Yellow Pines, Eastern and Western White Pines and many of the hardwoods.

KEEP OUT OF REACH OF CHILDREN

DANGER

See side panel for additional precautionary statements.

READ WARRANTY ON SIDE PANEL BEFORE BUYING OR USING. IF SUCH TERMS ARE NOT ACCEPTABLE, RETURN AT ONCE UNOPENED.

EPA Reg. No. 60061-27 EPA Est60061-MO-1

CEPLES

ing No.

ACTIVE INGREDIENTS
Didecyl dimethyl
Ammonium Chloride.... 64.80%
3-lodo-2-Propynyl
Butyl Carbamate....... 7.60%
INERT INGREDIENTS... 27.60%
TOTAL 100.00%

STATEMENTS OF PRACTICAL TREATMENT

IF IN EYES: Flush immediately with plenty of water. Get medical attention.

IF ON SKIN: Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Get medical attention.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate use of gastric lavage.

Kop-Coat, Inc.
Protection Products Division
5137 Southwest Avenue, St. Louis, MO 63110
314/772-2200

NET CONTENTS

U.S. GALLONS

for

PPD 1246 RO8 0295