

PM 22

60061-28

pg 1 of 4

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

MAY 6 1992

Alan S. Ross
Kop-Coat, Inc.
3020 William Pitt Way
Pittsburgh, PA 15238

Dear Mr. Ross:

Subject: Woodtreat™ MB RTU/Wolman™ Clear Wood
Finish and Preservative
EPA Reg. No. 60061-28
Re: Labeling Amendments
Your submission dated May 30, 1991

The labeling referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable subject to the comments listed below. Please submit five (5) copies of your final printed labeling incorporating these changes before releasing your product for shipment. A stamped copy is enclosed for your records.

1. Delete the "General Classification" statement under "Directions For Use".
2. Please revise the statement "Do not apply directly to any body of water" to read "Do not apply directly to water, to areas where surface water is present or to intertidal areas below the mean high water mark."

Sincerely,

Cynthia Giles-Parker

Cynthia Giles-Parker
Product Manager (22)
Fungicide-Herbicide Branch
Registration Division (H7505C)

enclosure

BEST AVAILABLE COPY

CONCURRENCES

SYMBOL	H7505C	H7505C						
SURNAME	Cole	Soble						
DATE	1/29/92	4/30/92						

KEEPS SIDING BEAUTIFUL LONGER
PROTECTS WOOD AGAINST:

- Mildew discoloration and decay
- Water and ultraviolet damage

Preserves new wood look. Restores weathered wood.

WOLMAN® Clear Wood Finish and Preservative combines the Beauty of a durable penetrating clear oil finish with the Protection of a premium wood preservative system. Periodic single coat reapplications will keep wood protected and looking its natural best.

Use WOLMAN® Clear Wood Finish and Preservative on all high quality exterior wood such as cedar and redwood. Apply to siding, fencing, shakes and shingles, and other above ground structures where protection is desired. Not recommended for outdoor furniture. Exceeds Federal specification for water repellency TT-W-572B, paragraph 3.7

DIRECTIONS FOR USE:

GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SURFACE PREPARATION: ALL SURFACES SHOULD BE CLEAN, DRY AND FREE OF MILDEW. WOLMAN® Deck Brightener is recommended to prepare and renew discolored surfaces. WOLMAN® Clear Wood Finish and Preservative must be able to penetrate surface to perform properly.

APPLICATION: Mix thoroughly before use and stir occasionally during application. Do not thin or combine WOLMAN® Clear Wood Finish and Preservative with other products. Apply by sprayer (backbrush with grain), brush, pad, roller, or dip (3 minutes).

New Wood: To help keep new wood looking new, apply two wet-on-wet coats of this product as soon as possible. When first applied, the wood will darken to a rich, natural tone. Over time it will lighten but the protection will be maintained. When a light gray color appears it is time to recoat.

Weathered Wood: To help restore the original color to weathered wood first remove mildew and dirt, then apply two wet-on-wet coats of WOLMAN® Clear Wood Finish and Preservative. Do not allow the product to dry between coats. Apply second coat no later than 12 hours after the first coat.

GENERAL INFORMATION:

- Coverage - One gallon covers up to 200 square feet, one coat. Coverage varies with application and wood texture.
- Apply when outside temperatures are between 40° and 90°F and when 24 hours of precipitation-free weather is expected.
- Surface will be dry to the touch in 24-48 hours, depending upon temperature and humidity.
- Do not apply over paint or stain. Do not use a primer coat. Surface may be stained or painted after sufficient weathering to allow thorough penetration.
- Clean equipment with mineral spirits or paint thinner.
- To determine appearance, a sample brushout in an inconspicuous area is recommended.

Need help with Wolman® Protection Products?
Call: 1-800-556-7737

ACCEPTED
FEB 6 1992
6661-28

M

F1

DANGER
CAUSES EYE AND
VAPORS MAY BE
EPA Reg. No. 6006
KEEP OUT OF
1 U.S. G

BEST AVAILABLE COPY

Wolman

Siding, Shingles, Untreated Wood

Clear Wood Finish And Preservative

Mildew and UV Resistant • Water Repellent



**Preserves The Natural Wood Look
From The Wolman® Wood Protection People**

DANGER! HARMFUL OR FATAL IF SWALLOWED.
CAUSES EYE AND SKIN IRRITATION.
VAPORS MAY BE HARMFUL. COMBUSTIBLE.
EPA No. 60061-28 EPA Est. 60061-MO-1
KEEP OUT OF THE REACH OF CHILDREN.
1 U.S. Gallon (3.8 Liters)

See side panel for first aid and additional precautionary statements.
ACTIVE INGREDIENTS:
3-Iodo-2-Propynyl butyl carbonate..... 0.50%
INERT INGREDIENTS..... 99.50%
TOTAL..... 100.00%

This product contains petroleum distillates (mineral spirits).
VOC max 2.5 lbs/gal (300 g/l)

BEST AVAILABLE COPY

4 of 4

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS (AND DOMESTIC ANIMALS)

DANGER

HARMFUL IF SWALLOWED, INHALED, OR ABSORBED THROUGH SKIN. MAY CAUSE EYE AND SKIN IRRITATION.

Avoid contact with eyes, skin or clothing. Use of goggles and protective clothing (rubber gloves) when dipping and an approved respirator when spraying is recommended. Avoid breathing of vapors, mist or substantially saturated atmosphere. Use only in well ventilated areas. Keep containers closed when not in use. Do not take internally.

FIRST AID: For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash clothes before reuse. In case of eye contact, flush immediately with plenty of water for 15 minutes and get medical attention. If swallowed, CALL A PHYSICIAN IMMEDIATELY. DO NOT induce vomiting. If inhaled, remove to fresh air.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to any body of water. Do not contaminate water when disposing of equipment washwaters. This product is toxic to domestic animals. Treated sawdust and other wood wastes should be disposed of properly and should not come in contact with domestic animals or be used as mulch where it will come in contact with useful living plants. Care should be taken to prevent drop or spray from contacting ornamental shrubs, trees, grass and other desirable vegetation.

Vapors may cause injury if adequate ventilation is not insured. Do not use this product indoors, or any other confined areas, where the vapors may concentrate or migrate indoors and cause injury to plant or animal life.

PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE. DO NOT use, pour, spill, or store near heat or open flame.

IN CASE OF FIRE: Use dry chemicals, foam, water, fog, or CO₂. Cool closed containers with water.

STORAGE AND DISPOSAL

STORAGE: Store this product in its originally labeled container in a storage area located in a cool place. Keep container and freshly treated articles away from high temperature areas, sparks, fire, or open flame. If static generating conditions exist, provide necessary grounding and bonding. Keep this product separate from other pesticides during storage to prevent cross contamination of other pesticides, fertilizers, food and feed. Remove sources of ignition if this product is released or spilled. Confine area of spill and avoid breathing vapors. Ventilate area. Cover with absorbent material and place in approved containers for disposal using non-sparking tools.

PESTICIDE DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Limited Warranty: Kop-Coat will refund the purchase price to the original consumer if within one year this product is shown to be defective. Notify Kop-Coat Inc. 436 7th Avenue Pittsburgh, PA 15219, within sixty (60) days of learning of defect. KOP-COAT MAKES NO FURTHER WARRANTIES EXPRESSED OR IMPLIED INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OF MERCHANTABILITY WHICH EXTEND BEYOND THE DURATION OF THIS WRITTEN WARRANTY. Kop-Coat shall not be liable for any incidental or consequential damages. Some states do not allow limitations on how long any implied warranty lasts and/or limitation of incidental or consequential damages, so the above limitation and exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

statements.
..... 0.50%
..... 98.50%
..... 100.00%
(fta).

00 g/l)

BEST AVAILABLE COPY