



United States
Environmental Protection Agency
 Washington, DC 20460

Registration
 Amendment
 Other

OPP Identifier Number
225780

Application for Pesticide - Section I

1. Company/Product Number 60061-49	2. EPA Product Manager Marion Johnson	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Pettit Trinidad Antifouling 1275 Blue	PM# 31	
5. Name and Address of Applicant (Include ZIP Code) Kop-Coat, Inc. 436 Seventh Avenue Pittsburgh, PA 15219 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Notification of alternate brand name:
 Pettit Marine Paint Professional Coatings
 Trinidad 75 Antifouling - 1071 Lt. Blue

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes* <input checked="" type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	If "Yes" Unit Packaging wgt. No. per container		<input checked="" type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____
* Certification must be submitted		If "Yes" Package wgt. No. per container			
3. Location of Net Contents Information <input checked="" type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container 1 quart, 1 gallon		5. Location of Label Directions <input checked="" type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input checked="" type="checkbox"/> Lithograph Paper glued Stenciled <input type="checkbox"/> Other _____					

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name ALAN S. ROSS	Title VICE PRESIDENT	Telephone No. (Include Area Code) (412) 826-3387
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature <i>Alan S. Ross</i>	3. Title VICE PRESIDENT	
4. Typed Name ALAN S. ROSS	5. Date December 11, 1995	

7/8

50-394

1.13.75

363

PETTIT

marine  *pa*

PROFESSIONAL CO

TRINIDAD 75 ANTIFOULING

1071 LT BLU

DISCLAIMER. The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company, including surface preparation, proper application and environmental conditions. Therefore, Pettit Paint Company cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. Pettit Paint Company shall not under any circumstances be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Pettit Paint's option.

NET CONTENTS
1 GALLON (128 FL. OZ.)
3.785 LITERS

FOR PROFESSIONAL USE ONLY
KEEP OUT OF REACH OF CHILDREN.
WARNING! SEE BACK PANEL FOR
ADDITIONAL PRECAUTIONARY STATEMENTS.

KOP-COAT INC., PETTIT P

BEST AVAILABLE COPY

3043

TIT paint

COATINGS

D 75 LING BLUE

USE ONLY
CHILDREN.
K PANEL FOR
STATEMENTS.

This product contains
petroleum distillates.

E.P.A. EST. NO. 60061-NJ-2

TIT PAINT DIV.

TRINIDAD 75

PRODUCT DESCRIPTION: TRINIDAD 75 antifouling is a hard protective paint for use on boat bottoms. It can be applied over most aged hard antifouling coatings. Old soft antifouling paints should be removed for best adhesion.

PREPARATION OF SURFACE: The surface to be painted should be dry, clean and oil free. It should be properly prepared by solvent cleaning and sanding before any primers or paints are applied. Follow the recommended systems below. When sanding old antifouling paint, use a face mask to prevent the inhalation of sanding dust.

APPLICATION AND TEMPERATURE: TRINIDAD 75 can be applied by brush, roller or spray. The work should be done between 9:00 a.m. and 4:00 p.m. under good drying conditions. The temperature range of application is 40° to 90°F. Two coats should be applied for best antifouling protection.

PREPARATION OF PAINT: TRINIDAD 75 is heavily loaded with cuprous oxide. As a result of this loading there is a tendency for settling to occur especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all the pigment has been mixed in. If mixing is going to be done with a wooden paddle or an electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment; then remix the two parts together thoroughly.

THINNER: Use Pettit 12120 Brushing Thinner for thinning the TRINIDAD 75 on a warm windy day or for cleaning up equipment. Do not over thin TRINIDAD 75 or inadequate paint application will occur. Use Pettit 12121 Spraying Thinner for spray application.

DRY TIMES: Let the first coat of TRINIDAD 75 dry four hours minimum before applying the second coat. After the second coat is applied, let the paint dry at least eight hours or preferably overnight before immersing the boat. Under adverse drying conditions, let the boat dry overnight to make sure all the solvent is out of the paint film. Maximum dry time before launching is two months.

COVERAGE: TRINIDAD 75 covers approximately 400 square feet per gallon.

MAINTENANCE OF ANTIFOULING PAINT: No antifouling paint can be effective under all conditions of exposure. Man-made pollution and natural occurrences can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, silt, dirt, oil, brackish water and even electrolysis can ruin an antifouling paint. Therefore, we strongly suggest that the bottom of the boat be checked several times a month to make sure it is clean and that no growth is occurring. Lightly scrub the bottom with a soft brush to remove anything from the antifouling paint surface.

**DO NOT USE THIS PRODUCT ON
ALUMINUM HULLS AND OUTDRIVES.**

**NOTE. THIS PRODUCT CONTAINS A CHEMICAL
KNOWN TO THE STATE OF CALIFORNIA TO
CAUSE CANCER
PRODUCT EMERGENCIES
1-800-548-0489**

ACTIVE INGREDIENTS	
Cuprous Oxide	65.00 %
INERT	
INGREDIENTS	35.00 %
	100.00%
COPPER AS METALLIC	57.7 %
EPA Reg. No. 60061- 49	

PAINT SYSTEMS

FIBERGLASS: Wash the fiberglass with Pettit 12120 Brushing Thinner or 15095 Dewaxer to remove parting agent, grease and dirt. Sand thoroughly with 80 grit sandpaper to dull the glossy fiberglass surface. Rewash the sanded surface and then apply two coats of TRINIDAD 75. To skip the sanding operation after the hull has been washed, apply a coat of Pettit 6999 Sandless Primer. Then apply two coats of TRINIDAD 75.

BUSTERED GELCOAT: TRINIDAD 75 is compatible over most two part Epoxy Gelcoat Repair Systems. Refer to Pettit Technical Bulletins or consult the Pettit Technical Department for complete information on Gelcoat repair procedures.

BARE WOOD: Sand entire surface with 80 grit paper, wash clean with 12120 Brushing Thinner. Apply one coat of TRINIDAD 75 thinned 25% with Pettit 12120 Brushing Thinner allowing the thinned paint to penetrate the bare wood. Follow with two full strength coats of TRINIDAD 75 observing the recommended dry times between all three coats.

STEEL HULLS*, UNDERWATER METAL PARTS, LEAD KEELS: To remove old rust and scale from the metal surface, scrape, sandblast or wire brush. Wash the surface with Pettit 12120 Brushing Thinner to remove grease and dirt. Apply one coat of Pettit Metal Primer to bare metal and let dry two hours. Follow with two coats of Pettit 6462 Q.D. Zinc Chromate Primer and let dry two hours between coats and four hours before applying two coats of TRINIDAD 75.

PREVIOUSLY PAINTED SURFACES: If the previous coating is in good condition, lightly sand with 80 grit paper then solvent clean with 12120 Brushing Thinner to remove residue. Apply two finish coats of TRINIDAD 75. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using Pettit Paint & Varnish Remover 9030 for fiberglass; 9022 for wood and metal. Proceed with appropriate bare system as described above.

* This is a simple system for small areas. For a more advanced, professional system, please consult the Pettit Technical Department.

PRECAUTIONARY STATEMENTS: HAZARDOUS TO HUMANS AND DOMESTIC ANIMALS
WARNING: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe sanding dust, vapor or spray mist. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT: IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

IF IN EYES: Flush with plenty of water. Get medical attention. **IF ON SKIN:** Wash with plenty of soap and water. Get medical attention. **IF INHALED:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARD: COMBUSTIBLE! DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

DIRECTIONS FOR USE: It is a violation of federal law to use this product in a manner inconsistent with its labeling. **NOTE:** When product is used in confined areas or applied by spraying, wear a respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provision of 30 CFR 11.

GENERAL DESCRIPTION: TRINIDAD 75 is an antifouling protective coating resistant to algae, barnacles and other marine fouling.

STORAGE & DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Open burning is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinse is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your state Pesticide or Environmental Control Agency, or the Hazardous Waste representative of the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

BOROUGH OF ROCKAWAY, N.J. 07866

BEST AVAILABLE COPY