



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

June 28, 2017

Angie Custer  
Regulatory Affairs Specialist  
Kop-Coat, Inc.  
3040 William Pitt Way  
Pittsburgh, PA 15238

Subject: Notification per PRN 98-10 – To update Storage and Disposal language  
Product Name: Pettit Marine Paint Unepoxy Plus Antifouling Bottom Paint  
EPA Registration Number: 60061-66  
Application Date: March 13, 2017  
Decision Number: 527358

Dear Ms. Custer:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact Emilia Oiguenblik by phone at 703 347 0199, or via email at [Oiguenblik.emilia@epa.gov](mailto:Oiguenblik.emilia@epa.gov) or Eric Miederhoff by phone at 703 347 8028, or via email at [Miederhoff.eric@epa.gov](mailto:Miederhoff.eric@epa.gov)

Sincerely,

A handwritten signature in blue ink that reads "E. Miederhoff". The signature is written in a cursive style with a large, stylized initial "E".

Eric Miederhoff  
Product Manager 31  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

# PETTIT



## NOTIFICATION

60061-66  
The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

06/28/2017

# MARINE PAINT UNEPOXY PLUS

## ANTIFOULING BOTTOM PAINT

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company, including surface preparation, proper application and environmental conditions. Therefore, Pettit Paint Company cannot guarantee the product's suitability for your particular purpose of application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. Pettit Paint Company shall not under any circumstances be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product of Pettit Paint's option.



NET CONTENTS  
1 GALLON (128 FL. OZ.)  
3.785 LITERS

[1071 LIGHT BLUE, 1072 BLUE, 1076 RED]

KEEP OUT OF REACH OF CHILDREN.  
**WARNING**  
HARMFUL IF ABSORBED THROUGH SKIN.  
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

**ACTIVE INGREDIENT:**  
Cuprous Oxide\* (CAS# 1317-39-1) 55.60%  
**OTHER INGREDIENTS** 44.40%  
100.00%  
\*Metallic Copper Equivalent 49.37%

EPA EST. NO. 60061-NJ-2  
EPA Registration No. 60061-66

Contains petroleum distillates, xylene or xylene range aromatic solvents.

NOP-COAT, INC.  
36 PINE STREET  
ROCKAWAY, NJ 07866

**PRECAUTIONARY STATEMENTS**  
**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**  
WARNING: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Do not breathe vapors, spray mist or sanding dust. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.  
**Personal Protective Equipment (PPE):** Wear gloves, goggles, respirators and other handwear must wear the following: Protective footwear, such as shoes or a shoe shield; chemical resistant gloves such as Nitrile Rubber gloves greater than 14 mils thick, long sleeved shirt, long pants and shoes plus socks.  
When removing wetting paint by sanding or blasting, or applying new antifoulants paint, commercial users must wear a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-55A), or a canister approved for pesticides (NIOSH approval number prefix TC-16), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any N, R, P or HE prefilter. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for respirables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's contents. Do not reuse them.

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**  
Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.  
Users should remove clothing PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothes. Users should remove PPE immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing.  
Wash the outside of gloves before removing.

**USER SAFETY RECOMMENDATIONS**  
Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.  
Users should remove clothing PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothes. Users should remove PPE immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing.  
Wash the outside of gloves before removing.

**FIRST AID**

<b>IF SWALLOWED:</b>	<ul style="list-style-type: none"> <li>Call a poison control center or doctor immediately for treatment advice.</li> <li>Do not give any liquid to the person.</li> <li>Do not induce vomiting unless told to do so by a poison control center or doctor.</li> <li>Do not give anything by mouth to an unconscious person.</li> </ul>
<b>IF IN EYES:</b>	<ul style="list-style-type: none"> <li>Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li> <li>Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.</li> <li>Call a poison control center or doctor for treatment advice.</li> </ul>
<b>IF ON SKIN OR CLOTHING:</b>	<ul style="list-style-type: none"> <li>Take off contaminated clothing.</li> <li>Rinse skin immediately with plenty of water for 15 - 20 minutes.</li> <li>Call a poison control center or doctor for treatment advice.</li> </ul>
<b>IF INHALED:</b>	<ul style="list-style-type: none"> <li>Move person to fresh air.</li> <li>If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.</li> <li>Call a poison control center or doctor for further treatment advice.</li> </ul>

**HOT LINE NUMBER**  
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0409 for emergency medical treatment information.

**NOTE TO PHYSICIAN**  
Contains petroleum distillate. Vomiting may cause aspiration pneumonia. Probable mucosal damage may contraindicate the use of gastric lavage.

**ENVIRONMENTAL HAZARDS**  
This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**Physical or Chemical Hazards: Combustible.** Do not use or store near heat or open flame. Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO2 or dry chemical. Wear MSHA/NIOSH certified breathing equipment.

**STORAGE AND DISPOSAL**  
Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.  
**Pesticide Storage:** Store in a closed, properly labeled container in a cool place. Keep containers tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.  
**Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or residue is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

**Container Disposal:** Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

**It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.**  
**Product Description:** This product is a hard protective antifouling coating resistant to algae, barnacles and other marine and freshwater fouling organisms for use on boat bottoms. It may be applied over most aged hard antifouling coatings. Old soft antifouling paints should be removed for best adhesion. It may be applied on fiberglass boats with outboards or outdrives with no danger of electrolysis, provided the drive units are not coated themselves. This product is also suitable for all non-aluminum fastened boats.  
**Surface Preparation:** The surface to be painted should be dry, clean and free of any contaminants. It should be properly prepared by solvent cleaning and sanding before any primers or paints are applied. Follow the recommended systems below. When sanding old antifouling paint, always wear Personal Protective Equipment (PPE) as described above to prevent the inhalation of sanding dust.  
**Preparation of Paint:** This product is heavily loaded with cuprous oxide. As a result of this loading there is a tendency for settling to occur, especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all the pigment has been mixed in. Mixing is going to be done with a wooden paddle or an electric drill mixer; pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment. Then remix the two parts together thoroughly.  
**Application Temperature:** 40°F to 90°F.  
**Application Method:** Brush, roller or spray.  
**Thinner:** Thinning this product is not normally required. If thinning is necessary, use Pettit 120 Brushing Thinner for a smoother finish on especially warm and breezy days. Use Pettit 121 Spraying Thinner for spray application. Do not thin more than 10% by volume (1/2 ounce per gallon), or inadequate paint film thickness may result in premature erosion of the finish. Use either thinner for clean-up.  
**Coverage:** This product covers approximately 400 square feet per gallon when applied at 2 dry mil film thickness.  
**Number of Coats:** Two or three coats should be applied for best antifouling protection. Do not apply this product if rain or dew is expected before the surface has dried completely.  
**Dry Time:**  

To touch	15 minutes
2 hours	8 hours
24 hours	24 hours

The above dry times are minimums. This product may be recoated after the minimum times shown and launched up to 60 days after painting.  
**WOC:** Less than 500 gal as supplied.  
**Maintenance Of Antifouling Paint:** No antifouling paint can be effective under all conditions of exposure. Man-made pollution and natural occurrences can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, oil, dirt, brackish water and even electrolysis can ruin an antifouling paint. Therefore, we strongly suggest that the bottom of the boat be checked regularly to make sure it is clean and that no growth is occurring. The self-cleaning nature of the coating is most effective when the boat is used periodically. Sooty and residue should not be scrubbed or cleaned for the first six months in the water and at intervals of not less than 3 months thereafter.  
**SYSTEMS**  
Mix paint thoroughly to ensure toxicants are evenly dispersed throughout the can. All surfaces must be clean, dry and properly prepared prior to painting.  
**Compatibility:** This product may be applied over most aged hard antifouling coatings. Old soft antifouling paints must be completely removed before applying this product. Old topcoatings must be removed completely or sealed with Pettit 802 The Coat Primer before applying this product. The paint systems outlined below contain references to other Pettit products. Please read and understand the label and/or Technical Bulletin for these products as well to ensure that they are used properly.  
**Previously Painted Surfaces:** If the previous coating is in good condition thoroughly sand with 80 grit paper and wipe clean with a rag dampened with Pettit 120 Brushing Thinner to remove sanding residue. Apply two coats of this product observing the proper dry time. If the previous coating is soft or in poor condition, remove the bare surface by sanding or using Pettit Bare Preparation. All bare fiberglass, regardless of age, must be thoroughly cleaned and de-waxed with Pettit 802-Bleu Hull Bare Preparation. All bare fiberglass and de-waxed surfaces must be thoroughly cleaned and de-waxed with Pettit 802-Bleu Hull Bare Preparation or de-waxed several times with Pettit 055 De-waxer. Sand thoroughly with 80 grit sandpaper to dull, frosty finish and remove the sanded surface with 120 Brushing Thinner to remove sanding residue. Then apply two coats of the product, following application instructions.  
To eliminate the sanding operation, use methods as available:  
1.) Clean and de-wax the surface as described above, apply one very thin coat of 6998 Sep-Sep-Primer using 3/16" or less nap roller or brush apply. Consult the primer label for complete application and antifouling top-coating instructions.  
2.) Clean, de-wax and etch the surface with 802-Bleu Hull Surface Prep using a coarse ScotchBrite® pad in a swirling motion. Clean off all residue by rinsing or wiping off with fresh water. Apply one coat of Pettit Protect Epoxy Primer. Consult the primer label for complete application and antifouling instructions. Then apply two coats of this product.  
**Bare Wood:** Sand the entire surface with 80 grit production paper and wipe clean with a rag dampened with 120 Brushing Thinner. Apply a coat of this product thinned 20% with 120 Brushing Thinner to penetrate and seal the wood. Fill any open seams with Pettit Seam Compound and allow to dry overnight. Apply two full coats of this product observing the proper dry times.  
**Steel Hulls, Underwater Metal Parts and Keels:** For clean hulls and metal keels, consult Pettit Technical Bulletin TB421 High Build Epoxy Primer for complete priming instructions or consult the Pettit Technical Department or your local Pettit representative. For underwater metal parts, consult Technical Bulletin TB112 Underwater Running Gear Finishing Specification for complete priming and application details.  
**All Other Substrates:** Please go to [www.pettit.com](http://www.pettit.com) and consult the product data sheet.  
**DO NOT USE THIS PRODUCT ON ALUMINUM HULLS OR OUTDRIVES**  
**Warnings:** We warrant this material to comply with our published specifications. Since the use of this material is beyond our control, we disclaim responsibility for its handling, use, storage, the results obtained or any injury or damage of any nature resulting therefrom.  
**REGULATORY INFORMATION**  
NOTICE: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.  
**REGULATORY INFORMATION**  
REGULATORY INFORMATION

REGULATORY INFORMATION

Manufactured in the U.S.A. P3408 GA-07/15