



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

November 19, 2019

Sandy Lea  
Pesticide Registrar  
Kop-Coat, Inc.  
36 Pine Street  
Rockaway, NJ 07866

Subject: Label Amendment – Update directions for use  
Product Name: Pettit Marine Paint Unepoxy Plus Antifouling Bottom Paint  
EPA Registration Number: 60061-66  
Application Date: August 12, 2019  
Decision Number: 554258

Dear Mr. Lea:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. “To distribute or sell” is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance

Page 2 of 2  
EPA Reg. No. 60061-66  
Decision No. 554258

with FIFRA section 6. If you have any questions, please contact Mohammad Alavi by phone at (703) 347-0522, or via email at [Alavi.mohammad@epa.gov](mailto:Alavi.mohammad@epa.gov).

Sincerely,



Eric Miederhoff  
Product Manager 31  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs


Enclosure



# MARINE PAINT UNEPOXY PLUS


## ANTIFOULING BOTTOM PAINT

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company, including surface preparation, proper application and environmental conditions. Therefore, Pettit Paint Company cannot guarantee the product's suitability for your particular purpose of application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. Pettit Paint Company shall not under any circumstances be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Pettit Paint's option.



Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 60061-66

[1071 LIGHT BLUE, 1072 BLUE, 1074 BLUE, 1076 RED]



NET CONTENTS  
1 GALLON (128 FL. OZ.)  
3.785 LITERS

KEEP OUT OF REACH OF CHILDREN.  
**WARNING**  
HARMFUL IF ABSORBED THROUGH SKIN.  
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

ACTIVE INGREDIENT:  
Cuprous Oxide\* (CAS# 1317-39-1) 55.60%  
OTHER INGREDIENTS 44.40%  
100.00%  
\*Metallic Copper Equivalent 49.37%

EPA EST. No. 60061-NJ-2  
EPA Registration No. 60061-66

Contains petroleum distillates, xylene or xylene range aromatic solvents.

NOP-COAT, INC.  
36 PINE STREET  
ROCKAWAY, NJ 07866

**PRECAUTIONARY STATEMENTS**  
**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**  
**WARNING:** Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Do not breathe vapors, spray mists or sand/dust. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.  
**Personal Protective Equipment (PPE):** Wear gloves, goggles, and other hand/eye protection. Use the following: Protective eyewear, such as goggles or a face shield, chemical resistant gloves such as Nitrile Rubber Gloves greater than 14 mil thickness, long pants and shoes plus socks. While removing existing paint by sanding or blasting, or applying new antifouling paint, users must wear a minimum of a half face NIOSH approved respirator (TC-54A) with organic vapor cartridges with any R or P combination filter. Higher level respirators that are NIOSH approved for organic vapors and particulates that contain oil can also be used. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Discard clothing and other absorbent material that has been drenched or heavily contaminated with the product's concentrate. Do not reuse them.

**USER SAFETY RECOMMENDATIONS**  
Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing/PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing. Wash the outside of gloves before removing.

FIRST AID	
<b>IF IN EYES:</b>	<ul style="list-style-type: none"> <li>Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li> <li>Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.</li> <li>Call a poison control center or doctor for treatment advice.</li> </ul>
<b>IF ON SKIN OR CLOTHING:</b>	<ul style="list-style-type: none"> <li>Take off contaminated clothing.</li> <li>Rinse skin immediately with plenty of water for 15 - 20 minutes.</li> <li>Call a poison control center or doctor for treatment advice.</li> </ul>
<b>IF INHALED:</b>	<ul style="list-style-type: none"> <li>Move person to fresh air.</li> <li>If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.</li> <li>Call a poison control center or doctor for further treatment advice.</li> <li>Call a poison control center or doctor immediately for treatment advice.</li> <li>Do not give any liquid to the person.</li> <li>Do not induce vomiting unless told to do so by a poison control center or doctor.</li> <li>Do not get anything by mouth to an unconscious person.</li> </ul>
<b>IF SWALLOWED:</b>	<ul style="list-style-type: none"> <li>Do not induce vomiting unless told to do so by a poison control center or doctor.</li> <li>Do not get anything by mouth to an unconscious person.</li> </ul>

**HOT LINE NUMBER**  
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-545-6625 for emergency medical treatment information.

**NOTE TO PHYSICIAN**  
Contains petroleum distillates. Vomiting may cause aspiration/pneumonia. Probable mucosal damage may contraindicate these use of gastric lavage.

**ENVIRONMENTAL HAZARDS**  
This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during part removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.  
Physical or Chemical Hazards: Combustible. Do not use or store near heat or open flame. Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO2 or dry chemical. Wear MS&H/ANSI certified breathing equipment.

**STORAGE AND DISPOSAL**  
Do not contaminate water, food, or feed by storage or disposal. Open burning is prohibited.  
Pesticide Storage: Store in a closed, properly labeled container in a cool place. Keep containers tight and upright to prevent leakage. Keep containers closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.  
Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixtures or residuals is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.  
Container Disposal: Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

**DIRECTIONS FOR USE**  
It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.  
Product Description: This product is a hard protective antifouling resistant to algae, barnacles and other marine and freshwater fouling organisms for use on boat bottoms. It may be applied over most aged hard antifouling coatings. Old soft antifouling paints should be removed for best adhesion. It may be applied on fiberglass boats with outboard or outdrives with no danger of electrolysis, provided the drive units are not coated themselves. This product is also suitable for aluminum hulls and rudders.

**Surface Preparation:** The surface to be painted should be dry, clean and free of any contaminants. It should be properly prepared by solvent cleaning and sanding before any primers or paints are applied. Follow the recommended systems below. When sanding old antifouling paint, always wear Personal Protective Equipment (PPE) as described above to prevent the inhalation of sand/dust.  
**Preparation of Paint:** This product is heavily loaded with cuprous oxide. As a result of this loading there is a tendency for settling to occur, especially if the paint has been on the shelf for several months. It is necessary to thoroughly stir the paint before using. If possible, shake the can of paint on a mechanical paint shaker. Before using, check the sides and bottom of the can to make sure all the pigment has been moved in. If mixing is going to be done with a wooden paddle or an electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment. Then return the two parts together thoroughly.

**Application Temperature:** 40°F to 90°F  
**Application Method:** Brush, roller or spray  
**Thinner:** Thinner for this product is not normally required. If thinning is necessary, use Pettit 120 Brushing Thinner for a smoother finish on especially warm and breezy days. Use Pettit 121 Spraying Thinner for spray application. Do not thin more than 10% by volume (15 ounces per gallon), or inadequate paint film thickness may result in premature erosion of the finish. Use either thinner for clean-up.  
**Coverage:** This product covers approximately 400 square feet per gallon when applied at 2 dry mil film thickness.  
**Number of Coats:** Two coats should be applied for best antifouling protection. Do not apply this product if rain or dew is expected before the surface has dried completely.

**Dry Times:**

	To touch	To launch
70°F	2 hours	6 hours
75°F	4 hours	8 hours
80°F	6 hours	24 hours

The above dry times are minimums. The product may be recoated after the minimum times shown and launched up to 90 days after painting.

**Maintenance of Antifouling Paint:** No antifouling paint can be effective under all conditions of exposure. Man-made pollution and natural occurrence can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, salt, dirt, oil, kerosene and even electrolysis can cause an antifouling paint. Therefore, we strongly suggest that the bottom of the boat be checked regularly to make sure it is clean and that no growth is occurring. The self-cleaning nature of the coating is most effective when the boat is used periodically. Boats and vessels should not be stored or cleaned for the first six months in the water and at intervals of not less than 3 months thereafter.

**SYSTEMS**  
Mix paint thoroughly to ensure bicarb is evenly dispersed throughout the can. All surfaces must be clean, dry and properly prepared prior to coating.  
Compatibility: The product may be applied over most aged hard antifouling coatings. Old soft antifouling paints must be completely removed before applying this product. Old topcoats must be removed completely or sanded with Pettit 6021 The Coat Primer before applying this product. The paint systems outlined below contain references to other Pettit products. Please read and understand the label and Technical Bulletin for these products as well to ensure that they are used properly.  
Previously Painted Surfaces: If the previous coating is in good condition thoroughly sand with 80 grit paper and wipe clean with a rag dampened with Pettit 120 Brushing Thinner to remove sanding media. Apply two coats of this product allowing the proper dry times. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using paint and varnish remover. Proceed with the appropriate bare system as described below.  
Bare Fiberglass Surface: Prep or de-wax several times with Pettit 0951 Dewaxer. Sand thoroughly with 80 grit sandpaper to a dull, frosty finish and rewash the sanded surface with 120 Brushing Thinner to remove sanding residue. Then apply two coats of this product, following application instructions. To eliminate the sanding operation, clean, de-wax and etch the surface with 52 Bio-Blue Hull Surface Prep using a coarse Scotchbrite® pad. Clean off all residue by rinsing or wiping off with fresh water. Apply one coat of Pettit Protect Epoxy Primer 47004701. Consult the primer labels for complete application and antifouling top-coating instructions. Then apply two coats of this product.  
Bare Wood: Sand the entire surface with 80 grit production paper and wipe clean with a rag dampened with 120 Brushing Thinner. Apply a coat of this product then 25% with 120 Brushing Thinner to penetrate and seal the wood. Fill any open areas with Pettit Seam Compound and allow to dry overnight. Apply two full coats of this product allowing the proper dry times.  
Steel Hulls, Underwater Metal Parts and Keels: For steel hulls and metal keels, consult Pettit Technical Bulletin 15431 High Build Epoxy Primer for complete priming instructions or consult the Pettit Technical Department or your local Pettit representative. For underwater metal parts, consult Technical Bulletin 16112 Underwater Running Gear Fitting Specification for complete priming application details.  
All Other Substrates: Please go to www.pettit.com and consult the product data sheet.

**Warranty:** We guarantee this material to comply with our published specifications. Since the use of this material is beyond our control, we disclaim responsibility for its handling, use, storage, the results obtained or any injury or damage of any nature resulting thereon.  
**Medical Emergencies:** 1-800-545-6625    **PRODUCT INFORMATION:** 1-800-221-4466 or [WWW.PETTIT.COM](http://WWW.PETTIT.COM)  
Manufactured in the U.S.A.    P3408 GA-07/15