

**UNITED STATES ENVIRONMENTAL PROTECTION AGENCY**

WASHINGTON, D.C. 20460

NOV 13 2003

OFFICE OF
PREVENTION, PESTICIDES
AND TOXIC SUBSTANCES

Ms. Kim Treloar
Product Registration Specialist for,
3020 William Pitt Way
Pittsburgh, PA 15238

Subject: Pettit Marine Paint Anti-Fouling 1933 Copper Bronze Color
EPA Registration Number 60061-86
Your Amendment Dated November 11th, 2003
EPA Received Date November 12th, 2003

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), as amended, to update the product labeling as per PR Notice 2001-1, is acceptable.

A stamped copy of the labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Karen M. Leavy-Munk at (703)-308-6237.

Sincerely,

A handwritten signature in cursive script that reads "M Swindell".

Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobial Division(7510C)

2/2

PETTIT

marine paint

ACCEPTED
DEC 04 2003
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 60061-56

ANTIFOULING

1933
COPPER BRONZE COLOR

COMMERCIAL AND NON-COMMERCIAL USE
KEEP OUT OF REACH OF CHILDREN.

WARNING

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

ACTIVE INGREDIENT:
Cuprous Oxide 33.26%
OTHER INGREDIENTS 66.74%
100.00%
COPPER AS METALLIC ... 29.54%

EPA Reg. No. 60061-56
EPA Est. No. 60061-01-2
This product contains petroleum distillates.



KOP-CON, INC.
PETTIT PAINT DIV.
ROCKAWAY, NJ 07866
An **RPM** Company

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: May be fatal if swallowed or inhaled. Do not breathe vapors, spray mist or sanding dust. Wear a MSHA/NIOSH certified mask or pesticide respirator. Remove contaminated clothing and wash clothing before reuse. Causes moderate eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. Wash thoroughly with soap and water after handling.

NOTE: When this product is used in confined areas or while spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Safety Health Administration and the National Institute for Occupational Safety and Health.

FIRST AID	
IF SWALLOWED:	<ul style="list-style-type: none"> Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.
IF IN EYES:	<ul style="list-style-type: none"> Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
IF ON SKIN OR CLOTHING:	<ul style="list-style-type: none"> Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
IF INHALED:	<ul style="list-style-type: none"> Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Contains petroleum distillate - vomiting may cause aspiration pneumonia.	

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of EPA.

PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE! Do not use or store near heat or open flame.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. **PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative of the nearest EPA Regional Office for guidance. **CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

NOTICE! THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. **Product Description:** This product is a hard protective antifouling paint for use on boat bottoms in both fresh and saltwater. It is resistant to barnacles, tubeworms, algae and other fouling organisms. This product may be applied on fiberglass, wood or properly primed steel boats. It is suitable for all non-aluminum trailer boats. This product is for use on boat bottoms only. **Surface Preparation:** The surface to be painted should be dry, clean and free of any contaminants. It should be properly prepared by solvent cleaning and sanding before any primers or paints are applied. Follow the recommended systems below. When sanding old antifouling paint, always use a face mask to prevent the inhalation of sanding dust.

Application between 40°F completely. Preparation to occur before using. bottom of the paddle or an 1 mix in any set. Thinner: 11 smoother finish. Dry Times: 30 70 50 The above dry to 60 days after. Coverage: thickness. VOC: Less than. Maintenance: Manmade pollutants, suggest that. Lightly scrub nature of the

Mix paint thoroughly and properly. Compatibility must be confirmed with Pettit 66. other Pettit products. Previously used then solvent previous coat removed. Pre-sealed with Pettit Bare Fiber Dewaxer or sanded surface coats of this long term ad fiberglass then follow careful product. Bare Wood 9677 Tie-Coat Bare Steel Pettit Techn complete, an over the epoxy coat of epoxy clean before underwater Warranty beyond our damage of MEDICAL PRODUCT