

PM-31

Reg # 60061-87

198 ✓

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (75-767) WASHINGTON, DC 20460	EPA REGISTRATION NO. 60061-87	DATE OF ISSUANCE NOV 01 1995
	TERM OF ISSUANCE	
NOTICE OF PESTICIDE: <input type="checkbox"/> REGISTRATION <input type="checkbox"/> REREГИSTRATION (Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)	NAME OF PESTICIDE PRODUCT Woolsey Hydrocoat Waterbased Antifouling 600 Blue	
NAME AND ADDRESS OF REGISTRANT (Include ZIP code)		
Kop-Coat, Inc. 436 Seventh Avenue Pittsburgh, PA 15219		
NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.		
On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.		
A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.		
Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.		
This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:		
1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.		
2. Make the labeling changes listed below before you release the product for shipment:		
a. Add the phrase "EPA Registration No. 60061-87".		
b. Delete the exclamation point which appears next to the heading: KEEP OUT OF REACH OF CHILDREN. (center panel).		
c. Include the degree symbols for all the temperatures as declared on the labels.		
<input type="checkbox"/> ATTACHMENT IS APPLICABLE		
SIGNATURE OF APPROVING OFFICIAL		DATE

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

29 8

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

Submit one (1) copy of the final printed label prior to release of the product for shipment.

A stamped copy of the label is enclosed for your records.

Sincerely,


Marion Johnson  
Product Manager (31)  
Antimicrobial Program Branch  
Registration Division (7505C)

Enclosures

CONCURRENCES							
SYMBOL							
SURNAME							
DATE							

365


# WOOD



HYDROCO  
WATERBASED AM  
600 BLU

NET CONTENTS  
**1 gallon (U.S.)**  
**3.785 liters**

ACTIVE INGREDIENT: Cuprous Oxide  
INERT INGREDIENTS:  
EPA Est. No. 60061-NJ-2  
EPA Registration No. 60061-



**BEST AVAILABLE COP**

Hydrocoat Water Based Antifouling is an antifouling protective coating resistant to algae, barnacles and other marine and freshwater fouling organisms. The high technology, waterbased resins used in Hydrocoat make the product a state of the art antifouling paint that withstands frequent trailering, beaching and launching while offering excellent antifouling protection. Hydrocoat contains Teflon, resulting in an easily burnished, slick film for maximum hull speed. Hydrocoat is for boats and vessels only.

#### DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

#### PREPARATION OF SURFACE

The surface to be painted must be clean, dry and free of any contamination or foreign matter. Prepare the surface by sanding thoroughly and solvent cleaning to remove sanding residue. When sanding old antifouling paints, use a dust mask to prevent the inhalation of sanding dust.

#### APPLICATION AND TEMPERATURE

Hydrocoat can be applied by brush, roller or spray. When brushing, use a good quality synthetic (nylon) bristle brush. Flow the product on, then brush it out. When rolling, use a short nap roller. If spraying, thin with water up to 10% if necessary. Otherwise, thinning is not recommended. Two coats are recommended for best performance. Do not apply at temperatures below 50 F.

#### PREPARATION OF PAINT

Hydrocoat contains cuprous oxide. As a result, there is a tendency for settling to occur, especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. A mechanical paint shaker will do the fastest, most thorough job of mixing. If mixing is to be done with a wooden paddle or electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment. Then remix the two parts together thoroughly. Regardless of mixing method, check the sides and bottom of the can before and during use to make sure all pigments and toxicants are thoroughly mixed.

698

APPROVED  
with 100%  
in 11/1/95

NOV 01 1995

**DRY TIMES**

Use the recommended dry times shown below as a guide.

	<u>To Recoat (min.)</u>	<u>To Launch (min.)</u>
50 F	4 Hours	48 Hours
70 F	2 Hours	16 Hours
90 F	1 Hour	12 Hours

Under the  
Fuselage  
Approved  
60061-87

Remember, this is only a guide. Dry times will vary with environmental conditions. If unsure of the dry time, it is safer to launch later rather than earlier. Maximum dry time before launching is thirty days.

**COVERAGE**

Hydrocoat will cover approximately 400 sq. ft. per gallon.

**CLEAN-UP**

Use clean water for cleaning equipment.

**MAINTENANCE OF ANTIFOULING PAINT**

No antifouling paint can be effective under all conditions of exposure. Man-made pollution and natural occurrences can adversely affect antifouling paint performance. Extremely hot and cold water temperatures, silt, dirt, oil, brackish water and even electrolysis can ruin an antifouling paint. Therefore, we strongly suggest that the bottom of the boat be checked several times a month to make sure it is clean and that no growth is occurring. Lightly scrub the bottom with a soft brush to remove anything from the antifouling paint surface. Scrubbing is particularly important with boats that are idle for extended periods of time. The self cleaning nature of the coating is most effective when the boat is used periodically.

**PAINT SYSTEMS**

Previously Painted Surfaces: To paint old, hard antifouling, Teflon based antifouling, or old tin copolymer antifouling, sand thoroughly with 80 grit sandpaper and wipe the surface to remove sanding residue with a damp rag. Then apply two coats of Hydrocoat. Traditional, soft antifouling must be removed before applying.

Old paint in poor condition (flaking, peeling, cracking, etc.) must be removed to the bare surface by sanding or using an appropriate paint and varnish remover. Then follow the appropriate bare system shown below.

Bare Fiberglass: Wash the fiberglass thoroughly with Woolsey 624 Dewaxer, changing rags frequently to ensure removal of parting agents, wax, grease and dirt. Sand thoroughly with 80 grit sandpaper to a dull frosty finish. Rewash with 624 Dewaxer to remove sanding residue and then apply two coats of Hydrocoat.

798  
7

To avoid the tedium of sanding, wash the fiberglass TWICE with 624 Dewaxer, then apply one thin coat of Woolsey 749 Sandnomore Primer. Let dry until tacky to the touch (usually 30-90 mins. depending on temperature and humidity) and then apply the first coat of Hydrocoat. Remember, do not let the Sandnomore Primer dry hard.

Bare Wood: Bare wooden hulls should be thoroughly sanded with 80 grit sandpaper and then wipe clean of sanding residue using a slightly damp, clean rag. Thin the first coat of Hydrocoat 10% with fresh water and apply. Let dry overnight and apply two additional coats at full body, following recommended dry times.

Bare Steel: Sandblast or disc sand with coarse grit sandpaper to a clean, bright surface. Use compressed air or a clean brush to remove residue. Apply two coats of Woolsey 340 Gold Primer. Consult the individual product tech sheets for detailed application instructions. Follow with two coats of Hydrocoat.

DO NOT USE THIS PRODUCT ON ALUMINUM HULLS OR OUTDRIVES

STORAGE & DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide, spray mixture or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent) and dispose of in an approved landfill. Consult Federal, State, or local disposal authorities for approved alternative procedures.

ACCEPTED  
with COPIES IN  
In EPA Lab

NOV 01 1995

UNITED STATES  
FEDERAL GOVERNMENT  
NOV 01 1995  
60061-87

898

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapors, spray mist or sanding dust. While spraying and/or sanding boat surfaces, wear a MSHA/NIOSH certified mask or respirator. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

IN EYES: Flush with plenty of water and get medical attention.

ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARDS: Material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes or allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS:

Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires blanket flames with foam, CO<sub>2</sub> or dry chemical. Wear MSHA/NIOSH certified breathing equipment.

NOV 01 1995  
Under the provisions of the  
Federal Insecticide, Fungicide,  
and Rodenticide Act  
registered under E.P.A. Reg. No. 60061-87

MF6. By KOR-COAT, INC. WOOLSEY MARINE UNIT  
ROCKAWAY, NJ 07866

MEDICAL EMERGENCIES 1-800-548-0489