3. goggles or face shield

4. chemical-resistant gloves (such as barrier laminate, nitrile rubber, neoprene rubber and viton)

Follow manufacturers' instructions for cleaning/maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

## USER SAFETY RECOMMENDATIONS

#### Users should:

- · Wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.
- Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.
- Remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly,

## **ENVIRONMENTAL HAZARDS:**

This pesticide is toxic to fish. Do not apply directly to any body of water or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters or rinsate. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other water unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

#### WARRANTY

We warrant this material to comply with our published specifications and to be of good merchantable quality and such as will regularly pass in the trade for goods within the description, and further warrant such goods to be fit for the normal purposes which goods are used. We assume no responsibility that the goods concerned in this contract are fit for any particular purpose for which they are being bought outside of the general purposes of goods of the description.

"RPM"

ACCEPTED
FEB 2 6 2002

KOP-COAT SSCC-3359 Sap Stain Control

CONCENTRATE

Before Using, Read Directions Under Dilution Ratio

**KEEP OUT OF REACH OF CHILDREN** 

WARNING

See side panel for additional precautionary statements.

3-lodo-2-Propynyl

FIRST AID

minutes, then continue rinsing eye.

for 15-20 minutes.

**ACTIVE INGREDIENTS** 

. Hold eve open and rinse slowly and cently with water

Remove contact lenses, if present, after the first 5

Butyl Carbamate ......4.00%

INERT INGREDIENTS...... 96.00%

TOTAL......100.00%

# It is a violation of Federal law to use this product in a manner inconsistent with its

#### GENERAL PRECAUTIONS AND RESTRICTIONS:

FOR INDUSTRIAL USE ONLY

**DILUTE BEFORE USING** 

labeling.

Do not apply this product in a way that will contact workers or other persons.

Apply this product only as specified on this label.

Wood treated with this product is intended only for exterior use.

Wear rubber gloves and protective clothing when handling freshly treated lumber.

#### GENERAL INFORMATION:

Description: SSCC-3359 Sap Stain Control is a liquid concentrate containing an effective funcicide for the control of sap stain and surface staining funci that cause discoloration and staining of freshly sawn lumber, SSCC-3359 Sap Stain Control is an aqueous solution which may be applied to dimensional lumber, plywood and particle board to prevent surface mold growth.

DIRECTIONS FOR USE

Dilution Ratio: SSCC-3359 Sap Stain Control is a concentrate dilutable with water. For lumber 2" or less in thickness, use 1 gallon of Concentrate per 150 gallons of water to protect against sap staining organisms during protected storage periods. For lumber thicker than 2" or where temperature and humidity conditions promote severe sap stain, use 1 gallon of concentrate per 100 gallons of water, or 1 gallon per 75 gallons of water. For spray systems use 1 gallon of concentrate per 10 to100 gallons of water.

#### APPLICATION INSTRUCTIONS:

Application: Flood spray or dip the freshly sawn clean lumber to be treated in SSCC-3359 Sap Stain Control solution within 24 hours after cutting. A dip of 15 seconds or more is sufficient. If not treated within 24 hours, stain may occur.

Lumber should be totally immersed or sprayed to insure treatment. Tanks should be covered by a roof to prevent the addition of rain water and consequent dilution of the solution. Vats and spray equipment should be cleaned regularly to remove sawdust and other debris. Freshly treated lumber should not be exposed to water. Store in protected area from rain and stack properly for best results.

Clean Up: Use water to clean immersion tanks, spray equipment and surrounding area. Soapy water may be required to remove SSCC-3359 Sap Stain Control from floors and equipment.

#### STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Pesticide Storage: Store in a closed, properly labeled container in a cool place. It static generating conditions exist, provide necessary grounding and bonding. Keep containers closed when

Pesticide Disposal: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Container Disposal: Triple rinse (or equivalent), then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

### PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE. DO NOT use, pour, spill or store near heat or open flame

 Call a poison control center or doctor for treatment advici- Call poison control center or doctor immediately for SWALLOWED: treatment advice. Have person sip a class of water if able to swallow. . Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious persor IF ON SKIN · Take off contaminated clothing. OR ON • Rinse skin immediately with plenty of water for 15-20 **CLOTHING:** . Call a poison control center or doctor for treatment advice. IF INHALED: · Move person to fresh air. If person is not breathing, call 911 or an ambulance. then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice. Have the product container or label with you when calling a poison control center or doctor, or going for treatment. In case of emergency call toll free: 1-800-548-0489.

use of gastric lavage.

Kop-Coat, Inc. **Protection Products Division** 5137 Southwest Avenue, St. Louis, MO 63110 314/772-2200

Probable mucosal damage may contraindicate the

**NET CONTENTS** 

NOTE TO

PHYSICIAN:

Read Warranty On Side Panel

Terms Are Not Acceptable.

Return At Once Unopened.

IF IN EYES

EPA Reg. No. 60061-88

EPA Est. No. 60061 -MO- 1

Before Buving Or Using, If Such

U.S. GALLONS

a

1000

,0061

01

60061-88