

60061-94

8-27-2003

1/4



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Program
Registration Division (H7505C)
401 "M" St., S.W.
Washington, D.C. 20460

EPA Reg. Number:

60061-94

Date of Issuance:

AUG 27 2003

NOTICE OF PESTICIDE:
 X Registration
 Reregistration

Term of Issuance: Expiration
Date 01/15/04

Name of Pesticide Product:

Pettit Marine Paint
Ultima SR Biocide
Antifouling

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Kop-Coat, Inc.
436 Seventh Avenue
Pittsburgh, PA 15219

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency request all registrants of similar product to submit such data; and submit acceptable response required for reregistration of your product under FIFRA section 4.

This product was first granted a time limited registration subject to our completion of an environmental risk assessment. We have completed our risk assessment and find we have concerns regarding the potential for Irgarol to impact aquatic plants, especially seagrass beds which are important as a nursery area and habitat for higher order species. We are concern that Irgarol is showing a trend to be an environmental problem. In order to allow you time to address our concerns we are extending this time limited registration to January 15, 2004. You were provided a copy of our risk assessment with a letter dated August 20, 2003.

Signature of Approving Official:

Marshall Swindell, *M Swindell*
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510C)

Date:

AUG 27 2003


2/4

2. This conditional registration will expire automatically on January 15, 2004. If you fail to satisfy the conditions imposed in the registration, EPA may issue a Notice To Cancel under Section 6(e) of FIFRA.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510C)

Enclosure

7 X 50-474-D 10/24/00

ACCEPTED
with COMMENTS
EPA Letter Dated:

AUG 27 2003

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

60061-94
AUG 27 2003

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company, including surface preparation, proper application and environmental conditions. Therefore, Pettit Paint Company cannot guarantee this product's suitability for your particular purpose of application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. Pettit Paint Company shall not under any circumstances be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Pettit Paint's option.

PETTIT
marine paint

Ultima^{SR}

**ABLATIVE DUAL BIOCIDES
ANTIFOULING BOTTOM PAINT**

- Slime resistant.
- High copper content.
- Multi-season technology.
- Self-polishing.
- Reduces paint build-up through controlled erosion.
- Excellent for fiberglass, wood & steel boats.

**COMMERCIAL AND NON-COMMERCIAL USE
KEEP OUT OF REACH OF CHILDREN.**

WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.


**NET CONTENTS
1 GALLON (128 FL. OZ.)
3.785 LITERS**

h/c

ACCEPTED
With COMMENTS
EPA Letter Dated:

AUG 27 2003
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the Pesticide Act as
registered under EPA Reg. No.
01061-94

- ACTIVE INGREDIENTS:**
- Cuprous Oxide 60.0%
 - N-Cyclopropyl-N(1,1-dimethylethyl)-6-(methylthio)-1,3,5-triazine-2,4-diamine 2.0%
- INERT INGREDIENTS**
- 38.0%
 - 100.0%
 - 53.3%
- COPPER AS METALLIC**



This product contains petroleum distillates.
EPA EST. NO. 60061-NJ-2
EPA REGISTRATION NO. 60061-94
KOP-COAT, INC.
PETTIT PAINT DIV.
ROCKAWAY, NJ 07866
An **RPM** Company

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS. Irritant. Causes eye irritation. Harmful if absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapors, spray mist or sanding dust. While spraying and for sanding boat surfaces, wear a NIOSH/MSHA certified mask or respirator. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. May pose an aspiration pneumonia hazard.

FIRST AID	
IF IN EYES:	<ul style="list-style-type: none"> Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
IF SWALLOWED:	<ul style="list-style-type: none"> Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person. Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.
IF ON SKIN OR CLOTHING:	<ul style="list-style-type: none"> Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

HOT LINE NUMBER

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.

NOTE TO PHYSICIAN

Probable mucosal damage may contribute to the use of gastric lavage. **ENVIRONMENTAL HAZARDS:** This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer system without previously notifying the local sewerage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS: Do not use or store near heat or open flame. Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires blanket flames with foam, CO₂ or dry chemical. Wear NIOSH/MSHA certified breathing equipment. **STORAGE & DISPOSAL:** Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. **PESTICIDE DISPOSAL:** Pesticide, spray mixture, or rinse that cannot be used or chemically processed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent) and dispose of in an approved landfill. Consult Federal, State or local disposal authorities for approved alternative procedures.

VOCS: (as supplied) 399 grams/liter maximum.

GENERAL DESCRIPTION: Pettit Ultima SR Ablative Dual Biocide Antifouling Bottom Paint is an antifouling protective coating resistant to slime, algae, barnacles and other marine fouling organisms. The high loading of cuprous oxide combined with an organic aldehyde offers unprecedented control over all types of fouling even in the most severe fouling areas. This product's unique controlled erosion minimizes coating build-up and keeps underwater surfaces smooth and clean.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. **PREPARATION OF SURFACE:** The surface to be painted should be clean, dry and free of any contamination or foreign matter. Always prepare the surface to be painted by sanding and solvent cleaning before any paints or primers are applied. When sanding old antifouling paint use a dust mask to prevent the inhalation of sanding dust. Old, soft bottom paints must be completely removed before applying. **COVERAGE, APPLICATION AND TEMPERATURE:** This product can be applied by brush, roller or spray. All painting should be done between 9:00 a.m. and 4:00 p.m. in order to avoid the possibility of dew or condensation spoiling the application. The temperature range of application should be between 50 and

90°F. At least two, and preferably three coats, should be applied for best performance, particularly in high wear areas such as the waterline. This product will cover approximately 400 square feet per gallon. **PREPARATION OF PAINT:** This product is heavily loaded with cuprous oxide. As a result there is a tendency for settling to occur especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all the pigment has been mixed in. If mixing is done with a wooden paddle or an electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment, then remix the two parts together thoroughly. **THINNING:** Use Pettit 185 ACP Thinner for thinning this product if needed, particularly on warm or breezy days. Pettit 185 ACP Thinner can also be used to thin this product for spraying and for cleaning equipment. Do not thin more than 10% (12 ounces per gallon) or inadequate paint film thickness will occur and premature erosion of the finish will be likely. **DRY TIMES:** The minimum recoat time is 6 hours. The minimum dry time between the final coat and launching is 16 hours. Under ideal conditions such as those encountered on cool or damp days extend the dry times by 50% in order to ensure that all the solvent is out of the paint film. There is no maximum time before launching. **MAINTENANCE OF ANTI-FOULING PAINT:** No sanding/painting can be effective under all conditions of exposure. Man-made pollution and natural occurrences can adversely affect antifouling paint performance. Excessive hot and cold water temperatures, silt, dirt, oil, brackish water and even electrolysis can ruin and antifouling paint. Therefore, we strongly suggest that the bottom of the boat be checked regularly to make sure it is clean and that no growth is occurring. Lightly scrub the bottom with a soft brush to remove anything from the antifouling paint surface. Scrubbing is particularly important with boats that are idle for extended periods of time. The self-cleaning nature of the coating is most effective when the boat is used periodically.

SYSTEMS

Mix paint thoroughly to ensure toxicants are evenly dispersed throughout the can. All surfaces must be clean, dry and properly prepared prior to painting. **DO NOT APPLY THIS PRODUCT ON ALUMINUM HULLS OR OUTDRIVES.** **PREVIOUSLY PAINTED SURFACES:** If the previous coating is in good condition, thoroughly sand with 80-grit paper, then solvent clean with Pettit 185 ACP Thinner to remove residue. Apply two finish coats of this product. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using a paint and varnish remover. Proceed with appropriate bare system as described below. Old tin copolymers should be removed or sealed with Pettit 6627 Tie-Coat Primer before applying this product.

BARE FIBERGLASS: All Bare fiberglass, regardless of age, should be thoroughly cleaned several times with Pettit 95 Dewaxer or 120 Brushing Thinner. Sand thoroughly with 80-grit sandpaper to a dull, frosty finish and rewash the sanded surface with 95 Fiberglass Dewaxer or 120 Brushing Thinner to remove sanding residue. Then apply two coats of this product following application instructions. Careful observation of the above instructions will help ensure long-term adhesion of this and subsequent years' antifouling paint. To eliminate the sanding operation, wash the fiberglass three times using Pettit 95 Dewaxer only. Then apply one coat of Pettit 6999 Sandless Primer. Read and follow carefully the application and topcoating instructions on the Sandless Primer label. Apply at least two coats of this product.

BARE WOOD: Sand entire surface with 80-grit paper, wash clean with Pettit 185 ACP Thinner. Apply a coat of this product thinned 25% with Pettit 185 ACP Thinner, allow an overnight dry, lightly sand and wipe clean. Apply two finish coats of this product. **BARE STEEL:** Sandblast to clean, bright metal and remove blasting residue with clean, dry compressed air or a clean brush. Immediately apply two coats of Pettit 4700/4701 Pettit Protect Epoxy Primer. Read and follow carefully the instructions on the 4700/4701 Pettit Protect Epoxy Primer label. If the surface to be painted will be prepared using hand tools such as wire wheels or sanders, clean off residue and immediately apply one coat of Pettit 6980 Rustol Steel Primer. Let dry 1-2 hours and follow with two coats of Pettit 4700/4701 Pettit Protect Epoxy Primer. Read and follow carefully the instructions for application and topcoating on both primer labels.

UNDERWATER METAL PARTS: Use Pettit 6456 Underwater Metal Kit for surface preparation instructions and priming underwater metal running gear. **WARRANTY:** We guarantee this material to comply with our published specifications. Since the use of this material is beyond our control, we disclaim responsibility for its handling, use or storage, the results obtained or any injury or damage of any nature resulting therefrom. **MEDICAL EMERGENCIES 1-800-548-0489** MADE IN USA P324B 10/01

4/4