

60061-95

09/15/2004

1/4



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Program
Registration Division (H7505C)
401 "M" St., S.W.
Washington, D.C. 20460

EPA Reg.
Number:

60061-95

Date of Issuance:

SEP 15 2004

NOTICE OF PESTICIDE:
 X Registration
 Reregistration

(under FIFRA, as amended)

Term of Issuance: Expiration
Date 06/15/05

Name of Pesticide Product:

Pettit Marine Paint
Trinidad SR
Antifouling Paint

Name and Address of Registrant (include ZIP Code):

Kop-Coat, Inc.
436 Seventh Avenue
Pittsburgh, PA 15219

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency request all registrants of similar product to submit such data; and submit acceptable response required for reregistration of your product under FIFRA section 4.

The Agency is currently reviewing additional information submitted by your supplier. Therefore, we are extending this limited registration to June 15, 2005.

Signature of Approving Official:

Marshall Swindell,
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510C)

Date:


SEP 15 2004

2. This conditional registration will expire automatically on June 15, 2005. If you fail to satisfy the conditions imposed in the registration, EPA may issue a Notice To Cancel under Section 6(e) of FIFRA.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510C)

Enclosure

3/4



TRINIDAD

ANTIFOULING BOTTOM PAINT



- Slime resistant.
- Very high copper content.
- Long-term protection.
- Effective in worst tropical conditions.
- Hard finish, easily burnished.
- Excellent for fiberglass, wood and steel boats.

NET CONTENTS
1 GALLON (128 FL. OZ.)
3.785 LITERS

COMMERCIAL AND PRIVATE CONSUMER USE
KEEP OUT OF REACH OF CHILDREN.

WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

SEP 15 2004

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide.
Registered under EPA Reg. No.

60061-95

ACCEPTED
WITH COMMENTS
In EPA Letter Dated:

SEP 15 2004

For use on and associated
Painting and Sandblasting
and for the purpose
registered under EPA Reg. No.
60061-95

ACTIVE INGREDIENTS:

Cuprous oxide	70.0%
N-Cyclopropyl-N(1,1-dimethylethyl)- 5-(methylthio)-1,3,5-triazine-2 4-diamine	2.0%

OTHER INGREDIENTS TOTAL

28.0%
100.0%

COPPER AS METALLIC	62.2%
--------------------	-------



This product contains petroleum distillates.

EPA EST. NO. 60061-NJ-2

EPA REGISTRATION NO. 60061-95

KOP-COAT, INC.

PETTIT PAINT DIV.

ROCKAWAY, NJ 07866

An RPM Company

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapors, spray mist or sanding dust. Remove contaminated clothing and wash clothing before reuse. Wash thoroughly with soap and water after handling. May pose an aspiration pneumonia hazard. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

NOTE: When this product is used in confined areas or while spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Safety Health Administration and the National Institute for Occupational Safety and Health.

FIRST AID	
IF SWALLOWED:	<ul style="list-style-type: none">Call a poison control center or doctor immediately for treatment advice.Have person sip a glass of water if able to swallow.Do not induce vomiting unless told to do so by a poison control center or doctor.Do not give anything by mouth to an unconscious person.
IF IN EYES:	<ul style="list-style-type: none">Hold eye open and rinse slowly and gently with water for 15-20 minutes.Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.Call a poison control center or doctor for treatment advice.
IF ON SKIN OR CLOTHING:	<ul style="list-style-type: none">Take off contaminated clothing.Rinse skin immediately with plenty of water for 15-20 minutes.Call a poison control center or doctor for treatment advice.
IF INHALED:	<ul style="list-style-type: none">Move person to fresh air.If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.Call a poison control center or doctor for further treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Contains petroleum distillate - vomiting may cause aspiration pneumonia.	

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of EPA.

PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE! Do not use or store near heat or open flame.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative of the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

VOC (as supplied): 300 g/l max.

VOC (thinned 5%): 325 g/l max.

NOTICE! THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

DIRECTION

It is a violation of Federal Law to use this product in a

Product Description: This product is a hard pro loading of cuprous oxide combined with a specially f to barnacles, algae, slime and other marine and fresh hard anti-fouling coatings. Old soft antifouling paints

Surface Preparation: The surface to be painted should be properly prepared by solvent cleaning and Follow the recommended systems below. When sand prevent the inhalation of sanding dust.

Application and Temperature: This product temperature between 40°F and 90°F. Do not appl surface has dried completely. Two coats should be ap

Preparation of Paint: This product is heavily k there is a tendency for settling to occur especially if t is necessary to thoroughly mix the paint before using paint shaker. Before using check the sides and bott mixed in. If mixing is going to be done with a wood liquid from the top of the can into another can and th two parts together thoroughly.

Thinner: Use Pettit 120 Brushing Thinner for br Thinner for spray application. In either case do not t

Dry Times: Let this product dry at least 2 hours b overnight before launching. This product may be app

Coverage: This product will cover approximately 40

Maintenance of Antifouling Paint: No antil exposure. Manmade pollution and natural occurrenc Extreme hot and cold temperatures, silt, dirt, oil, brack paint. Therefore we strongly suggest that the bottor clean and that no growth is occurring. Lightly scrub the antifouling paint surface.

SYS

Mix paint thoroughly to insure toxicants are evenly clean, dry and properly prepared prior to painting. D

Previously Painted Surfaces: If the previous grit paper then solvent clean with 120 Brushing Thi product. If the previous coating is soft or in poor co a paint & varnish remover. Proceed with appropriate

Bare Fiberglass: All bare fiberglass, regardless c Pettit 95 Dewaxer or 120 Brushing Thinner. Sand ti and rewash the sanded surface with 95 Fiberglass residue. Then apply two coats of this product, follo above instructions will help ensure long term adhes eliminate the sanding operation, wash the fibreglas one coat of Pettit 6999 Sandless Primer. Reac instructions on the Sandless Primer label. Apply tw

Bare Wood: Sand entire surface with 80 grit pap of this product thinned with 120 Brushing Thinner coats of this product.

Bare Steel, Lead Keels, or other Underv
Consult Pettit Technical Bulletin TB 431 Pettit Prote the priming is complete, and the last of the epoxy l may be applied directly over the epoxy primer with product. Alternatively, if the last coat of epoxy pri with 80 grit production paper and wiped clean bef

Warranty: We guarantee this material to compl material is beyond our control, we disclaim respor or any injury or damage of any nature resulting th

MEDICAL EMERGE