



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

June 25, 2020

Sandy Lea
Pesticide Registrar
Kop-Coat, Inc.
36 Pine Street
Rockaway, NJ 07866

Subject: Notification per PRN 98-10 – Updated disclaimer and marketing claims
Product Name: Pettit Marine Paint SR-21 Fresh Water Antifouling
EPA Registration Number: 60061-110
Application Date: January 27, 2020
Decision Number: 559923

Dear Mr. Lea:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact Tara Flint via email at flint.tara@epa.gov.

Sincerely,

A handwritten signature in blue ink that reads "Tara M. Flint".

For
Eric Miederhoff, Product Manager 31
Regulatory Management Branch 1
Antimicrobials Division (7510P)
Office of Pesticide Programs

PETTIT

marine  *paint*

SR-21 FRESH WATER ANTIFOULING PAINT 1621 BLUE

- Super Slick Finish
- Dual- Biocide Controls Hard and Soft Fouling
- Ultra- Thin Film Thickness Prevents Paint Build-Up
- Contains ingredients for Reducing Friction
- No Sanding Required
- Excellent for Fiberglass, Wood and Steel Boats
- Contains PTFE for Reducing Friction

**THIS PRODUCT IS A TWO-COMPONENT PRODUCT.
TO ONLY BE MIXED WITH COPPER POWDER 1921
LOCATED UNDER THE LID OF THIS CONTAINER
BEFORE USING.**

**KEEP OUT OF REACH OF CHILDREN
WARNING**

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

NET CONTENTS
0.75 QUART (U.S.)
710 ml

NOTIFICATION

60061-110

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

06/25/2020

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company ("Pettit"), including surface preparation, proper application, and environmental conditions. Therefore, Pettit cannot guarantee this product's suitability for your particular purpose of application. To the extent consistent with applicable law, Pettit EXPRESSLY DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE or otherwise that extend beyond the statements made on this label, and shall not be liable for special, incidental, or consequential damages resulting from the use or handling of this product, the exclusive remedy being the replacement of the product or refund of the purchase price of the product, at Pettit's sole discretion. To the extent consistent with applicable law, buyer/user assumes all risk of possession, handling, or use of this material when use and/or handling is contrary to label instructions.

ACTIVE INGREDIENTS:

N-Cyclopropyl-N'-(1,1-dimethylethyl)-6-(methylthio) -1,3,5- triazine-2 4-diamine 2.0%

INERT INGREDIENTS

TOTAL 98.0%

100.0%

This product contains petroleum distillates.

EPA REG. NO. 60061-110

EPA ESTABLISHMENT NO. 60061-NJ-2

KOP-COAT, INC.

PETTIT PAINT BRAND

ROCKAWAY, NJ 07866

SR-21 Liquid Portion-MUST be mixed with powder before use

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapors, spray mist, or sanding dust. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Safety and Health Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash clothing before reuse. Wash thoroughly with soap and water after handling. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

FIRST AID	
IF IN EYES:	* Hold eye open and rinse slowly and gently with water for 15 – 20 minutes. * Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. * Call a poison control center or doctor for treatment advice.
IF SWALLOWED:	* Call a poison control center or doctor immediately for treatment advice. * Do not induce vomiting unless told to do so by a poison control center or doctor
IF ON SKIN OR CLOTHING:	* Do not give any liquid to the person. * Do not give anything by mouth to an unconscious person. * Take off contaminated clothing. * Rinse skin immediately with plenty of water for 15 – 20 minutes. * Call a poison control center or doctor for treatment advice.
IF INHALED:	* Move person to fresh air. * If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. * Call a poison control center or doctor for further treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Contains petroleum distillate – vomiting may cause aspiration pneumonia.	

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes or allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE! Keep away from heat, sparks, and open flame. Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO₂, or dry chemical. Wear MSHA/NIOSH certified breathing equipment.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

Pesticide Storage: Store in a closed, properly labeled container in a cool place. Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

Container Disposal: Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. **THIS PRODUCT IS A TWO-COMPONENT PRODUCT. TO ONLY BE MIXED WITH POWDER PORTION LOCATED UNDER THE LID OF THIS CONTAINER BEFORE USING.**

Product Description: Pettit Marine Paint SR-21 Fresh Water Antifouling Paint forms an ultra thin low friction film on boat bottoms. It is the ideal racing finish for fresh water or cold salt-water boats. This product contains copper powder as well as a slime reducing biocide to prevent the attachment of fouling organisms such as barnacles, bryozoa, taredos, zebra mussels, and algae. This product contains two slicking agents PTFE (polytetrafluoroethylene) and molybdenum disulfide, which reduce surface friction allowing the hull to slide through the water. Pettit Marine Paint SR-21 Fresh Water Antifouling Paint is recommended for use on fiberglass, wood and properly primed steel boats.

Mixing: Mix all of the copper powder into the liquid portion stirring thoroughly to ensure the copper powder is evenly dispersed in the liquid. Stir occasionally during application. The mixed material should be used within 24 hours. If used after this time the color of the product will be somewhat darker than at the time of mixing. Additionally, the copper powder will tend to settle out and must be thoroughly remixed if used after 24 hours otherwise particles present in the applied coating. Unopened cans of SR-21 can be stored for 3 years at temperatures of 40 to 90°F without changing the properties of the product.

Application Method: Apply Pettit Marine Paint SR-21 Fresh Water Antifouling Paint with a **short nap** (no more than 3/16-inch nap) or foam roller. Roll quickly in one direction only using a fairly dry roller to minimize lap marks. For spray application use an airless spray gun with a .011 to .015 inch tip. Apply a wet coat of product by holding the gun no more than 10 inches from the hull. Do not use conventional spray equipment to apply this product. Apply at 3 mils wet to achieve a dry film thickness of 0.25 mils per coat.

Application Temperatures: 40°F and above.

Thinner: Thinning this product is not normally required. If thinning is necessary, use xylene or denatured alcohol only. Do not thin more than 10% by volume (2.5 ounces per quart kit) or inadequate paint film thickness may result in premature erosion of the finish.

Coverage: This product covers approximately 90 square feet per quart kit.

Color: 1921 Bronze will be a copper-bronze at application and will change to brownish gray after several weeks in fresh water. 1221 Blue will be a dark copper-bronze at application and will change to dark blue after several weeks in fresh water.

Number of Coats: For best antifouling protection at least three full coats of this product are recommended for the first year's protection. Apply one or two coats each season to follow.

Dry Times:

To recoat	5 minutes	1/2 hour
To launch	10 minutes	1 hour
	20 minutes	2 hours

The above dry times are minimums. This product may be recoated and launched after minimum times shown.

VOC: 735 g/l unthinned.

PAINT SYSTEMS

The paint systems outlined below contain references to other Pettit products. Please read and understand the label and/or Technical Bulletin for these products as well to ensure that they are used properly. For further guidance, please contact your local Pettit salesman or Pettit Customer Service Department at (800) 221-4466 between the hours of 8:30 a.m. and 4:30 p.m. EST

Previously Painted Surfaces: If the previous coating is in good condition, thoroughly sand with 80-grit paper followed by thorough sanding with 150-grit, then 220-grit and finally 320-grit sandpaper to achieve a smooth non-porous surface. Then solvent clean with Pettit 120 Brushing Thinner to remove residue. Apply three coats of this product. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using Pettit 9050 Bottom Paint Remover. Proceed with the appropriate bare system as described below. Old tin copolymers should be removed before applying this product.

Bare Fiberglass: All bare fiberglass, regardless of age, must be thoroughly cleaned using Pettit 95 Fiberglass Dewaxer and clean lint-free rags. Several cleanings may be necessary to ensure complete removal of contaminants, change rags frequently during the dewaxing/cleaning process to ensure complete removal of contaminants rather than merely smearing them on the surface. New boats must be scrubbed with a detergent and water solution and rinsed with fresh water prior to dewaxing. After the surface has been dewaxed, sand it thoroughly with 320-grit production paper and wash the sanded surfaces with Pettit 95 Dewaxer to remove sanding residue. Apply three coats of this product observing the proper dry times. If sanding is prohibited, as with certain vinyl-ester gelcoats, or is otherwise impractical, make sure the surface has been completely and thoroughly dewaxed and cleaned with Pettit 95 Fiberglass Dewaxer. Then apply one thin continuous coat of Pettit 6999 Sandless Primer. Topcoat with three coats of this product carefully following the topcoating instructions on the Sandless Primer label.

Bare Wood: Sand the entire surface with 80-grit production paper and wipe clean with a rag dampened with Pettit 120 Brushing Thinner. Apply three (3) coats of this product.

Bare Steel*: Sandblast or disc sand to a clean, bright finish and remove residue. Then immediately apply two coats of 6980 Rustlok Steel Primer, allowing each to dry only 1-2 hours prior to over coating. Follow with two coats of Pettit 4700/4701 High Build Epoxy Primer, allowing each to dry from two to 24 hours depending upon temperature. Apply three finish coats of this product.

Keels – Lead: Abrade surface to bright metal and clean off residue. Apply one thin coat of 6455/044 Metal Primer; allow to dry two hours. Apply one coat of Pettit 6627 Tie Coat Primer then, if fairing is required, apply 7000/7001 Epoxy Fairing Compound. Follow with an additional coat of 6627 Tie Coat Primer per label directions. Apply three finish coats of this product.

Keels – Steel or Cast Iron: Abrade surface to bright metal and clean off residue. Apply one coat of 6980 Rustlok Steel Primer, allowing to dry only 1-2 hours prior to over coating. Then, if fairing is required, apply 7000/7001 Epoxy Fairing Compound followed by two coats of Pettit 6627 Tie Coat Primer, finish with three coats of this product.

*This is a simplified system for smaller areas designed for good performance and easy application by the boatyard professional or do-it-yourselfer. For larger vessels or for applications where a high performance, professional system is desired, please refer to Technical Bulletin 431, Pettit Protect 4700/4701 High Build Epoxy Primer or consult your local Pettit representative or the Pettit Technical Department.

**DO NOT USE THIS PRODUCT ON ALUMINUM HULLS OR OUTDRIVES
NEVER OVERCOAT ZINC ANODES**