

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF PREVENTION, PESTICIDES AND TOXIC SUBSTANCES

July 5, 2006

Ms. Kim Trelor, Product Registration Specialist Kop-Coat, Inc. 3020 William Pitt Way Pittsburgh, PA 15238

Subject:

Notification Application per PR Notice 98-10

Bazooka Sapstain And Mold Control Product

EPA Registration No. 60061-112 Application Date: June 20, 2006 Receipt Date: June 27, 2006

Dear Ms. Trelor:

This acknowledges receipt of your notification, submitted under the provision of PR Notice 98-10, FIFRA section 3(c)9.

Proposed Notification:

Revised label to include US patent number 7056,919 on the product labeling.

General Comment:

Based on a review of the material submitted, the following comment applies:

The notification is acceptable and a copy of the revised labeling has been inserted in your file for future reference.

Should you have any questions or comments concerning this letter, please contact me at (703) 308-6422, or by email at heyward.adam@epa.gov or Killian Swift at (703) 308-6346 or by email at swift.killian@epa.gov

Sincerely,

Adam Heyward Product Manager (34)

Regulatory Management Branch II Antimicrobials Division (7510C) June 20, 2006

Document Processing Desk
Office of Pesticide Programs, Registration Division (H7505c)
U.S. Environmental Protection Agency
Mr. Adam Heyward, Product Manager #34
Room S 4900, One Potomac Yard
2777 South Crystal Drive
Arlington, VA 22202-4501

Re:

BAZOOKA SAPSTAIN AND MOLD CONTROL PRODUCT

EPA FILE symbol Number 60061-112

Notification of Label Change

Dear Mr. Heyward:

Kop-Coat Inc. wishes to submit a Notification to the label BAZOOKA SAPSTAIN AND MOLD CONTROL PRODUCT per PR Notice 98-10 to add the US patent number 7056,919 to the label.

This notification is consistent with the provisions of PR Notice 98-10 and EPA regulations at 40 CFR 152.46, and no other changes have been made to the labeling or confidential statement of formula of this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willfully make any false statement to EPA. I further understand that if this notification is not consistent with the terms for PR Notice 98-10 and 40 CFR 152.46, this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA.

Enclosed:

Please find three copies of the updated label for your files.

If you have any questions or comments please me at 412(826-3323) or email at ktreloar@kop-coat.com.

Sincerely yours,

Kim Treloar

Product Registration Specialist

Kop-Coat, Inc.

CC:

A. Ross, Kop-Coat, Inc.

H. Ward, Kop-Coat, Inc.

A. Wells, Kop-Coat, Inc.



DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

GENERAL PRECAUTIONS AND RESTRICTIONS:

FOR INDUSTRIAL USE ONLY

DILUTE BEFORE USING

Do not apply this product in a way that will contact workers or other persons.

Wear synthetic rubber gloves or plastic coated gloves in handling solutions and freshly treated

Treated sawdust and other wood wastes should be disposed of properly and should not be used as mulch where it will come into contact with useful living plants. Care should be taken to prevent drip or spray from contacting ornamental shrubs, trees, grass, and other desirable vegetation.

GENERAL INFORMATION:

Freshly dipped or sprayed lumber should be protected from rain-washing. Dip tanks and drip aprons must be roofed, paved, and drained to prevent dilution and loss of the anti-stain solution. Treatment concentrations must be geared to achieve protection of the thickest or most valuable item being treated. The concentration of the ready-to-use solution must be adjusted to accommodate seasonal changes in the exposure, species being treated, Dip tanks, and spray equipment must be properly maintained.

MIXING INSTRUCTIONS:

For high-pressure spray applications: Thoroughly mix one gallon of BAZOOKATH Sapstain and Mold Control Product per 2 to 500 gallons of water.

For dip applications: Thoroughly mix one gallon of BAZOOKATM Sapstain and Mold Control Product per 20 to 1,000 callons of water. In all cases, dilution levels will depend upon application methods, lumber species, and conditions of lumber storage. Mills should conduct tests to determine treatment requirements for their individual needs. Contact Kop-Coat for further information. When using proportioning pumps for mixing, this product should be maintained at temperatures above 50 °F to prevent inaccurate mixing due to viscosity changes. Minor proportioning rate changes can be affected by changing the setting on the pump dial.

NOTE: With normal dip or spray application long-term control of decay cannot be achieved. This product is intended to provide decay, mold, and blue stain control during storage. Such control would not likely extend to the use site.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

Pesticide Storage: Store in a closed, properly labeled container in a cool place. If static generating conditions exist, provide necessary grounding and bonding. Keep containers closed when not in use.

Pesticide Disposal; Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. It these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PHYSICAL OR CHEMICAL HAZARDS:

COMBUSTIBLE. DO NOT use, pour, srill, or store near heat or open flame. IN CASE OF FIRE: Use dry chemicals, fount, water fog, or CO2. Cool closed containers with water.

KOP-COAT

BAZOOKA TM

Sapstain and Mold Control Product

U.S. Patent Number 6,375,727and 7,056,919 additional Patents Pending

Aids in the control of blue stain, mold and decay of freshly cut lumber, dry lumber and other wood based products when properly used. Effective on softwoods including Douglas fir, White fir, Spruce, Hemlock, the Pines including both the Southern and Western Yellow Pines. Eastern and Western White Pines and many of the hardwoods.

KEEP OUT OF REACH OF CHILDREN **DANGER - PELIGRO**

See side panel for additional precautionary statements.

Oce side pair	rior dedication procuderation at y occionistical	•
Read Warranty On Side	ACTIVE INGREDIENTS	
Panel Before Buying Or	Diiodomethyl-para-Tolyl sulfone	0.95%
Using. If Such Terms Are	Propiconazole	3.50%
Not Acceptable, Return At Once Unopened.	3-lodo-2-Propynyl	
	Butyl Carbamate	.3.50%
EPA Reg. No. 60061-112 EPA Est. No. 60061-MO-1	OTHER INGREDIENTS	92.05%
	TOTAL	00.00%

FIRST AID	
IF IN EYES:	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice
IF SWALLOWED:	 Call poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.
IF ON SKIN OR ON CLOTHING:	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
IT INFIALED:	Move person to fresh air. If person is not breathing, call 911 or an ambutance, then gives artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice.
	ontainer or label with you when calling a poison control center or doctor, or reatment. In case of emergency call toll free: 1-800-548-0489.
NOTE TO PHYSICIAN:	Probable mucosal damage may contraindicate the use of gastric lavage.

Kop-Coat, Inc. **Protection Products Division** 5137 Southwest Avenue, St. Louis, MO 63110 314/772-2200

NET CONTENTS

U.S. GALLONS

PRECAUT HAZARDS TO HUM

CORROSIVE. Causes Irreversible Eve D absorbed through skin. Do not get in eyes, Wear protective evewear (goggles, face water after handling Remove contaminate

PERSONAL PR

Applicators and other handlers must wea 1. Coveralls over long-sleeved shirt and

- chemical-resistant footweer plus socks.
- 3. Googles or face shield
- 4. chemical-resistant gloves (such as ba-
- Respirator with an organic vapor-remo (MSHA/NIOSH approval prefix TC-236 approval prefix TC-14G) or a NIOSH a or canister with any R, P or HE prefitte
- 6. Follow manufacturers' instructions for for washables, use detergent and hot have been drenched or heavily cont them. Keep and wash PPE separately

USER SAFETY RE

Users should:

- Wash hands before eating, drink or using the toilet.
- Remove clothing immediately if thoroughly and put on clean cloth
- Remove personal protective equ this product. Wash outside of glo possible wash thoroughly.

This pesticide is toxic to fish. Do not app water is present or to intertidal areas bel when disposing of equipment washwat product into lakes, streams, ponds, estua requirements of a National Pollution D permitting authority has been notified in v sewer systems without previously notifying contact your State Water Board or Region

WARRANTY: We warrant this material good merchantable quality and such a description, and further warrant such ge used. We assume no responsibility th particular purpose for which they are being description.



PPD