

60061-112



1/28/2015
1/2
UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

January 28, 2015

Angie Custer
Regulatory Affairs Specialist/Quality Manager
Kop Coat, Inc.
3020 William Pitt Way
Pittsburg, PA 15238

Subject: Amended Reregistration Label
Product Name: BAZOOKA®
EPA Registration Number: 60061-112
EPA Decision Number for Amical 48: 428672
EPA Decision Number for Propiconazole: 454643

Dear Ms. Custer:

The Agency, in accordance with the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, has completed reviewing all of the information submitted with your application to support the reregistration of the above referenced product in connection with the Propiconazole RED and has concluded that your submission is acceptable.

NOTE: This product is not being reregistered under section 4(g) of FIFRA at this time.


Please note that the record for this product currently contains the Confidential Statement of Formulation (CSF) listed below. Any previously dated CSFs are superseded.

- Basic CSF, dated September 16, 2013
- Alternate CSF dated August 12, 2014

A copy of your label stamped "Accepted" is enclosed. Products shipped after 12 months from the date of this amendment or the next printing of the label whichever occurs first, must bear the new revised label. Your release for shipment of the product bearing the amended label constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6.

If you have any questions or comments about this letter, please contact Srinivas Gowda at (703) 308-6354 or by e-mail at gowda.srinivas@epa.gov.

Sincerely,


Jacqueline Hardy, Product Manager 34
Regulatory Management Branch II
Antimicrobials Division (7510P)
Office of Pesticide Programs

Enclosures: Label stamped "Accepted"

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
GENERAL PRECAUTIONS AND RESTRICTIONS:
FOR INDUSTRIAL USE

CONSULT SAFETY DATA SHEET (SDS) BEFORE USING

DILUTE BEFORE USING

Do not apply this product in a way that will contact workers or other persons, either directly or through spray drift. Only protected handlers may be in the area during application.

Wear synthetic rubber gloves or plastic coated gloves in handling solutions and freshly treated lumber.

Treated sawdust and other wood wastes should be disposed of properly and should not be used as much where it will come into contact with useful living plants. Care should be taken to prevent drip or spray from contacting ornamental shrubs, trees, grass, and other desirable vegetation.

GENERAL INFORMATION

Freshly dipped or sprayed lumber should be protected from rain-washing. Dip tanks and drip aprons must be roofed, paved, and drained to prevent dilution and loss of the anti-stain solution. Treatment concentrations must be geared to achieve protection of the thickest or most valuable item being treated. The concentration of the ready-to-use solution must be adjusted to accommodate seasonal changes in the exposure, species being treated, dip tanks, and spray equipment must be properly maintained.

INSTRUCTIONS

High-pressure spray applications: Thoroughly mix one gallon of Bazooka® Sapstain and Mold Control Product per 2 to 500 gallons of water.

For dip applications: Thoroughly mix one gallon of Bazooka® Sapstain and Mold Control Product per 20 to 1,000 gallons of water. In all cases, dilution levels will depend upon application methods, lumber species, and conditions of lumber storage. Mills should conduct tests to determine treatment requirements for their individual needs. Contact Kop-Coat for further information. When using proportioning pumps for mixing, this product should be maintained at temperatures above 50°F to prevent inaccurate mixing due to viscosity changes. Minor proportioning rate changes can be affected by changing the setting on the pump dial.

Minimum application rate is 0.08% w/v Diiodomethyl-para-Tolyl sulfone for sapstain wood preservation.

Maximum application rate is 0.1% Diiodomethyl-para-Tolyl sulfone for pressure treated wood application.

NOTE: With normal dip or spray application long-term control of decay cannot be achieved. This product is intended to provide decay, mold, and blue stain control on wood surfaces. Such control is not intended to be used on site.

ACCEPTED
01/28/2015
Under: the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the PESTICIDE registered under EPA Reg. No. 60061-112

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.
Storage: Store in a closed, properly labeled container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container 1/2 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth ensuring at least one complete revolution for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling if available.

Pesticide Disposal: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the nearest EPA Regional Office for guidance.

Container Handling: Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container 1/2 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth ensuring at least one complete revolution for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling if available.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

Corrosive. Causes skin burns. Causes irreversible eye damage. Harmful if swallowed, absorbed through skin, or inhaled. Do not get in eyes, on skin, or clothing. Avoid breathing vapor or spray mist. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

- Applications and other handlers must wear:
1. Coveralls over long-sleeved shirt and long pants
 2. Chemical-resistant footwear plus socks
 3. Goggles or face shield
 4. Chemical-resistant gloves (such as barrier laminate, nitrile rubber, neoprene rubber and viton)

USER SAFETY RECOMMENDATIONS

- User must:
- Follow manufacturer's instructions for clean/maintaining PPE. If no such instructions exist, use detergent and hot water. Keep and wash PPE separately from other laundry.
 - Discard clothing and other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them.

USER SAFETY INSTRUCTIONS

Users should:

- Wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.
- Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.
- Remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic invertebrates. Do not apply directly to water. Do not contaminate water when disposing equipment wastewater. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters, unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewerage treatment plant authority. For guidance, contact your State Water Board or Regional Office of Environmental Protection Agency.

Until product has dried, anti-sapstain treated lumber must be stored under cover, indoors, or at least 100 feet from any point lake, stream, wetland, or river to prevent possible runoff of the product into the waterway. Treated lumber stored within 100 feet of a pond, lake, stream, or river must be either covered with plastic or surrounded by a berm to prevent surface water runoff into the nearby waterway. If a berm or curb is used around the site, it should consist of impermeable material (clay, asphalt, concrete) and be of sufficient height to prevent runoff during heavy rainfall events.

PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE: Do not use, pour, spill, or store near heat or open flame

IN CASE OF FIRE

Use water, fog, beam, carbon dioxide or dry chemical. Cool closed containers with water.

LIMIT OF WARRANTY AND LIABILITY

We warrant this material to comply with our published specifications and to be of good mechanical quality and such as will regularly pass in the trade for goods within the description, and further warrant such goods to be fit for the normal purposes for which goods are used. We assume no responsibility that the goods concerned in this contract are fit for any particular purpose for which they are being bought outside of the general purposes of goods of the description.

15900/48A / R02/0105.15

Gallons

Net Contents

Kop-Coat, Inc.
Protection Products Division
5137 Southwest Avenue, St. Louis MO 63110
314-772-2200

Net Contents