# 11/21/2005





U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Registration Division (H7505C) 401 "M" St., S.W. Washington, D.C. 20460

<u>x</u> Registration

Reregistration

NOTICE OF PESTICIDE:

EPA Reg. Number:

Date of Issuance:

60061-120

NOV 2 1 2005

Term of Issuance:

Conditional

Name of Pesticide Product:

Pettit Marine Paint Alumaspray + Aerosol Antifouling Paint

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Kop-Coat, Inc. 1850 Koppers Building Pittsburg, PA 15219

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregisteration under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

- 1. Submit and/or cite all data or other material required for registration/reregistration of your product under FIFRA sec. 3(c)(5) or FIFRA sec. 4 when the Agency requires all registrants of similar products to submit such data.
  - 2. Make the following labeling change:

Add the phase EPA Registration No. "60061-120"

Signature of Approving Official:

Date

Marshall Swindell, Product Manager (33) Regulatory Management Branch I

Antimicrobials Division (7510C)

NOV 2 1 2005

EPA Form 8570-6

page 2 EPA Reg. No.60061-120

3. Submit five (2) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,

Marshall Swindell Product Manager 33

Regulatory Management Branch I Antimicrobials Division (7501C)

Enclosure



- For Aluminum Outdrives and Outboards
- Advanced Slime Resistance
- Excellent for All Underwater Metal Surfaces

**DANGER** 

EXTREMELY FLAMMABLE CONTENTS UNDER PRESSURE KEEP OUT OF REACH OF CHILDREN ACCEPTED
with COMMENTS
EPA Letter Dated:

NOV 2 1 2005

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

60061-120

**ACTIVE INGREDIENT:** 

Zinc Omadine® INERT INGREDIENTS:

1.43% 98.57%

100.00%

This product contains petroleum distillates.

EPA EST. NO. 5693-MA-1 EPA REGISTRATION NO. 60061-

KOP-COAT, INC.
PETTIT PAINT BRAND
36 PINE STREET
ROCKAWAY, NJ 07866
An RPM Company

NET WEIGHT 12 OZ.

### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes skin burns and moderate eye irritation. Do not get in eyes, on skin, or on ciothing. Avoid breathing spray mist, vapors or sanding dust. While spraying and/or sanding boat surfaces, wear a NIOSH/MSHA certified mask or respirator. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Wear coveralis worn over long-sleeved shirt and long pants, chemical resistant gloves, protective eyewear (goggles, face shield or safety glasses), socks, and chemical resistant footwear. Remove contaminated clothing and wash clothing before reuse. May pose an aspiration pneumonia hazard.

FIRST AID
Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Cail a poison control center or doctor for treatment advice.
Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.
Move person to fresh air.  If person is not breathing, call 911 or an ambulance then give artificial respiration, preferably mouth-to-mouth, if possible.  Call a poison control center or doctor for further treatment advice.
Take off contaminated clothing. Rinse skin immediately with plenty of water of 15-20 minutes. Call a poison control center or doctor for treatment advice.

#### HOT LINE NUMBER

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.

## NOTE TO PHYSICIAN

Probable mucosal damage may contraindicate the use of gastric lavage. This product contains petroleum distillates. Vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Poliution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS: EXTREMELY FLAMMABLE! Contents under pressure. Keep away from heat, sparks or open flame. Do not puncture or incinerate container. Exposure to temperatures above 130°F may cause bursting. Use only with adaquate ventilation during mixing application and drying. Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO<sub>2</sub> or dry chemical. Wear NIOSH/MSHA certified breathing equipment.

ACCEPTED
with COMMENTS
EPA Letter Dated:

NOV 2 1 2005

Under the Federal Insecticide, Fungiciae and Redenticide Act as amended, for the pesticide, registered under EPA Reg. No.

60061-120

## STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Keep away from heat, sparks and open flame. Store in a closed, properly labeled container in a cool, dry place. Keep container closed and upright to prevent leakage. In case of spillage, absorb and dispose of in accordance with local and state authorities.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. CONTAINER DISPOSAL: Do not puncture or incinerate. A completely empty can can be disposed of with household trash. Wrap in paper before disposing.

**MAXIMUM VOC: 75%** 

NOTICE! THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

GENERAL DESCRIPTION: Pettit Marine Paint Alumaspray+ Aerosol Antifouling Paint is an antifouling protective coating resistant to silme, algae, barnacles and other marine and freshwater fouling organisms. This product's unique controlled erosion polymers combined with the latest organic blockle technology minimizes coating build-up and keeps underwater surfaces smooth and clean. This product is for use in fresh, salt or brackish water on underwater metal parts such as outdrive units and outboard motors below the waterline. This paint is intended for use on underwater metal surfaces of recreational and commercial vessels of any size.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. NEW OUTDRIVE UNIT: Lightly sand the factory paint with 80-grit sandpaper to duli the surface, clean with Pettit 120/T-10 Brushing Thinner and apply two coats of Alumaspray+ Aerosol Antifouling Paint allowing a minimum of 6 hours at 70°F or 12 hours at 50°F drying time between coats.

OUTDRIVES PREVIOUSLY PAINTED WITH ANTIFOULING PAINT: Lightly sand the old antifouling paint, and then clean the sanded surface with Pettit 120/T-10 Brushing Thinner. Apply one coat of Pettit 6627 Tie-Coat Primer and allow to dry at least 4 hours, then apply two coats of Alumaspray+ Aerosol Antifouling Paint allowing a minimum of 6 hours drying time between coats. If the old paint has been chipped to bare metal, the entire surface must be primed. Smaller areas less than one square inch can be spot primed prior to applying Alumaspray+ Aerosol Antifouling Paint.

BARE ALUMIMUM OUTDRIVES AND OUTBOARDS: The metal surface should be properly sandblasted or cleaned to bright metal. Apply two coats of Pettit Aluma Protect Aluminum Epoxy Primer 4400/4401 followed by two coats of Pettit Protect High Build Epoxy Primer 4700/4701 and two coats of Alumaspray+ Aerosol Antifouling Paint.

DRY TIMES: The paint will dry to the touch in 30 minutes. The minimum recoat time is 6 hours. The minimum dry time between the final coat and launching is 16 hours. Under adverse drying conditions such as those encountered on cool or damp days extend the dry times by 50% in order to ensure that all the solvent is out of the paint film. There is no maximum time before launching.

APPLICATION: Shake can vigorously for at least one minute after mixing ball begins to rattle. Shake can often during use. Hold can 10-12 inches from the surface. Depress nozzle and spray with smooth even strokes. When finished spraying, clear spray valve by turning can upside down and spraying until no more paint comes out.

COVERAGE: One can covers approximately 15 square feet. Use the entire contents of one can for each lower unit or outboard.

CLEAN-UP: Use Pettit 120/T-10 Brushing Thinner.

MEDICAL EMERGENCIES: 1-800-548-0489

PRODUCT INFORMATION: 1-800-221-4466

MADE IN USA P3416 1763 3/05

