



## UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

WASHINGTON, D.C. 20460

OFFICE OF  
PREVENTION, PESTICIDES  
AND TOXIC SUBSTANCES

MAY 31 2011

Ms. Kim Treloar  
Product Registration Specialist for,  
Kop-Coat, Inc.  
3020 William Pitt Way  
Pittsburgh, PA 15238

Subject: Pettit Marine Paint Ultima SPC Antifouling Paint  
EPA Registration Number 60061-125  
Your Amendment Dated March 3<sup>rd</sup>, 2011  
EPA Received Date March 4<sup>th</sup>, 2011

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, FIFRA, as amended, to obtain approval approval for four Confidential Statements of Formula, is acceptable.

The concentrations of the active ingredients on the Confidential Statements of Formula dated 03/17/11 are consistent with the label declaration.

The Confidential Statements of Formula dated March 17, 2011, are acceptable.

A stamped copy of the labeling is enclosed for your records.

If you have questions concerning this letter, please contact Karen M. Leavy at (703)-308-6237.

Sincerely,

A handwritten signature in black ink that reads "M Swindell".

Marshall Swindell  
Product Manager 33  
Regulatory Management Branch I  
Antimicrobials Division(7510P)



ACCEPTED  
with COMMENTS  
EPA Letter Dated:

MAY 31 2011

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No. 60061-125

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company, including surface preparation, proper application and environmental conditions. Therefore, Pettit Paint Company cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. Pettit Paint Company shall not under any circumstances be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Pettit Paint's option.

## ULTIMA SPC

### ANTIFOULING PAINT

- Self-Polishing Copolymer Reduces Coating Build-Up
- Dual Biocide to Control Hard and Soft Fouling
- Advanced Slime Resistance
- Multi-Season Technology

#### ACTIVE INGREDIENT:

Cuprous Oxide*	40.43%
Zinc Omadine®**	3.00%
INERT INGREDIENTS:	56.57%
Total	100.00%

(\*\* Metallic zinc equivalent, 0.62%  
\*Metallic Copper equivalent, 36%)

This product contains petroleum distillates.

EPA EST. NO. 60061-NJ-2  
EPA REGISTRATION NO. 60061-125

KOP-COAT, INC.  
PETTIT PAINT BRAND  
ROCKAWAY, NJ 07866

An RPM Company

NET CONTENTS  
1 GAL. (128 FL. OZ.)  
3.785 LITERS

KEEP OUT OF REACH OF CHILDREN  
**DANGER**  
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**DANGER: Corrosive.** Causes skin burns and moderate eye irritation. Do not get in eyes, on skin, or on clothing. Avoid breathing spray mist, vapors or sanding dust. While spraying and/or sanding boat surfaces, wear a NIOSH/MSHA certified mask or respirator. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Wear coveralls worn over long-sleeved shirt and long pants, chemical resistant gloves, protective eyewear (goggles, face shield or safety glasses), socks, and chemical resistant footwear. Remove contaminated clothing and wash clothing before reuse. May pose an aspiration pneumonia hazard.

**For applications by residential (non-commercial) users: Do not apply by airless spray; Do not apply more than one coat of this product within 24 hours; Apply only in outdoor, non-enclosed spaces.**

Residential (non-commercial) users are advised to wear chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks and shoes. In addition to these minimum Personal Protective Equipment (PPE), commercial users must wear a disposable coverall with hood and chemical resistant footwear.

While removing existing paint by sanding or blasting, or applying new antifoulant paint, commercial users must wear a respirator with an **organic vapor removing cartridge with a pre-filter approved for pesticides (MSHA/NIOSH APPROVAL NUMBER TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 pre-filter. Residential (non-commercial) users are advised to wear the same respirators, cartridges and pre-filters as required by commercial users.**

<b>FIRST AID</b>	
<b>IF IN EYES:</b>	<ul style="list-style-type: none"> <li>Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li> <li>Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.</li> <li>Call a poison control center or doctor for treatment advice.</li> </ul>
<b>IF SWALLOWED:</b>	<ul style="list-style-type: none"> <li>Call a poison control center or doctor immediately for treatment advice.</li> <li>Do not induce vomiting unless told to do so by a poison control center or doctor.</li> <li>Do not give <b>any</b> liquid to the person.</li> <li>Do not give anything by mouth to an unconscious person.</li> </ul>
<b>IF INHALED:</b>	<ul style="list-style-type: none"> <li>Move person to fresh air.</li> <li>If person is not breathing, call 911 or an ambulance then give artificial respiration, preferably mouth-to-mouth, if possible.</li> <li>Call a poison control center or doctor for further treatment advice.</li> </ul>
<b>IF ON SKIN OR CLOTHING:</b>	<ul style="list-style-type: none"> <li>Take off contaminated clothing.</li> <li>Rinse skin immediately with plenty of water of 15-20 minutes.</li> <li>Call a poison control center or doctor for treatment advice.</li> </ul>
<b>HOT LINE NUMBER</b>	
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.	
<b>NOTE TO PHYSICIAN</b>	
Probable mucosal damage may contraindicate the use of gastric lavage. This product contains petroleum distillates. Vomiting may cause aspiration pneumonia.	

**ENVIRONMENTAL HAZARDS:** This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARDS: FLAMMABLE!** Keep away from heat, sparks or open flame. Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO<sub>2</sub> or dry chemical. Wear NIOSH/MSHA certified breathing equipment. **STORAGE AND DISPOSAL**  
Do not contaminate water, food or feed by storage or disposal.

**PESTICIDE STORAGE:** Keep away from heat and open flame. Store in a closed, properly labeled container in a cool, dry place. Keep container closed and upright to prevent leakage. In case of spillage, absorb and dispose of in accordance with local and state authorities.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL:** Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow

begins to drip. Fill the container ¼ full with Thinner or xylene and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times

**VOIC:** (as supplied) 490 grams/liter maximum.

**NOTICE! THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.**

**GENERAL DESCRIPTION:** Pettit Marine Paint Ultima SPC Antifouling Paint is an antifouling protective coating resistant to slime, algae, barnacles and other marine and freshwater fouling organisms. This product's unique controlled erosion, hydrolyzing copolymer combined with the latest organic biocide technology minimizes coating build-up and keeps underwater surfaces smooth and clean. This product is for use in fresh, salt or brackish water on hulls and underwater parts below the waterline. This paint is intended for use on recreational and commercial vessels of any size.

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**PREPARATION OF SURFACE:** The surface to be painted should be clean, dry and free of any contamination or foreign matter. Always prepare the surface to be painted by sanding and solvent cleaning before any paints or primers are applied. When sanding old antifouling paint use a dust mask to prevent the inhalation of sanding dust. Old, soft bottom paints must be completely removed before applying.

**COVERAGE, APPLICATION AND TEMPERATURE:** This product can be applied by brush or short nap roller. All painting should be done between 9:00 a.m. and 4:00 p.m. in order to avoid the possibility of dew or condensation spoiling the application. The temperature range of application should be between 50 and 90°F. At least two, and preferably three coats, should be applied for best performance, particularly in high wear areas such as the waterline. This product will cover approximately 360 square feet per gallon when applied at 2 dry mils film thickness.

**PREPARATION OF PAINT:** This product may exhibit pigment settling, especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all the pigment has been mixed in. If mixing is going to be done with a wood or electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment, then remix the two parts together thoroughly.

**THINNING:** Use Pettit 120 Brushing Thinner for thinning this product if needed, particularly on warm or breezy days. Do not thin more than 10% (12 ounces per gallon) or inadequate paint film thickness will occur and premature erosion of the finish will be likely.

**DRY TIMES:**

	To recoat	To launch
90°F	3 hours	8 hours
70°F	6 hours	16 hours
50°F	12 hours	24 hours

The above dry times are minimums. This product may be recoated and launched after the minimum times shown. There is no maximum time before launching.

**SYSTEMS**

Mix paint thoroughly to ensure toxicants are evenly dispersed throughout the can. All surfaces must be clean, dry and properly prepared prior to painting.

**PREVIOUSLY PAINTED SURFACES:** If the previous coating is in good condition, thoroughly sand with 80-grit sandpaper, then solvent clean with Pettit 120 Brushing Thinner to remove residue. Apply two finish coats of this product. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using a paint and varnish remover. Proceed with appropriate bare system as described below.

**BARE FIBERGLASS:** All bare fiberglass, regardless of age, should be thoroughly cleaned several times with Pettit D95 Fiberglass Dewaxer. Sand thoroughly with 80-grit sandpaper to a dull, frosty finish and rewash the sanded surface with D95 Fiberglass Dewaxer to remove sanding residue. Then apply two coats of this product following application instructions. Careful observation of the above instructions will help ensure long-term adhesion of this and subsequent years' antifouling paint. To eliminate the sanding operation, wash the fiberglass three times using Pettit D95 Dewaxer. Then apply one coat of Pettit 6998 Skip Sand Primer. Read and follow carefully the application and topcoating instructions on the Skip Sand Primer label. Apply at least two coats of this antifouling paint.

**BARE STEEL:** Sandblast to clean, bright metal and remove blasting residue with clean, dry compressed air or a clean brush. Immediately apply three coats of Pettit 4700/4701 Pettit Protect Epoxy Primer followed by two finish coats of this product. Read and follow carefully the instructions on the 4700/4701 Pettit Protect Epoxy Primer label. If the surface to be painted will be prepared using hand tools such as wire wheels or sanders, clean off residue and immediately apply one coat of Pettit 6980 Rustlok Steel Primer. Let dry 1-2 hours and follow with two coats of Pettit 4700/4701 Pettit Protect Epoxy Primer. Then apply two finish coats of this product. Read and follow carefully the instructions for application and topcoating on both primer labels.

**DO NOT USE THIS PRODUCT ON ALUMINUM HULLS OR OUTDRIVES**

**MEDICAL EMERGENCIES: 1-800-548-0489  
PRODUCT INFORMATION: 1-800-221-4466**

MADE IN USA P32-- 1299/GA 03/11

ACCEPTED  
WITH COMMENTS  
EPA Letter Dated:  
MAY 31 2011

under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
registered for the pesticide  
registered under EPA Reg. NO. 6061-12.

3  
3