

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

January 28, 2015

Angie Custer
Regulatory Affairs Specialist/Quality Manager
Kop Coat, Inc.
3020 William Pitt Way
Pittsburg, PA 15238

Subject:

Amended Reregistration Label
Product Name: MOLDSHIELD®
EPA Registration Number: 60061-127

EPA Decision Number for Amical 48: 428674 EPA Decision Number for Propiconazole: 454650

Dear Ms. Custer:

The Agency, in accordance with the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, has completed reviewing all of the information submitted with your application to support the reregistration of the above referenced product in connection with the Propiconazole RED and has concluded that your submission is acceptable.

NOTE: This product is **not** being reregistered under sections 4(g) of FIFRA at this time.

Please note that the record for this product currently contains the Confidential Statement of Formulation (CSF) listed below. Any previously dated CSFs are superseded.

- Basic CSF, dated June 5, 2014
- Alternate CSF, dated August 7, 2014

A copy of your label stamped "Accepted" is enclosed. Products shipped after 12 months from the date of this amendment or the next printing of the label whichever occurs first, must bear the new revised label. Your release for shipment of the product bearing the amended label constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6.

If you have any questions or comments about this letter, please contact Srinivas Gowda at (703) 308-6354 or by e-mail at gowda.srinivas@epa.gov.

Sincerely,

Jacqueline Hardly, Acting Product Manager 34

Regulatory Management Branch II Antimicrobials Division (7510P)

Office of Pesticide Programs

Enclosures: Label stamped "Accepted"

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in

GENERAL PRECAUTIONS AND RESTRICTIONS: FOR INDUSTRIAL USE

DILUTE BEFORE USING

CONSULT SAFETY DATA SHEET (SDS) BEFORE USING

Wear synthetic rubber gloves or plastic coaled gloves in handling solutions and freshly treated lumber.

id sawdust and other wood wastes should be disposed of properly and should not be used as mulch it will come into contact with useful living plants.

Care should be taken to prevent drip or spray from contacting ornamental shrubs, trees, grass and other

Description: Moldshield® Sapstain and Mold Control Chemical is a liquid concentrate containing an effective fungicide for the control of mold and sapstain fungithat cause discondation and staining of freshly sawn further. Moldshield® Sapstain and Mold Control Chemical is an entions solution within may be applied to dimensional further, logs, phywood, QBS and parite broad to prevent surface mold growth. Distintion Ratio: Moldshield® Sapstain and Mold Control Chemical is a concentrate dilutable with water. For tumber

in die systems, use 1 gation of concentrate per 25 gations to 400 gations of water to protect against staining organ-sms. For spray systems use 1 gation of concentrate per 5 to 150 gations of water. Contact Kop-Coat, Inc. for

Application: Flood spray or of the freshly sawn clean lumber to be trated in Motdshield® Sapsian and Mold Control Chemical solution within 24 hours of cutting. A dip of 15 seconds or more is sufficient, If not treated within 24 hours, stain may occur.

Lumber should be lotally immersed or sprayed to insure treatment. Tanks should be covered by a roof to prevent the addition of rain water and consequent dilution of the solution. Vats and spray equipment should be cleaned regularly to remove sawdust and other debrins. Freshly treated lumber should not be exposed to water. Store in protected area away from rain and stack property for best results.

Maximum application rate is 0.8% www Diiodomethyl-para-Tolyl suftone for sapstain wood preservation. Maximum application rate is 0.7 tb Diiodomethyl-para-Tolyl sulfone for pressure treated wood application.

Clean Up: Use water to clean immension tanks, spray required to remove Moldshield® Sapstain and Mold Confro

Chemical from floors and EVPTED

FASASSEG. No. 60061-127 pesticide registered under Oo not contaminate water, food, or feed by storage STORAGE AND DISPOSAL

Under the Federal Insecticido, Fungicitie

Pesticide Disposal: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide. provide necessary grounding and bonding. Keep containers closed when not in use.

spray mixture, or rinsate is a violation of Federal faw. It these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

(or equivalent) promptly after emptying. Tiple trises as follows. Empty the remaining contents into application equipment or a mix tank. Fill the container 1/s full with water. Replace and tighten closures. Tip container on its side and roll it that and forth resuring at least one complete revolution for 30 seconds. Stand the container on its end but the chart and forth several times. Turn the container over onto its coher and and to it back and forth several times. Turn the container over onto its coher and and to it back and forth several times. Empty the rinsale into application equipment or a mix tank or store rinsale for later use or disposal. Repeat this procedure two more times. Then container. Triple rinse container offer for recycling if available.

Sapstain and Mold Control Product **Moldshield®**

U.S. Patent Number 6,375,727 and 7,056,919, additional patents pending

Aists in the control of blue stain, mold and decay of freshly cut lumber, dry lumber and other wood based products when properly used. Effective on softwoods incitiding Douglas fit, White fit, Syzucut, Hennick, the Pines including both the Southern and Western Pines and many of the hardwoods.

KEEP OUT OF REACH OF CHILDREN

DANGER

Read Warranty on side panel before buying or using. If such terms are not acceptable, return at once unopened. EPA Reg. No. 60061-127 EPA Est. No. 60061-M0-1

phenyl)-4-propyl-1,3-dioxolan-2-yll-methyl-1H-1,2,4-triazole Diodomethyl-para-Tolyl sufronë · · · (Propiconazole) I-[12-(2.4-dichkorophenyl) 4-y (Bropiconazole) I-[12-(2.4-dichkorophenyl) 4-y (Brogoropher) 3-y (Brogoropher) 4-y (Brogor

0.19% 0.70% 0.70% 98.41% 100.00%

	FIRST AID	Hold over and the refusion of the state of t	Tion of copies and the same and sold will water to the transfer. Remove confact tenses,	if present, after the first 5 minutes, then continue rinsing eye.
		·		7,4
١				C IN CVEC

מועדרכוורם	•	Have a person sip a glass of water if able to swallow.
	٠	Do not give anything by mouth to an unconscious person.
	•	Move person to fresh air.
ביאוחעונט	٠	If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably m
ואושרבה		-to-mouth if possible.
	٠	Call a poison control center or doctor for further treatment advice.

Do not induce vomiting unless told to do so by a poison control center or doctor.

Call a poison control center immediately for treatment advice.

	L		
	•	 Have the product container or label with you when calling a poison control center or doctor, or going 	
HOT LINE NUMBERS		for treatment. You may also contact 800-548-0489 for emergency medical treatment information.	
	٠	Transportation emergency contact 800-424-9300.	-
	•.	 Probable mucosal damage may contraindicate the use of gastric leverage. 	1 .
NOTE TO PHYSICIAN	•	NOTE TO PHYSICIAN . • Corrosive to eyes and skin. Continue to flush eyes and skin with water until treatment advice	

5137 Southwest Avenue, St. Louis MO 63110 Protection Products Division

Net Contents

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

absorbed through skin, or inhalad. Do not get in eyes, on skin, or clothing. Avoid breathing vapor or spray mist. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using obacco, or using the totlet. Remove and wash contaminated clothing before reuse.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Mixers and loaders using liquid formulation must wear:

Coveralls over long-sleeved shirl and long pants. Chemical resistant footwear plus socks

Goggles or face shield.

Chemical resistant gloves (such as barrier laminate, nitrile rubber, neoprene rubber and viton.

JSER SAFETY REQUIREMENTS

Follow manufactures instructions for clean/maintaining PPE. If no such instructions exist, use delergent and hot water. Keep and wash PPE separately from other laundry

Discard clothing and other absorbent materials that have been drenched or heavily contaminated with

USER SAFETY RECOMMENDATIONS

Remove clothing/PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean cloth-Wash hands before ealing, drinking, chewing gum, using tobacco, or using the toilet

Remove PPE invnediately after handling this product. As soon as possible, wash thoroughly and change

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic invertebrates. Do not apply directly to water. Do not contaminate water when disposing equipment wastewaters. Do not discharge effluent containing this product into takes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of Environmental Protection Agency. Untif the product has dried, antisapstain treated lumber must be stored under cover, indoors, or at least 100 feet from any pond, lake, stream, wettand, or river to prevent possible runoff of the product into the waterway. Treated lumber stored within 100 feet of a pond, lake stream, or river must be either covered with plastic or surrounded by a berm to prevent surface water runoff into the nearby waterway, if a berm or curb is used around the site, it should consist of impermeable material (clay, asphalt, concrete) and be of sufficient height to prevent runoff

nouth

Keep container closed when not in use. Store in cool, well ventilated space PHYSICAL OR CHEMICAL HAZARDS

IN CASE OF FIRE

Use water spray or fog, foam, dry chemical or carbon dioxide to extinguish fire

We warrant this material to comply with our published specifications and to be of good merchantable quality and such as will regularly pass in the trade for goods within the description, and further warrant such goods LIMIT OF WARRANTY AND LIABILITY

concerned in this contract are fit for any particular purpose for which they are being bought outside of the to be fit for the normal purposes for which goods are used. We assume no responsibility that the goods general purposes of goods of the description.

3380 / 118 / R01 / 010515