

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

WASHINGTON, D.C. 20460

AUG 1 6 2010

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

Kop-Coat Inc. 1850 Koppers Building Pittsburgh, PA 15219

Attention: Kim Treloar

Product Registration Specialist

Subject:

Valvtect- Amendment

EPA Reg. No. 60061-128

Amendment Dated June 8, 2010

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable. The Agency approves the following Amendments to the label:

- Addition of the bullet point, "Contains less than 15 ppm sulfur", on the front panel of the label.
- Change of the brand name to ValvTect Marine Premium Diesel Additive with BioGuard Microbiocide.

A stamped copy of the accepted labeling is enclosed. Submit three copies of your final printed labeling to the Agency before distributing or selling the product bearing the revised labeling.

If you have any questions concerning this letter, please contact Abigail Downs at (703) 305-5259.

Sincerely,

Marshall Swindell Product Manager (33)

Regulatory Management Branch I Antimicrobials Division (7510P)

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with the labeling.

HYDROCARBON FLUIDS

ValvTect Marine Premium Diesel Additive with BioGuard Microbiocide is a highly effective multifunctional premium diesel fuel additive containing BioGuard Microbiocide to prevent bacterial growth in diesel fuel (No. 2 oil, intermediate fuel oil and No.6 oil). Add ValvTect Marine Premium Diesel Additive with BioGuard Microbiocide to storage tanks at a rate of one gallon to 1500Gallons (667ppm) or one quart to 375 gallons of diesel fuel.

SEE TECHNICAL DATA SHEET FOR MORE INFORMATION OR CALL 1-800-728-8258

DOSAGE RATE

Treatment may be performed by stug dosage or intermittent metering. To facilitate mixing by stug dosage, add ValvTect Marine Premium Diesel Additive with BioGuard Microbiocide to the fuel transport or storage tank prior to adding fuel. Storage tank should have a 20% heel of fuel and be free of excess water and /or studge.

ACTIVE INGREDIENTS

4-(2-Nitrobutyl) Morpholine	}	21.8% by wt
4, 4' - (2- Ethyl - 2- nitrotrin	nethylene)	•
Dimorpholine	·····	1.35% by wt
Inert Ingredients		76.85% by wt
•		100.00%

E.P.A. Registration No. 60061-128 E.P.A. Est. 036654 – IL - 001

DANGER KEEP OUT OF REACH OF CHILDREN

PRECAUTIONARY STATEMENTS

HAZARDOUS TO HUMANS AND DOMESTIC ANIMALS
CAUSES SEVERE EYE DAMAGE AND SKIN BURNS. MAY CAUSE
ALLERGIC SKIN REACTION. HARMFUL OR FATAL IF SWALLOWED
OR ABSORBED THROUGH THE SKIN.

Do not get in eyes, skin or clothing. Causes skin sensitization. Wear goggles and/or face shield and chemical - resistant gloves when handling. Wash thoroughly after handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally.

PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE: Do not use, or store near heat or open flame.

STORAGE AND DISPOSAL

Pesticide Disposal: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticides, spray mixture, or rinseate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

Pesticide Storage: Do not contaminate water, food, or feed by storage or disposal. Store in a cool dry place in

tightly closed original containers. Keep container tightly closed when not in use. Leaking or damaged drums should be placed in over pack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

Container Disposal: Nonrefillable Container: Do not reuse or refill this container. Triple rinse or pressure rinse container (or equivalent) promptly after emptying. Then offer for recycling, if available or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities by burning. If burned, stay out of smoke...

ValvTect Marine Premium Diesel Additive with BioGuard Microbiocide

- CONTAINS BIOGUARD BIOCIDE
- PREVENTS BACTERIA GROWTH
- INCREASES CETANE NUMBER
- CLEANS UP INJECTOR DEPOSITS
- LUBRICATES PUMPS & INJECTORS
- STABILIZES FUEL & PREVENTS SLUDGE
- PREVENTS RUST & CORROSION
- DISPERSES WATER
- CONTAINS NO ALCOHOL
- CONTAINS LESS THAN 15 PPM SULFUR

FIRST AID:	
If in Eyes	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice
If Swallowed	Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor.
lf on Skin	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment.
if inhaled	Move person to fresh air. If person is not breathing, call 911 or an ambulance and then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment
	HOT LINE NUMBER

IN CASE OF EMERGENCY endangering life or property involving this product, call toll free: 1-800-548-0489. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

Note to Physician: Contains petroleum distillate. Vomiting may cause aspiration pneumonia and probable mucosal damage may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System(NPDES) permit and the permitting authority has been notified in writing prior to the discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Notice: Seller warrants that the product conforms to its chemical description as contained on this label and is reasonably fit for the purposes stated on this Label when used in accordance with directions under normal conditions of use. THE WARRANTIES MADE IN THIS PARAGRAPH ARE SELLER'S SOLE WARRANTIES WITH RESPECT TO THE PRODUCT AND ARE MADE EXPRESSLY IN LIEU OF AND EXCLUDE ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER EXPRESS OR IMPLIED REPRESENTATIONS AND WARRANTIES.

This diesel fuel additive complies with the federal low sulfur content requirements for use in diesel motor vehicles and non-road engines.

ACCEPTED with COMMENTS EPA Letter Dated:

AUG 16 2010

KOP-COAT Inc. ValvTectPetroleum Products Div Northbrook, IL. 60062 800-728-8258 www.valvtect.com

55 GALLONS/208 L

VMD550410

((())) (() (()) (() (()) (() (()) (() (()) (() (()) (() (()) (()) (() (()) (()) (()) (() (()) (()) (()) (()) (()) (()) (()) (() (()) (()) (()) (() (()) (()) (()) (()) (() (()) (()) (()) (()) (()) (() (()) (()) (()) (() (()) (()) (()) (()) (()) (() (()) (()) (()) (()) (()) (()) (() (())

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 6006 1-128

