



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

October 23, 2018

Sandy Lea  
Pesticide Registrar  
Kop-Coat, INC.  
3040 William Pitt Way  
Pittsburg, PA 15238

Subject: Label Amendment – Minor Label Modifications  
Product Name: Pettit Ultima SSA LD Ablative Antifouling Paint  
EPA Registration Number: 60061-132  
Application Date: October 23, 2018  
Decision Number: 545294

Dear Mr. Lea:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance

Page 2 of 2  
EPA Reg. No. 60061-132  
Decision No. 545294

with FIFRA section 6. If you have any questions, you may contact Joe Daniels at (703) 347-8669 or via email at [daniels.joseph@epa.gov](mailto:daniels.joseph@epa.gov).

Sincerely,

A handwritten signature in blue ink that reads "E. Miederhoff". The signature is written in a cursive style with a large, stylized initial "E".

Eric Miederhoff  
Product Manager 31  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

Enclosure

**ACCEPTED**

10/23/2018

Under the Federal Insecticide, Fungicide  
and Rodenticide Act as amended, for the  
pesticide registered under  
EPA Reg. No. 60061-132



## ULTIMA SSA LD ABLATIVE ANTIFOULING PAINT

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company ("Pettit"), including surface preparation, proper application, and environmental conditions. Therefore, Pettit cannot guarantee this product's suitability for your particular purpose of application. To the extent consistent with applicable law, Pettit EXPRESSLY DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE or otherwise that extend beyond the statements made on this label, and shall not be liable for special, incidental, or consequential damages resulting from the use or handling of this product, the exclusive remedy being the replacement of the product or refund of the purchase price of the product, at Pettit's sole discretion. To the extent consistent with applicable law, buyer/user assumes all risk of possession, handling, or use this material when use and/or handling is contrary to label instructions.

- **Uses Low Density Copper Technology**
- **Economical Antifouling Protection**
- **Economical hybrid protection**
- **Smooth durable polishing finish**
- **Apply Over Most Other Antifouling**
- **Excellent for Fiberglass, Wood & Steel Boats**

**[1882 Black, 1282 Blue, 1382 Green, 1682 Red]**

COMMERCIAL AND NON-COMMERCIAL USE  
KEEP OUT OF REACH OF CHILDREN  
**WARNING**

COMBUSTIBLE LIQUID AND VAPOR. VAPOR HARMFUL.  
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

NET CONTENTS  
1 GAL. (128 FL. OZ.)  
3.785 LITERS

**ACTIVE INGREDIENTS:**

Cuprous Oxide\* (CAS# 1317-39-1) 23.70%

**OTHER INGREDIENTS:**

Total 76.30%  
100.00%

\*Metallic copper equivalent 21.05%

Contains petroleum distillates, xylene or xylene range aromatic solvents.

EPA EST. NO. 60061-NJ-2  
EPA REGISTRATION NO. 60061-132

KOP-COAT, INC.  
36 PINE STREET  
ROCKAWAY, NJ 07866

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC  
ANIMALS**

**WARNING:** May be fatal if swallowed. May be fatal if inhaled. Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Do not breathe vapors, spray mist or sanding dust. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.

**Personal Protective Equipment:** Mixers, loaders, applicators and other handlers must wear the following: protective eye wear such as goggles or face shield, chemical resistant gloves such as Nitrile Rubber Gloves greater than 14 mils thick, long sleeved shirt, long pants, and shoes plus socks, a disposable cover all with hood and chemical resistant footwear while removing existing paint by sanding or blasting, or applying new antifoulant paint. Users must wear a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C), or a canister approved for pesticides (NIOSSH approval number prefix TC-23C), or a canister approved for pesticides (NIOSH approval number TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-200 prefilter, while removing existing paint by sanding or blasting, or applying new antifoulant paint. If no such instructions for washables exist, user detergent and hot water. Keep and wash PPE separately from other laundry. Discard clothing and other absorbent material that have been drenched or heavily contaminated with prod product's concentrate. Do not reuse them.

**ENVIRONMENTAL  
HAZARDS**

This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact you State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE.** Do not use or store near heat or open flame. Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO2 or dry chemical. Wear NIOSH certified breathing equipment.

**FIRST AID**

<b>IF SWALLOWED:</b>	<ul style="list-style-type: none"> <li>• Call a poison control center or doctor immediately for treatment advice.</li> <li>• Do not give any liquid to the person.</li> <li>• Do not induce vomiting unless told to do so by a poison control center or doctor.</li> <li>• Do not give anything by mouth to an unconscious person.</li> </ul>
<b>IF IN EYES:</b>	<ul style="list-style-type: none"> <li>• Hold eye open and rinse slowly and gently with water for 15 – 20 minutes.</li> <li>• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye</li> <li>• Call a poison control center or doctor for treatment advice.</li> </ul>
<b>IF ON SKIN OR CLOTHING:</b>	<ul style="list-style-type: none"> <li>• Take off contaminated clothing.</li> <li>• Rinse skin immediately with plenty of water for 15-20 minutes.</li> <li>• Call a poison control center or doctor for treatment advice.</li> </ul>
<b>IF INHALED:</b>	<ul style="list-style-type: none"> <li>• Move person to fresh air.</li> <li>• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.</li> <li>• Call a poison control center or doctor for further treatment advice.</li> </ul>

**HOT LINE  
NUMBER**

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.

**NOTE TO  
PHYSICIAN**

Contains petroleum distillate. Vomiting may cause aspiration pneumonia.

### STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

**Pesticide Storage:** Store in a closed, properly labeled container in a cool place. Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

**Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

**Container Disposal:** Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

### NOTICE! THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

### DIRECTION S FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**Product Description:** This product's durable hybrid surface resists paint buildup by slowly polishing which constantly exposes a fresh surface for economical antifouling protection. The controlled erosion minimizes coating buildup and keeps underwater surfaces smooth and clean. This product may be applied on all boats substrates except aluminum. This product is for use in fresh, salt or brackish water on hulls below the waterline and prevents attachment of hard fouling such as barnacles, and other fouling organisms. This paint is intended for use on vessels of any size. (or) This product uses the latest developments in copper technology. Composite cuprous oxide contains the same level of copper by volume as traditional cuprous oxide but at a much lower weight and therefore less copper by weight is needed to provide maximum protection from fouling of all kinds. Low density copper guards against attachment of barnacles, annelids, tunicates, bryozoa, hydroids, algae and other fouling organisms. This product applies easily and dries quickly. It may be used over old antifouling finishes in good condition. This product is ideal for fiberglass, wood and properly primed steel boats.

**Compatibility:** This product may be applied over most aged hard antifouling coatings. Old soft antifouling paints must be completely removed before applying this product. The paint systems outlined below contain references to other Pettit products. Please read and understand the label and/or Technical Bulletin for these products as well to ensure that they are used properly. (or) This product may be applied over most aged hard and soft antifouling coatings. Old tin copolymers and Teflon finishes must be completely removed before applying this product.

**Mixing:** It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all the pigment has been mixed in. If mixing is going to be done

with a wooden paddle or an electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment, then remix the two parts together thoroughly.

**Application Temperatures:** 40°F to 90°F. (or) 40°F and above.

**Application Method:** Brush, roller, airless or conventional spray.

**Thinner:** 120 Brushing Thinner. Thinning this product is not normally required. If thinning is necessary, use Pettit 120 Brushing Thinner for a smoother finish on especially warm and breezy days. Use Pettit 121 Spraying Thinner for spray application. Do not thin more than 10% by volume (12 ounces per gallon), or inadequate paint film thickness may result in premature erosion of the finish. Use any of the above thinners for clean-up.

**Coverage:** 500 square feet per gallon.

**Number of Coats:** Two or three coats should be applied for best antifouling protection. Do not apply this product if rain or dew is expected before the surface has dried completely.

<b>Dry Times:</b>	To recoat	To launch
90°F	2 hours	2 hours
70°F	3 hours	4 hours
50°F	6 hours	8 hours

The above dry times are minimums. This product may be recoated and launched after the minimum times shown. There is no maximum dry time before launching.

**VOC:** Less than 320 grams/liter (2.67 lbs/gallon) as supplied

**Maintenance Of Antifouling Paint:** No antifouling paint can be effective under all conditions of exposure. Man-made pollution and natural occurrences can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, silt, dirt, oil, brackish water and even electrolysis can ruin an antifouling paint.

Therefore, we strongly suggest that the bottom of the boat be checked regularly to make sure it is clean and that

no growth is occurring. The self-cleaning nature of the coating is most effective when the boat is used periodically. Boats and vessels should not be scrubbed or cleaned for the first six months in the water and at intervals of not less than 3 months thereafter.

## SYSTEMS

Mix paint thoroughly to ensure toxicants are evenly dispersed throughout the can. All surfaces must be clean, dry and properly prepared prior to painting.

**Previously Painted Surfaces:** If the previous coating is in good condition thoroughly sand with 80 grit paper then solvent clean with Pettit 120 Brushing Thinner to remove sanding residue. Apply two coats of this product observing the proper dry times. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using paint and varnish remover. Proceed with the appropriate bare system as described below. Old tin copolymer paints must be removed or may be sealed with Pettit 6627 Tie-Coat Primer before applying this product.

**Bare Fiberglass:** All bare fiberglass, regardless of age, must be thoroughly cleaned and de-waxed with Pettit 92 Bio- Blue Hull Surface Prep or de-waxed several times with Pettit D95 Dewaxer. Sand thoroughly with 80 grit sandpaper to a dull, frosty finish and rewash the sanded surface with 120 Brushing Thinner to remove sanding residue. Then apply two coats of this product, following application instructions.

To eliminate the sanding operation, two methods are available:

1. Clean and de-wax the surface as described above, apply one very thin coat of 6998 Skip-Sand Primer using 3/16" or less nap roller or brush apply. Consult the primer label for complete application and antifouling top-coating instructions. Then apply two coats of this product or
2. Clean, de-wax and etch the surface with 92 Bio-Blue Hull Surface Prep using a coarse Scotchbrite® pad in a swirling motion. Clean off all residue by rinsing or wiping off with fresh water. Apply one coat of Pettit Protect Epoxy Primer. Consult the primer labels for complete application and antifouling top-coating instructions. Then apply two coats of this product.

**Bare Wood:** Sand the entire surface with 80 grit paper and wipe clean with a rag dampened with 120 Brushing Thinner. Apply a coat of this product thinned 25% with 120 Brushing Thinner to penetrate and seal the wood. Fill any open seams with Pettit Seam Compound and allow to dry overnight. Apply two full coats of this product observing the proper dry times.

**Steel Hulls, Underwater Metal Parts and Keels:** For steel hulls and metal keels, consult Pettit Technical Bulletin TB431 High Build Epoxy Primer for complete priming instructions or consult the Pettit Technical Department or your local Pettit representative. For underwater metal parts, consult Technical Bulletin TB112 Underwater Running Gear Painting Specification for complete priming and application details.

**All Other Substrates:** Please go to [www.pettipaint.com](http://www.pettipaint.com) and consult the product data sheet.

## DO NOT USE THIS PRODUCT ON ALUMINUM HULLS OR OUTDRIVES

**Warranty:** We guarantee this material to comply with our published specifications. Since the use of this material is beyond our control, we disclaim responsibility for its handling, use, storage, the results obtained or any injury or damage of any nature resulting therein to the extent consistent with State law.

**MEDICAL EMERGENCIES: 1-800-548-0489**      Manufactured in the United States  
**PRODUCT INFORMATION: 1-800-221-4466 or WWW.PETTIT PAINT.COM**