



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

July 25, 2017

Angie Custer
Regulatory Affairs Specialist
Kop-Coat, Inc.
3040 William Pitt Way
Pittsburgh, PA 15238

Subject: Notification per PRN 98-10 – To update Storage and Disposal language
Product Name: Pettit Ultima ECO Ablative Antifouling Paint
EPA Registration Number: 60061-134
Application Date: March 13, 2017
Decision Number: 527334

Dear Ms. Custer:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact Emilia Oiguenblik by phone at 703 347 0199, or via email at Oiguenblik.emilia@epa.gov or Eric Miederhoff by phone at 703 347 8028, or via email at Miederhoff.eric@epa.gov.

Sincerely,

A handwritten signature in blue ink that reads "E. Miederhoff". The signature is written in a cursive style with a large, stylized initial "E".

Eric Miederhoff
Product Manager 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

ELM621026

802511

PETTIT



NOTIFICATION

60061-134

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

07/25/2017



DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company, including surface preparation, proper application and environmental conditions. Therefore, Pettit Paint Company cannot guarantee the product's suitability for your particular purpose of application. Implied warranties of fitness for a particular purpose and of merchantability are excluded to the extent consistent with State law. Pettit Paint Company shall not under any circumstances be liable for incidental or consequential damages by purchase or use of this product, even if caused by the sale and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Pettit Paint's option.

Ultima ^{eco}

ABLATIVE ANTIFOULING PAINT

- Uses Copper-Free Technology
- Dual Biocide to Control Hard and Soft Fouling
- Clean, Bright Colors
- Economical Antifouling Protection

1808 BLACK

KEEP OUT OF REACH OF CHILDREN.

WARNING
COMBUSTIBLE LIQUID AND VAPOR. VAPOR HARMFUL.
HARMFUL OR FATAL IF SWALLOWED.
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

NET CONTENTS
1 GALLON (128 FL. OZ.)
3.785 LITERS



ACTIVE INGREDIENT:

Triacrylate	6.00%
Zinc Pyrithione	4.50%
OTHER INGREDIENTS	89.50%
TOTAL	100.00%

Contains petroleum distillates, xylene or xylene range aromatic solvents.

EPA REG. NO. 0209-0412

EPA REGISTRATION NO. 62081-014

TOP COAT INC.
3006 W. STREET
RICHMOND, VA 23260

PRECAUTIONARY STATEMENTS

HAZARD TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes substantial but temporary eye injury. Causes skin irritation. Do not get in eyes, on skin, or on clothing. Avoid breathing spray mist, vapors or sanding dust. While spraying and/or sanding boat surfaces, wear a NIOSH certified mask or respirator. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Wear coveralls worn over long-sleeved shirt and long pants, chemical resistant gloves, protective eyewear (goggles, face shield or safety glasses), socks, and chemical resistant footwear. Remove contaminated clothing and wash clothing before reuse. May pose an aspiration pneumonia hazard.

For application by professional commercial users: Do not apply to passenger, Ducted propellers, transducers or propellers within 24 hours. Apply only to outdoor, non-enclosed spaces. Residential (non-commercial) users are advised to wear chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks and shoes. In addition to these minimum Personal Protective Equipment (PPE), commercial users must wear a disposable coverall with hood and chemical resistant footwear.

While removing existing paint by sanding or blasting, or applying new ablative paint, commercial users must wear a minimum of full face NIOSH approved respirator (1.5A4) with a organic vapor cartridges with any P or combination filter. Higher level respirators that are NIOSH Approved for organic vapors and particulates that contain oil can also be used. Residential (non-commercial) users are advised to wear the same respirators, cartridged sandpro- filters as required by commercial users.

FIRST AID

IF EYE:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

IF SWALLOWED:

- Call a poison control center or doctor immediately for treatment advice.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not get any liquid in the mouth.
- Do not give anything by mouth to an unconscious person.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.
- Call a poison control center or doctor for further treatment advice.

IF ON SKIN OR CLOTHING:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15 - 20 minutes.
- Call a poison control center or doctor for treatment advice.

NOTICE

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-6888 for emergency medical treatment information.

NOTE TO PHYICIAN

Probable mucosal damage may contraindicate the use of gastric lavage. This product contains petroleum distillates. Avoiding eye contact is essential to avoid eye injury.

ENVIRONMENTAL HAZARD: This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer system without previously notifying the local sewage treatment plant. For further information see State Water Board or Regional Office of the EPA. **PHYSICAL OR CHEMICAL HAZARD:** Combustible. Do not use or store near heat or open flame. Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires, blanked flames with foam, CO₂ or dry chemical. Wear NIOSH/MSHA certified breathing equipment.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage and disposal. Open dumping is prohibited. **PESTICIDE STORAGE:** Store in a closed, properly labeled container in a cool place. Keep children, pets and animals away from this product. Do not use. In case of spillage, absorb and dispose of in accordance with local applicable regulations. **PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or waste is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

Container Disposal: Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to dry fully. Dispose of the container in accordance with Federal, State or local disposal regulations.

NOTE: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HAZARD. GENERAL PRECAUTIONS: Do not breathe dust. Avoid skin contact. Do not get on clothes. Wash hands after use. Do not eat, drink or smoke while using. Do not get in eyes. Do not get on face. Do not get on children's hands. Do not use in enclosed areas. Do not use on food. Do not use on animals. Do not use on plants. Do not use on children's toys. Do not use on children's furniture. Do not use on children's clothing. Do not use on children's shoes. Do not use on children's bedding. Do not use on children's bath towels. Do not use on children's bath mats. Do not use on children's bath toys. Do not use on children's bath sponges. Do not use on children's bath brushes. Do not use on children's bath brushes. Do not use on children's bath brushes.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. **PREPARATION OF SURFACE:** The surface to be painted should be clean, dry and free of any contamination or foreign matter. Always prepare the surface to be painted by sanding and solvent cleaning before any primers or paints are applied. When sanding and/or blasting paint use a dust mask to prevent the inhalation of sanding dust. Oil, salt and other contaminants should be removed before applying.

COVERAGE, APPLICATION AND TEMPERATURE: The product can be applied by brush or short nap roller. All painting should be done between 50°F and 90°F in order to avoid the possibility of dew or condensation spoiling the application. The temperature range of application should be between 50 and 90°F. At least two, and preferably three coats, should be applied for best performance, particularly in high wear areas such as the hull. This product will cover approximately 100 square feet per gallon when applied at 2.0 dry mils film thickness.

PREPARATION OF PAINT: This product may exhibit pigment settling, especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all the pigment has been mixed in. If mixing is going to be done with a wooden paddle or an electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment, then return the two parts together thoroughly.

THINNING: Use Pettit 100 Brushing Thinner for thinning this product if needed, particularly on warm or breezy days. Do not thin more than 10% (12 ounces per gallon) or inadequate paint film thickness will occur and premature erosion of the finish will be likely.

DRY TIMES:

To moist	To launch
90°F	2 hours
70°F	3 hours
50°F	6 hours

The above dry times are minimums. This product may be recoated and launched after the minimum times shown. There is no maximum time before launching.

SYSTEM: Mix paint thoroughly to ensure ingredients are evenly dispersed throughout the can. All surfaces must be clean, dry and completely prepared prior to painting. **PREVIOUSLY PAINTED SURFACES:** If the previous coating is in good condition, thoroughly sand with 80-grit sandpaper to a dull, frosty finish and resawn the sanded surface with fresh water to remove sanding residue. Then apply two coats of the product following application instructions. Careful observation of the above instructions will help ensure long-term adhesion of this and subsequent years' antifouling paint. To eliminate the sanding operation, scrub the surface using 50 Bio-Blue Pre-Paint Cleaner and a coarse Scotch-Steel pad. Clean-up all residue with fresh water and allow the hull to dry thoroughly. Then apply one coat of Pettit 6956 Slip Sand Primer. Read and follow carefully the application and topcoating instructions on the Slip Sand Primer label. Apply at least two coats of this antifouling paint. **BARE ALUMINUM:** Scuffblast to clean, bright metal and remove blasting residue with clean, dry compressed air or a clean brush. Immediately apply three coats of Pettit 4000/401 Alumina Protect Epoxy Primer followed by two finish coats of this product. Read and follow carefully the instructions on the Pettit 4000/401 Alumina Protect Epoxy Primer label. If the surface to be painted is smooth aluminum, apply one coat of 6952/6954 Metal Primer and allow to dry for 2 hours. Then apply two finish coats of this product. Read and follow carefully the instructions for application and topcoating on the 6952/6954 primer label.

Medical Emergencies: 1-800-548-6888
Product Information: 1-800-221-4408
Manufactured in the United States, P-3559, 180 GA, 09/11

50-629 gal 4/c
Cyan Mag Yel Black

50-629 gal

08/20/13