



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

April 13, 2023

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

Sandy Lea
Authorized Representative
Kop-Coat Inc.
436 Seventh Avenue
Pittsburgh, PA 15219
Electronic Transmittal: slea@pettitpaint.com

Subject: Notification per PRN 98-10 – Additional language specific to paint products
Product Name: Petit Ultima Eco Ablative Antifouling Paint
EPA Registration Number: 60061-134
Received Date: 08/06/2020
Action Case Number: 00218100

Dear Sandy:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Assurance.

If you have any questions, please contact Melanie Bolden at (202) 566-0674 or by email at Bolden.Melanie@epa.gov.

Best,

A handwritten signature in cursive script that reads "Melanie Bolden for".

Demson Fuller, Product Manager 32
Antimicrobials Division (7510P)
Regulatory Management Branch I
Office of Pesticide Programs



ULTIMA ECO

ABLATIVE ANTIFOULING PAINT

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company ("Pettit"), including surface preparation, proper application, and environmental conditions. Therefore, Pettit cannot guarantee this product's suitability for your particular purpose of application. To the extent consistent with applicable law, Pettit EXPRESSLY DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE or otherwise that extend beyond the statements made on this label, and shall not be liable for special, incidental, or consequential damages resulting from the use or handling of this product, the exclusive remedy being the replacement of the product or refund of the purchase price of the product, at Pettit's sole discretion. To the extent consistent with applicable law, buyer/user assumes all risk of possession, handling, or use this material when use and/or handling is contrary to label instructions.

NET CONTENTS
1 GAL. (128 FL. OZ.)
3.785 LITERS

- **Uses Copper Free Technology**
- **Dual Biocide to Control Hard and Soft Fouling**
- **Clean, Bright Colors**
- **Economical Antifouling Protection**
- **Economical hybrid protection**
- **Smooth durable polishing finish**
- **For Pontoon Boats and Aluminum Hulls**
- **Copper-Free Ablative Antifouling Paint**
- **Apply over most antifouling paints**

KEEP OUT OF REACH OF CHILDREN
WARNING
COMBUSTIBLE LIQUID AND VAPOR.
VAPOR HARMFUL.
HARMFUL OR FATAL IF SWALLOWED.
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

NOTIFICATION

60061-134

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

04/13/2023

ACTIVE INGREDIENT:

Tralopyril	6.00%
Zinc Pyrithione	4.80%
INERT INGREDIENTS:	89.20%
TOTAL	100.00%

Contains petroleum distillates, xylene or xylene range aromatic solvents.

EPA EST. NO. 60061-NJ-2
EPA REGISTRATION NO. 60061-134

KOP-COAT, INC.
36 Pine Street
ROCKAWAY, NJ 07866

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes substantial but temporary eye injury. Causes skin irritation. Do not get in eyes, on skin, or on clothing. Harmful if swallowed. Harmful if inhaled. Avoid breathing spray mist, vapors, or sanding dust.

Personal Protective Equipment: Mixers, loaders, applicators and other handlers must wear the following: protective eye wear such as goggles or face shield, chemical resistant gloves such as Nitrile Rubber Gloves greater than 14 mils thick, long sleeved shirt, long pants, and shoes plus socks, a disposable cover all with hood and chemical resistant footwear while removing existing paint by sanding or blasting, or applying new antifoulant paint. Users must wear a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (NIOSH approval number prefix TC-23C), or a canister approved for pesticides (NIOSH approval number prefix TC-23C), or a canister approved for pesticides (NIOSH approval number TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-200 prefilter, while removing existing paint by sanding or blasting, or applying new antifoulant paint. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Discard clothing and other absorbent material that have been drenched or heavily contaminated with product's concentrate. Do not reuse them. May pose an aspiration pneumonia hazard.

FIRST AID	
IF IN EYES:	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
IF SWALLOWED:	Call a poison control center or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.
IF INHALED:	Move person to fresh air. If person is not breathing, call 911 or an ambulance then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.
IF ON SKIN OR CLOTHING:	Take off contaminated clothing. Rinse skin immediately with plenty of water of 15-20 minutes. Call a poison control center or doctor for treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Probable mucosal damage may contraindicate the use of gastric lavage. This product contains petroleum distillates. Vomiting may cause aspiration pneumonia.	

ENVIRONMENTAL HAZARDS: This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE! Do not use or store near heat or open flame. Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO₂ or dry chemical. Wear NIOSH certified breathing equipment.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

Pesticide Storage: Store in a closed, properly labeled container in a cool place. Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

Container Disposal: Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

VOC: (as supplied) 324 grams/liter maximum.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Product Description: This product is a copper free antifouling protective coating resistant to slime, algae, barnacles and other marine and freshwater fouling organisms. This product's state-of-the-art organic biocide technology coupled with a unique abrasive vehicle minimizes coating build-up and keeps underwater surfaces smooth and clean. This product is for use in fresh, salt or brackish water on hulls and underwater parts below the waterline. This paint is intended for use on recreational and commercial vessels of any size. This product's durable hybrid surface resists paint buildup by slowly polishing which constantly exposes a fresh surface for economical copper free antifouling protection. The controlled erosion minimizes coating buildup and keeps underwater surfaces smooth and clean. This product may be applied on all boat substrates including Pontoon boats and other aluminum vessels. This product is for use in fresh, salt or brackish water on hulls and metal parts below the waterline and resists algae, barnacles, other fouling organisms.

Surface Preparation: The surface to be painted should be dry, clean and free of any contaminants. It should be properly prepared by solvent cleaning and sanding before any primers or paints are applied. Follow the recommended systems below. When sanding old antifouling paint, always wear Personal Protective Equipment (PPE) as described above to prevent the inhalation of sanding dust.

COVERAGE, APPLICATION AND TEMPERATURE: This product can be applied by brush, short nap roller or spray. All painting should be done between 9:00 a.m. and 4:00 p.m. in order to avoid the possibility of dew or condensation spoiling the application. The temperature range of application should be between 50 and 90°F. Two coats should be applied for best performance, particularly in high wear areas such as the waterline. This product will cover approximately 500 square feet per gallon when applied at 2 dry mils film thickness.

PREPARATION OF PAINT: This product may exhibit pigment settling, especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all the pigment has been mixed in. If mixing is going to be done with a wooden paddle or an electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment, then remix the two parts together thoroughly.

THINNER/CLEAN-UP: Use Pettit 120 Brushing Thinner if needed. Do not thin more than 10% (12 ounces per gallon).

DRY TIMES:	To recoat	To launch
90°F	1 hour	2 hours
70°F	2 hours	4 hours
50°F	4 hours	8 hours

The above dry times are minimums. This product may be recoated and launched after the minimum times shown. There is no maximum time before launching.

SYSTEMS

Mix paint thoroughly to ensure toxicants are evenly dispersed throughout the can. All surfaces must be clean, dry and properly prepared prior to painting.

PREVIOUSLY PAINTED SURFACES: If the previous coating is in good condition, thoroughly sand with 80-grit sandpaper, then solvent clean with Pettit 120 Brushing Thinner to remove residue. Apply two finish coats of this product. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using a paint and varnish remover. Proceed with appropriate bare system as described below.

BARE FIBERGLASS: All bare fiberglass, regardless of age, should be thoroughly cleaned several times with 92 Bio-Blue Pre-Paint Cleaner following the instruction of the Bio-Blue can. Sand thoroughly with 80-grit sandpaper to a dull, frosty finish and rewash the sanded surface with fresh water to remove sanding residue. Then apply two coats of this product following application instructions. Careful observation of the above instructions will help ensure long-term adhesion of this and subsequent years' antifouling paint. To eliminate the sanding operation, scrub the surface using 92 Bio-Blue Pre-Paint Cleaner and a coarse Scotch-Brite® pad. Clean-up all residue with fresh water and allow the hull to dry thoroughly. Then apply one coat of Pettit Protect 4700/4701. Read and follow carefully the application and topcoating instructions on the Skip Sand Primer label. Apply two coats of this antifouling paint.

BARE ALUMINUM: Sandblast to clean, bright metal and remove blasting residue with clean, dry compressed air or a clean brush. Immediately apply three coats of Pettit 4400/4401 Aluma Protect Epoxy Primer followed by two finish coats of this product. Read and follow carefully the instructions on the Pettit 4400/4401 Aluma Protect Epoxy Primer label.

MAINTENANCE OF ANTIFOULING PAINT: No antifouling paint can be effective under all conditions of exposure. Man-made pollution and natural occurrences can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, silt, dirt, oil, brackish water and even electrolysis can ruin an antifouling paint. Therefore, we strongly suggest that the bottom of the boat be checked regularly to make sure it is clean and that no growth is occurring. The self-cleaning nature of the coating is most effective when the boat is used periodically. Boats and vessels should not be scrubbed or cleaned for the first six months in the water and at intervals of not less than 3 months thereafter.

MEDICAL EMERGENCIES: 1-800-548-0489

Manufactured in the United States
P35-- 1108 GA 06/18

PRODUCT INFORMATION: 1-800-221-4466 or WWW.PETTITPAINT.COM

Warranty: We guarantee this material to comply with our published specifications. Since the use of this material is beyond our control, we disclaim responsibility for its handling, use, storage, the results obtained or any injury or damage of any nature resulting therein to the extent consistent with State law, when not used as directed.