



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

July 25, 2017

Angie Custer
Regulatory Affairs Specialist
Kop-Coat, Inc.
3040 William Pitt Way
Pittsburgh, PA 15238

Subject: Notification per PRN 98-10 – To update Storage and Disposal language
Product Name: Pettite Hydrocoat SR Dual-Biocide Ablative Antifouling
EPA Registration Number: 60061-136
Application Date: March 13, 2017
Decision Number: 527360

Dear Ms. Custer:


The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact Emilia Oiguenblik by phone at 703 347 0199, or via email at Oiguenblik.emilia@epa.gov or Eric Miederhoff by phone at 703 347 8028, or via email at Miederhoff.eric@epa.gov.

Sincerely,

A handwritten signature in blue ink that reads "E. Miederhoff". The signature is written in a cursive style with a large, stylized initial "E".

Eric Miederhoff
Product Manager 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs



NOTIFICATION

60061-136

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

07/25/2017

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company, including surface preparation, proper application and environmental conditions. Therefore, Pettit Paint Company cannot guarantee this product's suitability for your particular purpose of application. Implied warranties of fitness for a particular purpose and of merchantability are excluded to the extent consistent with State law. Pettit Paint Company shall not under any circumstances be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Pettit Paint's option.

HYDROCOAT SR

DUAL-BIOCIDEABLATIVE ANTIFOULING

- **Dual Biocides Provide Multi-Season Protection**
- **Uses Copper Composite Technology**
- **Easy Cleanup with Soap & Water**
- **Dual Biocides Control Hard and Soft Growth**
- **Reduces Paint Buildup Through Controlled Erosion**
- **Water-Based Formula**
- **Ablative Technology Eliminates Sanding & Paint Build-Up**

ACTIVE INGREDIENT:

Cuprous Oxide	25.25%
N-Cyclopropyl-N'(1,1-dimethylethyl)-6-(methylthio)-1,3,5 triazine-2 4-diamine	2.00%

OTHER INGREDIENTS:	<u>72.75%</u>
TOTAL	100.00%

Metallic Copper Equivalent	22.42%
----------------------------	--------

Contains petroleum distillates, xylene or xylene range aromatic solvents.

NET CONTENTS
1 GAL. (128 FL. OZ.)
3.785 LITERS

KEEP OUT OF REACH OF CHILDREN

WARNING

CAUSES EYE IRRITATION. HARMFUL IF ABSORBED THROUGH SKIN. MAY BE FATAL IF SWALLOWED OR INHALED.
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

EPA EST. NO. 60061-NJ-2
EPA REGISTRATION NO. 60061-136

KOP-COAT, INC.
36 PINE STREET
ROCKAWAY, NJ 07866

General Description: This product is an abrasive antifouling coating designed to polish away at a controlled rate, constantly exposing a fresh surface for aggressive multi-season antifouling protection. The high loading of cuprous oxide in the formula with the addition of a second biocide enables the paint to perform well in even the most severe fouling areas. The controlled erosion minimizes coating buildup and keeps underwater surfaces smooth and clean. This product is effective against algae, barnacles, and other marine and freshwater fouling organisms.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Coverage, Application and Temperature: This product can be applied by brush, roller or spray. All painting should be done between 9:00 a.m. and 4:00 p.m. in order to avoid the possibility of dew or condensation spoiling the application. The temperature range of application should be between 50 and 90°F. At least two coats should be applied for best performance, particularly in high wear areas such as the waterline. This product will cover approximately 450 square feet per gallon when applied at 2 dry mils film thickness.

Preparation of Paint: It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all the pigment has been mixed in. If mixing is going to be done with a wooden paddle or an electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment, then remix the two parts together thoroughly.

Thinning: Thinning this product is not normally required. If thinning is necessary, use clean water only. Do not thin more than 10% (12 ounces per gallon) or inadequate paint film thickness will occur and premature erosion of the finish will be likely. Use clean water for cleaning up equipment.

Dry Times: The minimum recoat time is 3 hours. The minimum dry time between the final coat and launching is 16 hours. Under adverse drying conditions such as those encountered on cool or damp days extend the dry times by 50% in order to ensure that all the solvent is out of the paint film. There is no maximum dry time before launching.

SYSTEMS

Previously Painted Surfaces: If the previous coating is in good condition, thoroughly sand with 80-grit sandpaper, then solvent clean with Pettit 120/T-10 Brushing Thinner to remove residue. Apply two finish coats of this product. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using a paint and varnish remover. Proceed with appropriate bare system as described below.

Bare Fiberglass: All bare fiberglass, regardless of age, should be thoroughly cleaned and de-waxed with 92 Bio-Blue Hull Surface Prep or de-waxed several times with Pettit D-95 De-waxer. Sand thoroughly with 80 grit sandpaper to a dull, frosty finish and rewash the sanded surface with 120 Brushing Thinner to remove sanding residue. Then apply two coats of this product, following application instructions.

To eliminate the sanding operation, two methods are available:

1. Clean and de-wax the surface as described above, apply one very thin coat of 6998 Skip-Sand Primer using a 3/16" or less nap roller or brush, apply. Consult the primer label for complete application and antifouling top coating instructions. Then apply 2 coats of this product or
2. Clean, de-wax and etch the surface with 92 Bio-Blue Hull Surface Prep using a course Scotch-Brite pad in a swirling motion. Apply one coat of Pettit Protect Epoxy Primer. Consult the primer labels for complete application and antifouling top coating instructions. Then apply 2 coats of this product.

Underwater Running Gear: Use Pettit 6456 Underwater Metal Kit following all instructions before applying this product.

All Other Substrates: Please go to www.pettitpaint.com and consult the product data sheet

DO NOT USE THIS PRODUCT ON ALUMINUM HULLS OR OUTDRIVES.

Maintenance of Antifouling Paint: No antifouling paint can be effective under all conditions of exposure. Man-made pollution and natural occurrences can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, silt, dirt, oil, brackish water and even electrolysis can ruin an antifouling paint. Therefore, we strongly suggest that the bottom of the boat be checked regularly to make sure it is clean and that no growth is occurring. Lightly wipe the bottom with a soft cloth or sponge to remove anything from the antifouling paint surface. Wiping is particularly important with boats that are idle for extended periods of time. The self-cleaning nature of the product is most effective when the boat is used periodically.

VOC: (as supplied) 150 grams/liter maximum.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye irritation. Harmful if absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapors, spray mist or sanding dust. While spraying and/or sanding boat surfaces, wear protective eye wear such as goggles or a face shield **NIOSH certified mask or respirator. A minimum of a half face NIOSH approved respirator (TC-84A) with organic vapor cartridges with any R or P combination filter. Higher level respirators that are NIOSH Approved for organic vapors and particulates that contain oil can also be used.** Remove contaminated clothing and wash clothing before reuse. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco or using the toilet.

ENVIRONMENTAL HAZARDS

This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS: Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO₂ or dry chemical.

STORAGE & DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

STORAGE: Store in a closed, properly labeled container in a cool place. Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and disposal of in accordance with local applicable regulations.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

FIRST AID

- IF IN EYES:**
- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
 - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
 - Call a poison control center or doctor for treatment advice.
- IF SWALLOWED:**
- Call a poison control center or doctor immediately for treatment advice.
 - Have person sip a glass of water if able to swallow.
 - Do not induce vomiting unless told to do so by a poison control center or doctor.
 - Do not give anything by mouth to an unconscious person.
- IF INHALED:**
- Move person to fresh air.
 - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.
 - Call a poison control center or doctor for further treatment advice.
- IF ON SKIN OR CLOTHING:**
- Take off contaminated clothing.
 - Rinse skin immediately with plenty of water for 15 – 20 minutes.
 - Call a poison control center or doctor for treatment advice.

Hot Line Number

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.

Note to Physician

Probable mucosal damage may contraindicate the use of gastric lavage. This product contains petroleum distillates. Vomiting may cause aspiration pneumonia.

Medical Emergencies: 1-800-548-0489

Product Information: 1-800-221-4466 or WWW.PETTITPAINT.COM

Manufactured in the United States