

60061-137

9/3/2013

116

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460



Office of Pesticide Programs

Kop-Coat, Inc.
3020 William Pitt Way
Pittsburgh, PA 15238

SEP -3 2013

Attention: Angie Custer
Regulatory Affairs Specialist

Subject: Pettit Hydrocoat aco Copper-Free Multi-Season Ablative
EPA Registration No. 60061-137
Your Amendment Dated August 8, 2013

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable.

Proposed Amendment

- Parent Product Name :Change:

OLD: Hydrocoat ECO Ablative Antifouling Paint

NEW: Pettit Hydrocoat ~~E~~co Copper-Free Multi-Season Ablative

- Updated Storage and Disposal Instructions

General Comments

A stamped copy of the "accepted" labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely,

Marshall Swindell
Product Manager (33)
Regulatory Management Branch 1
Antimicrobials Division (7510P)

Enclosure



United States
Environmental Protection Agency
 Washington, DC 20460

Registration
 Amendment
 Other

OPP Identifier Number

Application for Pesticide - Section I

1. Company/Product Number Kop-Coat, Inc. / 60061-137		2. EPA Product Manager Marshall Swindell	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Pettit Hydrocoat eco Copper-Free Multi-Season Ablative		PM# 33	
5. Name and Address of Applicant (Include ZIP Code) Kop-Coat, Inc. 3020 William Pitt Way Pittsburgh, PA 15238 <input type="checkbox"/> Check if this is a new address		6. Expedited Review. In accordance with FIFRA Section 3(c)(3)(b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. 60061-137 Product Name Hydrocoat ECO Ablative Antifouling Paint	

Section - II

Amendment - Explain below. Final printed labels in response to Agency letter dated _____

Resubmission in response to Agency letter dated _____ "Me Too" Application.

Notification - Explain below. Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Change of Parent Product name and updated Storage and Disposal Statement for 60061-137: New Parent Name: Pettit Hydrocoat eco Copper-Free Multi-Season Ablative (See attached cover letter).

Section - III

1. Material This Product Will Be Packaged In:

Child-Resistant Packaging <input type="checkbox"/> Yes* <input checked="" type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	2. Type of Container <input type="checkbox"/> Metal <input checked="" type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____
* Certification must be submitted		If "Yes" Unit Packaging wgt. No. per container	If "Yes" Package wgt. No. per container

3. Location of Net Contents Information
 Label Container

4. Size(s) Retail Container
Gallon, Quart

5. Location of Label Directions
 On Label
 On Labeling accompanying product

6. Manner in Which Label is Affixed to Product
 Lithograph Paper glued
 Stenciled Other _____

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)

Name Angie Custer	Title Reg. Affairs Specialist	Telephone No. (Include Area Code) 412-826-3323
----------------------	----------------------------------	---

Certification
 I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.

2. Signature
Ronald W. Clawson Jr. / jaco


3. Title
Research & Development Manager

4. Typed Name
Ronald W. Clawson, Jr., Ph.D.

5. Date
7/29/13

6. Date Application Received (Stamped)

PETTIT



HYDROCC

COPPER FREE MULTI-SEASON AB

- *Easy Soap and Water Clean Up*
- *Compatible Over Almost All Bottom Paints*
- *Extremely Effective and Environmentally Friendly*
- *Dual Biocide Ablative Offers Excellent Multi-Seas*

1204 BLUE

KEEP OUT OF REACH OF CHILDREN

WARNING


COMBUSTIBLE LIQUID AND VAPOR. VAPOR HARMFUL.
HARMFUL OR FATAL IF SWALLOWED.
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company, including surface preparation, proper application and environmental conditions. Therefore, Pettit Paint Company cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. Pettit Paint Company shall not under any circumstances be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Pettit Paint's option.

NET CONTENTS
1 GALLON (128 FL. OZ.)
3.785 LITERS

BJ EFF

BE D



PETTIT

HYDROCOAT


eco

BI-SEASON ABLATIVE

Up
Bottom Paints
Environmentally Friendly
Excellent Multi-Season Protection

BLUE

KEEP OUT OF REACH OF CHILDREN
WARNING: FUMES OR VAPOR HARMFUL IF SWALLOWED
SEE PRECAUTIONARY STATEMENTS



ACTIVE INGREDIENTS:
 Tralopyril 6.00%
 Zinc Pyrithione 4.80%

INERT INGREDIENTS 89.20%
TOTAL 100.00%



This product contains petroleum distillates.

EPA EST. NO. 60061-NJ-2
EPA REGISTRATION NO. 60061-137

KOP-COAT, INC.
PETTIT PAINT BRAND
ROCKAWAY, NJ 07866 An RPM Company

GENERAL DESCRIPTION: Pettit Hydrocoat ECO Ablative free, multi-season ablative antifouling protective coating and freshwater fouling organisms. This product's state-of-the-art unique ablative vehicle is designed to polish away old paint and keeps underwater surfaces smooth and clean. This product is suitable for use on the hulls and underwater parts below the waterline. This product is suitable for use on vessels of any size.

DIRECTION:

It is a violation of Federal law to use this product in a way that is not in accordance with the label. **PREPARATION OF SURFACE:** The surface to be painted must be clean, dry and free of foreign matter. Always prepare the surface to be painted by sanding old antifouling paint or primers are applied. When sanding old antifouling paint, use a fine sandpaper and remove all sanding dust. Old, soft bottom paints must be completely removed. **COVERAGE, APPLICATION AND TEMPERATURE:** This product should be applied between 9:00 a.m. and 4:00 p.m. to avoid condensation spoiling the application. The temperature should be between 50°F and 90°F. This product will cover approximately 375 square feet of surface per gallon of paint on a mechanical paint shaker. **PREPARATION OF PAINT:** It is necessary to thoroughly mix the two parts together before using. The pigment has been mixed in. If mixing is going to be done, pour off half of the liquid from the top of the can into a separate container and mix thoroughly. **THINNING:** Thinning this product is not normally required. Thinning more than 10% (12 ounces per gallon) or more will result in erosion of the finish will be likely. Use clean water for thinning.

DRY TIMES:

	To recoat
90°F	1-1/2 hours
70°F	3 hours
50°F	6 hours

The above dry times are minimums. This product may be applied in cooler temperatures. There is no maximum time before launching.

SYSTEMS:

Mix paint thoroughly to ensure toxicants are evenly distributed. **PREVIOUSLY PAINTED SURFACES:** If the previous coating is sandpaper then solvent clean with Pettit 120 Brushing solvent. If the previous coating is soft or in poor condition, use a paint and varnish remover. Proceed with application of this product. **BARE FIBERGLASS:** All bare fiberglass, regardless of whether it is painted or not, should be cleaned with Pre-Paint Cleaner following the instruction on the Bio-Blast label. **BARE ALUMINUM:** Sandblast to clean, bright metal and then apply a clean brush. Immediately apply two coats of this product. **ALL OTHER SUBSTRATES:** Please go to www.pettitpa.com for more information. **VOC:** (as supplied) 150 grams/liter maximum.

PRECAUTIONARY STATEMENTS:

HAZARDS TO HUMANS AND DOMESTIC ANIMALS:
WARNING: Causes substantial but temporary eye injury or on clothing. Harmful if swallowed. Harmful if inhaled. While spraying and/or sanding boat surfaces, wear eye protection. Wash thoroughly with soap and water after handling and before eating, drinking, or smoking. Wear coveralls worn over long-sleeved shirt and long pants. Wear goggles, face shield or safety glasses, socks, and gloves. Wash clothing before reuse. May pose a risk to aquatic life in water bodies.

MEDICAL EMERGENCIES: 1-800-548-0489
PRODUCT INFORMATION: 1-800-221-4466 or 1-800-548-0489

50-662 gal 4/c
Cyan Mag Black

GENERAL DESCRIPTION: Pettit Hydrocoat ECO Ablative Antifouling Paint is an extremely effective, copper multi-season ablative antifouling protective coating resistant to slime, algae, barnacles and other marine freshwater fouling organisms. This product's state-of-the-art organic biocide technology coupled with a unique ablative vehicle is designed to polish away at a controlled rate, which minimizes coating build-up and keeps underwater surfaces smooth and clean. This product is for use in fresh, salt or brackish water on above and underwater parts below the waterline. This paint is intended for use on recreational and commercial vessels of any size.

DIRECTIONS FOR USE

VIOLATION OF FEDERAL LAW: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
PREPARATION OF SURFACE: The surface to be painted should be clean, dry and free of any contamination or foreign matter. Always prepare the surface to be painted by sanding and solvent cleaning before any primers are applied. When sanding old antifouling paint use a dust mask to prevent the inhalation of fine dust. Old, soft bottom paints must be completely removed before applying.

APPLICATION, APPLICATION AND TEMPERATURE: This product can be applied by brush or short nap roller. All painting should be done between 9:00 a.m. and 4:00 p.m. in order to avoid the possibility of dew or condensation spoiling the application. The temperature range of application should be between 50 and 90°F. At two coats, should be applied for best performance, particularly in high wear areas such as the waterline. The product will cover approximately 375 square feet per gallon when applied at 1.5 dry mils film thickness.

PREPARATION OF PAINT: It is necessary to thoroughly mix the paint before using. If possible shake the can until on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all pigment has been mixed in. If mixing is going to be done with a wooden paddle or an electric drill mixer, dip off half of the liquid from the top of the can into another can and then properly mix in any settled sediment, then remix the two parts together thoroughly.

THINNING: Thinning this product is not normally required. If thinning is necessary, use clean water only. Do not thin more than 10% (12 ounces per gallon) or inadequate paint film thickness will occur and premature failure of the finish will be likely. Use clean water for cleaning up equipment.

RECOAT TIMES:

Temperature	To recoat	To launch
90°F	1-1/2 hours	12 hours
70°F	3 hours	16 hours
50°F	6 hours	48 hours

Minimum above dry times are minimums. This product may be recoated and launched after the minimum times shown. There is no maximum time before launching.

SYSTEMS

Apply paint thoroughly to ensure toxicants are evenly dispersed throughout the can. All surfaces must be clean, dry and properly prepared prior to painting.

PREVIOUSLY PAINTED SURFACES: If the previous coating is in good condition, thoroughly sand with 80-grit sandpaper then solvent clean with Pettit 120 Brushing Thinner to remove residue. Apply two finish coats of product. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using a paint and varnish remover. Proceed with appropriate bare system as described below.

FIBERGLASS: All bare fiberglass, regardless of age, should be thoroughly cleaned with 92 Bio-Blue Pre-Paint Cleaner following the instruction on the Bio-Blue can. Sand thoroughly with 80-grit sandpaper to a smooth, frosty finish and wash the sanded surface with fresh water to remove sanding residue. Then apply two coats of this product following application instructions. Careful observation of the above instructions will ensure long-term adhesion of this and subsequent years' antifouling paint. To eliminate the sanding residue, scrub the surface using 92 Bio-Blue Pre-Paint Cleaner and a coarse Scotch-Brite® pad. Clean-up residue with fresh water and allow the hull to dry thoroughly. Then apply one coat of Pettit 6998 Skip Sand Primer using a 3/16-inch or less nap roller or brush. Read and follow carefully the application and topcoating instructions on the Skip Sand Primer label. Apply at least two coats of this antifouling paint.

ALUMINUM: Sandblast to clean, bright metal and remove blasting residue with clean, dry compressed air and a clean brush. Immediately apply two coats of Pettit 4400/4401 Alumina-Protect Epoxy Primer followed by two finish coats of this product. Read and follow carefully the instructions on the 4400/4401 Alumina-Protect Epoxy Primer label. If the surface to be painted is smooth aluminum, apply one coat of 6455/044 Skip Sand Primer and allow to dry for 2 hours, then apply two finish coats of this product. Read and follow carefully the instructions for application and topcoating on the 6455/044 Primer label.

OTHER SUBSTRATES: Please go to www.pettitpaint.com and consult the product data sheet. (as supplied) 150 grams/liter maximum.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

WARNING: Causes substantial but temporary eye injury. Causes skin irritation. Do not get in eyes, on skin, or on clothing. Harmful if swallowed. Harmful if inhaled. Avoid breathing spray mist, vapors or sanding dust. While spraying and/or sanding boat surfaces, wear a NIOSH/MSHA certified mask or respirator. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Do not use coversalls worn over long-sleeved shirt and long pants, chemical resistant gloves, protective eyewear (goggles, face shield or safety glasses), socks, and chemical resistant footwear. Remove contaminated clothing and wash clothing before reuse. May pose an aspiration pneumonia hazard.

EMERGENCY INFORMATION: 1-800-548-0489
PRODUCT INFORMATION: 1-800-221-4466 or WWW.PETTITPAINT.COM

For applications by residential (non-commercial) users: Do not apply by airless spray; Do not apply more than one coat of this product within 24 hours; Apply only in outdoor, non-enclosed spaces. Residential (non-commercial) users are advised to wear chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks and shoes. In addition to these minimum Personal Protective Equipment (PPE), commercial users must wear a disposable coverall with hood and chemical resistant footwear. While removing existing paint by sanding or blasting, or applying new antifouling paint, commercial users must wear a respirator with an organic vapor removing cartridge with a pre-filter approved for pesticides (MSHA/NIOSH APPROVAL NUMBER TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 pre-filter. Residential (non-commercial) users are advised to wear the same respirators, cartridges and pre-filters as required by commercial users.

FIRST AID	
IF IN EYES:	<ul style="list-style-type: none">Hold eye open and rinse slowly and gently with water for 15-20 minutes.Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.Call a poison control center or doctor for treatment advice.
IF SWALLOWED:	<ul style="list-style-type: none">Call a poison control center or doctor immediately for treatment advice.Do not induce vomiting unless told to do so by a poison control center or doctor.Do not give any liquid to the person.Do not give anything by mouth to an unconscious person.
IF INHALED:	<ul style="list-style-type: none">Move person to fresh air.If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.Call a poison control center or doctor for further treatment advice.
IF ON SKIN OR CLOTHING:	<ul style="list-style-type: none">Take off contaminated clothing.Rinse skin immediately with plenty of water for 15 - 20 minutes.Call a poison control center or doctor for treatment advice.

HOT LINE NUMBER

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.

NOTE TO PHYSICIAN

Probable mucosal damage may contraindicate the use of gastric lavage. This product contains petroleum distillates. Vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS: Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO2 or dry chemical. Wear NIOSH/MSHA certified breathing equipment.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.
Storage: Store in a closed, properly labeled container in a cool place. Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.
Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.
Container Handling: Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

NOTICE! THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

Made in U.S.A.  P3563 GA.-03/13